MILITARY SPECIFICATION

CONTROL, RADIO SET C-4684(*)/ASQ-56A

This specification has been approved by
the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 Scope - The equipment covered by this specification shall be of one type and shall provide the following functions within the Integrated Electronic Central AN/ASQ-56A.

(1) Selection of uhf navigation channel.

(2) Function selection of uhf navigation equipment (OFF, REC, T/R, A/A).

(3) Control of uhf navigation volume

1.2 Associated Equipment - The equipment shall be capable of operating with the following associated equipment which is not to be supplied as part of this equipment.

Item	Type Designation
Receiver-Transmitter, Radio	RT-384/ARN-52(V)
Adapter, Mounting	MX-4773/ASQ-56A

2. APPLICABLE DOCUMENTS

2.1 General - The following documents of the issue in effect on the date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-P-7788	Plate, Plastic, Lighting
MIL-I-81007	Integrated Electronic Central AN/ASQ-56A
MIL-C-26482	Connectors, Electric, Circular, Miniature, Quick Disconnect

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-704	Electrical Power, Aircraft, Characteristics and Utilization of
MS 25212	Control Panel, Console Type, Aircraft Equipment, Basic Dimensions
MS-25213	Control Panel, Aircraft Equipment, Typical Installation

2.2 Availability of Documents -

(1) When requesting specifications, standards, drawings, and publications, refer to both title and number. Copies of this specification and applicable specifications required by contractors in connection with specific procurement functions may be obtained upon application to the Commanding Officer, Naval Supply Depot, Code DCI, 5801 Tabor Avenue, Philadelphia 20, Pennsylvnia

3. REQUIREMENTS

3.1 Parts and Materials - In the selection of parts and materials, fulfillment of major design objectives shall be the prime consideration. In so doing, parts and materials requirements shall conform to Specification MIL-I-81007.

3.2 Design and Construction -

3.2.1 General - This equipment shall conform with the applicable requirements of MIL-I-81007 for design, construction, and workmanship.

3.2.2 Operational Stability - The equipment shall operate with optimum performance for 2,000 cycles, continuously or intermittently, without the necessity for readjustment of any controls which are inaccessible during flight.

3.2.3 Total Operating Life - The equipment shall have a minimum total operating life of 50,000 cycles with reasonable servicing and replacement of parts. Parts requiring replacement within this interval and the life of such parts shall be specified by the manufacturer.

3.2.4 Reliability in Mean Time Between Failures - The control shall have 5000 hours of mean (operating) time between failures when tested and accepted as outlined under the requirements of 4.4.3.(of MIL-I-81007)

3.2.5 External Connectors - External connectors shall be Bendix Type PT02A-16-26P, or an approved equivalent in accordance with Specification MIL-C-26482.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

3.2.6 Input Power Requirements - The equipment shall meet all applicable requirements of MIL-STD-704 and shall give performance from a Category "B", 28 V DC source as defined in MIL-STD-704. The power required shall not exceed 3 watts.

3.3 Performance - The performance of the equipment shall be as set forth below. Unless otherwise specified, these requirements apply under standard conditions.

3.3.1 Visual Display - A visual display of the operating uhf navigation channel shall be contained on the front of the unit.

3.4 Detail Requirements -

3.4.1 Form Factor and Mounting - The radio set control shall conform to the basic form factor of MS 25212. The mounting and installation shall conform to MS 25213. The dimensions shall not exceed 2 1/4 inches high by 4 7/16 inches deep (measured from mounting surface) by 5 3/4 inches wide and the total weight shall not exceed 2.25 pounds.

3.4.2 Illumination - Red lighting and a plastic light plate in accordance with Specification MIL-P-7788 shall be provided.

3.4.3 Controls - The following controls shall be provided on the face of the equipment.

3.4.3.1 Volume Control - A rotary volume control shall be provided to adjust the amplitude of audio identification signal. Clockwise rotation shall increase the signal intensity.

3.4.3.2 Function Selector Switch - The function selector switch shall be a rotary wafer switch with a pointer knob to select OFF, REC, T/R, A/A, in that order, with clockwise rotation of the knob. The OFF position shall de-energize the uhf navigation equipment; REC position shall energize the receiver portion of the central to provide bearing information and tone identity; T/R position shall energize both the receiver and transmitter portions of the central to provide bearing, distance, and tone identity; A/A position shall energize both the receiver and transmitter portions of the central in a special mode to provide distance information to another aircraft.

3.4.3.3 Channel Selector - Channel selection shall be provided by 2 rotary knobs, also controlling presentation of channel numbers in a digital counter window. Operation of the left knob shall control the tens and hundreds digits. Operation of the right knob shall control the units digit. Both knobs shall increase in digital value with a clockwise rotation of the knob. Digital display shall be from 00 to 129 but equipment shall operate only in the range of 01 to 126.

3.4.4 Control Functions - Control, Radio Set C-4684(*)/ASQ-56A shall provide the means for controlling all of the operating functions of the Receiver-Transmitter, Radio RT-384/ARN-52 and Adapter, Mounting Plenum MX-4773/ASQ-56A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISION

4.1 General - The control shall be subjected to the test requirements of Specification MIL-I-81007 to determine compliance with all applicable requirements.

5. PREPARATION FOR DELIVERY

5.1 General - The equipment shall be preserved, packaged, packed, and marked for the level of shipment specified in the contract or order in accordance with Specification MIL-I-81007.

6. NOTES

6.1 Use - This equipment is intended to be a part of the Integrated Electronic Central AN/ASQ-56A. In this application, it provides primary control of Receiver-Transmitter, Radio RT-384/ARN-52 and Adapter, Mounting Planum MX-4773/ASQ-56A.

6.2 Precedence of Documents - When the requirements of the contract, this specification, or applicable subsidiary specifications, are in conflict the following precedence shall apply:

(1) Contract - The contract shall have precedence over any specification.

(2) Central Specification - Integrated Electronic Central AN/ASQ-56A Specification MIL-I-81007 shall have precedence over this specification.

(3) This Specification - This specification shall have precedence over all applicable subsidiary specifications. Any deviation from this specification, or from subsidiary specifications where applicable, shall be approved in writing by the procuring activity.

(4) Referenced Specifications - Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply only to the extent indicated.

6.3 The parentheses (*), when used in the type designation, shall be replaced by either a number or letter furnished by the procuring activity upon application by the contractor for assignment of nomenclature in accordance with 3.2.10 of Specification MIL-I-81007. The complete type number shall be used in nameplates, shipping records and instructions books, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL- C-81009(Wep) Control Set C-4684(*)/ASQ-56A

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Bureau of Naval Weapons
Washington, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

BUREAU OF NAVAL WEAPONS (RREN-5)
DEPARTMENT OF THE NAVI
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.