INCH-POUND

MIL-DTL-55302/74D
w/AMENDMENT 1
26 July 2010
SUPERSEDING
MIL-DTL-55302/74D
12 November 2004


DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PIN, RIGHT ANGLE, PLUG, ELECTRICAL, POLARIZED FOR PRINTED WIRING BOARDS (.100 SPACING)

Inactive for new design after 1 October 1986.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




Inches	mm	Inches	mm
.001	0.03	.093	2.36
.002	0.05	.097	2.46
.003	0.08	.100	2.54
.004	0.10	.125	3.18
.005	0.13	.140	3.56
.007	0.18	.145	3.68
.008	0.20	.158	4.01
.010	0.25	.162	4.11
.015	0.38	.274	6.96
.020	0.51	.310	7.87
.022	0.56	.386	9.80
.030	0.76	.436	11.07
.060	1.52	.564	14.33
.064	1.63		
.075	1.91		

FIGURE 1. Connectors, plug, .100 (2.54 mm) contact spacing, pin terminal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Nominal spacing between any two adjacent pin contacts shall be .100 (2.29 ± .08 mm).
4. Unless otherwise specified, tolerances are ±.010 (0.25 mm).
5. For dimensions A through D see table I.
6. Gold plating shall not be cracked or scratched.
7. Mating connectors provide a total of 256 different polarization positions. Polarization components conforming to M55302/78-02 are supplied with the connector uninstalled.

FIGURE 1. Connectors, plug, .100 (2.54 mm) contact spacing, pin terminal - Continued.




Inches	mm
.050	1.27
.100	2.54
.150	3.81
.200	5.08
.250	6.35
.300	7.62
.350	8.89
.400	10.16
.450	11.43
.500	12.70
.550	13.97
.600	15.24
.650	16.51
.700	17.78
.750	19.05
.800	20.32
.850	21.59
.900	22.86
.950	24.13

NOTE: Contacts 1, 20, 21 and 39 are identified on the front and rear of the connector per the insert arrangement.

FIGURE 2. Insert arrangement for .100 (2.54 mm) contact spacing connectors (male engaging face).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.050	1.27	.850	21.59
.100	2.54	.900	22.86
.150	3.81	.950	24.13
.200	5.08	1.000	25.40
.250	6.35	1.050	26.67
.300	7.62	1.100	27.94
.350	8.89	1.150	29.21
.400	10.16	1.200	30.48
.450	11.43	1.250	31.75
.500	12.70	1.300	33.02
.550	13.97	1.350	34.29
.600	15.24	1.400	35.56
.650	16.51	1.450	36.83
.700	17.78		
.750	19.05		
.800	20.32		

NOTE: Contacts 1, 30, 31, and 59 are identified on the front and rear of the connector per the insert arrangements.

FIGURE 2. Insert arrangement for .100 (2.54 mm) contact spacing connectors (male engaging face) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.

Requirements:

Dimensions and configuration: See figure 1 and table I.

Material: In accordance with MIL-DTL-55302.

Plating: The contact plating shall be gold in accordance with ASTM B488, type II, code C, class 1.27 over 100 microinches of copper in accordance with SAE-AMS2418.

Contact identification: Contact locations are identified numerically as shown on figure 2.

Mating and unmating: The maximum mating force, in pounds, shall be 0.5 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of 0.08 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: With a test current of 3 A dc, the average resistance of all contact pairs measured shall not exceed 0.010 ohm, and no individual contact pair shall have a resistance exceeding 0.020 ohm.

Dielectric withstanding voltage:

Sea level: 1,300 volts rms, 60 Hz, ac.
High altitude: 325 volts rms, 60 Hz, ac.

Current rating: 3.0 amperes.

Insert arrangement: See figure 2.

High potential test voltage: 1,300 V rms, at sea level.

Mating connectors: See MIL-DTL-55302/75.

Part or Identifying Number (PIN): M55302/74-(dash number from table I).

TABLE I. Dash numbers and dimensions.

Dash number	Dimensions 1/						Number of contacts
	A +.005 (0.013)	B	C min	+.008 (0.20) D -.000	E	J +.035 (0.89) -.020 (0.51)	
01	2.700 (68.58)	2.400 (60.96)	2.040 (51.82)	2.093 (53.16)	1.200 (30.48)	.097 (2.46)	39
02	3.700 (93.98)	3.400 (86.36)	3.040 (77.22)	3.093 (78.56)	1.700 (43.18)	.097 (2.46)	59
03	2.700 (68.58)	2.400 (60.96)	2.040 (51.82)	2.093 (53.16)	1.200 (30.48)	.159 (4.04)	39
04	3.700 (93.98)	3.400 (86.36)	3.040 (77.22)	3.093 (78.56)	1.700 (43.18)	.159 (4.04)	59

1/ Metric equivalents are given for information only. Millimeters are in parentheses.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/75
ASTM B488
SAE-AMS2418

CONCLUDING MATERIAL

Custodians:
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2010-109)

Review activity:
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.