MIL-E-63399B(AR)
AMENDMENT 3
17 August 1983
SUPERSEDING
AMENDMENT 2
15 April 1983

MILITARY SPECIFICATION

ELECTRONICS-MCD ASSEMBLY
FOR
MINE, ANTITANK: HE, M75

This amendment forms a part of Military Specification MIL-E-63399B(AR), dated 16 November 1981, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, SPECIFICATIONS:

MILITARY: Add the following:

MIL-B-117	- Bags, Sleeves and Tubing - Interior Packaging
MIL-P-14232	- Parts Equipment and Tools For Army Materiel, Packaging of
MIL-S-19500	- Semiconductor Devices, General Specification For

PAGE 4

PRODUCT AND PACKAGING DRAWINGS: Delete:

"7258943 - Shipping and Storage Container, M548."

PAGE 7

* 3.5.3.8a: Delete in its entirety.

3.5.3.8b, line 2: Delete "2.5 Volts" and substitute "V_B-.3 Volts".

FSC 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

PAGE 9

3.5.7.1 Solderability: Delete in its entirety and substitute:

"3.5.7.1 Solderability. Electronic and electric assembly parts that are to be soldered shall comply with the solderability requirements of MIL-S-45743 and MIL-S-46844 except integrated circuits shall be tested for solderability using the methods and acceptance criteria of MIL-STD-883 and diode and transitors shall be tested for solderability using the methods and acceptance criteria of MIL-STD-750 provided the leads are not gold plated. When gold plated leads are used, the provisions of MIL-S-45743 apply. For assembly parts without gold plated leads, Method 208 of MIL-STD-202 may be used as an alternate to that specified in MIL-STD-750 or MIL-STD-883."

* 3.5.7.2, line 9: Delete "ARRADCOM, DRDAR-QAT-M" and substitute "ARDC, DRSMC-QAT-M (D)".

3.7 First Article Inspection: Add at the end of the paragraph "(see 4.3 and 6.2)."

3.8 Surveillance units: Change "Electronic - MCD" to "Electronics - MCD".

PAGE 10

4.3 First Article Inspection: Add after title "(see also 6.2)".

4.3.1:

Change "Lid, Electric Assembly" to "Lid, Electronics Assembly"

Change "Housing, Electic Assembly" to "Housing, Electronics Assembly".

Change "Pinted Wiring Board" to "Board, Printed Wiring".

Drawings: Delete "9345328" and substitute "9292256".

PAGE 12

TABLE I, line 1: Delete "Dwg. 9345328" and substitute " Dwg. 9292256".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

PAGE 13

Table I:

Magnetometer Assembly: Delete "9292146" and substitute "9287146".

Lines 3, 4, 5, 6: Following test(s) add "2/".

Shorting Bar and Connector Assembly: Delete "4.4.2.46 and substitute "4.4.2.45".

Notes: Add "2/ These tests may be omitted at this sub-assembly if performed on Electronic Assembly, DWG. 9292223."

PAGE 15

4.4.2.1:

Drawing Number: Delete "9345328" and substitute "9292256".

Major 107: Delete "143 places" and substitute "144 places".

PAGE 16

4.4.2.2:

Major 101: Delete "Any component . . . assembled, 1/" and substitute "Any component damaged, missing or improperly oriented or assembled".

Majors 102, 103 and 104: Delete in their entirety.

Majors 105, 108, 109, 110, Inspection Method Column: Add 1/.

Minor 201: Delete in its entirety.

NOTES: Change note 1/ to read: "Inspection shall be performed prior to assembling subassembly of shorting bars and power supply to Printed Board Assembly."

PAGE 17

4.4.2.3, Major 101: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

PAGE 19

4.4.2.4, Majors 108 and 109, Requirement Column: Delete "3.5.3.11a and 3.5.3.11b" and substitute "3.5.3.11".

PAGE 21

4.4.2.6:

Major 102: Delete in its entirety.

Major 109: Change "(9-12)" to "(9 to 12)". Change "Visual" to "Ohmmeter".

PAGE 22

4.4.2.7: Delete Minors 203 and 204.

PAGE 24

4.4.2.9:

Majors 104 and 108, No. of Samples Units Column: Add "2/".

Major 106: Delete "& - 45 Oersted," and substitute "& - 0.45 Oersted,".

Major 109: Delete in its entirety.

NOTES: Delete "note 2/" and substitute "2/ Majors 104, 105, 106, 107, 108 may be omitted at this subassembly if performed on Electronic Assembly Dwg. 9292223."

PAGE 28

4.4.2.13, Drawing Number: Delete "9292151 P/N 9292151-1/-2" and substitute "9287177/9292151".

PAGE 35

4.4.2.20:

Major 104: Delete "3.2" and substitute "3.5.7.1".

Major 105: Delete "6/".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

Major 106: Delete "all entries" and substitute "Internal visual - 6/ - LTPD 10% - 3.2 - MIL-STD-750, Method 2072, Para. 3.2 only".

Notes, 6/: Delete "note 6/" and substitute "6/ Sample per MIL-S-19500, APPENDIX C."

PAGE 36

4.4.2.21:

Major 104: Delete "3.2" and substitute "3.5.7.1".

Major 105: Delete "6/".

Major 106: Delete "all entries" and substitute "Internal visual - 6/ - LTPD 10% - 3.2 - MIL-STD-750, Method 2072, Para. 3.2 only".

Notes, 6/: Delete "note 6/" and substitute "6/ Sample per MIL-S-19500, APPENDIX C."

PAGE 39

4.4.2.24, Drawing Number: Delete "9292138" and substitute "92187175".

PAGE 41

4.4.2.26: Delete in its entirety.

PAGE 42

4.4.2.27, Major 103: Delete "3.2" and substitute "3.5.7.1".

PAGE 43

4.4.2.28, Major 105: Delete "3.2" and substitute "3.5.7.1".

PAGE 44

4.4.2.29, Major 102: Delete ".5" and substitute "5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

PAGE 45

4.4.2.30:

Title: Delete and substitute "Integrated Circuit, Single CMOS, Target Sensor".

Drawing Number: Delete "9287124" and substitute "9287173".

Major 102: Delete ".5" and substitute "5".

Delete "Visual" and substitute "2/".

PAGE 46

4.4.2.31, Major 102: Delete ".5" and substitute "5".

PAGE 47

4.4.2.32, Major 102: Delete ".5" and substitute "5".

PAGE 54

Major 101: Delete "Diameter of EBP lead, 2 places" and substitute "Diameter of hole for EBP lead, 2 places".

PAGE 63

4.4.2.48:

Major 101: Delete.

Major 102: Delete "Conductive . . . liners" and substitute "Any defect of barrier bag".

Major 103: Delete "5.1" and substitute "5.1, 5.2".

Major 104: Delete.

PAGE 65

* 4.4.5:

Line 30: Delete "ARRADCOM" and substitute "ARDC".
Line 31: Delete "DRDAR-QAT-I" and substitute "DRSMC-QAT-I (D)".

* Note 1, line 6: Delete "ARRADCOM" and substitute "ARDC".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

* Note 1, line 7: Delete "DRDAR-QAT-M" and substitute "DRSMC-QAT-I (D)".

PAGE 68

* 4.5.9, line 7: Delete "and spurious outputs".

4.5.12, line 1: Delete "elecronic" and substitute "electronic".

PAGE 69

4.5.20, line 2: Delete "to the Government" and substitute "for Government approval".

PAGE 71

4.5.26 subpara f: Change "Electronic-MCD" to "Electronics-MCD".

PAGE 72

5. PACKAGING: Delete "5.1, 5.2, 5.3 in their entirety" and substitute the following:

5.1 Packaging. The Electronics-MCD assembly shall be preserved and packaged in accordance with level B of MIL-P-14232. Each assembly shall be wrapped in aluminum foil, packaged in a fiberboard box and separated by loose partitions and separators as required. Cushioning as needed shall be used; the fiberboard box shall be sealed in a barrier bag conforming to Type I, Class F, Style 1, Spec. MIL-B-117. (Material used to fabricate the barrier bag must include metal foil). The packaging materials shall not contain silicones, sulphur compounds or polysulphides.

5.2 Packing. The Electronics-MCD assemblies in box and barrier bag shall be packed in accordance with Level B of MIL-P-14232 and Code of Federal Regulations, Title 49 with the following mandatory requirements: The outer packing box shall be wood or fiberboard conforming to the requirements of code of Federal Regulation, Title 49. Sufficient cushioning and separators must be used between the barrier bag and outer box to prevent damage to the items or tearing of the barrier bag.

5.3 Marking. The marking of the outer box shall be in accordance with MIL-STD-129, and DOT marking per Code of Federal Regulation, Title 49. Marking indicating the components are fragile electronics shall be employed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

PAGE 73

FIGURE 1: Delete.

PAGE 74

FIGURE 2a, b: Delete.

PAGE 75

6.2 subpara a: Delete title of MIL-E-63399 and substitute "Electronics-MCD Assembly".

In title of MIL-P-63421 change "Fascom" to "FASCAM".

* 6.3:

Line 3: Delete "US ... Command" and substitute "U.S. Army Armament Research and Development Center".
Line 4: Delete "DRDAR-QAT-I" and substitute "DRSMC-QAT-I (D)".

* 6.4:

Lines 2 and 3: Delete "US .. (ARRADCOM)" and substitute "US Army Armament Research and Development Center (ARDC)".
Line 7: Delete "ARRADCOM" and substitute "ARDC".

PAGE 76

* 6.5, lines 4 and 5: Delete "US ... DRDAR-QAT-M" and substitute "U.S. Army Armament Research and Development Center, ATTN: DRSMC-QAT-M (D)".

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A287)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.