MILITARY SPECIFICATION

FUZE, MTSQ, M564, LOADING AND PACKING (ALTERNATE)

1. SCOPE

1.1 This specification covers Fuze, MTSQ, M564 Assembly (Alternate).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

Military

MIL-P-60412	-	Packaging, packing and Marking for Shipment of Artillery Type and Rocket Fuzes: General Specification for

STANDARDS

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-331	-	Fuze and Fuze Components Environmental and Performance Test for
MIL-STD-1167	-	Ammunition Data Card

DRAWINGS

Munitions Command

C11738593	-	Booster Pellet
F11738600	-	Fuze, MTSQ, M564 Assembly (Alternate)
IEL-11738600	-	Inspection Equipment List for Fuze, M564 Assembly (Alternate)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, references standards and specifications.

3.2 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.2.1 Foreign matter. - No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

3.3 Waterproofness.- The fuze shall comply with MIL-STD-331, Test No. 108, except that the duration of immersion shall be five (5) minutes and the pressure shall be three (3) psi gauge.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Lot formation.- Each inspection lot of fuzes shall be comprised of components (except explosive components) each produced by one manufacturer, by one process, in accordance with the same drawing and revision and specification and revisions, as applicable, and assembled on one assembly line. Each explosive component within a lot of assembled fuzes shall be limited to one manufacturer and one interfix number.

4.2 First article sample.

4.2.1 Inspection provisions for first article not required.

4.3 Inspection provisions.

4.3.1 Submission of product.- The product shall be presented in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for defects shall be performed on a single defect bases in accordance with MIL-STD-105. For each classification of defects contained herein, the AQL given shall be applied to each major defect contained herein. All nonconforming material shall be rejected. Four power (4X) magnification may be used in performing visual examination.

4.3.2.1 Fuze subassembly Drawing F11738601 should be visually examined for the following in order to determine condition of material as received:

a. Fuze not set on safe "S" (Critical)

* b. Foreign matter in flash hole (Major-AQL = 0.40%)

* c. Fuze damaged (Major-AQL = 0.40%)

* (to be checked after removing dust seal

4.3.2.2 Closing Cup Assembly, Drawing B8595506, covering a detail of Drawing F11738600.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR AQL = 0.40%	
101. Explosive above flush	Gage
102. Explosive below flush exceeds max.	Gage
103. Cup damaged	Visual
104. Foreign matter on external surface	Visual

4.3.2.3 Booster Pellet Drawing C11738593 covering a detail of Drawing F11738600.

CRITICAL	
None defined	
MAJOR AQL = .40%	
101. Diameter, improper	Gage
102. Width, improper	Gage
103. Weight, improper	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

4.3.2.4 Fuze, MTSQ, M564 (Alternate) Assembly, Drawing F11738600.

CRITICAL		
1.	Explosive material on internal thread of booster cup (small amount of explosive dust is acceptable)	Visual
2.	Fuze not set on safety "S"	Visual
MAJOR	AQL = 0.40%	
101.	Length from flange to bottom of cup exceeds maximum	Gage
102.	Booster cup split or damaged	Visual
103.	Booster pellet missing (as indicated by booster cup contacting shoulder of body)	Visual

4.3.2.5 Packaging, packing and marking. - The sample size and acceptance criteria for packaging, packing and marking shall be in accordance with MIL-P-60412.

4.3.3 Inspection testing. - The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Process control audit. - Periodic (at least once during each 8 hour shift) unscheduled monitoring shall be conducted for the process operations on the following assemblies to determine compliance with the requirements of the applicable drawings.

a. Fuze Subassembly, Drawing F11738601

(1) Removal of dust cover and insertion of closing cup assembly.

b. Fuze, MTSQ, M564 (Alternate) Assembly, Drawing F11738600.

(1) Insertion of booster pellet in booster cup.

(2) Application of correct quantity of sealing compound on the booster pellets.

(3) Tightening of booster cup on D.A.M. assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

4.3.3.2 Waterproofness test.-Four fuze assemblies per F11738600 shall be selected from each lot and subjected to the waterproofness test. Evidence of water entry through the booster cup or the booster cup joint shall be cause for rejection of the lot. Water entry into the fuze (O-ring, etc.) shall not be cause for rejection of the lot. Record and forward data to technical agency.

4.3.4 Inspection Equipment.-The examinations and tests shall be made using equipment listed in IEL-11738600. Equipment design shall be in accordance with the code designation on the applicable IEL.

4.4 Test methods and procedures.

4.4.1 Waterproofness.-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 108, except as provided in 3.3. The fuze shall be disassembled and inspected as follows:

a. Remove booster cup, D.A.M., head, lower cap, check all visible internal surfaces for evidence of water entry.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-Packing, packaging, and marking shall be as specified in the contract in accordance with MIL-P-60412.

5.2 Data cards.-Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

6.2 Statement of Safety Requirements.

6.2.1 Safety Limitations and Precautions Relating to Production Equipment and Facilities:

Assembly of explosive elements into fuzes shall be performed under protective hoods with static electricity controls. Protective barrier should be used when performing the MIL-Standards tests.

6.2.2 Hazards Presented by Materials:

Possible injury (burns or dismemberment) to limbs and body from flash or detonation of explosive elements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

6.2.3 Known Hazards in Hazardous Areas:

All areas in which explosive elements are used in assembly operations or stored.

6.2.4 Specific Instructions Relative to Manufacture, Handling, Storage, and Shipment of Material: The number of persons exposed to explosive operations and quantities of explosive materials should at all times be the minimum consistent with safety and the efficiency of operation. Signs setting forth personnel and explosive limits also should be posted. Prior to starting operations including any of the hazardous materials or items described herein, a standard operating procedure should be developed and approved by the contractor outlining the specific requirements to safely perform the particular operation. All personnel concerned should be cognizant of SOP contents. Applicable portions of the approved procedure should be conspicuously posted convenient to all stations involved in the operation for guidance of all personnel.

6.2.5 Explosive Hazard Classification of Material:

Assembled fuzes - Class I, Detonators in Storage - Class 7.

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1390-A119

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.