MIL-H-50235(AR)
7 July 1977
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

HANDLING DEVICE, ADAPTION KIT: H4235

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of handling device entitled Handling Device, Adaption Kit: H4235 which is used with the Sprint warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8888999	- Handling Device Adaption Kit: H4235.
9248926	- Handle, AK Assembly.
9260287	- Box, Fiberboard, Packing Ammunition for Handle, Device, Adaption Kit: H4235.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The handling device shall comply with all requirements specified on the drawing (dwg) 8888999, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Proof Load. Each AK Handle Assembly dwg 9248926, of the H4235 Adaption Kit Handling Device shall withstand a static load of 33 plus or minus (+) 1 pound applied for 30 minutes minimum without damage. Testing shall be as described in 4.4.1.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 2 complete assemblies (see dwg 8888999) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:17Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Proof load (see 3.5)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:17Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Handling Device, AD (see dwg 8888999).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Mislocation of hole (2)	Gage
	102. Diameter of hole (2)	Gage
	103. Improper contour of handle	Visual
	104. Evidence of plastisol on area other than specified on dwg	Visual
	105. Serialization improper or missing	Visual
	106. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Handle, AK Assembly (see dwg 9248926).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Components missing, damaged, loose or improper	Visual/Manual
102.	Chamfer and knurl on screw fastener missing or improper	Visual
103.	Distance of screw protrusion incorrect	Gage
104.	Flaring missing	Visual
105.	Marking, missing, illegible, misplaced or improper	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.3 Preparation for delivery (see 5.)

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packing, and packaging not in accordance with dwg 9260287	Visual
102.	Marking not in accordance with dwg 9260287	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Proof load	Major

This test is not considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Proof load. Each handling device shall be tested in accordance with 4.4.1. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major and Minor characteristics and tests. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Proof load. The handling device shall permit the installation and removal of an approved load of 33 ± 1 pound. The load shall possess the identical mounting features and center of gravity of an adaption kit (Sprint), thereby simulating the "In-use Conditions" for transporting the adaption kit. The device shall be suspended to permit the load to remain suspended for 30 minutes, minimum. After the load remains suspended for the specified time, it shall be removed and the device shall be examined for damage (see 6.4) requirements shall be as specified in 3.5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The handling device shall be packaged in accordance with dwg 9260287 using the specified moisture barrier.

5.1.2 Level C. The handling device shall be packaged in accordance with dwg 9260287 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The handling device shall be packed in accordance with dwg 9260287.

5.3 Marking. Marking shall be as specified in accordance with dwg 9260287.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 *Damage. A defect that is detectable by visual examination. Typical defects are as follows: Crack in weldment, damaged threads, deformed structural member, cracked structural member, damage finish exposing base metal; marking obliterated.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2258 dated 8 October 1971.

*A 5X magnifying glass may be used while examining for damages.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No. 1190-A101

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAN-Q
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.