MILITARY SPECIFICATION SHEET

MODULE ASSEMBLY (DIODE)

The complete requirements for procuring the module described herein shall consist of this document and the latest issue of specification MIL-M-50276(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Module Assembly (DIODE) used in the Atomic Demolition charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY
MIL-M-50276 - Modules, General Specification for
MIL-S-60902(MU) - Soldering Electrical Connections for Nuclear Weapons Systems, Procedure for.

STANDARDS

MILITARY
NAS671 - Nut
MIL-STD-750 - Test Methods for Semiconductor Devices
MS35275 - Screw

DRAWINGS

ORDNANCE CORPS
8808362 - Packing and Marking for Storage and Shipments
8822613 - Diode
8826290 - Potting Data
8857425 - Module Assembly (Diode)
8860651 - Board, Diode Assembly
8860652 - Board, Term Assy
8860653 - Board, Terminal
8860654 - Terminal
8883539 - Bag, Packing for Repair Parts
ET-8857425 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-M-50276(MU) and as specified herein.

3.2 Functioning. The module shall comply with table I when tested as specified in 4.5.2.

Table I

Functioning test (see dwg 8860651)

+ From Terminal	-To Terminal	Controlled Input	Maximum Output
1	2	I_F 100-5 ma	V_F 2.2 Volts
3	2	I_F 100-5 ma	V_F 2.2 Volts
2	1	V_R 125-5 Volts	I_R 0.052 Amps
2	3	V_R 125-5 Volts	I_R 0.052 Amps

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-M-50276(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following inspections in MIL-M-50276(MU) are not applicable.

a. 4.3.2.1.1 Transistor 2N425 (see MIL-T-19500/41); insulation tubing (see 8826340); eyelet (see dwgs 8826307 and 8836476).

b. 4.3.2.1.2 Insulation paper (see dwg 8826313); base-board, module (see dwg 8826168) covering details of plug-in modules and baseboard as applicable.

c. 4.3.2.1.3 Contact pin (see dwg 8826288) and guide pin, module (see dwgs 8826308 and 8866640) covering details of plug-in modules.

d. 4.3.2.1.4 All plug-in type modules (see dwg in detail specification (see 6.2).

4.2 Classification of characteristics.

4.2.1 Diode (see dwg 8822613); terminal (see dwg 8860654); Nut (see NAS 671-4); screw (see MS 35275-18) covering details of dwgs 8860651 and 8860652 as applicable.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see Objective evidence, section 6, MIL-M-50276(MU) available for part in accordance with applicable standard or drawing.....	Visual
Minor: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

4.2.2 Board, terminal (see dwg 8860653 covering a detail of dwg 8860652).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length	Gage
102.	Width	Gage
103.	Location of holes	Gage
104.	Thickness, min	Gage
105.	Material (see Material, section 3, MIL-M-50276(MU)	Visual
Minor:		
201.	Workmanship (see Workmanship, section 3, MIL-M-50276(MU)	Visual-Manual

4.2.3 Board, term, assy (see dwg 8860652 covering a detail of dwg 8860651).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Terminals tight	Manual
Minor: None defined.		

4.2.4 Board, diode, assembly (see dwg 8860651 covering a detail of dwg 8857425).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Soldering in accordance with MIL-S-60902(MU)	Manual
102.	Distance to top of wire, max	Gage
103.	Wiring	Visual
104.	Circuit resistance (see 3.2)	Gage
105.	Screws tight	Manual
106.	Material (see Material, section 3, MIL-M-50276(MU)	Visual
Minor:		
201.	Workmanship (see Workmanship, section 3, MIL-M-50276(MU)	Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

4.2.5 Module assembly (diode)(see dwg 8857425).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Potting in accordance with dwg 8826290	Visual
102.	Location of terminals	Gage
103.	Location of screws	Gage
104.	Perpendicularity of screws	Gage
105.	Length of mold	*Measure
106.	Width of mold	*Measure
107.	Height of mold	*Measure
108.	Terminals free of potting material	Visual
109.	Height of base of terminal	Gage
110.	Marking	Visual
111.	Materials (see Material, section 3, MIL-M-50276(MU)	Visual
*Measure with suitable scale.		
Minor:		
201.	Workmanship (see Workmanship, section 3, MIL-M-50276(MU)	Visual-Manual

4.3 Insulation resistance. The module insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8857425)

Positive potential applied to terminal	Minus potential to
1	Screws
2	Screws

4.4 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-M-50276(MU) and ET-8857425.

4.5 Test methods.

4.5.1 Test methods. Test methods shall comply with MIL-M-50276(MU) and as specified herein.

4.5.2 Functioning (see 3.2). The module shall be tested in accordance with MIL-STD-750, test methods 4011.1 and 4016.1 as applicable.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

5.1 Preparation for delivery for production modules. Preparation for delivery for production modules shall be in accordance with MIL-M-50276(MU).

5.2 Preparation for delivery for repair modules.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-M-50276(MU).

5.2.1.1 Level A. The modules shall be packaged in accordance with dwgs 8883539-3 and 8808362 and as specified in MIL-M-50276(MU).

5.2.1.2 Level C. The modules shall be packaged in accordance with dwg 8808362 and MIL-M-50276(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The modules shall be packed in accordance with dwgs 8883539-3 and 8808362 and MIL-M-50276(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8883539-3 and 8808362 and MIL-M-50276(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-M-50276(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU
Project No. 1125-A019

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-M-50276/14(MU) Module Assembly (Diode)

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.