INCH-POUND
MIL-P-55695(CR)
AMENDMENT 2
2 February 1989
SUPERSEDING
AMENDMENT 1
30 October 1974

MILITARY SPECIFICATION

Power Supply PP-4763( )/GRC

This amendment forms a part of Military Specification MIL-P-55695(EL), dated 14 April 1970, and is approved for use by the Communications-Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

Page 1

Paragraph 2.1 Add:

TT-P-1757	Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity

Delete:

QQ-S-781	Steel Strapping, Flat
TT-P-636	Primer coating, Synthetic, Wood and Ferrous Metal
PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated-Plywood
PPP-B-621	Box, Wood, Nailed and Lockcorner
PPP-B-636	Box, Fiberboard
PPP-F-320	Fiberboard, Corrugated and solid, Sheet Stock (Container Grade) Cut Shapes
PPP-T-97	Tape Pressure Sensitive Adhesive, Filament Reinforced
MIL-P-116	Preservation, Methods of
MIL-B-131	Barrier Material, Water vapor proof, Flexible

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:57Z
Check the source to verify that this is the current version before use.

Paragraph 2.1 Add:

MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment, Subsystem and System
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-HDBK-781	Reliability Test Methods, Plans, and Environments for Engineering Development, Qualification and Production
SM-D-633300	Power Supply PP-4763( )/GRC

Delete:

MIL-I-6181	Interference Control Requirements, Aircraft Equipment
MIL-P-8585	Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity
MIL-STD-147	Palletized and Containorized Unit Loads 40 inch x 48 inch Pallets, Skids, Runners, or Pallet Type Base
DL SM-A-640000	Power Supply PP-4763( )/GRC

Paragraph 3.2 Delete references to "Preproduction" and substitute "First Article".

Paragraph 3.3 Delete references to "DL-SM-A-640000" and substitute "SM-D-633300".

Paragraphs 3.5.1, 3.5.2 and 3.5.2.1 Delete references to "MIL-P-8585" and substitute "TT-P-1757".

Paragraph 3.11.4 Delete and substitute "+0.5%" with "1% overall".

Paragrph 3.15 Delete and substitute:

3.15 Electromagnetic Interference. The equipment shall comply with Table A-VI of Notice 4, MIL-STD-461A as modified by Table V of this specification (see 4.8.8 and Table V).

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:57Z
Check the source to verify that this is the current version before use.

Page 8

Paragraph 4.2 Delete references to "Preproduction" and substitute "First Article".

Page 9

Paragraph 4.3 Delete references to "Preproduction" and substitute "First Article".

Page 15

Paragraph 4.8.5 Delete and substitute:

4.8.5 Salt Fog Test (See 3.14.2.5). After completion of the salt fog test in accordance with Method 509, Procedure 1 of MIL-STD-810, the Power Supply shall be examined visually with the aid of a 10 power magnifier. The Power Supply shall show no evidence of degradation such as flaking, pitting, blistering or loosing of finish on metal surfaces. Electrical operation is not required.

Paragraph 4.8.6 Add:

Note: maximum frequency for all tests shall be 33 Hz.

Paragraph 4.8.7 Delete the last sentence.

Page 16

Paragraph 4.8.8 Delete and substitute:

4.8.8 Electromagnetic Interference (See 3.15). The equipment shall be tested for compliance with 3.15 using test setups and procedures of Notice 3, MIL-STD-462. During testing performance, the equipment shall be operated to supply 50 amperes (constant current) at 28 volt DC into a non-inductive load.

Paragraph 4.8.9 Delete and substitute:

4.8.9 Fungus Test (See 3.7.2). The Power Supply shall be subjected to 28 days of the fungus test specified in MIL-STD-810, Method 508, Procedure 1. After completion of the test the power supply shall be inspected for evidence of damage and deterioration. Electrical operation is not required.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:57Z
Check the source to verify that this is the current version before use.

Paragraph 4.12 Delete and substitute:

4.12 Production Reliability Testing. Production reliability testing shall be conducted as a sequential acceptance test in accordance with Test Plan XXID of MIL-HDBK-781, using an Upper Test MTBF of 7500 hours.

Paragraph 4.12.2 Delete and substitute:

4.12.2 Equipment Quantity. A minimum of ten (10) equipments shall be selected from each production lot for each reliability acceptance test. More than (15) equipments shall not be used at any one time for reliability acceptance test. A production lot is defined as two months production, unless otherwise specified in the contract.

Paragraph 4.12.3 Delete and substitute:

4.12.3 Reliability Test Conditions. The reliability Test conditions shall be that of fixed ground equipment with no vibration stress.

Paragraph 5 Delete and substitute:

5 PACKAGING

5.1 Packaging Requirements. The packaging requirements for the desired level(s) of protection shall be as specified by the acquisition activity (see 6.2).

Paragraph 6.2(b) Delete and substitute:

(b) Levels of preservation and packing (see section 5).

Paragraph 6.2(c) Delete.

Paragraphs 6.2(d)(2) and 6.2(j) Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:57Z
Check the source to verify that this is the current version before use.

Add Table V:

Table V. - Electromagnetic Interference Requirements

Test Req'd	Para MIL-STD-462 Notice 3	Lines Subjted	Lines Monitd	Freqy Range	Limits per MIL-STD-461A Notice 4	Test Set Up MIL-STD-462 Notice 3
CE04	(B), Page 41	-	AC & DC	150KHz to 25MHz	Fig A-3c/d*	CE04-2
CS02	B, Page 67	AC	DC	150KHz to 65MHz	See para 3, Page 67, of MIL-STD-462 Notice 3	See para 3, page 67
RE02 (BB)	Pages 87 to 89	-	-	150KHz to 400MHz	Fig 13 and as modded by Fig A-1e	RE02-1**
RE02.1 (NB)	Pages 87 to 89	-	-	150KHz to 10GHz	Fig 12 as modded by Fig A-1d	RE02-1**
RS03	Pages 116 to 131	-	DC	150KHz to 10GHz	Pages 20, 21 and 42 (Note 47)	RS03***

Notes:

* Deviations are permitted IAW Note 19 of Page 39 of MIL-STD-461A Notice 4.

** Required deviation to Test Set Up IAW Note 46 of Page 42 of MIL-STD-461A, Notice 4.

*** Figures as appropriate.

Custodian:
Army - CR

Preparing Activity:
Army - CR
(Project 5820-A872)

Source: https://assist.dla.mil -- Downloaded: 202640-22T23:57Z
Check the source to verify that this is the current version before use.