MIL-C-392H(ME)
AMENDMENT 2
18 July 1986
SUPERSEDING
MIL-C-392H(ME)
AMENDMENT 1
22 January 1986

MILITARY SPECIFICATION

CONVEYOR, BELT: PORTABLE

This amendment forms a part of MIL-C-392H(ME), dated 3 September 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.1, under SPECIFICATIONS, MILITARY, add:

"MIL-A-8421 - Air Transportability Requirements, General Specifications for."

PAGE 3

Under "MS 35000 - Battery, Storage, Lead-Acid, Waterproof.", add:

"MS 52131 - Connector, Plug, Electrical Intervehicle Power Cable."

PAGE 18

Add new paragraph:

"3.20.6.2 Slaving components. The conveyor shall be equipped with a 24 volt slave receptacle conforming to MS52131. The slave receptacle shall permit charging of the batteries and slave starting of the engine from an external power source and shall also provide a power source for charging and slaving other equipment. The slave receptacle shall be installed on the exterior of the conveyor near the battery compartment and shall be accessible to personnel standing on the ground. The voltage potential of the slave receptacle shall be identified on a plate mounted adjacent to the receptacle. The plate shall be in accordance with the requirements of 3.28. (This slave receptacle shall be compatible with NATO Slave Cable, NSN 2590-00-148-7961.)"

AMSC N/A FSC 3910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:17Z
Check the source to verify that this is the current version before use.

PAGE 19

* 3.21.1, line 4, after "figure 4", add, "when loaded atop a 50-inch (1270 mm) high rail car."

* 3.21.1.4, line 1, after title, add, "The conveyor shall be air transportable by C-130, C-141, and C-5 aircraft and meet the requirements of MIL-A-8421."

* 3.21.6, line 4, after "specified" add, "in MIL-A-8421, for equipment restraint criteria and in MIL-STD-209, for . . .".

PAGE 27

4.5.2, line 10, add:

"13b. Stave components not as specified."

PAGE 28

* 4.5.3.7, line 2, after "compliance with" add, "MIL-A-8421 and".

* 4.5

"4.5.3.8
Attached equipment in rail transport configuration shall be tested in accordance with the rail impact test procedures outlined in appendix A of MIL-STD-1186."

PAGE 37

* 6.2, add:

"t. When rail impact test is not required (see 4.5.3.8)."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 3910-A076

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:17Z
Check the source to verify that this is the current version before use.