NOT MEASUREMENT SENSITIVE

MIL-I-11132/20D
17 January 1995
SUPERSEDING
MIL-I-11132/20C
30 June 1987

MILITARY SPECIFICATION SHEET

INSIGNIA, CAP, ADVANCE COURSE, SENIOR DIVISION, ROTC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-11132.



DASH NO.
-1: Male
-2: Female

MATERIAL: Red Brass

FINISH:
CAP INSIGNIA EXCEPT LETTERING: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
LETTERING: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
-1:
HEIGHT (Overall): 2-1/4 inches (5.72 cm) (REF)
WIDTH (Overall): 2-5/8 inches (6.67 cm) (REF)
THICKNESS (Minimum): 0.040 inch (0.101 cm)
-2:
HEIGHT (Overall): 1-5/8 inches (4.13 cm) (REF)
WIDTH (Overall): 1-3/4 inches (4.45 cm) (REF)
THICKNESS (On Torch): 0.060 inch ± 0.010 inch (0.152 cm ± 0.25 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:14Z
Check the source to verify that this is the current version before use.

NOTES:

1. In Dash No. -1, the device shall be pierced as shown. Area inside and around lettering and between the parallel curved bars shall be pierced. In Dash No. - 2, piercing is not required.

2. The term (REF) refers to the measurements taken from the Government furnished hub or die.

3. Except for size and piercing, the design for Dash No. -1 and -2 are identical to the figure shown.

4. In Dash No. -1, a full force shall be used to bring up the design of the shield, eagle and wreath. At the option of the manufacturer, the forcer may also be used to bring up the letters. A full forcer shall be used for Dash No. -2.

5. The insignia shall be dapped in a horizontal direction along a 3-1/2 inches ± 1/2 inch (8.89 cm ± 1.27 cm) radius.

6. In Dash No. -1, the attaching device shall consist of a screw post with thumb nut and two registering prongs. The screw post shall be located on the vertical center line 1-1/8 inches ± 1/16 inch (2.86 cm ± 0.12 cm) below the top of the insignia. The registering prongs shall be located on a horizontal line 9/16 inch ± 1/16 inch (1.43 cm ± 0.12 cm) below the top of the insignia. In Dash No. -2, the attaching device shall be prong and clutch type. The prongs shall be located on the horizontal line 5/8 inch ± 1/64 inch (1.59 cm ± 0.08 cm) above the bottom of the device and 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08 cm) apart.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0791)

Source: https://assist.dla.mil - Downloaded: 2026-10-17T15:14Z
Check the source to verify that this is the current version before use.