NOT MEASUREMENT SENSITIVE

MIL-DTL-11132/20K(IH)
19 May 2026
SUPERSEDING
MIL-DTL-11132/20J(IH)
22 June 2021

DETAIL SPECIFICATION SHEET

INSIGNIA, CAP, ADVANCE COURSE, SENIOR DIVISION, ROTC, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-I-11132.



DASH NO.
-1: Male
-2: Female

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
CAP INSIGNIA EXCEPT LETTERING: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
LETTERING: 24K Gold Plated, Mirror-like Polished and shall match the TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
-1: 2-1/4 inches (REF)
-2: 1-5/8 inches (REF)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:14Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1: 2-5/8 inches (REF)
-2: 1-3/4 inches (REF)
THICKNESS (Minimum):
-1: 0.040 inch
THICKNEST (On torch):
-2: 0.060 inch ± 0.05 inch

ATTACHING DEVICE:
-1: The attaching device shall consist of a screw post with thumb nut and two registering prongs. The screw post shall be located on the vertical center line 1-1/8 inches ± 1/16 inch below the top of the insignia. The registering prongs shall be located on a horizontal line 9/16 inch ± 1/16 inch below the top of the insignia.

-2: The attaching device shall be prong and clutch type. Two prongs shall be located on the horizontal line 5/8 inch ± 1/64 inch above the bottom of the device and 1-1/2 inches ± 1/32 inch apart.

PIERCING:
-1: As shown. Area inside and around lettering and between the parallel curved bars shall also be pierced.

-2: As shown except that area inside and around lettering and between the parallel curved bars shall not be pierced.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. For -1, a full forcer shall be used to bring up the design of the shield, eagle, and wreath. At the option of the manufacturer, the forcer may also be used to bring up the letters.

3. The insignia shall be dapped in a horizontal direction along a 3-1/2 inch ± 1/2 inch radius.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:14Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2026-303)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:14Z
Check the source to verify that this is the current version before use.