A-A-571A
February 28, 1986

COMMERCIAL ITEM DESCRIPTION

NUTRUNNER AND SCREWDRIVER, ELECTRIC

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers a nutrunner and screwdriver designed for driving self-tapping screws.

Salient characteristics:

Conforms to the requirements of Underwriters' Laboratories Standard No. 45.
Double insulated or conventional 3-wire construction.
Operates from a 120-VAC power source.
Rated 4.0 amperes minimum.
Instant release switch.
Reversible.
Variable speed rated no load 0-1800 rpm minimum and 0-2500 rpm maximum.
All ball bearing or ball and needle bearing construction.
Straight drive with a positive type clutch.
Pistol grip handle.
Socket type chuck - 1/4-inch hexagon shape.
Capacity: Number 12 (5/16" x 2") minimum rated wood screw size.
1/4-inch rated machine screw size.
Maximum weight 4 pounds 8 ounces (including power cord).
Furnished with one each of the following accessories:
Number 2 point Phillips bit with 1/4-inch hexagon male drive.
5/16-inch hexagon socket with 1/4-inch hexagon male drive.
3/8-inch hexagon socket with 1/4-inch hexagon male drive.
Complete set of operating and maintenance instructions.
Illustrated parts breakdown.
List of available accessory equipment.
Any special equipment and tools necessary to assure efficient operation in accordance with the operating instructions.

Workmanship. The nutrunner and screwdriver, including all parts and accessories, shall be free of fins, burrs, rust, external sharp or rough edges, imperfections, and any other defects which may impair serviceability, durability, or appearance.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes:

Assigned National Stock Number (NSN) is 5130-00-177-7085.
The issue of UL Standards No. 45 in effect on the date of invitation for bid or request for proposals shall be used to determine compliance with the stated requirements.
Copies of Underwriters' Laboratories Standards may be obtained from Underwriters' Laboratories Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11747.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

FSC 5130