MIL-P-13269A(MU)
AMENDMENT 3
17 NOVEMBER 1966

SUPERSEDING
AMENDMENT 2
20 JANUARY 1966

MILITARY SPECIFICATION

PERISCOPE, TANK: M20 SERIES

This amendment forms a part of Military Specification MIL-P-13269A (Ord), 10 November 1960.

Paragraph 2.1. Under "SPECIFICATIONS" delete "MIL-P-13462 — Periscopes M20 Series; Packaging of" and substitute "MIL-P-14232 — Parts, Equipment and Tools for Ordnance Materiel, Packaging of".

Under "DRAWINGS," add "and M20A3G" as follows:

F8585211 — Periscopes: M20A3C and M20A3G

LSQAP-8585211 — Supplementary Quality Assurance Provisions List for Periscopes: M20A3C and M20A3G

IEL-8585211 — Inspection Equipment List for Periscopes: M20A3C and M20A3G

Add packaging data sheet after "DRAWINGS" as follows:

"PACKAGING DATA SHEET

MIL-P-14232/P7652791 — Packaging and Periscopes, Tank: M20 Series"

Add the following paragraph after paragraph 3.6.5:

"**3.6.6** *Torque.* The running torque required to rotate the coupling through maximum elevation and depression shall not exceed 3 pound-inches at a standard ambient temperature of 60° to 90°F. The torque shall not change from the value obtained by more than 2 pound-inches when subjected to the temperature specified in 3.5.2."

Add the following paragraph after paragraph 3.8:

"**3.9 Sealing.** The periscope (head assembly and body assembly) shall show no evidence of leakage when subjected to an external pressure of 5.0 ± 0.1 pounds per square inch gage (psig)."

Paragraph 4.7.2, table II. Add the following in proper sequence under "Head Assembly":

"107a. Torque ..... 3.6.6 ..... 4.9.2.6."

Add the following paragraph after paragraph 4.9.2.5:

"**4.9.2.6** *Torque.* The torque required to rotate the input coupling through the specified excursion shall be measured using standard measuring equipment affixed to the coupling. The measured torque shall not ex-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.

ceed the value specified in 3.6.6 for the temperature indicated in 3.5.2."

Paragraph 4.9.5: Delete and substitute the following paragraphs:

"**4.9.5** *Sealing test.* The external pressurizing of the periscope head and body assemblies to test sealing shall be performed with special testing equipment conforming to Drawings F7680673, F7680674, and F7680675. The test shall be conducted in accordance with the instructions on Sheet 1 of Drawing F7680673. The assemblies shall be subjected to the specified pressure for a period of 5 minutes ± 15 seconds during which time there shall be no evidence of leakage as indicated by the testing equipment. Sampling for examination and tests shall be in accordance with MIL–STD–105 utilizing an AQL of 0.65 percent in conjunction with Table II–A of MIL–STD–105."

"**4.9.6** *Packaging, packing, and marking.* Examination and tests for packaging, packing, and marking shall be in accordance with MIL–P–14232 and Section 5 herein."

Paragraph 5.1, first sentence. Delete "Specification MIL–P–13462" and substitute "MIL–P–14232 and Packaging Data Sheet MIL–P–14232/P7652791."

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1240–A569Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.