MILITARY SPECIFICATION

SIGNAL, ILLUMINATION, GROUND PARACHUTE, RED STAR, M126A1, WHITE STAR, M127A1 AND GREEN STAR, M195, PARTS AND LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-S-13257H(AR) dated 12 February 1980.

PAGE 32

Paragaph 4.4.3.2, TABLE III, add the following inspection:

"Cork sealing disc in end of barrel loose (see label dwgs. 8797931-2, -3 and -10).

PAGE 34

Paragraph 4.4.3.3, second sentence, delete the phrase "... as classified in Table III of 4.4.3.2..." and replace with the following:

"(See para. 3.3.1),"

PAGE 36

a. Paragraph 4.5.2.1, NOTE: Delete "60 seconds" and replace with "three minutes".

b. Paragraph 4.5.2.2, NOTE: Delete "60 seconds" and replace with "three minutes".

PAGE 37

a. Paragraph 4.5.2.3.1, NOTE: Delete "60 seconds" and replace with "three minutes".

b. Paragraph 4.5.2.3.2, NOTE: Delete "60 seconds" and replace with "three minutes".

FSC: 1370

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

PAGE 38

Paragraph 4.5.10, Delete the last sentence, "Any sample ... defective" and replace with the following:

"If one or more assemblies fail to comply with the color value requirement or if two or more assemblies fail to meet the candlepower requirement, the lot shall be rejected."

PAGE 40

Paragraph 6.7, Delete the table and replace with the following:

Firing Method & Conditioning Temp	First Article Qty.	PRODUCTION LOT QTYS. (Until 3 consec lots accepted)	(Normal Prod)	(Reqm't Para.)
Fixture:				
69° to 73°C (160° ± 5°F)	32	100	25	See 3.4.3
19° to 23°C (70° ± 5°F)	32	125	50	See 3.4.4
-52° to -56°C (-65° ± 5°F)	16	32	10	See 3.4.5
Hand:				
-52° to -56°C (-65° ± 5°F)	16	125	50	See 3.4.5

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1370-A129

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.