MIL-S-13257H(AR)
AMENDMENT 2
10 June 1983
SUPERSEDING
AMENDMENT 1
5 May 1981

MILITARY SPECIFICATION

SIGNAL, ILLUMINATION, GROUND PARACHUTE, RED STAR, M126A1, WHITE STAR, M127A1 AND GREEN STAR, M195, PARTS AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-S-13257H(AR) dated 12 February 1980, and is approved for use by the US Army Armament Research and Development Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 25

* 4.4.2.19:

Add: Critical 2 Initiating Charge missing, 100%, 3.2, Visual.

Change Major 103 from "Initiating Charge missing 0.40% 3.2 Visual" to "Initiating Charge over max (See Note), 0.40% 3.2 Balance".

PAGE 32

4.4.3.2, TABLE III: Add the following inspection:

"Cork sealing disc in end of barrel loose (see label dwgs. 8797931-2, -3 and -10).

PAGE 34

4.4.3.3, second sentence: Delete the phrase "... as classified in Table III of 4.4.3.2..." and replace with the following:

"(See para. 3.3.1),".

PAGE 36

4.5.2.1, NOTE: Delete "60 seconds" and replace with "three minutes".

FSC 1370

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

4.5.2.2, NOTE: Delete "60 seconds" and replace with "three minutes".

PAGE 37

4.5.2.3.1, NOTE: Delete "60 seconds" and replace with "three minutes".

4.5.2.3.2, NOTE: Delete "60 seconds" and replace with "three minutes".

PAGE 38

4.5.10, Delete the last sentence, "Any sample ... defective" and replace with the following:

If one or more assemblies fail to comply with the color value requirement or it two or more assemblies fail to meet the candlepower requirement, the lot shall be rejected.'

PAGE 40

Paragraph 6.7: Delete the table and replace with the following:

FUNCTIONING TEST

Firing Method & Conditioning Temp	First Article Qty	PRODUCTION LOT QTYS. (Until 3 consec lots accepted)	(Normal Prod)	(Reqm't Para.)
Fixture:				
69° to 73°C (160° ± 5°F)	32	100	25	See 3.4.3
19° to 23°C (70° ± 5°F)	32	125	50	See 3.4.4
-52° to _56°C) -65° ± 5°F)	16	32	10	See 3.4.5
Hand:				
-52° to -56° (-65° ± 5°F)	16	125	50	See 3.4.5

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1370-A158)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.