INCH-POUND

MIL-S-13257H(AR)
AMENDMENT 5
30 MAY 1989
SUPERSEDING
AMENDMENT 4
12 March 1988

MILITARY SPECIFICATION

SIGNAL, ILLUMINATION, GROUND PARACHUTE, RED STAR, M126A1, WHITE STAR, M127A1 AND GREEN STAR, M195, PARTS AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-S-13257H(AR) dated 12 February 1980, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 7

4.4.2.1: Delete defects in their entirety, and substitute the following:

"Critical				
1	Hydrostatic pressure test	100% (Note 1)	3.2	4.5.6
2	Presence of cracks	100%	3.7	Visual
Major				
101	Perpendicularity of ends	0.40%	3.2	Gage
102	Total length, max.	0.40%	3.2	Gage
103	Inside diameter at ends, max.	0.40%	3.2	Gage
Minor				
201	Poor workmanship	1.00%	3.8	Visual

Note 1 -Tubing stock used to manufacture the casing tube shall be 100% hydrostatically tested as specified in Para. 4.5.6. All remaining classified defects shall be checked on the finished item."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2.2, Note (a): Delete "200 samples" and substitute "20 samples".

PAGE 10

4.4.2.4: Delete in its entirety and substitute included page.

PAGE 11

4.4.2.5, Note (a): Delete "200 samples" and substitute "20 samples".

PAGE 25

4.4.2.19:

Add: Critical 2, Initiating Charge missing, 100%, 3.2, Visual.

Delete "Major 103, "Initiating Charge missing, 0.40%, 3.2, Visual" and substitute "Major 103, "Initiating Charge over max (See Note), 0.40%, 3.2, Balance".

PAGE 30

* 4.4.2.25: Add new Classification of Defects for Signal Body (Dwg. 8797963) as included.

PAGE 31

4.4.3.1: Delete "4.5.2" in last sentence of Note and substitute "4.5.1".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Tail Assembly				8797947
					NEXT HIGHER ASSEMBLY 8797968 or 9255112
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Tail fin missing, Cracked or inverted		100%	3.2	Visual
Major					
101	Length, max		0.40%	3.2	Gage
102	Location of tail vanes with diameter and each other, including maximum vane extension from centerline		0.40%	3.2	Gage
103	Inside diameter of upper tail ring, min		0.40%	3.2	Gage
104	Perpendicularity of ends with diameter		0.40%	3.2	Gage
105	Position of rib inside diameter with upper tail ring diameter		0.40%	3.2	Gage
106	Weld missing		0.40%	3.2	Visual
107	Weld flash excessive to the extent that function will be impaired		0.40%	3.2	Visual
108	Weld peel test	(a)	--	3.2	4.5.11
109	Hardness Test (See Dwg. 8797951)	(b)	--	3.2	4.5.8
Minor					
201	Clearance between lowertail ring and tail vane		0.65%	3.2	Gage
202	Poor workmanship		1.00%	3.8	Visual

NOTES: (a) 32 samples/lot, 1 upper tail ring weld and 1 lower tail ring weld per assembly (64 weld total); accept 0 reject 1. (b) Twenty (20) tail vanes shall be selected from each heat treated batch for hardness testing.

Source: https://assist.dla.mil - Downloaded: 2026-10-18T01:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.25	Signal Body				8797963
					NEXT HIGHER ASSEMBLY 8797920
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Small inside diameter		0.40%	3.2	Gage
Minor					
201	Large outside diameter, max.		0.65%	3.2	Gage
202	Large inside diameter, min.		0.65%	3.2	Gage
203	Overall length		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

PAGE 32

4.4.3.2, TABLE III: Add the following inspection:

"Cork sealing disc in end of barrel loose (see label dwgs. 8797931-2, -3 and -10), Major"

4.4.3.2.1.1: Delete "one hundred (100) assemblies" and substitute "fifty (50) assemblies."

4.4.3.2.1.2: Delete "twenty-five (25) assemblies" and substitute "twenty (20) assemblies."

4.4.3.2.2.1:

Delete "one hundred and twenty-five (125) assemblies and substitute "one hundred (100) assemblies."

Delete "or if eight (8) or more" and substitute "or if six (6) or more."

PAGE 33

4.4.3.2.3.1: Delete in its entirety and substitute the following:

"4.4.3.2.3.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have been found to be acceptable, fifty (50) assemblies shall be selected from each lot for test. The lot shall be rejected if, during the test a critical defect occurs, the average angle from the vertical exceeds the requirements, or if four (4) or more assemblies exhibit any of the remaining major defects listed in Table III. (See note after the following paragraph)."

4.4.3.2.3.2: Delete in its entirety and substitute the following:

"4.4.3.2.3.2 After three (3) consecutive lots have complied with the criteria of 4.4.3.2.3.1, thirty-two (32) assemblies shall be selected from each lot for test. The lot shall be rejected, if during the test, a critical defect occurs, the average angle from the vertical exceeds the requirement or if three (3) or more assemblies exhibit any of the remaining major defects listed in Table III. (see note)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

Note: A star which ignites and burns normally but subsequently fails to meet minimum burning time requirement due to ground impact, will not be classified defective. Firing records will be annotated accordingly."

4.4.3.2.4: Delete in its entirety.

PAGE 34

4.4.3.3, second sentence: Delete the phrase "... as classified in Table III of 4.4.3.2..." and substitute "(See 3.3.1),".

PAGE 36

4.5.2.1, NOTE: Delete "60 seconds" and substitute "three minutes".

4.5.2.2, NOTE: Delete "60 seconds" and substitute "three minutes".

PAGE 37

4.5.2.3.1, NOTE: Delete "60 seconds" and substitute "three minutes".

4.5.2.3.2, NOTE: Delete "60 seconds" and substitute "three minutes".

PAGE 38

4.5.6: Delete in its entirety and substitute the following:

"4.5.6 Hydrostatic test of tube, casing. In lieu of testing each individual casing tube, the tubing stock, which is used to manufacture the casing tube, shall be 100% tested in a hydrostatic test device (see 4.4.4). The minimum pressure shall be applied for not less that 5 seconds. The tubing shall be observed for evidence of failure to comply with the requirements. Any full length of tubing that bursts, cracks, or shows evidence of distortion shall be classified as defective and removed from production."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.

4.5.10, Delete the last sentence, "Any sample ... defective" and substitute the following:

"If one or more assemblies fail to comply with the color value requirement or if two or more assemblies fail to meet the candlepower requirement, the lot shall be rejected."

PAGE 40

6.7: Delete the table and substitute the following:

PRODUCTION LOTS

Firing Method & Conditioning Temp. Fixture:	First Article	First Three Consecutive Acceptable	Normal Production	Requirement Paragraph
68° to 74°C (155° to 165°F)	32	50	20	See 3.3.3
18° to 24°C (65° to 75°F)	32	100	50	See 3.3.4
-57° to -51°C (-70° to -60°F)	16	50	32	See 3.3.5

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1370-A293)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:18Z
Check the source to verify that this is the current version before use.