INCH-POUND

MIL-S-13261G(AR)
AMENDMENT 5
30 MAY 1989
SUPERSEDING
AMENDMENT 4
12 March 1988

MILITARY SPECIFICATION

SIGNAL, ILLUMINATION, GROUND, GREEN STAR CLUSTER M125A1, RED STAR CLUSTER M158, AND WHITE STAR CLUSTER M159, PARTS AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-S-13261G(AR) dated 12 February 1980, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 3

3.3.5: Cold temperature: Delete "3.3.5" and substitute "3.4.5".

3.4.2: Delete "Buring time of illuminant charges." and substi- "Burning time of illuminant charges."

3.4.3: Hot temperature: Line 1 delete "(18 to 24°C or 65 to 75°F)" and substitute "(68 to 74°C or 155 to 165°F)".

3.4.4: Ambient temperature: Line 1 delete "(70 plus or minus 5 degrees F)" and substitute "(18 to 24°C or 65 to 75°F)". Change 4th subparagraph lettered "c" to subparagraph "d".

PAGE 5

* Delete from Table I - First Article Inspection

Functioning, cold, hand fired, 16, 100%, 3.4.5, 4.5.2.3.1/hand"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.2.6, Note (a): Delete "200 samples" and substitute "20 samples".

PAGE 13

4.4.2.7, Note (b): Delete the first sentence, "200 samples ..." and substitute "20 (twenty) samples/lot or batch - same sample for both tests."

PAGE 18

4.4.2.12 Delete in its entirety and substitute included page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.12	Tail Assembly	1	1	8797947
				NEXT HIGHER ASSEMBLY: 8797920

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Tail fin missing, cracked or inverted		100%	3.2	Visual
Major					
101	Length, max		0.40%	3.2	Gage
102	Location of tail vanes with diameter and each other, including maximum vane extension from centerline		0.40%	3.2	Gage
103	Inside diameter of upper tail ring, min		0.40%	3.2	Gage
104	Perpendicularity of ends with diameter		0.40%	3.2	Gage
105	Position of rib inside diameter with upper tail ring diameter		0.40%	3.2	Gage
106	Weld missing		0.40%	3.2	Gage
107	Weld flash excessive to extent that function will be impaired		0.40%	3.2	Visual
108	Weld peel test	(a)	--	3.2	4.4.11
109	Hardness test (See Dwg. 8797951)	(b)	--	3.2	4.5.8
Minor					
201	Clearance between lower tail ring and tail vane		0.65%	3.2	Gage
203	Poor workmanship		1.00%	3.8	Visual

NOTES: (a) 32 samples/lot, 1 upper tail ring weld and 1 lower tail ring weld per assembly (64 weld total); accept 0, reject 1. (b) Twenty (20) tail vanes shall be selected from each heat treated batch for hardness testing.

Source: https://assist.dla.mil - Downloaded: 2024-10-13T00:09Z
Check the source to verify that this is the current version before use.

PAGE 20

4.4.2.14: Delete defects in their entirety and substitute the following:

"Critical				
1	Hydrostatic pressure test	100% (Note 1)	3.2	4.5.6
2	Presence of cracks	100%	3.3	Visual
Major				
101	Perpendicularity of ends	0.40%	3.2	Gage
102	Total length, max.	0.40%	3.2	Gage
103	Inside diameter at ends, max.	0.40%	3.2	Gage
Minor				
201	Poor workmanship	1.00%	3.8	Visual

Note 1 -Tubing stock used to manufacture the casing tube shall be 100% hydrostatically tested as specified in Para. 4.5.6. All remaining classified defects shall be checked on the finished item."

PAGE 30

* 4.4.2.25 Add new Classification of defects for Signal Body (Dwg. 8797963) as included.

PAGE 31

4.4.3.1, TABLE II, under "Material" heading: Delete the word "Fiberboard" and substitute "Hardboard".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.25	Signal Body	1	1	8797963
				NEXT HIGHER ASSEMBLY: 8797920

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Small inside diameter		0.40%	3.2	Gage
Minor					
201	Large outside diameter, max		0.65%	3.2	Gage
202	Large inside diameter, min.		0.65%	3.2	Gage
203	Overall length		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: DRSM2076A10 (13T06:49Z
Check the source to verify that this is the current version before use.

PAGE 32

4.4.3.2, TABLE III, eleven lines below "Defect Classification,": Delete the reference, ("See 3.e.4d)" and substitute "(See 3.4.4.d)".

4.4.3.2.1.1: Delete "one hundred (100) assemblies" and substitute "fifty (50) assemblies."

4.4.3.2.1.2: Delete "twenty-five (25) assemblies" and substitute "twenty (20) assemblies."

4.4.3.2.2.1:

Delete "one hundred and twenty-five (125) assemblies" and substitute "one hundred (100) assemblies."

Delete "or if eight (8) or more" and substitute "or if six (6) or more."

PAGE 33

4.4.3.2.3.1: Delete entire paragraph and substitute the following:

"4.4.3.2.3.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have been found to be acceptable, fifty (50) assemblies shall be selected from each lot for test. The lot shall be rejected if, during the test a critical defect occurs, the average angle from the vertical exceeds the requirements, of if four (4) or more assemblies exhibit any of the remaining major defects listed in Table III. (See note after the following paragraph)."

4.4.3.2.3.2: Delete entire paragraph and substitute the following:

"4.4.3.2.3.2 After three (3) consecutive lots have complied with the criteria of 4.4.3.2.3.1, thirty-two (32) assemblies shall be selected from each lot for test. The lot shall be rejected, if during the test, a critical defect occurs, the average angle from the vertical exceeds the requirement or if three (3) or more assemblies exhibit any of the remaining major defects listed in Table III. (see note)

Note: A star which ignites and burns normally but subsequently fails to meet minimum burning time requirement due to ground impact, will not be classified defective. Firing records will be annotated accordingly."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.

* 4.4.3.2.4 Delete Cold temperature, hand fired, in its entirety.

4.4.3.2.4.1:

Delete "one hundred and twenty-five (125)" and substitute "fifty (50)".

Delete "or if eight (8)" and substitute "or if four (4)".

Delete "or exceed twelve (12)" and substitute "or exceed nine (9)".

4.4.3.2.4.2:

Delete "fifty (50)" and substitute "twenty-five (25)".

Delete "if 4 or more" and substitute "if three (3) or more".

PAGE 34

4.4.3.3, Second sentence: Delete "... as classified in Table III of 4.4.3.2 ..." and substitute "(See para. 3.4.1),".

PAGE 36

4.5.2.1, NOTE: Delete "60 seconds" and substitute "three minutes".

4.5.2.2, NOTE: Delete "60 seconds" and substitute "three minutes".

PAGE 37

4.5.2.3.1, NOTE: Delete "60 seconds" and substitute "three minutes".

4.5.2.3.2, NOTE: Delete "60 seconds" and substitute "three minutes".

* 4.5.2.3.2 Delete Hand fired. in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.

PAGE 38

4.5.6: Delete in its entirety and substitute the following:

"4.5.6 Hydrostatic test of tube, casing. In lieu of testing each individual casing tube, the tubing stock, which is used to manufacture the casing tube, shall be 100% tested in a hydrostatic test device (see 4.4.4). The minimum pressure shall be applied for not less than 5 seconds. The tubing shall be observed for evidence of failure to comply with the requirements. Any full length of tubing that bursts, cracks, or shows evidence of distortion shall be classified as defective and removed from production."

4.5.9: Delete the second sentence, "If any sample ..." and substitute "If any sample fails to comply with the applicable requirement, it shall be classed defective."

PAGE 40

* 6.4 Delete Hand firing. in its entirety.

* 6.7 Delete 6.7 in its entirety and substitute the following:

"6.7 Proving ground functioning test summary production lots.

Firing Method & Conditioning Temp.	1st Article	First Three Consecutive	Remaining Acceptable	Requirement
Fixture:				
68° to 74°C (155° to 165°F)	32	50	20	See 3.4.3
18° to 24°C (65° to 75°F)	32	100	50	See 3.3.4
-57° to -51°C (-70° to -60°F)	16	50	32	See 3.3.5"

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1370-A296)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:19Z
Check the source to verify that this is the current version before use.