MIL-B-36039A
15 February 1968
SUPERSEDING
MIL-B-36039
30 June 1960

MILITARY SPECIFICATION

BAG, GUN CREW FIRST AID KIT, EMPTY

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers an empty canvas case, fitted with a cord (drawstring) closure.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

V-T-276	Thread, Cotton.
CCC-C-419	Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army and Numbered.
CCC-D-950	Dyeing and Aftertreating Processes for Cotton Cloths.
CCC-T-191	Textile Test Methods.
MMM-A-250	Adhesive, Water-Resistant, (for Sealing Fiberboard Boxes).
PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Boxes, Setup.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, (for Carton Sealing).

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

Military

MIL-T-3530	Thread and Twine; Mildew-Resistant or Water Repellent Treated.
MIL-C-5040	Cord, Nylon.
MIL-G-16491	Grommet, Metallic.

STANDARDS

Federal

Fed. Test Method Std. No. 151	Metals, Test Methods.
Fed. Std. No. 751	Stitches, Seams, and Stitchings.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS 16686	Medical Services Symbol.

DRAWING

Defense Personnel Support Center

1365	Bag, Gun Crew First Aid Kit, Empty.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Color Association of the United States, Incorporated.

Standard Color Card for the Official Standardized Shades of Sewing Threads - U.S. Army.

(Application for copies should be addressed to the Color Association of the United States, Incorporated, 200 Madison Avenue, New York, N.Y. 10016.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing listed herein, and be subjected to the tests and meet the requirements specified therein. The metal shall conform to the chemical requirements of the applicable specifications when tested as specified in 4.4.4.1. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

3.1.1 Body fabric. The body fabric, before finishing, shall be ply yarn cotton duck, 9.85 ounces per square yard, minimum, conforming to type III of CCC-C-419.

3.1.1.1 Color and treatment. The cotton duck shall be vat dyed olive drab No. 7, water-repellent and mildew-resistant conforming to type I, class B of CCC-D-950, except that the cloth shall be made mildew resistant by treatment limited to one of the following mildew inhibitors only:

a. 2, 2' methylene-bis-(4-chlorophenol).
b. Copper-8-quinolinolate.

3.1.2 Thread. The thread shall conform to V-T-276, and for all stitching, with the exception of bar tacking, shall be type IB3, glazed finish, 4 ply, ticket No. 20. Thread for bar tacking (when used) shall be type IB3, glazed finish, 4-ply, ticket No. 30. All references to approved shade standard, standard sample, standard shade and the paragraph titled certification of V-T-276 shall not apply. The untreated and treated thread shall be tested as specified in 4.4.2.

3.1.2.1 Color and treatment. The thread shall be vat dyed to match olive drab shade S-1, Cable No. 66022, of the United States Army Standard Color Card for the Official Standardized Shades of Sewing Threads. The cotton thread shall be mildew resistant in accordance with type 1, class 1 of MIL-T-3530.

3.1.3 Cord. The nylon cord shall be olive drab No. 7, conforming to type III of MIL-C-5040.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

3.1.4 Grommets, brass. Brass grommets shall conform to type II, class 3, size No. 1 of MIL-G-16491.

3.2 Style and design. The bag shall have a square bottom and an open upper end. The open end shall be hemmed, and the outside surface of the hemmed portion shall be provided with two grommets to permit insertion of the cord. The upper end of the bag shall be provided with a flap.

3.3 Construction. Construction shall conform to the requirements specified herein, and as shown in the drawing.

3.3.1 Stitches, seams, and stitchings. All seams and stitchings shall be straight, conform to Federal Standard No. 751, and consist of stitch type 301 stitches formed by machine, with not less than eight evenly spaced stitches per inch, except that bar tacking (optional method of stitching cord to reinforcement piece) shall be 5/8 inch tacks with 1/8 inch bights, each made with not less than 42 stitches. Thread tension shall be properly maintained so that lock will be imbedded in the middle of the material sewed. All seams shall be straight and evenly spaced.

3.3.1.1 Anchorage. The ends of each continuous row of stitches, including ends due to thread breaks, shall be anchored by backstitching for a length of not less than one inch, except where anchorage is provided by another seam or stitching.

3.3.1.2 Bar tacks. Bar tacks shall be free of thread breaks and loose stitches.

3.3.2 Details. The bag shall be formed as shown in the drawing, from a body piece, a bottom piece, and a flap, all fabricated from duck as specified in 3.1.1.

3.3.2.1 Cords. Each cord shall be as specified in 3.1.3, shall be fastened to the bag within the hem, and pass through a grommet at the opposite end. Cords shall be either double stitched or bar tacked through the cord and reinforcement piece as shown in the drawing.

3.3.2.2 Grommet. The grommets for the cords shall be as specified in 3.1.4, and shall be securely attached on the outer surface of the hemmed portion of the body, and positioned as shown in the drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

3.3.2.3 Reinforcement piece. To reinforce the bag for the attachment of each grommet, there shall be provided a reinforcement piece made of duck as specified in 3.1.1 and as shown in the drawing. Both layers of the reinforcement piece and the outer surface of the hemmed portion of the body shall be firmly clinched between the grommet and the washer.

3.3.2.4 Attachment of grommet. Grommet shall be tightly clinched without cutting the duck. The hole punched in the duck to receive the grommet shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole.

3.4 Marking for identification. Each bag shall be permanently marked by stencilling or printing with black waterproof paint or ink as shown in the drawing.

3.5 Workmanship. Workmanship shall be first class throughout. Completed bags shall be clean, and free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, and investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4.1.3 Government furnished material shall not be sampled or tested unless specifically requested by the Government.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. Inspection level and AQL shall be as shown in table I.

Table I. Examination

	Inspection level	AQL (percent defective)
For visual examination:*		
Major defects (each component).	II	1.0
Minor defects (each component).	II	2.5
For dimensional examination.	S-3	2.5

* When the complete bag is examined, each component shall be examined in addition to the complete bag assembly.

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, as indicated in table II.

Table II. Tests

Component (unit of product)	Characteristic	Req.	Test procedure	Sample unit	Insp. level	AQL
Duck, treated.	Mildew resistance	3.1.1.1		3	S-1	*

* Acceptance number shall be zero for all sample sizes.

4.2.3 Component materials. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the bags to perform tests as required by the applicable subsidiary specifications or by tests specified herein. When sample size for component materials covered by the subsidiary specifications is not specified, the sample size for each test shall be as indicated in 4.2.2. The unit of product for testing shall be the quantity of material necessary to perform all required tests one time each, taking into consideration the fact that, where possible, the same material may be used to perform two or more tests. Lot sizes are expressed in multiples of the following:

Duck.....Yards.
Thread.....Cone or spool.
Cord.....Yards.
Grommets.....Each (grommet plus washer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4.2.4 For chemical testing of metal. Four ounces of the metal used in the construction of the grommets shall be selected for chemical analysis as specified in 4.4.4.1.

4.3 Examination. The bags shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Dimensional examination. The bags shall be examined for defects in dimensions. Any dimension not within the tolerances specified herein or in the drawing shall be classified as a defect.

4.4 Tests. Tests shall be conducted, as necessary, to determine compliance with specification requirements.

4.4.1 Cotton duck. The unfinished duck shall be tested in accordance with the test procedure of CCC-C-419. The finished duck shall be tested in accordance with the test procedures of CCC-D-950, except that the performance of the tests for mildew inhibitor content and mildew resistance shall be conducted under the following conditions:

a. If the material conforms to the requirements for mildew inhibitor content, the mildew resistance test shall not be performed and the material shall be considered as complying with mildew resistance requirements.

b. If the mildew inhibitor content exceeds the maximum requirement, the material shall be rejected.

c. If the mildew inhibitor content is found to be below the minimum requirement, the material may be accepted with respect to mildew resistance, provided it passes the mildew resistance test, method 5762, as specified in the test section of CCC-D-950. When the mildew resistance test is performed, the leaching process shall be omitted.

4.4.2 Thread. The untreated thread shall be tested in accordance with the test procedures of V-T-276. The treated thread shall be tested as specified in the test section of MIL-T-3530.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4.4.3 Cord. The nylon cord shall be tested in accordance with the test procedures of MIL-C-5040.

4.4.4 Grommets. The grommets shall be tested in accordance with the test procedures of MIL-G-16491.

4.4.4.1 Chemical analysis of the metal (grommets). The samples selected in accordance with 4.2.4 shall be analyzed in comformance with methods 111 or 112 of Federal Test Method Standard No. 151. In case of dispute, method 111 shall be used for referee analysis.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. Each bag, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table III shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table III. Packaging quantities

Unit package	Intermediate package	Exterior container
1 unit	10 units	100 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Each unit shall be neatly folded and packaged in a carton of appropriate size and design constructed in accordance with PPP-B-566 or PPP-B-676, except that commercial colors are acceptable. Closure shall be adequate to prevent spilling of contents under normal handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

5.1.3.2 Intermediate package. Intermediate package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class weather-resistant. Boxes shall be closed by taping the top and bottom flaps with two inch wide tape conforming to PPP-T-76. Closing of bottom flaps with adhesive conforming to MMM-A-250, or metal stitches is permitted.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type I, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather-resistant. Closure and strapping shall be in accordance with appendix of applicable box specification.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table I, using type III, class 1 plywood; or shall be designed for type 2 load and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class domestic. Closure shall be in accordance with appendix of applicable box specification.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The gun crew first aid kit bag covered by this specification is intended to hold supplies for administering first aid to gun crews.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the items which are normally procured to meet Military requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Review activities:
Army - MD
Navy - MS
Air Force - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Category: N
Project number: 6545-1020

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-B-36039A

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACED EDITION OF 1 OCT 64, WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.