INCH/POUND
MIL-B-36039B
30 June 1989
SUPERSEDING
MIL-B-36039A
15 February 1968

MILITARY SPECIFICATION

BAG, GUN CREW FIRST AID KIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers an empty canvas case, fitted with a cord (drawstring) closure.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

VT-276	Thread, Cotton.
VT-285	Thread, Polyester
CCC-C-419	Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army and Numbered.
CCC-D-950	Dyeing and Aftertreating Processes for Cotton Cloths.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Boxes, Setup.

AMSC N/A FSC 6545

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Headquarters, Defense Personnel Support Center ATTN: Directorate of Medical Materiel DPSC-RST, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

Military

MIL-T-3530	Thread and Twine; Mildew-Resistant or Water Repellent Treated.
MIL-C-5040	Cord, Nylon.
MIL-L-10547	Liners, Case, Waterproof.
MIL-G-16491	Grommet, Metallic.

STANDARDS

Federal

FED-STD-151	Metals, Test Methods.
FED-STD-595	Colors.
FED-STD-751	Stitches, Seams, and Stitchings.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS 16686	Medical Services Symbol.

DRAWING

Defense Personnel Support Center

1365	Bag, Gun Crew First Aid Kit

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Color Association of the United States, Incorporated.

Department of Defense Standard Shades for Sewing Threads - 1968.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Color Association of the United States, Incorporated, 200 Madison Avenue, New York, NY 10016.)

3. REQUIREMENTS

3.1 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing listed herein, and be subjected to the tests and meet the requirements specified therein. The metal shall conform to the chemical requirements of the applicable specifications when tested as specified in 4.4.4.1. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

3.1.1 Body fabric. The body fabric, before finishing, shall be ply yarn cotton duck, 9.85 ounces per square yard, minimum, conforming to type III of CCC-C-419.

3.1.1.1 Color and treatment. The cotton duck shall be vat dyed olive drab No. 7, water-repellent and mildew-resistant conforming to type I, class B of CCC-D-950, except that the cloth shall be made mildew resistant by treatment limited to one of the following mildew inhibitors only:

a. 2, 2' methylene-bis-(4-chlorophenol).

b. Copper-8-quinolinolate.

3.1.2 Thread. The thread for all stitching, including bartacking, shall conform to V-T-276, type IA3, 4 ply, Ticket No. 16. All references to approved shade standard, standard sample, and standard shade shall not apply. Thread shall be tested as specified in 4.4.2. Thread conforming to Type I, Class 1, Size f of Federal Specification V-T-285 is accpetable as an alternate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

3.1.2.1 Color and treatment. The thread shall be vat dyed to match olive drab shade S-1, Cable No. 66022, of the Department of Defense Standard Shades for Sewing Threads - 1968. The cotton shall be mildew resistant in accordance with type 1, class 1 of MIL-T-3530.

3.1.3 Cord. The nylon cord shall be olive drab No. 7, conforming to type III of MIL-C-5040.

3.1.4 Grommets, brass. Brass grommets shall conform to type II, class 3, size No. 1 of MIL-G-16491.

3.2 Style and design. The bag shall have a square bottom and an open upper end. The open end shall be hemmed, and the outside surface of the hemmed portion shall be provided with two grommets to permit insertion of the cord. The upper end of the bag shall be provided with a flap.

3.3 Construction. Construction shall conform to the requirements specified herein, and as shown in drawing 1365.

3.3.1 Stitches, seams, and stitchings. All seams and stitchings shall be straight, conform to FED-STD-151, and consist of stitch type 301 with not less than eight evenly spaced stitches per inch, except that bartacking shall be 1/2 to 5/8 inch tacks with 1/8 inch bights, each made with not less that 28 stitches. Thread tension shall be properly maintained so that lock will be imbedded in the middle of the material sewed. As an alternate, stitch type 401 may be used to join sides of bag with seam type LSc-2. Double needle stitching for side seams, type LCs-2, shall be 3/16 to 5/16 inch gage, with the outer row of stitching 1/16 inch from the turned edge. As an alternate for construction of the three exposed sides of the nomenclature flap, hem stitching, type EFb-1, may be used. All seams shall be straight and evenly spaced.

3.3.1.1 Anchorage. The ends of each continuous row of stitches, including ends due to thread breaks, shall be anchored by backstitching for a length of not less than one inch, except where anchorage is provided by another seam or stitching.

3.3.1.2 Bar tacks. Bar tack shall be free of thread breaks and loose stitches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

3.3.2 Details. The bag shall be formed as shown in the drawing, from a body piece, a bottom piece, and a flap, all fabricated from duck as specified in 3.1.1.

3.3.2.1 Cords. Each cord shall be as specified in 3.1.3, shall be fastened to the bag within the hem, and pass through a grommet at the opposite end. Cords shall be bar tacked through the cord and reinforcement piece as shown in the drawing.

3.3.2.2 Grommet. The grommets for the cords shall be as specified in 3.1.4, and shall be securely attached on the outer surface of the hemmed portion of the body, and positioned as shown in the drawing.

3.3.2.3 Reinforcement piece. To reinforce the bag for the attachment of each grommet, there shall be provided a reinforcement piece made of duck as specified in 3.1.1 and as shown in the drawing. Both layers of the reinforcement piece and the outer surface of the hemmed portion of the body shall be firmly clinched between the grommet and the washer.

3.3.2.4 Attachment of grommet. Grommet shall be tightly clinched without cutting the duck. The hole punched in the duck to receive the grommet shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole.

3.4 Marking for identification. The bag shall be permanently and legibly marked with black waterproof paint or ink in accordance with the drawing, except for the red cross. A Geneva Red Cross on a white background shall be applied in the location shown on the drawing. Color of the cross shall be approximate Color 11105 (gloss red) as shown in FED-STD-595 and white background shall approximate color 17886 (gloss white) of the same specification. All marking shall be well defined, clearly legible, and shall not show smearing, bleeding, or offsetting and shall not show objectionable strike-through of the cloth to which applied.

3.5 Workmanship. The completed bags shall be clean and free from defects which detract from their appearance or may impair their serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may utilize his facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for Compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Inspection. Inspection, as used herein, is defined as both examination (such as visual, and investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. Inspection level and AQL shall be as shown in Table I.

TABLE I. Examination.

	Inspection level	AQL (percent defective)
For visual examination*		
Major defects (each component)	II	1.0
Minor defects (each component)	II	2.5
For dimensional examination	S-3	2.5

* When the complete bag is examined, each component shall be examined in addition to the complete bag assembly.

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, as indicated in Table II.

Table II. Tests.

Component (unit of product)	Characteristic	Req.	Test procedure	Sample unit	Insp. level	AQL
Duck, treated.	Mildew resistance	3.1.1.1		3	S-1	*

Acceptance number shall be zero for all sample sizes.

4.2.3 Component materials. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the bags to perform tests as required by the applicable subsidiary specifications or by tests specified herein. When sample size for component materials covered by the subsidiary specifications is not specified, the sample size for each test shall be as indicated in 4.2.2. The unit of product for testing shall be the quantity of material necessary to perform all required tests one time each, taking into consideration the fact that, where possible, the same material may be used to perform two or more tests. Lot sizes are expressed in multiples of the following:

Duck.....Yards
Thread.....Cone or spool
Cord.....Yards
Grommets.....Each (grommet plus washer)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4.2.4 For chemical testing of metal. Four ounces of the metal used in the construction of the grommets shall be selected for chemical analysis as specified in 4.4.4.1.

4.3 Examination. The bags shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Dimensional examination. The bags shall be examined for defects in dimensions. Any dimension not within the tolerances specified herein or in the drawing shall be classified as a defect.

4.3.2 Classification of defects. Examination shall be conducted in accordance with the following classification of defects:

Major	
101	Any component missing.
102	Any required operation omitted or improperly performed.
103	Any hole, cut, tear, mend, patch, or unauthorized splice.
104	Needle chews that may develop into hole.
105	One or more spots or stains of an obviously permanent nature.
106	Seam type other than specified.
107	Stitch type other than specified.
108	Less than 8 stitches per inch.
109	Any open seams - 1/2 inch or more.
110	Markings missing, incorrect or illegible.

Minor	
201	One or more removable spots or stains clearly noticeable.
202	Thread ends not trimmed.
203	Any part of bag pleated, twisted, or caught in any unrelated row of stitching.
204	Broken or skipped stitch not amounting to an open seam.
205	Seams not straight and evenly spaced.
206	Stitch tension tight, causing puckering.
207	Thread breaks not backstitched for 1 inch.
208	Color of markings not uniform.

4.4 Tests. Tests shall be conducted, as necessary, to determine compliance with specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

4.4.1 Cotton duck. The unfinished duck shall be tested in accordance with the test procedure of CCC-C-419. The finished duck shall be tested in accordance with the test procedures of CCC-D-950, except that the performance of the tests for mildew inhibitor content and mildew resistance shall be conducted under the following conditions:

a. If the material conforms to the requirements for mildew inhibitor content, the mildew resistance test shall not be performed and the material shall be considered as complying with mildew resistance requirements.

b. If the mildew inhibitor content exceeds the maximum requirement, the material shall be rejected.

c. If the mildew inhibitor content is found to be below the minimum requirement, the material may be accepted with respect to mildew resistance, provided it passes the mildew resistance test, method 5762, as specified in the test section of CCC-C-950. When the mildew resistance test is performed, the leaching process shall be omitted.

4.4.2 Thread. The untreated thread shall be tested in accordance with the test procedures of V-T-276. The treated thread shall be tested as specified in the test section of MIL-T-3530.

4.4.3 Cord. The nylon cord shall be tested in accordance with the test procedures of MIL-C-5040.

4.4.4 Grommets. The grommets shall be tested in accordance with the test procedures of MIL-G-16491.

4.4.4.1 Chemical analysis of the metal (grommets). The samples selected in accordance with 4.2.4 shall be analyzed in conformance with methods 111 or 112 of Federal Test Method Standard No. 151. In case of dispute, method 111 shall be used for referee analysis.

4.5 Inspection of packaging. The sampling and inspection of the packaging and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C, as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Unit package. Each bag shall be neatly folded to approximately 8-1/4 by 7-3/4 inches and inserted in a snug fitting, flat style, clear, heat sealed polyethylene bag having a minimum thickness of 0.00125 inches. A 1/4 inch diameter hole shall be made at one corner of the polyethylene bag to allow excess to escape.

5.1.1.2 Intermediate package. Ten unit packages containing bag shall be packaged in a box conforming to PPP-B-566, PPP-B-636, class domestic or PPP-B-676. Closure shall be as specified in the applicable box specification.

5.1.2 Level C.

5.1.2.1 Unit package. Preservation for bags shall conform to the requirements of MIL-STD-794 for level C.

5.1.2.2 Intermediate package. Ten unit packages shall be packaged in accordance with the requirements of MIL-STD-794 for level C.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.1).

5.2.1 Level A. Ten intermediate packages (100 units) containing bags shall be packed in an exterior container designed for a type 2 load and conforming to PPP-B-601, overseas type, PPP-B-621, class 2, or PPP-B-636, class weather-resistant. Closure and strapping shall be as specified in the applicable box specification.

5.2.1.1 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall be as specified in the liner specification. Case liner shall not be required for fiberboard boxes. Each fiberboard box shall be waterproofed as specified in PPP-B-636.

5.2.2 Level B. Ten intermediate packages (100 units) containing bags shall be packaged in an exterior container designed for a type 2 load and conforming to PPP-B-601, domestic type, PPP-B-621, class 1, or PPP-B-636, class domestic. Closure shall be as specified in the applicable box specification.

5.2.3 Level C. The level C packing for bags shall be packed in accordance with the requirements of MIL-STD-794 for level C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

5.2.4 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.2.5 Unitized loads. Unitized load, commensurate with the level of packing specified in the contract or order, shall be used whenever total quantities for shipment to one destination exceed 250 pounds or 20 cubic feet. Loads shall be unitized on pallets conforming to MIL-STD-147. Quantities less than 20 cubic feet need not be unitized. Pallet loads including the pallet shall not exceed 43 inches in length, 52 inches in width, and 54 inches in height. Pallet shall conform to Type IV or Type V.

5.2.5.1 Levels A and B. Bag packed as specified in 5.2.1 and 5.2.2 shall be unitized on pallets as specified in 5.2.5.

5.2.5.2 Level C. Bag packed as specified in 5.2.3 shall be unitized as specified in MIL-STD-794.

5.3 Marking.

5.3.1 Levels A, B, and C. Each unit package, exterior ontainer and unitized load shall be marked as specified in MIL-STD-129.

5.4 General.

5.4.1 Exterior container. Exterior container (see 5.2.1, 5.2.2, and 5.2.3) shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered items to the greatest extent practicable.

5.4.2 Packaging inspection. The inspection of these packaging requirements shall be in accordance with 4.5.

6. NOTES

6.1 Intended use. The gun crew first aid kit bag covered by this specification is intended to hold supplies for administering first aid to gun crews.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Subject items (Key Word Listing).

Backstitching
Bartacking
Color
Fabric Treatment
Grommet
Mildew-Resistant
Stitching
Water-Resistant

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet military requirements.

6.5 This specification covers the following item listed in the Federal Supply Catalog:

NSN	Item Identification
6545-00-911-8725	BAG, GUN CREW FIRST AID KIT

Custodians:

Army - MD
Navy - MS
Air Force - 03

Preparing activity:

DoD - MB

Agent:

DLA - DM

Review Activities:

Army - MD
Navy - MS
Air Force - 03

Project No. 6545-0086

Location: Disk No. 14
MIL/BAG/GUN-CREW/S3B

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Staff Director
Defense Medical Material Board
Fort Detrick
Frederick, MD 21701

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2020-10-21T06:00Z
Check the source to verify validity of this document before use.