MILITARY SPECIFICATION

CASE, MEDICAL INSTRUMENT AND SUPPLY SET, NONRIGID, NO. 5, EMPTY

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers an empty canvas case for use by parachutists in carrying a large supply of medical supplies when jumping. Case is to be packed in the field.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

V-F-106 — Fasteners, Slide; Interlocking.

V-T-291 — Thread, Linen.

CCC-C-419 — Cloth, Cotton, Duck, Plied-Yarns (Army and Numbered).

CCC-T-191 — Textile Test Methods.

DDD-S-751 — Stitches; Seams; and Stitching.

PPP-B-585 — Boxes, Wood, Wirebound.

PPP-B-601 — Boxes, Wood, Cleated-Plywood.

PPP-B-621 — Boxes, Wood, Nailed and Lock-Corner.

PPP-B-636 — Boxes, Fiber.

PPP-B-676 — Boxes, Set-Up, Paperboard.

MILITARY

MIL-D-504 — Dyeing and After-treating Processes for Cotton Duck and Twill.

MIL-W-530 — Webbing, Textile, Cotton, General Purpose, Natural or in Colors.

MIL-B-543 — Buckles, Tongueless and Web Strap.

MIL-L-3129 — Life Preservers, Jacket Type, Fibrous Glass.

MIL-T-3530 — Treatment, Mildew-Resistant, for Thread and Twine.

MIL-B-10377 — Box, Wood, Cleated, Veneer, Paper Overlaid.

MIL-L-10547 — Liners, Case, Waterproof.

STANDARDS

AIR FORCE-NAVY AERONAUTICAL

AN227 — Fasteners—Snap and Curtain.

FEDERAL

Fed. Test Method Std. No. 151 — Metals; Test Methods.

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

MIL–STD–129 — Marking for Shipment and Storage.

MS16686 — Medical Services Symbol.

DRAWING.

MILITARY MEDICAL SUPPLY AGENCY

20052 — Case, Medical Instrument and Supply Set, Nonrigid, No. 5, Empty (7 sheets).

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

COLOR ASSOCIATION OF THE UNITED STATES, INC.

United States Army Standard Color Card for the Official Standardized Shades of Sewing Threads.

United States Army Color Card of Standard Shades for Slide Fastener Tapes.

(Application for copies should be addressed to the Color Association of the United States, Inc., 200 Madison Avenue, New York 16, N.Y.)

3. REQUIREMENTS

3.1 Component parts. The case consists of a large compartment (the case proper), three smaller compartments (a large pocket and two small pockets), two shoulder straps, four adjusting straps, and two "D" rings with retainers. The case proper is fitted with a slide fastener, and the pockets with curtain type fasteners. Attached to, and within the case proper, are four small pockets, a partition, two tie ribbons, and an insert fitted with retaining loops for six vials. Each adjusting strap includes a tongueless double bar buckle and a snap hook. Two of the adjusting straps are attached to the shoulder straps, while the other two are assembled to the case proper by attachments, one of which is small and one large.

3.2 Materials. Except as specified herein, materials shall conform to the applicable portions of the specifications and drawing listed in section 2, and be subjected to the tests and requirements specified therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in 4.4.3. When materials to be used are not specifically designated, those used shall be entirely suitable for the purpose intended.

3.2.1 *Body fabric.* The body fabric, before finishing, shall be ply yarn cotton duck conforming to Specification CCC–C–419, for type I, No. 10, hard texture, as shown in table I of the same specification.

3.2.1.1 *Color and treatment.* Cotton duck shall be vat dyed olive drab No. 7, water-repellent and mildew-resistant, conforming to type I, class B of Specification MIL–D–504, except that the cloth shall be made mildew-resistant by treatment limited to two mildew-inhibitors only: (a) dihydroxydichlorodiphenyl methane, or (b) copper-8-quinolinolate, in accordance with the requirements as shown in table III of the same specification (see 4.4.1.1).

3.2.2 *Webbing.* Webbing shall conform to the requirements of Specification MIL–W–530, shall be class 4, and shall be of the types and widths as shown on Drawing 20052. Webbing shall be vat dyed olive drab No. 7 (see 4.4.1.2).

3.2.3 *Thread, linen.* Except as specified herein, the thread for all stitching shall conform to Specification V–T–291, and shall be type B, 3-ply, class 1. It shall be vat dyed olive drab shade S–1 conforming to U. S. Army Standard Color Card. All references to "approved shade standard", "approved standard shade", and "approved shade sample" made in Specification V–T–291 shall not apply. The finished thread shall show good colorfastness to laundering, chlorine bleaching, and weather. Paragraph titled: "Certification" of Specification V–T–291 shall not apply (see 4.4 1.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

3.2.3.1 *Mildew-resistance.* The thread shall be treated for mildew-resistance in accordance with Specification MIL-T-3530, using class 1 mildew-inhibiting agent (see 4.4.1.3).

3.2.4 *Fasteners, slide.* Except as specified herein, slide fasteners shall conform to Specification V-F-106. Slide fasteners shall be type I, style No. 18, class B, size H, two slider, with wire stirrup pulls fitted with webbing thongs as specified in 3.2.4.2. The metal parts shall be zinc alloy with white metal finish. The thongs shall be fabricated from webbing as shown on the drawing. The tapes shall be vat dyed olive drab shade S, conforming to U. S. Army Standard Color Card of Standard Shades for Slide Fastener Tapes, and shall be water-repellent and mildew-resistant. Mildew-resistance shall be obtained by treatment of the tape with a mixture of zinc salts of dimethyl dithiocarbamate in accordance with the requirements shown in table III of Specification MIL-D-504 (see 4.4.1.4.2).

3.2.4.1 *Water-repellence.* The finished tape shall be tested as specified in 4.4.1.4.1.

3.2.4.2 *Webbing for thongs.* Webbing for slide fastener pull thongs shall have the dimensions and strength as shown on the drawing, shall be vat dyed olive drab to match the tape specified in 3.2.4, and shall be water-repellent and mildew-resistant. Water-repellence and mildew-resistance shall be obtained by the methods as specified for the webbing in 3.2.2. Compliance with the requirements for water-repellence and mildew-resistance shall be determined as specified in 4.4.1.2.

3.2.4.3 *Salt spray resistance.* The slide fasteners shall be tested as specified in 4.4.1.4.4. The fasteners shall meet the requirements specified in Specification V-F-106 for class A fasteners.

3.2.5 *Snap hooks.* The snap hooks shall be made of brass or bronze with a black oxidized finish, and shall be of the style and design as shown on the drawing. The dimensions of the snap hooks shall be as shown on the drawing and shall be suitable for use with type III webbing, 1 inch wide. The snap hooks shall be tested as specified in 4.4.2.1, and shall be capable of withstanding, without breaking, a force of 360 pounds.

3.2.6 *Rings, "D".* "D" rings shall be made of brass or bronze with a black oxidized finish, and shall conform to the style and design as shown on the drawing. If wire is used to fabricate the rings, the ends shall be brazed. The dimensions of the "D" ring shall be as shown on the drawing, and shall be suitable for use with type IIB webbing, 1 inch wide. The "D" rings shall be tested as specified in 4.4.2.2, and shall be capable of withstanding, without breaking, a force of 360 pounds.

3.2.7 *Buckles, tongueless, double bar.* Buckles shall conform to Specification MIL-B-543 for type II, class 1, 1-inch, and shall be made of brass or bronze

3.2.8 *Fasteners, curtain type, large.* Curtain type fasteners shall conform to 19BS post stud, 20B plate, 15BS socket and 16B plate as shown on Standard AN227. Material shall be brass

3.3 **Construction.** Construction of the case shall conform in all details to the requirements specified herein and as shown on the drawing

3.3.1 *Stitches, seams, and stitching.* All seams and stitching shall conform to Specification DDD-S-751, shall be straight, and shall consist of type 301 stitches formed by machine, with not less than six evenly spaced stitches per inch Thread tension shall be properly maintained so that the lock will be imbedded in the center of the materials sewed.

3.3.1.1 *Anchorage* The ends of each continuous row of stitches (including ends due to thread breaks) shall be anchored by backstitches for a length of not less than 1 inch, except where anchorage is provided by another seam or stitching.

3.3.2 *Attachment of "D" ring retainer to case* The "D" ring retainer shall be attached

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

to the case as shown on the drawing. The "D" ring assembly ("D" ring, retainer, and attachment to case) shall be capable of withstanding, without breaking, a force of 360 pounds. The assembly shall be tested as specified in 4.4.2.2.

3.3.3 *Attachment of snap hooks to adjusting straps.* The snap hooks shall be attached to the adjusting straps as shown on the drawing. The snap hook and adjusting strap assemblies shall be capable of withstanding, without breaking, a force of 360 pounds. The assemblies shall be tested as specified in 4.4.2.1.

3.3.4 *Attachment of straps.* All attachments of straps to the case, and attachments of straps to each other, by sewing, shall be capable of withstanding, without breaking, a force of 360 pounds. The attachment of straps shall be tested as specified in 4.4.2.3

3.3.5 *Attachment of fasteners, curtain type, large.* Holes shall be punched in the fabric before insertion of the tube of the male element and prongs of the female element. Holes shall be small enough to require tubes and prongs to be forced through Fastener elements shall be tightly clinched so as not to become detached from the fabric in normal use.

3.4 Marking for identification.

3.4.1 Each case shall be legibly and permanently marked in black in accordance with sheet 7 of the drawing.

3.5 Workmanship. Workmanship shall be first class throughout. The finished cases shall be clean, well made, and free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibilities for inspection. Such examinations and tests as are set forth in this specification or as shall otherwise be appropriate or necessary to insure that the supplies conform to specification requirements, shall be performed by and at the expense of the supplier. Suppliers who do not have facilities adequate for such tests shall arrange for the use of test facilities acceptable to the Government. Records of examinations and tests performed by the supplier shall be maintained by the supplier and made available to the Government, upon the Government's request, at any time, or from time to time, for a period of 2 years after delivery of the supplies to which such records relate.

4.1.1 Inspection, as used in this specification, is defined as both examination (such as visual, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 *Certificates of quality.* When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.1.3 Government furnished material shall not be sampled or tested unless specifically requested by the Government (see 6.3).

4.2 Sampling. Sampling shall be conducted in accordance with Standard MIL–STD–105, and appendix thereto.

	Inspection level	*AQL (percent defective)*	*Minimum sample size*
For visual examination			
Major defects	II	1.0	..... --
Total (major and minor combined) defects	II	4.0	---- --
For dimensional examination	L5	2.5	--
For end item testing			
Each test	L2	*	3
For component material testing	L2	*	3

* Acceptance number shall be zero (0) for all sample sizes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

4.2.1 *For chemical analysis of metals.* Four (4) ounces of each lot of each metal used in the construction of the case shall be selected for chemical analysis as specified in 4.4.3.

4.2.2 *Component materials.* Sufficient samples of the components shall be selected from each lot of raw materials to perform tests as required by the applicable subsidiary specifications and by tests specified herein. When sample size for components covered by subsidiary specifications is not specified, the sample size for each test shall be as indicated in 4.2. No test result shall fall below the minimum or exceed the maximum values specified. The sample unit for testing shall be the quantity necessary to perform all required tests one time each. Lot sizes are expressed as follows:

Duck	Yards.
Webbing	Yards.
Tape	Yards.
Thread	Cone or spool.
Fasteners, curtains type	Each (male and female elements).
Slide fasteners	Each
Buckles	Each.
"D" rings	Each.
Snap hooks	Each.

4.2.3 Where possible, the same sample unit shall be used for the determination of two or more test characteristics.

4.3 **Examination.** The case shall be examined to determine compliance with all requirements contained in this specification. Nonconformance with these requirements will be permitted to the extent indicated in 4.2.

4.3.1 *Classification of defects for visual examination.* Examination shall be conducted in accordance with the following classification of defects:

Major	Categories and defects**
101.	Case not complete with all specified component parts.
102	Ends of stitch rows not properly anchored by backstitching for at least 1 inch
103.	Curtain type fasteners not properly located and not firmly attached to appropriate fabric components.
104.	Curtain type fasteners fail to function properly.
105	Slide fasteners fail to open and close fully or operate smoothly without jamming.
106.	Metal parts not free of cracks, burs, or sharp edges.
107	Tongue of snap hooks not properly set in closed position.
108.	Snap hooks fail to function (open and close) properly.
109	Textile components not free of cuts, holes, and tears.
110	Seams not free of dropped or damaged stitches (not suitably repaired).
111.	Color of cotton duck, thread, webbing, and slide fastener tape and thong webbing not as specified.
112	Wire stirrup pulls and webbing thongs missing from slide fastener.
Minor	
201.	Stitching not evenly spaced with a pitch 6 stitches per inch.
202.	Finish applied to metal components not as specified, or not free of chipped, excessively scratched, or bare areas.
203	Identification marking not present or not as specified
204	Medical Services Symbol marking not present or not as specified.
205	Labels or printing on unit packages not legible and free of defacing marks, scratches, or tears.

** Examination is not restricted to the classified possible defects listed above

4.3.2 *Dimensional examination.* The case shall be examined for defects in dimensions. Any dimension not within the tolerance specified herein shall be classified as a defect.

4.4 **Tests.** Tests of the materials used in fabrication of the cases shall be made as specified herein. Other tests may be made, as necessary, to determine that the finished cases comply with this specification, and that the materials comply with the applicable portions of the specifications, standards, and drawing listed in section 2.

4.4.1 *Material testing.*

4.4.1.1 *Cloth, cotton, duck.* The unfinished duck shall be tested in accordance with the test procedures of Specification CCC-C-419 (see 3.2.1). The finished duck shall be tested in accordance with test procedures of Specifi-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

cation MIL–D–504, except that performance of the tests for mildew-inhibitor content and mildew-resistance shall be conducted under the following conditions:

(a) If the material conforms to the requirements for mildew-inhibitor content, the mildew-resistance tests shall not be performed, and the material shall be considered as complying with mildew-resistance requirements.

(b) If the mildew-inhibitor content exceeds the maximum requirement, the material shall be rejected.

(c) If the mildew-inhibitor content is found to be below the minimum requirement, the material may be accepted with respect to mildew-resistance provided it passes the mildew-resistance test, method 5762, as specified in the test section of Specification MIL–D–504. When the mildew-resistance test is performed, the leaching process shall be omitted, and the breaking strength shall be determined by method 5100 of Specification CCC–T–191.

4.4.1.2 *Tests on webbing.* The webbing shall be tested in accordance with the test procedures of Specification MIL–W–530, except that the performance of the tests for mildew-inhibitor content and mildew-resistance shall be conducted under the following conditions:

(a) If the material conforms to the requirements for mildew-inhibitor content, the mildew-resistance tests shall not be performed, and the material shall be considered as complying with mildew-resistance requirements.

(b) If the mildew-inhibitor content exceeds the maximum requirement, the material shall be rejected.

(c) If the mildew-inhibitor content is found to be below the minimum requirement, the material may be accepted with respect to mildew-resistance provided it passes the mildew-resistance test.

4.4.1.2.1 *Mildew-resistance.* The finished webbing shall be tested in accordance with method 4762 as specified in the test section of Specification MIL–W–530. The leaching process shall be omitted.

4.4.1.2.2 *Water absorption.* The finished webbing shall be tested for water absorption by method 5500 as specified in the test section of Specification MIL–W–530, except that the size of the specimen and the size of the blotting paper shall conform to method 5502 of Specification CCC–T–191.

4.4.1.3 *Thread.* The untreated thread shall be tested in accordance with the test procedures of Specification V–T–291 (see 3.2.3). The treated thread shall be tested as specified in the test section of Specification MIL–T–3530, except that the performance of the tests for mildew-inhibitor content and mildew-resistance shall be conducted under the following conditions:

(a) If the material conforms to the requirements for mildew-inhibitor content, the mildew-resistance test shall be performed, and the material shall be considered as complying with mildew-resistance requirements.

(b) If the mildew-inhibitor content exceeds the maximum requirement, the material shall be rejected.

(c) If the mildew-inhibitor content is found to be below the minimum requirement, the material may be accepted with respect to mildew-resistance provided it passes the mildew-resistance test. The mildew-resistance shall be determined by either the soil burial method (20 percent loss in tensile strength, 14 days) or the direct inoculation method. The leaching process on the test specimens shall be omitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

4.4.1.3.1 *Colorfastness to laundering.* The finished thread shall be tested for colorfastness to laundering by method 4610 of Specification CCC-T-191.

4.4.1.4 *Slide fasteners.* The slide fasteners shall be tested as specified in Specification V-F-106, except as modified herein.

4.4.1.4.1 *Water repellency.* The finished tape shall be tested for water repellency as specified in the test section of Specification V-F-106. The method used shall be 5500 of Specification CCC-T-191, except that the size of the specimen and the size of the blotting paper shall conform to method 5502 of the same specification.

4.4.1.4.2 *Mildew-inhibitor content.* The zinc salts content of the finished slide fastener tape shall be determined as specified in the test section of Specification MIL-D-504. Performance of the tests shall be conducted under the following conditions:

(a) If the material conforms to the requirements for the mildew-inhibitor content, the test specified in 4.4.1.4.3 shall not be required and material shall be considered as complying with the mildew-resistance requirements.

(b) The material shall be rejected if the mildew-inhibitor content is found to exceed the maximum requirements.

(c) If the mildew-inhibitor content is found to be below the minimum requirements, the material may be accepted with respect to mildew-resistance provided it passes the test specified in 4.4.1.4.3.

4.4.1.4.3 *Mildew - resistance.* The finished slide fastener tape shall be subjected to the 14-day soil burial test by method 4762 of Specification CCC-T-191, except that the leaching process shall be omitted. The test specimens shall include the chain. At the end of the test, the slide fastener crosswise shall meet the requirements of Specification V-F-106 for the minimum breaking strength of the fastener specified.

4.4.1.4.4 *Salt spray resistance.* The slide fasteners shall be tested in accordance with salt spray test specified in the test section of Specification V-F-106.

4.4.2 *End item testing.*

4.4.2.1 *Snap hooks.* A section of each adjusting strap with snap hook, including the buckle, shall be taken for test. The snap hook shall be engaged by a suitable "D" ring attached to a suitable piece of webbing ("D" ring and webbing shall be capable of withstanding, without breaking, a force of 360 pounds). The adjusting strap and the piece of webbing holding the "D" ring shall be clamped for testing in the jaws of a tensile testing machine. The rate of separation of the jaws during the test shall be approximately 12 inches per minute, and the initial separation approximately 10 inches.

4.4.2.2 *"D" ring assembly.* The "D" ring shall be engaged by a snap hook mounted on a piece of webbing (hook and webbing shall be capable of withstanding, without breaking, a 360 pound force) which is held in one of the jaws of a tensile testing machine. The shoulder strap diagonally opposite the "D" ring, together with sufficient duck to provide a double thickness for clamping in the tensile testing machine, shall be clamped in the other jaw in such a manner that the stress on the "D" ring assembly will be in line with its long axis. The rate of separation of the jaws of the testing machine during the test shall be approximately 12 inches per minute.

4.4.2.3 *Tests of strap attachments.*

4.4.2.3.1 *Attachment of adjustment strap to shoulder strap.* Attachment of adjustment strap to shoulder strap shall be tested by clamping the shoulder strap in one jaw of a tensile testing machine and the adjusting strap in the other, then separating the jaws at the rate of approximately 12 inches per minute. The distance between jaws with the specimen

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

in place, ready for testing, shall be approximately 10 inches

4.4.2.3.2 *Attachment to case of small adjusting strap attachment.* Attachment to case of small adjusting strap attachment shall be tested by clamping the small adjusting strap and the shoulder strap on the opposite side of the case to opposing jaws of a tensile testing machine, in such a manner that the stress on the small adjusting strap attachment will be in line with its long axis. Sufficient canvas duck shall be allowed to remain about the attachment areas to provide a double thickness for clamping in the tensile tester. The rate of separation of the jaws of the testing machine during the test shall be approximately 12 inches per minute.

4.4.2.3.3 *Attachment to case of large adjusting strap attachment.* Attachment to case of large adjusting strap attachment shall be tested by clamping the large adjusting strap and the "D" ring retainer, together with sufficient canvas duck to allow a double thickness for clamping in the tensile tester, on the opposite corners of the case to opposing jaws of a tensile strength testing machine, in such a manner that the stress on the large adjusting strap attachment will be in line with its long axis. The rate of separation of the jaws of the testing machine during the test shall be approximately 12 inches per minute.

4.4.3 *Chemical analysis.* The samples selected in accordance with 4.2.1 shall be analyzed in conformance with method 111 or 112 of Fed. Test Method Std. No. 151. In case of dispute, method 111 shall be used for referee analysis.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 *Unit of issue.* One (1) case, as specified constitutes one unit

5.1.2 *Packaging quantities.* The number of units of issue indicated in table I shall be packaged in each unit and exterior container, as applicable, for the required level of protection specified in procurement documents.

TABLE I. *Packaging quantities*

Federal stock number	Unit package	Intermediate package	Exterior container
6545–912–9890	1 unit	Not required	24 units

5.1.2.1 *Packing variation permitted.* If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.1.3 *Level A.*

5.1.3.1 *Unit package.* Each unit shall be packaged in a carton of appropriate size constructed in accordance with Specification PPP–B–636, type I, class 1, or PPP–B–676 Closure shall be adequate to prevent spillage of contents under normal handling.

5.2 Packing.

5.2.1 *Level A.*

5.2.1.1 *Exterior container.* Exterior container shall be designed for type 2 load and constructed in accordance with Specification PPP–B–585, style 3, for class 3 use; PPP–B–601, table II, using type III, class 1 plywood; PPP–B–621, table III; or MIL–B–10377, table II.

5.2.1.2 *Case liner.* Each level A box shall be lined with a waterproof case liner conforming to Specification MIL–L–10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto.

5.2.1.3 *Strapping* Strapping, when required, shall be in accordance with applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.

NOTE. Strapping will not be required for shipment forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 *Level B*

5.2.2.1 *Exterior container.* Exterior container shall conform to Specification PPP-B-601, table I, using type III, class 1 plywood, or shall be designed for type 2 load and constructed in accordance with Specification PPP-B-585, style 3, for class 2 use; PPP-B-621, table I, or MIL-B-10377, table I.

5.3 **Marking.**

5.3.1 *Unit package.* Each unit package shall be marked in accordance with Standard MIL-STD-129.

5.3.2 *Exterior container* Exterior container shall be marked in accordance with Standard MIL-STD-129, except that 6.2(c), 6.2(d), 6.5, and 7.5.1 shall not be applicable. Service color and service symbol markings are required only on direct shipments from the contractor's plant to overseas activities

6. NOTES

6.1 **Intended use.** The Case, Medical Instrument and Supply Set, Nonrigid, No. 5, Empty, is intended to be used by medical parachutists to pack and carry medical supplies as required. It is issued empty and filled with necessary material at the direction of the medical officer. The material should be selected so that the weight of the filled case does not exceed 30 pounds.

6.2 The snap hooks and "D" rings are generally similar to the snap hooks and "D" rings specified in Specification MIL-L-3129.

6.3 **Ordering data.** Procurement documents should specify the following:

(a) Number and date of this specification.

(b) When sampling or testing of Government supplied material is required (see 4.1.3).

(c) Selection of applicable levels of packing (see 5.2).

6.4 This specification covers the following item appearing in the Federal Supply Catalog, Department of Defense Section for Medical Materiel:

6545-912-9890 CASE, MEDICAL INSTRUMENT AND SUPPLY SET, Nonrigid, No 5, Empty.

6.5 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

6.6 **Transportation description.** Transportation description applicable to this item is:

Haversacks, knapsacks or pack carriers in boxes.

Carload minimum weight 30,000 pounds per Uniform Freight Classification

Truckload minimum weight 30,000 pounds per National Motor Freight Classification

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto

Custodians:
Army—Army Medical Service
Navy—Bureau of Medicine and Surgery
Air Force

Preparing activity.
Navy—Bureau of Medicine and Surgery (MMSA)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:58Z
Check the source to verify that this is the current version before use.