MIL-I-35085C
13 July 1978
SUPERSEDING
MIL-I-35085B
26 January 1973

MILITARY SPECIFICATION

ICING MIX POWDER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers icing mix powders which, when mixed with water, may be used as icing on bakery products and are intended for use by the Armed Forces.

1.2 Classification. The product shall be of the following flavors, as specified (see 6.1):

Flavor 1 - Vanilla
Flavor 2 - Chocolate
Flavor 3 - Other flavors, as specified (see 6.1)

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing Of.
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Natick Research and Development Command, ATTN: DRDNA-ES, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8925

Source: https://assist.dla.mil -- Downloaded: 20261O-21T07:55Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items.
MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-668 - Sanitary Standards for Food Plants.

(Copies of specifications and standards, required by contractors in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

US DEPARTMENT OF HEALTH, EDUCATION AND WELFARE

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

Definitions and Standards for Cocoa Products.

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

US DEPARTMENT OF AGRICULTURE

US Standards for Grades of Nonfat Dry Milk (Spray Process)

Official Grain Standards of the United States SRA-AMS-177

(Application for copies should be addressed to the Food Safety and Quality Service, US Department of Agriculture, Washington, DC 20250.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

NATIONAL RESEARCH COUNCIL

Food Chemicals Codex (F.C.C.)

(Application for copies should be addressed to the Office of Director, National Academy of Science, National Research Council, 2101 Constitution Ave., N.W., Washington, DC 20418.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS

Official Methods of Analysis of the Association of Official Analytical Chemists.

(Application for copies should be addressed to the Association of Official Analytical Chemists, Box 540, Benjamin Franklin Station, Washington, DC 20044.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

E 380 Standard for Metric Practice.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for references from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. All material shall be edible, clean, sound, wholesome, and free from any foreign odors, flavors, or extraneous matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

* 3.1.1 Confectioner's sugar. Confectioner's sugar shall be of the type in the range of 10X to 12X granulation.

* 3.1.2 Corn sirup solids. Corn sirup solids shall be the free flowing dry solids of corn sirup and shall have a dextrose equivalent of 28 ± 2.

3.1.3 Shortening. Shortening shall be hydrogenated vegetable oil and shall contain 2.7 ± 0.3 percent alpha monoglyceride (monostearine) and 0.7 ± 0.1 percent polysorbate 60 emulsifier (polyoxethylene (20) sorbitan monostearate). The free-fatty acid content shall be not more than 0.10 percent; the peroxide value shall be not more than 1.0 milliequivalents of peroxide per kilogram; th fat stability shall be not less than 70 hours (anti-oxidant may be used); Wiley melting point shall be 117°F ± 3°F (47°C ± 1°C); moisture and volatile matter shall be not more than 0.1 percent; and Lovibond color shall be 15 yellow/2.2 red maximum (applicable only when imitation vanilla icing mix is being procured). Solid fat index shall be within the following ranges:

*

°F	°C	Solid fat index
50	(10°C)	27-33
70	(21°C)	21-27
92	(33°C)	14-20
104	(40°C)	9-13

3.1.4 Salt. Salt shall be white, refined, free-flowing sodium chloride with or without anticaking agents. Iodized salt shall not be used.

3.1.5 Cocoa. Cocoa powder shall be made from the nibs of domestically roasted, mature, well-fermented cocoa beans which had been properly dried. It shall meet the Definitions and Standards for Cocoa Products of the Federal Food, Drug, and Cosmetic Act, as specified for medium fat cocoa, it shall be of a natural process cocoa. When washed with petroleum ether, not less than 99.0 percent shall pass through a U. S. Standard No. 140 sieve.

3.1.6 Flavoring. The flavoring shall be vanilla, vanillin or ethyl vanillin, or a combination thereof.

3.1.7 Other flavors. When other flavors are specified, they shall comply with requirements of 3.1 and shall possess flavor and color typical of the flavor designated.

* 3.1.8 Nonfat dry milk solids. The nonfat dry milk solid shall conform to US Extra Grade of the low or medium heat classification in accordance with the US Standards for Grade of Nonfat Dry Milk (Spray Process). In addition, milk shall be spray dried not more than 90 days prior to the time icing mix is manufactured.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

3.1.9 Sodium silicoaluminate. Sodium silicoaluminate may be used as an optional anticaking agent. It shall comply with the requirements of the Food Chemical Codex.

3.1.10 Flour, hard, wheat. Hard wheat flour shall be milled from hard red winter wheat as defined in the Official Grain Standards of the United States.

3.1.11 Emulsifier. The emulsifier shall be a free flowing powder derived from vegetable origin consisting of sorbitan monostearate, glyceryl monostearate, propylene glycol monostearate and polysorbate 60 with nonfat dry milk solids as a filler. Alternatively, an emulsifier system which will produce equivalent results may be used providing the resultant icing meets all other requirements of the specification. The emulsifier may be incorporated by the shortening manufacturer.

3.1.12 Starch. Starch shall be derived from either tapioca, waxy maize, dent or a combination thereof. It shall be modified or pregelatinized starch Starch, when used, shall result in a finished product which meets the requirements of 3.3.

* 3.2 Formula. The product shall be prepared according to the following formula:

Ingredients	Percent by weight	
	Vanilla	Chocolate
Confectioner's sugar	67.7	58.6
Shortening	14.0	13.8
Corn sirup solids	9.0	9.0
Cocoa	-	9.0
Flour, hard wheat 1/	5.0	5.0
Nonfat dry milk solids	3.0	3.0
Salt	0.2	0.5
Flavoring	0.1	0.1
Emulsifier	1.0	1.0
Sodium silicoaluminate	2/	2/

Sift all dry ingredients before use. Blend dry ingredients thoroughly before incorporating shortening. Mix until shortening is thoroughly dispersed.

1/ Starch - starch may be used in place of hard wheat flour at 100% level of substitution.

2/ If sodium silicoaluminate is used as a flowing agent, the amount used shall be removed from the sugar. Not more than 1.0 percent shall be used in the formulation.

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:55Z
Check the source to verify that this is the currentversion before use.

3.3 Finished product. The finished product shall be uniformly blended, free from undesirable flavors or odors, free from lumps that do not fall apart under light pressure, and free from foreign materials.

* 3.3.1 Moisture content. The finished product shall meet the following requirement.

Vanilla	not more than 1.8 percent moisture
Chocolate	not more than 2.3 percent moisture

* 3.3.2 Prepared product. The icing, when prepared according to directions (see 5.4.2), shall possess a creamy, uniform texture, free from graininess and consistency devoid of cocoa, color, or shortening specks. It shall be easy to spread and shall possess high sheen and flavor and color typical of the product. The icing shall set within 30 minutes at room temperature without any curdling or visible free water.

3.4 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

3.5 Workmanship. The product shall be prepared, processed and packaged under modern sanitary conditions and in accordance with good commercial practice. The product shall be prepared in plants meeting the requirements of MIL-STD-668.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preacceptance inspection. The product shall be rejected if produced in plants not meeting the requirements of 3.5.

4.3 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except as otherwise indicated hereinafter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

* 4.3.1.1 Examination of ingredients. Conformance of ingredients to the requirements of 3.1 through 3.1.12 as concerns identity (kind, composition and grade) shall be determined by review of labels, invoices, grade certificates, applicable certificate of analysis (shortening and cocoa), or other valid documents and by visual examination, as applicable. In addition, each ingredient shall be examined organoleptically as necessary to determine conformance to condition requirements of 3.1 and as may be contained in the pertinent ingredient paragraph. The sample unit shall be 4 ounces (113 g) of ingredient taken from each of five primary containers (or each container if less than five form a lot). Nonconformance to identity requirements of one or more sample units not conforming to condition requirements shall indicate an unacceptable ingredient, and use of such shall be cause for rejection of the involved quantity of finished product.

4.3.1.2 Testing of components. Testing of components described in this specification and changes in the testing of components listed in subsidiary specifications shall be as shown in table I. Test requirements for characteristics listed in table I shall be lot average requirements. Nonconformance to test requirements shall indicate an unacceptable component, and use of such shall be cause for rejection of the involved quantity of finished product.

TABLE I. Testing of components (see 4.4.1.2)

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref & reqmt para
Can and lid 1/	One can and lid	Cans	S-1	Tin plate	Nearest 0.01 lb/ (4 g) base box	4.4.1.2 5.1.1

1/ Testing of can coating (when required) and can labeling shall be performed on the same cans submitted for tin plate test, with additional cans as required to complete the sample plan of TT-C-495.

4.3.2 Examination of formulation. Examination shall be performed to the extent necessary to determine conformance to 3.2. Records of formulation shall be maintained. Any nonconformance indicated by actual examination or as reflected by the formulation record shall be cause for rejection of the involved quantity of finished product.

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:55Z
Check the source to verify that this is the currentversion before use.

4.3.3 Examination of end item. Examinations shall be in accordance with tables III and IV and 4.3.3.1 through 4.3.3.5. The sampling plans for the aforementioned tables shall be in accordance with table II shown below. The acceptable quality levels (AQLs) shall be expressed as percent defective for table III and defects per hundred units for table IV.

TABLE II. Sampling plans

Table	Inspection level	Sample unit	Lot size expressed in	AQLs Major	AQLs Minor
III	S-3	One can	Cans	-	2.5
IV 1/	S-2	Contents of one can	Cans	1.5	4.0

1/ Each flavor shall be examined as a separate lot.

* TABLE III. Examination for net weight 1/

Category	Defect
Minor	
201	Net weight less than 4 pounds 3-3/4 ounces (1.92 kg) (vanilla icing)
202	Net weight less than 3 pounds 15-3/4 ounces (1.80 kg) (chocolate icing)

1/ Weigh to nearest ounce (4 g). The lot shall be rejected if the average net weight of the sample is less than the net weight specified.

TABLE IV. Examination of can contents and prepared product 1/

Category		Defect
Major	Minor	Can contents:
101		Not free from undesirable flavors or odors.
102		Lumps that do not fall apart under light pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

TABLE IV. Examination of can contents and prepared product 1/ (cont'd)

Category		Defect
Major	Minor	
103		Direction sheet missing (when cans are not lithographed with directions for use).
	201	Direction sheet not placed on top of product.
104		Information on direction sheet missing, incorrect or illegible.
	202	Print on direction sheet not size specified.
105		Not blended uniformly.
		Prepared product 2/:
	203	Presence of cocoa, color or shortening specks.
106		Does not have a creamy, uniform texture or consistency.
107		Taste not typical of flavor represented.
108		Color not typical of flavor represented.
109		Not easy to spread. 3/
110		Thirty minutes after preparation spread product curdles or shows free water.
* 111		Graininess (based on mouth feel)..
	204	Prepared spread product does not possess a high sheen.

1/ Presence of foreign material (e.g., rust, dirt, wood particles, paint, enamel, insects, insect fragments, glass, metal, or other extraneous materials) shall be cause for rejection of the entire lot.

2/ Prepare product in accordance with directions specified in 5.4.2, except that one half the can shall be utilized, using a proportionate amount of water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

3/ The prepared product shall be spread on a standard white cake. The cake shall be a "sheet" cake, evenly divided and cut into the number of cakes necessary to utilize each sample unit of prepared product.

4.3.3.1 Examination of can labeling. Examination of can for labeling shall be in accordance with the quality assurance provisions contained in MIL-L-1497.

4.3.3.2 Examination of can coating. When exterior coating of can is required to be in accordance with TT-C-495, examination of can coating shall be in accordance with the quality assurance provisions of that specification.

4.3.3.3 Examination of cans. Examination of cans for external condition and seam leakage shall be in accordance with the applicable quality assurance provisions of PPP-C-29.

4.3.3.4 Examination of shipping container. Examination of the filled and closed shipping container shall be in accordance with the quality assurance provisions in the appendix to PPP-B-636. In addition, the following defects shall be included in the table of examination: Major: NSN, contract no., item description or date of pack marking; missing, incorrect, or illegible. Minor: (1) Not a snug-fitting shipping container. (2) Arrangement not as specified. (3) Other marking requirements not as specified. For level C pack, examination shall be in accordance with the aforementioned specification except that only the additional defects and closure requirements (see 5.2.3) shall apply.

4.3.3.5 Examination of unit loads. Examination of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078, and the applicable specification sheet for the type and class of load specified.

4.3.3.6 Can seam leakage. Procedure for determining can seam leakage shall be in accordance with PPP-C-29.

4.3.4 Testing of finished product. The finished product shall be tested for moisture in accordance with 4.4. The sample for testing shall be an 8-ounce (227 g) composite derived from the number of primary containers indicated by inspection level S-2. Lot size shall be expressed in terms of primary containers. Results shall be reported to the nearest 0.1 percent. Test failure shall be cause for rejection of the lot.

4.4 Test methods. Test procedures which differ from those specified herein, unless otherwise excepted, may be used by the contractor if they provide a quality assurance equivalent to that specified. If the Government contracting officer determines that such procedures and control do not provide, as a minimum, such quality assurance, the contractor will use the test procedures set forth herein. In case of dispute as to test results, the test methods specified herein will govern.

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:55Z
Check the source to verify that this is the current version before use.

4.4.1 Test procedures.

4.4.1.1 Chemical analysis. The chemical analysis for moisture of finished icing mixture shall be made in accordance with the methods from Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Sugar and Sugar Products, Section: Sugar and Sirups, Methods: Vacuum Drying.

4.4.1.2 Tin coating weights. Tin coating weights shall be determined by any method specified in PPP-C-96.

5. PACKAGING

5.1 Preservation-packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

* 5.1.1 Level A. The product shall be filled into a size 603 by 700 can. The net weight shall be 4 pounds, 4 ounces (1.927 kg) for vanilla icing mix and 4 pounds (1.814 kg) for chocolate icing mix. A minus 1/4 ounce (7 g) tolerance will be allowed in any one container, provided the average net weight of the cans, inspected in accordance with table III, is not less than 4 pounds, 4 ounces (1.927 kg) or 4 pounds (1.814 kg), as applicable. The cans shall be open-top style, round, metal, with soldered or welded side seams and compound-lined, double-seamed ends. The cans shall be made throughout from not less than 0.25 pound (113 g) electrolytic tin plate per base box (see 4.4.1.2), and shall be coated outside with a coating conforming to type I of TT-C-495. The cans shall be hermetically sealed and shall not show leakage when tested in accordance with 4.4.1.1.

5.1.2 Level C. The product shall be packaged in accordance with 5.1.1, except that cans with or without an exterior coating will be acceptable.

5.2 Packing. Six cans of the product, arranged 3 in length and 2 in width, shall be packed on end in shipping containers in accordance with level A, B or C as specified (see 6.1).

5.2.1 Level A packing. The shipping container shall be a snug-fitting fiberboard box constructed, closed and reinforced in accordance with style RSC, V2s of PPP-B-636.

5.2.2 Level B packing. The shipping container shall be a snug-fitting fiberboard box constructed, closed and reinforced in accordance with style RSC, V3c, V3s or V4s of PPP-B-636.

5.2.2.1 Nonmetallic reinforcement of shipping containers. When specified (see 6.1 and 6.3), the shipping container specified in 5.2.2 shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive, filament reinforced tape in accordance with the appendix of PPP-T-636, except that two reinforcing bands shall be used, one lengthwise and one girthwise.

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:55Z
Check the source to verify that this is the currentversion before use.

5.2.3 Level C packing. The shipping container shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable, except that the closure of fiberboard boxes shall be in accordance with the appendix of PPP-B-636 (see 6.4).

5.3 Unitized loads. When specified (see 6.1), the product, packed as specified in 5.2, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified.

5.4 Marking.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497, and as follows:

ICING MIX POWDER

.....Flavor
.....Net weight
Directions for use inside can (omit if directions are on exterior of can)

5.4.2 Directions for use. The following directions for use shall be either lithographed on the body of the can, or printed on a sheet of good quality paper. The paper used shall take clear, readable impressions without blurring or smudging. The letters shall be printed in not less than 8-point bold-face type. One direction sheet shall be placed on top of the product in each can. All materials used in printing the recipes shall comply with the regulations of the Federal Food and Drug Administration.

Directions for use (as applicable)
(for 603 by 700 can)

* Vanilla icing

Icing mix, vanilla	4 lb 4 oz (1 #10 can)
Hot water	12 fl oz (1-1/2 cups)

Place icing mix in mixing bowl. Add hot water gradually while mixing at low speed. Scrape down bowl, beat at high speed 3 minutes or until thick and smooth.

APPROXIMATE YIELD: 2-1/2 quarts

Chocolate icing

Icing mix, chocolate	4 lb (1 #10 can)
Hot water	16 fl oz (2 cups)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

APPROXIMATE YIELD: 2-1/2 quarts.

NOTE: The amount of water in the last stage is variable. (Use slightly more or less water, as necessary, to obtain spreading consistency).

5.4.3 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129. In addition, the shipping container shall be marked with the container net weight.

5.4.4 Unitized loads. Unitized loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Flavor required (see 1.2).
(c) Flavor required when flavor 3 is specified (see 1.2).
(d) Level of packaging and packing required (see 5.1 and 5.2).
(e) When packing specified in 5.2.2.1 is required (see 6.3).
(f) Type and class of unit load when specified (see 5.3).

* 6.2 Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the contracting officer should select the appropriate level of pack in accordance with the criteria established in AR700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.14D/ or DSAR 4145.7, as applicable.

6.3 Packing specified in 5.2.2.1 is intended for transfer at sea operation or specific overseas operations.

* 6.4 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous specification were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:55Z
Check the source to verify that this is the currentversion before use.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities.

Army - MD
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Project No. 8925-0129

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-I-35085C - Icing Mix Powder

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.