MIL-P-35090B

30 JUNE 1970
SUPERSEDING
MIL-P-35090A
26 April 1966

MILITARY SPECIFICATION

PARSLEY, DEHYDRATED, FLAKES

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers dehydrated parsley flakes for use by the Armed Forces as an item of general issue.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| TT-C-495 | - | Coatings, Exterior, for Tinned Food Cans. |
| PPP-B-636 | - | Box, Fiberboard. |
| PPP-C-29 | - | Canned Subsistence Items, Packaging and Packing Of. |
| PPP-C-96 | - | Cans, Metal, 28 Gage and Lighter. |

MILITARY

| | | |
|---|---|---|
| MIL-L-1497 | - | Labeling of Metal Cans for Subsistence Items. |
| MIL-L-35078 | - | Loads, Unit; Preparation of Nonperishable Subsistence In. |

STANDARDS

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - | Marking for Shipment and Storage. |
| MIL-STD-668 | - | Sanitary Standards for Food Plants. |

FSC 8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply:

U.S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE

Federal Food, Drug, and Cosmetic Act and
Regulations Promulgated Thereunder

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

U.S. DEPARTMENT OF AGRICULTURE

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Information Division, Consumer and Marketing Service, U.S. Department of Agriculture, Washington, D.C. 20250.)

AMERICAN DRY MILK INSTITUTE, INC.

Standards for Grades of Dry Milks, Including
Methods of Analysis, Bulletin 916

(Application for copies should be addressed to the American Dry Milk Institute, Inc., 130 North Franklin Street, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Attn: Traffic Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Ill. 60606.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.- The parsley shall be clean, sound, and mature, of good green color, and preferably of the Moss Curled (double curled) variety. Varieties possessing similar characteristics may be used. Parsley of the flatleaf type shall not be used.

* 3.2 Preparation.- The parsley shall be properly inspected and trimmed to remove discolored, damaged, or diseased portions, and washed to remove soil and foreign materials.

3.3 Processing.-

3.3.1 Dehydration.- Dehydration shall be by such methods that the product shall not be scorched or otherwise damaged by heat or drying and shall meet the requirements specified in 3.4.

3.4 Finished product.-

* 3.4.1 Dehydrated product.- The dehydrated parsley shall possess a characteristic uniform green color, and a good typical aroma free from scorched, musty or other objectionable odors. The moisture content shall not exceed 4.0 percent, by weight. The product shall be free flowing, and free from clumps and matted or rolled material. The product shall be of such particle size that not more than 20 percent, by weight, shall pass through a U. S. Standard No. 20 sieve.

3.4.1.1 Defect tolerances.- The dehydrated product shall not contain more than 1.0 percent, by weight, of defective pieces. A piece shall be considered defective if it is damaged by insect or pathological injury, decay, scorch, sunburn, freezing, bruise, dirt, discoloration, or any other abnormality. The product shall not contain more than 2.0 percent, by weight, of stems longer than 1/4 inch, free or attached, and shall be practically free of large, coarse stems, and other extraneous materials. The dehydrated product shall be free from foreign material such as stones, splinters, paint, varnish, rubber, metals, etc. The product and packages shall be free from insect infestation.

3.4.2 Rehydrated product.- The dehydrated product shall be rehydrated by mixing 2 grams of the dry product with 120 milliliters (ml.) of water and soaking for 30 minutes. The rehydrated product shall have good flavor, texture, odor, and color, typical of fresh parsley.

3.5 All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

3.6 Workmanship.- The product shall be processed in establishments meeting the requirements of MIL-STD-668. The product shall be prepared, processed and dehydrated with minimum delay between the various steps in production.

* 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Pre-acceptance inspection.- The product shall be rejected if produced in plants not meeting the requirements of MIL-STD-668.

4.3 Sampling for inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except as otherwise indicated herein.

4.3.1 Component and material inspection.- In accordance with 4.1 components and material shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards, unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.1.1 Testing of cans.- Cans shall be tested for tin plate in accordance with 4.5. The sample unit shall be one can with lid. The sample size shall be the number of sample units indicated by inspection level S-1. Lot size shall be expressed in terms of the sample unit. Test requirement shall be an average requirement. Results shall be reported to the nearest 0.01 lb. tinplate/base box. Tests on can label and external can coating (when required) shall be performed on the same cans submitted for tin plate testing, in accordance with the pertinent subsidiary specifications. A test failure shall indicate unacceptable cans and use of such shall be cause for rejection of the involved end item.

4.3.2 Process examination.- Examination shall be performed to determine conformance with 3.1 as concerns variety of parsley and to 3.2 as concerns trimming and cleaning. Nonconformance shall be cause for rejection of the involved finished product.

4.3.3 Examination of end item.- The end item shall be examined in accordance with tables II and III and 4.3.3.1 through 4.3.3.3. Sampling plans for the tables shall be in accordance with table I. The acceptable quality levels (AQL's) shall be expressed as defects per hundred units for table III and percent defective for table II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

TABLE I.- Sampling plan

| Table | Inspection level | Sample unit | Lot size expressed in | AQL's Major | Minor | Total |
|---|---|---|---|---|---|---|
| II | S-3 | 1-Filled can | Cans | | 2.5 | |
| III | S-2 | 1-Filled can | Cans | 1.5 | | 6.5 |

TABLE II.- Examination for net weight 1/

| Category | Defect |
|---|---|
| Minor | |
| 201 | Less than 40.4 grams. |

1/ Report results to nearest 0.1 gram. Lot shall be rejected if sample data indicate a lot average net weight less than 42.5 grams (1-1/2 ounces).

TABLE III.- Examination of product 1/

| Category | | Defect |
|---|---|---|
| | | Dehydrated product |
| Major | Minor | |
| 101 | | Not a uniform characteristic green color. |
| 102 | | Not free from scorched, musty or other objectionable odors. |
| 103 | | More than 1.0 percent, by weight, of defective pieces (see 3.4.1.1). |
| 104 | | More than 2.0 percent, by weight, of stems longer than 1/4 inch, free or attached. 2/ |
| 105 | | Not practically free from large coarse stems and other extraneous vegetable material. |
| | 201 | Not free flowing. |
| | 202 | Not free from clumps, matted or rolled material. |
| | 203 | More than 20 percent, by weight, passes through a U.S. Standard No. 20 sieve. 3/ |



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

TABLE III.- Examination of product 1/ (cont'd)

| Category | | Defect |
|---|---|---|
| | | Rehydrated product 4/ |
| Major | Minor | |
| 106 | | Flavor or aroma not typical of fresh parsley. |
| 107 | | Texture not typical of fresh parsley. |
| 108 | | Color not typical of fresh parsley. |

1/ Presense of foreign material (see 3.4.1.1) shall be cause for rejection of the lot.

2/ Measuring device shall be calibrated in 1/16 inch increments.

3/ See 4.5 for procedure.

4/ See 3.4.2 for rehydration procedure. Make one determination per sample unit.

4.3.3.1 Examination of cans.- Examination of cans for condition and label shall be in accordance with the United States Standards for Condition of Food Containers. Examiniation of seam leakage shall be in accordance with the Quality Assurance Provisions of PPP-C-29.

4.3.3.2 Examination of shipping container.- Examination of filled and sealed shipping containers shall be in accordance with the criteria in the appendix of PPP-B-636. In addition, the following defects shall be included in the examination: Major - Markings missing, incorrect or illegible; Minor - Number or arrangement of contents not as specified. For level C pack, only the defects applicable to marking shall apply.

4.3.3.3 Examination of unit loads.- Unit loads shall be examined in accordance with the quality assurance provisions of MIL-L-35078.

4.3.4 Testing for oxygen content of cans and testing of finished product.- Cans shall be tested for oxygen content and the finshed product shall be tested for moisture in accordance with 4.5. The sample unit for the oxygen test shall be 1 filled and sealed can. The sample size shall be the number of cans indicated by inspection level S-2. Lot size shall be expressed in cans. The acceptable quality level expressed as percent defective shall be 2.5. Results shall be expressed to the nearest 0.1 percent. A sample unit having a residual oxygen content of more than 2.0 percent shall be a defective unit. The sample for testing of the finished product shall be a one ounce composite derived from the number of cans indicated by inspection level S-2. Results shall be reported to the nearest 0.1 percent. A test failure shall be cause for rejection of the lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

4.4 Standby test samples.- The Government reserves the right to withdraw and hold standby test samples of components or finished product or both (quantity of which shall be not more than twice that required by this specification) for inspection purposes. Samples not used will be returned to the supplier.

4.5 Test methods.- Examination and test procedures which differ from those specified herein, unless otherwise excepted, may be used by the supplier if they provide a quality assurance equivalent to that specified. If the Government inspection activity determines that such procedures and controls do not provide, as a minimum such quality assurance, the supplier will use the procedures set forth herein. In case of dispute as to examination or test results, the procedures specified herein will govern.

4.5.1 Examination procedures.-

4.5.1.1 Screening.- Screening shall be performed as follows: Weigh entire contents of can. Place approximately 1/4 ounce of the dehydrated material on an 8-inch or 1/2 ounce of the dehydrated material on a 12-inch diameter U. S. Standard No. 20 sieve equipped with a receiving pan. Tip back and forth through a 90-degree arc 25 times. Remove material retained on No. 20 sieve and repeat screening procedure until entire contents of the can have been screened. Calculate total percentage of material passing through the No. 20 sieve.

4.5.2 Test procedures.-

4.5.2.1 Moisture.- Moisture determination shall be made by the vacuum oven method as specified in 4.5.2.1.1 and 4.5.2.1.2.

NOTE: Samples for moisture determination shall be collected in clean, dry jars which shall be completely filled, sealed with airtight lids, and held until analyzed.

4.5.2.1.1 Preparation of sample.- Sample shall be prepared as follows: Grind approximately 25 grams of a well-mixed sample in a clean, dry, Waring blender or similar mill for 1 minute.

4.5.2.1.2 Procedure.- Moisture determination procedure shall be as follows: Weigh two samples of approximately 1 gram each of the ground material into tared, dry, aluminum weighing dishes (approximately 2 to 2-1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70° C. under a pressure of not more than 100 mm. of mercury. During drying,



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

admit to the oven a slow current of air (approximately 2 bubbles per second), dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.5.2.2 Oxygen content.- Oxygen content in headspace gas in container shall be determined in accordance with American Dry Milk Institute Inc., publication Bulletin 916, Standards for Grades of Dry Milks; Chapter: Methods of Analysis: Determination of oxygen.

4.5.2.3 Tin coating weight.- Tin coating weight shall be determined by any method specified in PPP-C-96.

* 5. PREPARATION FOR DELIVERY

5.1 Packaging.- The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A.- One and one-half ounces of the product shall be filled into a size 401 by 411 open-top style, round, metal can, with soldered sideseam and compound-lined double-seamed ends. The can shall be made throughout from commercial electrolytic tin plate of not less than 0.25 pound per base box (see 4.5.2.3) and shall be coated outside with a coating conforming to type I, or when specified (see 6.1), type III of TT-C-495. The cans shall be hermetically sealed. The product shall be packaged under an atmosphere of nitrogen. The oxygen content of the gases at whatever pressure is in the sealed container, not sooner than two days after filling, shall not exceed 2.0 percent when tested as specified in 4.5.2.2. A close-fitting plastic lid shall be affixed securely to one end of the can. If the plastic lid is not transparent it shall be affixed to the unmarked end of the can. The plastic lid shall meet the requirements of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

5.1.2 Level C.- The product shall be packaged in accordance with 5.1.1 except that cans with or without commercial exterior coating will be acceptable.

5.2 Packing.- Twenty-four cans of the product, arranged 4 in length, 3 in width, and 2 in depth, shall be packed on end into a snug-fitting shipping container in accordance with level A, B, or C as specified (see 6.1). RSC containers may be top-opening or end-opening.

5.2.1 Level A.- The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, V2s, of PPP-B-636.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.- The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, W5c or W5s, of PPP-B-636.

5.2.2.1 When specified (see 6.1 and 6.2) the shipping container shall be a fiberboard box, constructed closed and reinforced with nonmetallic strapping or pressure sensitive adhesive, filament reinforced tape in accordance with style RSC, V3c, V3s, or V4s, of PPP-B-636. Reinforcement of end-opening containers shall be in the same relationship to the contents as for top-opening containers.

5.2.3 Level C.- The shipping container shall be a fiberboard box, constructed and closed in accordance with style RSC, type CF or SF, class domestic, method II closure of PPP-B-636.

5.2.3.1 When specified (see 6.1 and 6.3), cans of the product shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The shipping container shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Unit loads.- When specified (see 6.1), the product packed as specified in 5.2 shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1).

5.4 Labeling and marking.-

5.4.1 Cans.- Cans shall be labeled in accordance with MIL-L-1497, and as follows:

Parsley, Dehydrated

Use for garnishing and seasoning

Add dry parsley to soups, stews, gravies, etc.

Reconstitute by soaking 1 volume of dehydrated flakes in 4 volumes of water for 3 minutes. Use one tablespoon of dehydrated parsley to yield 4 tablespoons of chopped fresh parsley.

In addition the following information shall appear on each can:

This product is gas packed.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.

5.4.2 Shipping containers.- Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads.- Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Levels of packaging and packing required (see 5.1 and 5.2).
(c) When type III exterior can coating is required (see 5.1.1).
(d) When packing specified in 5.2.2.1 and 5.2.3.1 is required.
(e) When unit loading is required and, when applicable, type and class of load required (see 5.3).

6.2 Packing specified in 5.2.2.1 is intended to provide limited Military protection for specific operational requirements.

6.3 Packing specified in 5.2.3.1 is intended for direct shipment from the supplier to the first receiving activity for immediate use within CONUS.

6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 45

Preparing activity:

Army - GL

Project No. 8915-0294

Review activities:

Army - MD
Navy - MC, MS
Air Force - 03
DSA - SS



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:55Z
Check the source to verify that this is the current version before use.