INCH-POUND

MIL-C-48396A (AR)
AMENDMENT 4
16 February 2001
SUPERSEDING
AMENDMENT 3
17 February 1995

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M752A1 PARTS FOR

This amendment forms a part of MIL-C-48396A (AR), dated 17 February 1995, and is approved for use by the U.S. Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, Change “M853” to “M853A1”

2.1.1, Add “MIL-STD-810 – Environment Test Methods."

PAGE 2

3.2, Add the following paragraph:

“3.2.1 Corrosion resistance (salt spray). Parts selected for the salt spray test shall show in evidence of pitting or mottling when tested in accordance with 4.5.2.”

PAGE 8

4.4.2.2, Major 108: Delete in its entirety and substitute the following:

“108 Diameter of flashole rear of pellet cavity … 0.40% … 3.2 … Gage.”

Major 109: Delete in its entirety.

AMSC N/A FSC 1315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.2.2, Major 126: Delete in its entirety.

Under Major category, add the following:

"129 Salt spray test … (a) … 3.2.1 … Visual/4.5.2.
Note (a) See sampling plans described in paragraph 4.4.3.2"

"130 Inside chamfer at entrance of primer cavity incorrect … 0.40% … 3.2 … Gage."

* 4.4.2.2, Add Major 131 as follows:

"131Radius or chamfer, max. … 0.40% … 3.2 … Gage
of outside corner at base
of flash tube cavity"

PAGE 13

4.4.2.5 Major 103, add "to forward outside diameter and rear face" after "True Position of flash holes"

Major 113, Delete in its entirety.

Under Major category add the following:

"114 Salt Spray test … (a) … 3.2.1 … Visual/4.5.2
Note (a) See sampling plans described in paragraph 4.4.3.2"

PAGE 14

4.4.2.6,

Major 101, delete: "Outside diameter" and substitute, "Forward outside diameter (OD)."

Major 103, delete: "Depth of groove" and substitute, "Rear OD."

Major 104, delete: "Width of groove" and substitute, "Distance from rear face to shoulder."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

Major 107, delete: "Examination callout in its entirety" and substitute, “True position of cavity with rear OD."

Major 109, delete: "Examination callout in its entirety" and substitute, “True position of forward OD with rear OD."

Add Major 110 and 111 as follows:

“110 Radius at bottom of cavity over maximum … 0.40% … 3.2 … Gage
111 Marking missing … 0.40% … 3.2 … Visual.”

Add Minor 204 as follows:

“204 Marking incomplete or illegible … 065% … 3.2 … Visual.”

PAGE 15

4.4.3.2.1, Delete text in its entirety and substitute:

“4.4.3.2.1 Sampling plan. For the purpose of the salt spray test, the lot size shall not exceed the number of parts anodized during one eight (8) hour production period. Sampling of flash tubes from the anodized lot shall be in accordance with MIL-STD-105, Table IIA, Level S-3 at 0.63% AQL.

In performing the test, samples from more than one lot may be tested in the same salt spray chamber; however, identity of components and their representative test specimens must be maintained. After passing the test, anodized lots from which the samples were selected may be mixed together in accordance with normal procedures and identity of the anodizing lot(s) is no longer required. (The test shall be performed as specified in Para. 4.5.2).”

4.5, Add the following paragraph:

“4.5.2 Salt spray test. Samples selected shall be tested using equipment and procedures in accordance with MIL-STD-810, Method 509.2, Salt Fog. Parts shall be tested with the black powder pellet end up and the pellet cavity or contact surface inclined approximately six (6) degrees from vertical in fixturing, which does not obstruct the longitudinal flush-hole. Parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

shall be tested for 96 hours minimum. After testing, parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish. Particular attention shall be paid to the black powder pellet cavity inside the body. The technique used to inspect the cavity must be capable of thoroughly inspecting all surfaces of the cavity (face, walls, inside and outside corners), otherwise the body shall be transversely sectioned approximately 1.75 inches from the front face in order to facilitate visual inspection. The cutting tool (if used) must not remove any part of the pellet cavity. One or more pits or mottling shall be cause of rejection of the anodized parts represented by the sample. Parts subjected salt shall not be returned to the lot."

Add the following new paragraph:

"4.5.2.1 Alternate method for salt spray test inspection. If the contractor can demonstrate the capability of thoroughly inspecting all surfaces of the black powder pellet cavity (face, walls, inside and outside corners) in the body, then sectioning after salt spray testing is not required."

The margins of this amendment are marked with an asterisk or vertical lined to indicate where changes (additions, modifications, corrections and deletions) from previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notations. Bidders and contractors are cautioned to evaluate the requirements of this document base on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-0262)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.