INCH-POUND

MIL-C-48397A(AR)
AMENDMENT 5
31 January 2000
SUPERSEDING
AMENDMENT 4
03 July 1996

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M752A1
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-C-48397A (AR), dated 22 October 1986, and is approved for use by the U.S. Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, Delete: "M853", and substitute: "M853A1".

PAGE 2

* 2.1.2, Under “Drawings”, delete:

"Inspection equipment drawings 9278622 – Envelope drawing for leak testing of ignition cartridges.”

PAGE 4

3.5, Delete in its entirety and substitute:

"3.5 Leak tests. Each body assembly, after the primer is loaded and the lacquer cured, and each loaded ignition cartridge, shall satisfactorily pass the leak tests specified in 4.5.4.".

* 3.6.2, Delete in its entirety and substitute:

AMSC N/A FSC 1315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

"3.6.2 Velocity and functioning. The cartridge assemblies shall function and shall impart a corrected muzzle velocity as specified in Table II. In addition, the velocity standard deviation of the lot shall be no greater than 3.1 fps."

* 3.7, Delete in its entirety and substitute:

"3.7 Propellant charge uniformity. The M9 propellant lots shall achieve a velocity as specified in Table II (see 4.5.7). This test shall be required when a lapse of six months or more occurs between propellant acceptance and LAP initiation."

PAGE 6

Table I, under "Body Assembly (dwg. 12630551)", delete:

"Push-out test ...10 ...100% ...3.2 ...4.4.3.1/4.5.1".

* Under "Cartridge, ignition, after assembly of cap (dwg. 9294752)", add:

"Propellant weight ...25 ...100% ...3.2 ...4.4.3.2.2/4.5.5.2".

PAGE 8

* 4.4.2.1, Delete Criticals 1 and 2 in their entirety.

* Add Majors 102 and 103 as follows:

"102 Heat shrinkable tubing missing, loose or does not completely cover all flash holes ...100% ...3.2 ...Visual/Manual".

"103 Pin missing ...100% ...3.2 ...Visual".

PAGE 9

4.4.2.2, Major 102: Delete in its entirety.

Major 103: Delete: "Gage", and substitute: "Visual".

PAGE 10

4.4.2.3, Major 101, 102, 103, 105 and 106: Delete in their entirety and substitute:
"101 Primer missing or inverted ...100% ...3.2 ... Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

102 Primer above flush or more than .015 in. below flush ...0.4% ...3.2 ...Gage

103 Lacquer seal missing or inadequate ...( ) ...100% ...3.2 ... Gage/4.5.4.1

105 Staking process inadequate ...2/ ...( ) ...3.2 ... Gage/4.4.3.1

106 Primer bulged after staking ...100% ...3.2 ... Visual".

Major 104, Delete: "lacquer", and substitute: "any adhesive or sealant".

Add Major 107 as follows:

"107 One or more stakes missing or not full ...1/ ...3.2 ...Visual".

Note "(a)", Delete in its entirety and substitute:

"1/ Inspect the tool or one body at the start of each day's production and each hour thereafter. A missing or broken tooth shall be cause for rejection of all parts staked since the last successful inspection.

2/ See 4.4.3.1".

4.4.2.4, Delete: drawing number "9549177", and substitute: "7549177".

Major 106, Delete in its entirety.

Note (a): Delete in its entirety and substitute:

* "(a) Twenty-five randomly selected pellets from each shift production. If a Ohaus moisture determination meter is the method of test, the sample shall consist of the quantity of pellets required to equal not less than 10 grams."

* 4.4.2.5, Delete Critical 2 in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

Add Critical 5 as folows:

"5 Firing plug above flush with head surface ...100% ...3.2 ...Gage".

Majors 101, 102, 103 and 104, Delete in their entirety.

Major 106, Delete: "Gage", and substitute: "Visual".

Major 107, Change "Pellet missing" to "Pellet missing or broken c/".

* Add Major 111 as follows:

"111 Flash tube assembly missing ...100% ...3.2 ...Visual".

Add Note c/ as follows:

"c/ Minor chipping of edges acceptable, no chunks or excessive chipping.".

* 4.4.2.6, Add Major 101 as follows:

"101 Propellant weight (after loading) (b)..100% ...3.2 ...4.4.3.2.1/4.5.5.1".

* Delete Major 102 in its entirety.

Add Major 103 as follows:

"103 Environmental conditions inadequate ...a/ ...3.2 ...Gage".

Add Note a/ as follows:

"a/: Temperature and humidity shall be checked at the beginning and end of each shift. If conditions are not proper at either time, the quantity of product represented by the conditioning shall be rejected.".

* Add Note b/ as follows:

"b /: See 4.4.3.2.1 for defect description. Same sample for both inspections."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

4.4.2.7, Major 101, Delete examination callout in its entirety, and substitute:

"Channel not completely filled with RTV sealant".

Major 104, Delete in its entirety.

Major 105, Delete in its entirety and substitute:

"105 True position of outside diameter with major diameter of head thread ...0.40% ...3.2 ...Gage".

* Major 106, Delete in its entirety and substitute the following:

“106 Propellant weight ...c/ ...3.2 ...4.4.3.2.2/4.5.5.2”.

Major 107, Delete “4.5.4” and substitute “4.5.4.2”.

Add Majors 110, 111 as follows:

"110 Environmental conditions inadequate ...b/ ...3.2 ...Gage

111 Presence of excessive sealant ... 0.40% ... 3.2 ... Visual".

Add Note b/ as follows:

"b/ Temperature and humidity shall be checked at the beginning and end of each shift. If conditions are not proper at either time, the quantity of product represented by the conditioning shall be rejected.".

* Delete note c/ in its entirety and substitute:

“c/ See 4.4.3.2.2 for defect description.”.

4.4.3.1, Delete in its entirety and substitute:

"4.4.3.1 Staking process (primer security). Each hour, and on the last units staked before a scheduled staking tool change, five (5) primed bodies shall be inspected before and after staking, using any method that can verify that the primer cups have been pushed down as a result of the staking

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

operation. If none of the primer cups have been pushed down, all units loaded since the last successful inspection shall be rejected. If one or more primer cups have been pushed down by any amount, the process may continue unchanged at the discretion of the contractor."

* 4.4.3.2, Delete in its entirety and substitute:

"4.4.3.2 Weight of Propellant"

* 4.4.3.2.1, Delete in its entirety and substitute:

"4.4.3.2.1 Prior to assembly of cap (see dwg. 9294752). The propellant charge shall be volumetrically dispensed (or tare-weighed) in a container, transferred to the ignition cartridge and then check-weighed 100 percent. The check-weighing shall be as specified in paragraph 4.5.5.1. The volumetric dispensing (or initial weighing) and check-weighing shall be performed by different operators on different scales. Weight limits for weighing shall be established within the applicable requirements, depending upon the accuracy and precision of the weighing system, to assure compliance with the charge weight requirements. Any charge of bulk propellant failing to meet the applicable requirements shall be classed defective using criteria for critical and major defects as defined in paragraph 4.4.3.2.2 and removed from the lot."

* 4.4.3.2.2, Delete in its entirety substitute:

"4.4.3.2.2 After assembly of cap (See dwg 9294752). Major defect - more than 1 grain below assessed weight. Major defect - More than 1 grain above assessed weight. 315 sample ignition cartridge assemblies shall be randomly selected from each lot for this test. If any sample exceeds the assessed weight by 10 or more grains or if two or more samples exceed the assessed weight by more than 1 grain but less than 10 grains, the lot shall be rejected. If any sample is under the assessed weight by 10 or more grains, or if two or more samples are under the assessed weight by more than 1 grain but less than 10 grains, the lot shall be rejected. Testing shall be as specified in paragraph 4.5.5.2."

* 4.4.3.3, Delete in its entirety.

* 4.4.3.3.1, Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

PAGE 21

4.4.3.4.1, Delete: "0.025", and substitute: "0.25".

4.4.3.4.1.1, Delete: "0.040", and substitute: "0.40".

PAGE 22

4.5.1, Delete in its entirety.

* 4.5.2, Delete the text in its entirety and substitute:

"The moisture content of the black powder pellets shall be determined in accordance with the procedures specified in MIL-P-223. A sample of 25 black powder pellets or a single sample of not less than 10 grams of pellets shall be randomly selected from each production shift. If any pellet or if the 10 gram sample fails to comply with the requirement cited in paragraph 3.3 herein, all pellets in the production shift represented shall be rejected. If loading with propellant has begun, ignition cartridges loaded with the non-conforming black powder pellets shall be rejected.".

PAGE 23

4.5.3.2, Delete sentence 2 in its entirety and substitute:

"The firing pin of the test fixture shall be adjusted so that it impacts the firing plug at 0.025 inch off-center.".

PAGE 24

4.5.4, Delete in its entirety and substitute:

"4.5.4 Leak tests."

* 4.5.4.1, Delete in its entirety and substitute:

"4.5.4.1 Body assembly. After the lacquer has cured, each primed body assembly shall be tested for leakage around the primer. The pressure differential and duration of the test shall be as specified for the leak test of the fully assembled ignition cartridge (see 4.5.4.2). Any body assembly which fails the test shall be classed defective and removed from the lot."

* 4.5.4.2, Delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

"4.5.4.2 Ignition cartridge. The ignition cartridge shall be subjected to a pressure of 3+1 psig for a duration of five (5) seconds minimum. Any ignition cartridge with a leak rate of 1.5 CC per minute or greater shall be rejected and removed from the lot. The test equipment shall be calibrated at the start of each day's operation and prior to production restarts. A restart results from any break in continuous production whether it is due to equipment stoppage/failure or operator breaks. Both accept and reject standards shall be used for each calibration occasion. If the equipment is out of calibration, the ignition cartridges tested since the last successful calibration shall be retested after correction of the equipment. Equipment design shall be submitted for approval (see 4.4.4)."

* 4.5.5, Delete in its entirety and substitute:

"4.5.5 Weight of propellant.".

* Add 4.5.5.1 as follows:

"4.5.5.1 Prior to assembly of cap. The ignition cartridge subassembly shall be weighed before and after the propellant is loaded. The weight of the propellant charge shall be determined by subtracting the tare weight of the ignition cartridge subassembly from the gross weight (after loading). The contractor may elect to perform the 100 percent check-weighing operation with automated equipment and mandatory process controls. In such cases, process control plans in accordance with data item description DI-P-1604 must be submitted to the technical agency (see 6.10) for approval of the automated operation.".

* Add 4.5.5.2 as follows:

"4.5.5.2 After assembly of cap. The propellant shall be removed from each ignition cartridge sample, placed on the pan of a precision or analytic balance and weighed. Alternatively, each ignition cartridge assembly may be weighed and reweighed after removal of the propellant. The weight of the propellant charge shall be determined by subtracting the weight of the empty ignition cartridge from the loaded (gross) weight. The weight of the propellant in each sample shall be determined to the nearest 0.01 grain.".

* 4.5.6, Delete second paragraph in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.

"The sample ignition cartridges shall be assembled to 81mm ctgs, M819 or M853A1 having ctg weights as defined in Table II. The complete round, less propelling charges, shall be fired from a M252 81mm mortar at an elevation of forty-five degrees."

* 4.5.7, Delete third sentence in its entirety and substitute:

"Rounds shall be inert loaded to achieve a total weight as specified in Table II."

* Add Table II as follows:

"TABLE II Cartridge Weights"

"

CTG	CTG WEIGHT	MAX VELOCITY (Para. 3.6.2)	MIN VELOCITY (Para. 3.6.2)	UNIFORMITY VELOCITY (Para. 3.7)
M819	10.35 +/-0.02 lbs	200 fps	180 fps	190 fps
M853A1	8.9 +/-0.02 lbs	220 fps	200 fps	210 fps

6.1, Delete: "M853", and substitute: "M853A1".

6.3, Last sentence, delete: "... AMSMC-QAT-I, Dover, NJ 07801-5000" and substitute:

"AMSTA-AR-QAA-C, Picatinny Arsenal, NJ 07806-5000.".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, deletions, modifications, corrections) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-0232)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:24Z
Check the source to verify that this is the current version before use.