INCH-POUND

MIL-F-48370A (AR)
AMENDMENT 1
17 APRIL 1989

MILITARY SPECIFICATION

FUZE, M934E6, HYBRID MICROCIRCUITS FOR

This Amendment forms part of Military Specification MIL-F-48370A (AR), dated 01 July 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.1.4, a: Delete first sentence and substitute "Iron, Nickel, Cobalt alloy (KOVAR) per MIL-I-23011, Class I, ASTM F-15.".

3.1.5: Delete first sentence and substitute "The lead material shall consist of Iron, Nickel, Cobalt alloy (KOVAR) per MIL-I-23011, Class I, ASTM F-15.".

Page 4

3.2.3: Add the following sentence at the end of the paragraph "Aluminum shall be used for wire bonding on substrate interconnects."

3.2.4, line 2: Add "or vacuum, min $4(10)^{-2}$Torr." after "atmosphere".

PAGE 10

Add "5/"after "Group I-1/".

PAGE 11

Notes: Add new note "5/ Electrical rejects may be used provided their construction and processing through final seal is identical to that of the device.".

PAGE 14

4.4.2.2, minor 201: Add "2/" after "(Non-destructive)".

Note 2: Add "I", after "Groups".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:23Z
Check the source to verify that this is the current version before use.

4.5.1, line 2: Delete "determine the minimum strength" and substitute "destruction".

4.5.1, last sentence: Delete in its entirety.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A587)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:23Z
Check the source to verify that this is the current version before use.