INCH-POUND

MIL-C-53128(ME)
10 April 1992

MILITARY SPECIFICATION
FOR
CLEARED LANE MARKING SYSTEM (CLAMS)

This specification is approved for use within the USA Belvoir Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for manufacture and acceptance of the Cleared Lane Marking System (CLAMS).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2590

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

TT-C-490	- Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic coatings.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.

MILITARY

MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-C-16173	- Corrosion Preventative Compound, Solvent Cutback, Cold Application.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-P-53022	- Primer, Epoxy Coating, Corrosion Inhibiting Lead and Chromate Free.
MIL-P-53030	- Primer Coating, Epoxy Water Reducible Lead and Chromate Free.
MIL-C-53039	- Coating, Aliphatic Polyurethane Single Component, Chemical Agent Resistant.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Tables and Procedures for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U.S. Military Property.
MIL-STD-280	- Definitions of Item Levels, Item Exchangeability, Models, and Related Terms.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.
MIL-STD-810	- Environmental Test Methods and Engineering Guidelines.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing: With Appropriate Test Methods.
MIL-STD-1472	- Human Engineering Design Criteria for Military Systems, Equipment, and Facilities.
MIL-STD-45662	- Calibration System Requirements.

(Unless otherwise indicated, copies of Federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

of this document to the extent specified herein. Unless otherwise specified, the issues are those in the solicitation.

DEPARTMENT OF LABOR, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

29 CFR, Chapter XVII, Part 1910
Occupational Safety and Health Standards

(Applications for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

DRAWINGS

ME

TA13227E0200 - Cleared Lane Marking System (CLAMS)

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development and Engineering Center, ATTN: STRBE-NDM, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARD INSTITUTE (ANSI)

ANSI/AS 478 - Identification Marking Methods

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Qualification Standard for Welding and Brazing Procedures, Welders, Brazers, and Welding and Brazing Operators.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY (AWS)

D 1.1 - Structural Welding Code - Steel

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJeune Rd., P.O. Box 351040, Miami, FL 33135.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other information services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable law and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General description. The CLAMS shall be in accordance with TA13227E0200 and as specified herein. The CLAMS consists of the following items:

	PART NUMBER	DESCRIPTION	UNIT	QTY
1.	13227E0170	Dispenser Assembly	EA	1
2.	13227E0150	Control Box Assembly	EA	1
3.	13227E0260	Refill Marking Kit	EA	1

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviations from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operating of the item. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3.1 Material deterioration prevention and control. The CLAMS shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration: that may be encountered in any of the applicable operating and storage environments to which the item may be exposed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish, or treatment for use with component and subcomponent and shall make information available upon request to the contracting officer or designated representative.

3.3.3 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, ad distinguished from virgin raw materials. The components, pieces, and parts incorporated in the CLAMS may be newly fabricated from recovered materials to the maximum extent practicable, provided the mounting kit produced meets all other requirements of this specification. Used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the CLAMS.

3.4 Design and construction. The CLAMS shall conform to the parts inventory list of TA13227E0200.

3.4.1 Interchangeability. Interchangeability of CLAMS components shall be in accordance with MIL-STD-280.

3.4.2 Soldering. Unless otherwise specified, soldering of electrical connections shall be in accordance with MIL-STD-454.

3.4.3 Human factors engineering. The CLAMS shall conform to human factors engineering design criteria as described in MIL-STD-1472. Special design emphasis shall be given, but not limited to, paragraphs 4 (General Requirements), 5.1 (Control/Display Integration), 5.2 (Visual Displays), 5.4 (Controls), 5.5 (Labeling), 5.6 (Anthropometry), 5.9 (Design for Maintainer), and 5.13 (Hazards and Safety) of MIL-STD-1472, as applicable.

3.5 Environmental requirements.

3.5.1 Temperature.

3.5.1.1 Operating temperature. The CLAMS shall be capable of dispensing markers during and after exposure to temperatures in the range of -25 to +140°F.

3.5.1.2 Storage temperature. The CLAMS shall be capable of dispensing markers after exposure to temperatures in the range of -60 to +160°F.

3.6 Treatment and painting. The CLAMS shall be finished or painted to provide a low gloss, camouflage surface. All hardware not normally painted shall be treated to provide lusterless finish. Normally painted surfaces

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:13Z
Check the source to verify that this is the current version before use.

shall be cleaned and treated conforming to TT-C-490, applicable method I through IV, type I (zinc phosphate) or III (wash primer), 0.3 - 0.5 mil thick. Prime per MIL-P-53030 or MIL-P-53022. Primer shall have a dry film thickness of 1.0 - 1.5 mils. The top coat color shall be camouflage green 383, applied to a dry film thickness of at least 1.8 mils without sags, runs, or thin areas and shall conform to MIL-C-46168 or MIL-C-53039.

3.7 Identification and marking. The CLAMS shall be identified in accordance with MIL-STD-130 and marked in accordance with ANSI/AS 478.

3.8 Safety. The contractor shall assure that the equipment meets applicable US Army safety requirements as presented within and presents no hazards to personnel during any phase of its life cycle.

3.8.1 Safety engineering. The system design criteria shall be in accordance with CFR 1910, Requirement 1, MIL-STD-454, and paragraphs entitled "Labeling" and "Hazards and Safety" of MIL-STD-1472, and shall include but not be limited to the following:

3.8.1.1 Personnel safety. The system shall be designed to minimize the probability and severity of injury to personnel throughout the system life cycle. Personnel safety shall not be considered as a candidate for trade-off.

3.8.1.2 Mechanical safety. The system design shall include the safety provisions called for in the paragraph entitled "Mechanical Hazards" of Requirement 1, MIL-STD-454. Sharp edges and corners which present personal safety hazards or potential damage to equipment during operation shall be adequately protected or rounded to a minimum radius of 13 mm (1/2 in). Where applicable, all other exposed edges and corners shall be rounded to a minimum radius of 0.75 mm (0.03 in).

3.8.1.3 Electrical safety. The system design shall include the safety provisions called for in paragraph entitled "Electrical" of Requirement 1, MIL-STD-454.

3.9 Workmanship. Workmanship shall be such that the assembly shall be free of burrs, sharp edges, cracks, corrosion, surfaces out of alignment or out of contour (visually apparent). There shall be no evidence of conditions that could present a safety hazard to operating or maintenance personnel. The assembly shall contain no loose or foreign material. Workmanship of electrical components shall be in accordance with MIL-STD-454, requirement 9.

3.9.1 Welding certification.

3.9.1.1 Welding. The surface of parts to be welded shall be free from rust, corrosion, scale paint, grease, and mill scale that can be removed by chipping and wire brushing, as well as from other foreign matter. Welds shall withstand stress without permanent deformation, or failure, when the parts connected by the welds are subjected to proof and service loading. Parts to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

be joined by fillet welds shall be bought into close contact as possible and in no event shall be separated by more than 3/16 inch unless appropriate bridging techniques are used. The welding process used in fabrication of the CLAMS shall be as specified in applicable drawings. No deviations from these requirements are permissible without prior approval from the procuring activity.

3.9.1.2 Welders or welding operator. Before assigning any welder or welding operator to manual welding work covered by this specification, the contractor shall obtain certification that the welder or welding operator has passed qualification tests as prescribed by either AWS D1.1 or the ASME code for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined. Contractors who only make horizontal welds need not qualify welders for "all position welding." The contractor is responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes. In the event of evidence of poor welds, the Government reserves the right to require retesting of any welder or welding operator (see 6.5).

3.10 Operation. The CLAMS shall be capable of manually dispensing markers and automatically dispensing markers at intervals of 6, 12, 18, 24, 36, and 48 meters (+/- 0.3 meters).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, not does it commit the Government to acceptance of defective material.

4.1.2 Inspection of equipment. Unless otherwise specified in the contract, the contractor is responsible for the provisioning and maintenance of all inspection and test equipment necessary to assure that supplies and services conform to contract requirements. Commercial, modified commercial, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

contractor deigned inspection equipment or measuring set-ups must be capable of repetitive measurements to an accuracy of 10 percent of component tolerance. Calibration of inspection and test equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection. The inspection specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The CLAMS shall be examined as specified in 4.5.1 in the order shown. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The CLAMS shall be subjected to tests marked "X" in column 2 of the table in 4.5.2.1, in the order shown. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105, table I and table II-A.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5. Accept if zero defects found, reject if one or more defects found.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.1. Failure of any test shall be cause for rejection.

4.5 Examination procedure.

4.5.1 Examination. The CLAMS shall be examined as specified herein for the following defects:

MAJOR

101. Material not as specified.
102. Components missing, not as specified, or damaged.
103. Dimensions not as specified.
104. Treatment and painting not as specified.
105. Interchangeability not as specified.
106. Soldering not as specified.
107. Hardware not as specified.
108. Human Factors Engineering not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

109. Welding and welds not as specified.
110. Safety not as specified.
111. Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments as specified.
112. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other as specified.
113. Contractor does not have documentation available for identification of material, material finishes, or treatment.
114. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the CLAMS.
115. Welders and welding operators not certified as specified.
116. Identification and marking not as specified.
117. Workmanship not as specified.

4.5.2 Operational. The CLAMS shall be operated to demonstrate the manual and automatic drop mechanism. The distance at which the markers drop in the automatic mode must be measurable. The CLAMS shall drop at least 5 markers in the manual mode and 5 markers at each of the automatic settings.

4.5.2.1 Test schedule

TABLE I. Test schedules.

Test Order 1	First Article 2	Quality Conform 3	Test 4	Test Paragraph 5	Requirement Paragraph 6
1	X		Low temperature	4.5.3.1	3.5.1.1
2	X		High temperature	4.5.3.2	3.5.1.1
3	X		Storage temperature	4.5.3.3	3.5.1.2
4	X	X	Operational	4.5.4	3.10

4.5.3 Operating temperature.

4.5.3.1 Low temperature. Subject the CLAMS to the low-temperature test specified in MIL-STD-810, method 502.2, procedure II to verify conformance to 3.5.1.1. Maintain the temperature at -6°F for a period of 24 hours. At the conclusion of this time, stabilize the assembly at low extreme temperature specified in 3.5.1.1 and operate system manually and drop at least 10 markers.

4.5.3.2 High temperature. Subject the CLAMS to the high-temperature test specified in MIL-STD-810, method 501.2, procedure II to verify conformance to 3.5.1.1. Maintain the temperature at 160°F for a period of 48 hours. At the conclusion of this time, stabilize the assembly at the high extreme

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

temperature specified in 3.5.1.1 and operate system manually and drop at least 10 markers.

4.5.3.3 Storage temperature. The CLAMS is to be tested in accordance with MIL-STD-810, method 502.2 and method 501.2, procedure I to verify conformance with 3.5.1.2.

4.5.4 Operational. The CLAMS shall be operated in the manual and automatic modes. The CLAMS control box shall be used to dispense and activate five markers in the manual mode and in each of the automatic settings specified in 3.10. Failure to dispense or activate any marker shall be cause for rejection.

4.6 Inspection of packaging.

4.6.1 First article packaging inspection. The first article pack shall be examined for the defects listed in 4.6.2.3. The presence of one or more defects shall be cause for rejection.

4.6.2 Quality conformance inspection of packaging.

4.6.2.1 Unit of product. For the purpose of inspection only, a unit of product shall be a complete CLAMS that has been prepared for shipment.

4.6.2.2 Sampling. Sampling for inspection shall be in accordance with MIL-STD-105, table I and table II-A.

4.6.2.3 Examination. Samples selected for examination in accordance with 4.6.2.2 shall be examined for the following defects. One or more defects shall be cause for rejection.

No.	Defect	Level A	Level C
118	Unpainted or machined ferrous metal surfaces not preserved as specified.	5.2.1	
119	Items in carton not wrapped as specified.	5.2.1	
120	Technical publications not sealed in polyethylene bag as specified.	5.2.2	
121	Shipping container not as specified.	5.3.1	5.3.2
122	Strapping not as specified.	5.3.1	5.3.2
123	Contents not cushioned, blocked, braced, and anchored within shipping container as specified.	5.3.1	5.3.2
124	Marking not as specified.	5.4	5.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 First article pack. The contractor shall furnish a first article pack for examination within the time frame specified (see 6.2), to prove, prior to starting production packaging, that the applied preservation, packing, and marking comply with the requirements of this specification. Examination shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 3.1.1). The first article pack may be accomplished utilizing either the first article model or a production model. If the first article model is utilized and the Government requests a comparison between the first article model and a production model, any preservation and packing shall be removed by the contractor at no expense to the Government.

5.2 Preservation. Level of preservation shall be level A as specified (see 5.3).

5.2.1 Ferrous metal surfaces. Any unpainted or machined ferrous metal surfaces on any of the CLAMS components shall be coated with preservative conforming to MIL-C-16173, grade 2, or equivalent. Those items placed in individual cartons shall be wrapped with barrier material conforming to MIL-B-121.

5.2.2 Technical publications. Technical publications shall be placed together in a suitably sized polyethylene bag, not less than 4 mils thick. The bag shall be closed by heat sealing.

5.3 Packing. Packing shall be level A or C as specified (see 6.2).

5.3.1 Level A. Each complete CLAMS, preserved as specified in 5.2, shall be packed as a kit in a snug-fitting box conforming to PPP-B-601, overseas type, style A. Box enclosure and strapping shall be as specified therein, except that the strapping shall be flat and zinc coated. The contents shall, as applicable to prevent damage to the contents or box, be cushioned, blocked, braced, and anchored in accordance with the requirements of MIL-STD-1186.

5.3.2 Level C. Each complete CLAMS, preserved as specified in 5.2, shall be packed for level C in the same manner as specified for level A in 5.3.1 except that the box shall be domestic type and the strapping shall be coated finish.

5.4 Marking. In addition to any special or identification markings required by the contract or purchase order, each container shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The CLAMS is mounted on main battle tanks equipped with a mine neutralization device, such as a mine roller or blade during mine-field breaching. The CLAMS is used to center mark the cleared vehicle path through mine fields. Then other vehicles lacking countermine capability can traverse the cleared lane marked by the CLAMS. Attachment to the tank is provided by a CLAMS mounting kit.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1).
c. Time frame required for submission of first article kit (see 3.2).
d. Data requirements.
e. Government and contractor inspection responsibilities (see 4.1).
f. Level of preservation and level of packing required (see 5.2 and 5.3).
g. Number of units required for first article inspection.
h. Time frame for submission of first article pack (see 5.1).
i. Any special markings (5.4).

6.3 First article. When a first article inspection is required, the item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements of examinations, approval of the first article test results, and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 First article pack. Any changes or deviations of production packs from the approved first article pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, pack, and mark the items in accordance with this specification.

6.5 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Description (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are resulted/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD Far Supplement 27.475-1 exempts the requirements for a DD Form 1423.

Reference paragraph	DID Number	DID Title
3.9.1.2	DI-MISC-80876	Welding Procedure Qualification Test Report
3.9.1.2	DI-MISC-80875	Welding Procedures

6.6 Subject term (key word) listing.

Chemical lighting
Cleared lane marking system
Countermine equipment
Mine warfare

Custodian:
Army - ME

Review activity:
Army - AT

Preparing activity:
Army - ME

Project 2590-A014

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-53128(ME)	2. DOCUMENT DATE (YYMMDD) 920410

3. DOCUMENT TITLE Cleared Land Marking System (CLAMS)

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Gerry Harlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3469 (2) AUTOVON 654-3469
c. ADDRESS (Include Zip Code US Army Belvoir RDE Center ATTN: STRBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 Previous editions are obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:13Z
Check the source to verify that this is the current version before use.