MILITARY SPECIFICATION

DISTRIBUTOR, WATER, SELF-PROPELLED; MINIMUM 2500 GALLON, SECTIONALIZED AND NON-SECTIONALIZED

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial water distributor of the articulated, tractor-tanker type equipped with a diesel engine, a power-shift transmission, and off-the-road earthmover tires on 2-axles. The distributor shall self-load, transport, and evenly distribute a minimum of 2500 gallons of water.

1.2 Classification. The distributor shall be of the following types, as specified (see 6.2):

Type I - Non-sectionalized (Air Transportable and Airdroppable).
Type II - Sectionalized (Air Transportable, Airdroppable, and Helicopter Transportable).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-514	- Plates, Identification, Instruction, and Marking, Blank.
MIL-L-2104	- Lubricating Oil, Internal Combustion Engine Tactical Service.

FSC 3825

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

MIL-L-2105	- Lubricating Oil, Gear, Multipurpose.
MIL-T-3351	- Tractor, Full-Tracked, Low Speed; Tractor, Wheeled, Agricultural; and Tractor, Wheeled, Industrial; and Their Attachments, Packaging of.
MIL-M-7866	- Molybdenum Disulfide, Technical, Lubrication Grade.
MIL-G-10924	- Grease, Automotive and Artillery.
MIL-G-23827	- Grease, Aircraft and Instrument, Gear and Actuator Screw.
MIL-A-46153	- Antifreeze, Ethylene Glycol, Inhibited, Heavy Duty, Single Package.
MIL-L-46167	- Lubricating Oil, Internal Combustion Engine, Arctic.
MIL-B-46176	- Brake Fluid, Silcone, Automotive, All Weather, Operational and Preservative.
MIL-E-52798	- Enamel, Alkyd, Camouflage.
MIL-S-52986(ME)	- Scraper, Elevating, Self-Propelled, 9 Cycle Minimum Heaped Capacity, Sectionalized and Non-Sectionalized.

STANDARDS

MILITARY

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-209	- Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment
MIL-STD-669	- Loading Environment and Related Requirements for Platform Rigged Airdrop Materiel.
MIL-STD-814	- Requirements for Tiedown, Suspension and Extraction Provisions on Military Materiel for Airdrop.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment

MILITARY HANDBOOK

AIR FORCE SYSTEM COMMAND

Design Handbook DH1-11	- Air Transportability.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ANSI/ASTM A120	- Black and Hot-Dipped Zinc-Coated (Galvanized) Welded and Seamless Steel Pipe for Ordinary Uses, Specification For.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

ANSI/ASTM D2239	- Polyethylene (PE) Plastic Pipe (SD R-PR), Specification For.
ASTM D2737	- Polyethylene (PE) Plastic Tubing, Specification For.
ASTM/ASTM D2751	- Acrylonitrile - Butadiene - Styrene (ABS) Sewer Pipe and Fittings, Specification For.

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 194 - Fire Hose Coupling, Screw Threads.

NFPA No. 196 - Fire Hose.

(Application for copies should be addressed to the National Fire Protection Association International, 60 Battery March Street, Boston, MA 02110.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TECHNICAL INFORMATION PACKAGE

(Application for copies should be addressed to US Army Mobility Equipment Research and Development Command, ATTN: DRDME-H, Fort Belvoir, VA 22060.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 General. The water distributor shall be the latest model of the standard product of the contractor and shall have demonstrated industry acceptability by having been manufactured, marketed, and sold in significant numbers to the commercial public for the same or similar application, interfacing with the same or similar components, except as specified herein, for at least 1 year prior to invitation for bids or request for proposal. Product improvements incorporated in the commercial production units in this 1 year period are acceptable. In the case of a recently introduced item, the contractor shall submit sufficient valid industrial operational/test data including all test reports for the item and its components, such as engine, transmission and hydraulic system, field user reports, including any failures or problem areas, and corrective action taken to demonstrate acceptability of the item. When specified requirements are not stated herein, all items listed as standard equipment in the contractor's published specification brochures and catalogs, or normally furnished to com-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

mercial customers as standard equipment, shall be furnished. The distributor shall be equipped with any optional equipment necessary to comply with requirements specified herein. Optional equipment is defined as equipment not standard with the distributor but which has been furnished to the commercial customer, such as special features or allied equipment. The distributor shall be equipped with all components necessary to enable the distributor to function reliably and efficiently in sustained operation. The distributor shall conform to all Federal Laws and regulations governing safety, noise levels, and pollution, which are in effect on the date of invitation for bids or request for proposal. The tractor section shall be interchangeable with the tractor section of the scraper conforming to MIL-S-52986. The interchangeability requirement shall be accomplished at the user level without cutting or welding.

3.2 Description. The water distributor shall consist of a tractor front section and a tanker rear section. The distributor shall be of the diesel engine driven, earthmoving equipment type having 4 off-the-road tire assemblies with the 2 front tires driving and the 2 rear tires trailing. The distributor shall consist of the following:

(a) Tractor section. (In accordance with MIL-S-52986(ME) - - - - - -3.10
(b) Hydraulic System. -3.15
(c) Tank Body and Equipment Section.- - - - - - - - - - - - - - - - -3.11
(d) Pump and Plumbing -3.12, 3.13
(e) Distributor System. -3.14

Component and vehicle ratings shall be not greater than each manufacturer's published rating. Components and equipment ratings shall not be raised to meet the requirements of this specification.

3.2.1 Type I. The type I distributor with rollover protecting structure/falling object protective structure (ROPS/FOPS) removed shall be capable of being loaded and rigged on an air delivery platform in accordance with MIL-STD-669, air transported and air delivered by parachutes.

3.2.2 Type II. The type II distributor with ROPS/FOPS removed shall meet the requirements specified for type I (see 3.2.1) and shall also be capable of being sectionalized into 2 sections for external air transport by helicopter. Sectionalization material may be removed for airdrops.

3.3 First article (preproduction models). The contractor shall furnish two distributors of each type for examination and demonstration within the time frame specified (see 6.2), to prove prior to starting production that the production methods and choice of design detail will produce distributors that comply with the requirements of this specification. The examination and demonstrations shall be as specified in Section 4. Following successful completion of the examination and demonstration by the contractor, the Government shall perform a simulated airdrop demonstration on one of each type distributor at a site selected by the Government. The examination and all demonstrations conducted by the contractor shall be subject to surveillance and approval by the Government. Acceptance of the preproduction models will be dependent on successful completion of the examination, contractor demonstrations, and the Government conducted simulated airdrop demonstration.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

3.4 Production equipment. All distributors of the same type furnished under this specification shall be physically and mechanically identical to the first article distributor approved by the Government.

3.5 Material. Material not specified herein shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.6 Safety. All available standard or optional accessories shall be included to provide protection for maintenance and operating personnel from rotating or reciprocating parts and from all parts subject to high operational temperatures and so located as to be a hazard. Exhaust discharges shall be directed so as to not endanger personnel. All platforms and steps shall have anti-skid surfaces. Contractor's standard grab irons shall be provided. A decal shall be furnished and shall be located in the area of the articulation point, warning of limited personnel clearance during frame articulation and placement of safety pin or bar for the distributor operating and transport modes.

3.6.1 Sound level. The exterior sound level of the distributor shall not exceed 88 dB(A) when measured in accordance with SAE J88. If the sound level in the area occupied by the operator exceeds 85 dB(A) when measured in accordance with SAE J919, a warning plate containing the following shall be permanently affixed to the distributor in a conspicuous protected location.

"WARNING, EAR PROTECTION REQUIRED WHEN OPERATING THIS EQUIPMENT."

The plate shall have a yellow background with black lettering and shall be on corrosion-resistant material.

3.7 Physical characteristics.

3.7.1 Weight limits. For airdrop, the distributor, without the removeable ROPS/FOPS, without auxiliary hose assembly, without sectionalization kit, but with all other attachments, accessories, coolant, lubricating and hydraulic systems filled to capacity and with not less than 25 percent nor more than 75 percent fuel, shall weigh no more than 30,600 pounds. The type II distributor when sectionalized into 2 sections shall weigh not more than 16,000 pounds per section.

3.7.2 Dimensions. The overall width of the distributor shall not exceed 98 inches except that the width may be increased to not more than 105-inches to accomodate special airborne/airmobile provisions. The overall length of the distributor shall not exceed 372-inches. In order to conform to a height limit of 100 inches when rigged for airdrop, the reducible height of the distributor should be not more than 91 inches. No major component removal, except ROPS/FOPS canopy, shall be required to obtain the reduced height. If the height exceeds 91 inches, the contractor must demonstrate prior to step I proposal opening date that the distributor can be rigged so as to conform to the 100 inch limit, and withstand the forces encountered in the simulated airdrop impact test (see 4.5.2.12) without damage or permanent deformation.

3.8 Sectionalization. The type II distributor,less ROPS/FOPS shall be capable of being sectionalized into two sections for helicopter transport. The weight of either section shall not exceed 16,000 pounds. The powered section

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

shall be driveable and steerable under its own power for a distance of 50 feet over relatively flat unimproved areas. Reassembly time with tools furnished with the distributor under field conditions without assistance of other powered equipment shall not exceed 4 hours. Cutting and welding are not permitted. Components and accessories used in sectionalization and reassembly shall be stored on the distributor or in a demountable container attached to the vehicle but shall not interfere with the operation of the equipment.

3.9 Performance. The distributor shall withstand the usage encountered in military operations such as self-loading, hauling and evenly distributing water. The distributor shall withstand crossing roadless rough terrain, including gullies causing the tractor tanker to oscillate in both directions, fording streams, and negotiating steep longitudinal and sidehill slopes, without damage. The distributor shall be capable of having its normal construction tasks performed by one operator including filling of the tank. The distributor shall be capable of driving at maximum travel speed in transport, being towed by another vehicle, and limited towing of other equipment.

3.9.1 Travel speed. The distributor shall be capable of a forward travel speed of not less than 20 mph, loaded, on level pavement.

3.9.2 Braking. The distributor's braking performance shall be in accordance with SAE J1152.

3.9.3 Stability. The distributor shall be capable of negotiating at least a 10-percent side slope.

3.9.4 Fording. The distributor shall start and operate during and after fording operations in fresh water to a depth of 20 inches including wave action without damage and without leakage of water into any resorvoir including reservoirs containing lubricants.

3.9.5 Environmental conditions. The water tanker section shall be capable of distributing water in temperatures from plus 35° to 120° F. The tractor section shall be as specified in 3.10.

3.10 Tractor section. The forward tractor section of the distributor shall be in accordance with the tractor requirements for the earthmoving scraper in MIL-S-52986(ME). The tractor shall be physically interchangeable from distributor to scraper and from scraper to distributor including scraper controls.

3.11 Water tanker section. The rear water tanker section of the distributor shall be as specified herein. The tanker section shall provide the volume and structure necessary for the capacity of at least 2500-gallons of water plus 3 percent expansion space. The payload weight shall be based on water at 8.3 pounds per gallon and 62.3 pounds per cubic foot. The tanker section shall include a coupler and gooseneck, water tank, running gear, guarded water lever sight gage, hydraulically driven pump, plumbing, and nozzles.

3.11.1 Tank. The tank shall be fabricated from steel of at least 1/4-inch plate and shall have the front and rear heads welded into the tank skin employing either lap joint or ring stiffener design. The tank shall include structurally

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:11Z
Check the source to verify that this is the current version before use.

reinforcing lognitudinal and transverse baffle members to strengthen the tank and restrict water surge. The interior of the tank shall be treated to resist the corrosive effects of air and water. Drains shall be provided at the lowest portions of the tank and all plumbing components so that all water can be drained by gravity to prevent damage during freezing ambient temperatures. The materials and treatments used in the construction of surfaces in contact with the water shall be non-toxic to the health of personnel when the distributor is used to transport potable water.

3.11.2 Manhole. The tank shall be equipped with a round or oval manhole opening not less than 30-inches in major diameter. A light weight, liquid-tight, easy opening, quick-latching manhole cover shall be supplied. Hinged covers shall be hinged at the forward edge.

3.11.3 Vents. Vents shall be provided to allow for expansion of the water in the tank and discharging the tank at maximum rate with the manhole and fill cover sealed.

3.11.4 Catwalk and ladder. A catwalk not less than 24-inches wide shall be provided over the top of the tank. The catwalk shall be centrally located at the manhole. The catwalk shall withstand a minimum loading of 300-pounds on each square foot and shall be of the open serrated grating type. A non-skid access ladder shall be provided for access to the catwalk. Both catwalk and ladder shall be in accordance with SAE J185. All operator access areas shall be equipped with non-skid decking surfaces and handholds that permit use of arctic mittens as shown in SAE J925.

3.11.5 Rear running gear. The rear running gear on the rear section of the distributor shall include a non-driving axle or twin spindles having the same interchangeable brakes and tire and wheel assemblies, including scraper rear frame and bumper as provided for the scraper. The equipment rear running gear shall be equipped with rear fenders to restrict mud throwing and splash from the tire. The fenders shall support a minimum weight of 300 pounds over any 1 square foot area.

3.12 Pump. A hydraulically driven, minimum 4-inch centrifugal pump shall be installed either in the tank or at the rear of the tank. The pump shall be of the self-loading type. The pump self-loading system shall include plumbing and valving with an isolating auxilary water section in the main tank of at least 100 gallons to assure at least two primings of the water pump. Pump impeller materials shall be corrosion resistant. The pump, shall be capable of lifting water from 10-feet below ground level through the 30-feet of suction hose to self-load water to the top of the tank. The pump and tank shall be equipped with a low water level warning indicator. Waterproof instruction cards, in accordance with 3.21, shall be provided in Government furnished container to provide the operator with the water distribution rate on the ground in gallon-per-100-foot length pattern, correlated to the following variables:

(a) First and second tractor transmission geared speeds at governed engine rpm.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

(b) Water pump speeds of 100 percent and 50 percent of engine governed rpm.
(c) Per nozzle at maximum opening size, using 1, 2, 3, and 4 nozzles.

3.13 Plumbing. The distributor plumbing shall conform to the following:

(a) Provide a mesh screen strainer in the pump inlet line which is removable and accessible for cleaning to prevent damage to the pump.
(b) Provide an outlet valve with remote operator control; locate valves within the perimeter of the distributor and include break-away-joints between the valve and the nozzles.
(c) Provide plumbing to the water distribution system using metal water pipe covered by ASTM A120 and elastomer water pipe covered by ASTM D-2239, D2737, or D2751.
(d) Provide both gravity and pump pressure feed from the tank to the water distribution system; in addition, also furnish a capped outlet fitting for future user installation of a multi-nozzle, transverse rear spraybar.
(e) Provide two lengths of suction hose, for self loading, each length 15-feet long; provide male and female couplings of the cam-lock type on the hose and the tank; provide a strainer and foot valve for the hose; provide hose tubes for securely stowing the hose on the tank; provide each open end of the hose stowage tube with a latching metal protective cap to prevent entry of dirt and water; provide cap with hinges or captive chains to prevent loss of caps.

3.14 Water distribution system. The water distribution system shall be by pressurized nozzles. The distribution system shall route water from the pump outlet to a rear mounted transverse pipe feeding four (4) adjustable, non-ferrous fan spray nozzles. Each nozzle shall be independently compressed air remote controlled from the tractor operator's compartment having air pressure open and spring close features. Each nozzle shall be horizontally adjustable 180 degrees using common hand tools and provide coverage from a 15-foot swath to not less than a 30-foot swath. The width of nozzle spray shall be manually adjustable at the nozzle. The maximum operation of all four nozzles shall provide a width coverage of not less than a 65-foot swath.

3.15 Hydraulic system. The water distribution system shall be actuated by the tractor hydraulic system in MIL-S-52986. The hydraulic system shall be as follows:

(a) Provide the complete hydraulic system having all components as recommended by the hydraulic pump and motor manufacturer's recommendations.

(1) Operate with rated load without overheating binding, malfunction, or permanent deformation.
(2) Capable of withstanding maximum proof pressure without leakage as recommended by the pump manufacturer.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

3.16 Electrical system. The contractor's standard 24 volt electrical system shall be furnished.

3.16.1 Lighting. In addition to the tractor section lighting in MIL-S-52986, the following lights with associated circuits, and switches shall be provided:

(a) Combination stop and taillights.
(b) Turn signals.
(c) Two rear floodlamps.

3.16.2 Electromagnetic. The distributor (including the tractor in MIL-S-52986) shall comply with the electromagnetic radiation limits of SAE J551.

3.16.3 Back-up alarm. A back-up alarm conforming to SAE J994 shall be furnished.

3.17 Towing devices. The distributor shall be equipped with a rear towing device, in addition to the tractor's front towing device in MIL-S-52986.

3.18 Attachments. The removable attachments shall not be included in determining the airborne and airmobile weights of the distributor in 3.7.1 and 3.8.

3.18.1 Auxiliary discharge hose and reel. A removable auxiliary hose and reel assembly shall be furnished. The assembly shall be a hose reel with swivel, valve, and at least 70-feet of 1-1/2 inch inside diameter, elastomer lined, NFPA No. 194 and 196 fire hose assembly. A crank shall be provided for hand rewind of the winding mechanism. A ratchet device shall be provided to prevent tension or looseness on the hose. Four-way roller guides shall be provided to prevent damage to the hose when used other than straight out. The hose and reel assembly shall be mounted between the rear wheels. The free end of the hose shall be fitted with a delivery nozzle. The nozzle shall be equipped with a 1-1/2-inch diameter rigid spout. The nozzle shall be of the shutoff type or shall have a shutoff valve at the nozzle inlet. A metallic dust cap shall be furnished for the nozzle spout.

3.19 Transportability. The distributor shall be capable of being transported by surface, rail, ocean-going carriers, and C130, C141, and C5A aircraft. The distributor shall withstand the impact forces encountered in air and rail shipments without damage or permanent deformation. The distributor shall conform to MIL-STD-669 for airdrop from C-130 aircraft and shall withstand stresses imposed when tested in accordance with 4.5.2.12 without breakage or permanent deformation of any structural member or component, or loss of ability of the distributor to perform all of its intended functions. When rigged for airdrop in accordance with MIL-STD-669, the distributor shall meet the established tip-off curves for C-130 and C-141 aircraft as defined in AFSC Design Handbook DH1-11. The distributor shall be equipped with slinging provisions and shall be capable of being lifted without damage using slings. The distributor shall be equipped with tiedown provisions for transport by the above modes. Suspension and extraction parachute provisions shall be provided for parachute delivery. Complete diagrams and instructions for lifting the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

distributor and tying down the distributor on freight cars and truck trailers shall be furnished in the operator's manual. The operator's manual shall also include instructions for component removal when required for transport. The contractor shall provide sufficient data to the Government with the step I proposal to confirm that the distributor being supplied can be loaded and transported in the C130, C141 and C5A aircraft. A steering frame lock in accordance with SAE J276 shall be provided. Removal of ROPS and other components to reduce overall height or width shall not prevent the distributor from driving onto military transport equipment under its own power.

3.19.1 Parachute suspension provisions. Four integral suspension provisions conforming to MIL-STD-814 shall be furnished on the distributor. The parachute suspension provisions shall withstand the stresses in the amount and direction of pull specified without weld failure or permanent deformation of the distributor or the provision.

3.19.2 Slinging provisions. The distributor shall be provided with four slinging provisions conforming to MIL-STD-209. In addition, each section of the type II distributors shall be provided with four slinging provisions conforming to MIL-STD-209. The provisions shall enable the distributor to be lifted in the normal traveling or operating position. Provisions shall be positioned so that the lifting strain shall be in line with the longitudinal axis of the eye of the provision. Provisions shall be fastened to members which will withstand stresses in the amount and direction of pull specified for the provision without weld failure or permanent deformation of the distributor or the provision. Parachute suspension provisions may be used as slinging provisions if they meet the requirements of MIL-STD-209.

3.19.3 Tiedown provisions. The distributor shall be provided with integral provisions to permit tiedown of the distributor to the floor or deck of the transportation medium or the airdrop platform. The tiedown provisions shall conform to MIL-STD-209 and MIL-STD-814 and shall withstand stresses in the amount and direction of pull specified without weld failure or permanent deformation of the distributor or the provision.

3.19.4 Extraction parachute provision. A single fitting shall be provided on the distributor for attachment of the parachute extraction system. Except as specified herein, the fitting shall conform to MIL-STD-814 and shall withstand stresses in the amount and direction of pull specified without weld failure or permanent deformation of the distributor or the provision. In lieu of the limit load specified in MIL-STD-814, the limit load of the provision shall be 56,580 pounds. The design ultimate strength of welded sections shall be four times the limit load.

3.20 Identification plates and marking. Each distributor shall be furnished with an indentification plate showing the contractor's model number, NSN, USA registration number, vehicle identification number, weight, date of manufacture and date of delivery. The identification plate shall be permanently affixed to the distributor in a readily accessible and conspicuous location. Plates shall conform to MIL-P-514 or contractor's standard plates subject to the approval of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

the contracting officer. All attachments or components removed or disassembled for shipment shall be matchmarked for proper reassembly. The distributor and each attachment shall be identified in accordance with the contractor's standard method.

3.21 Instruction plates. The distributor shall be equipped with instruction plates including warnings and cautions suitably located and permanently affixed, describing any special or important procedure to be followed in operating and servicing the distributor. Plates shall conform to MIL-P-514 or contractor's standard plates subject to the approval of the contracting officer. Instructions for water distribution rate (see 3.12) and for disassembly of the type II distributor into two sections and reassembly shall be provided on cards, approximately 8-1/2-inches by 11-inches, which shall be encased in laminated plastic. One set of these cards shall be furnished with each distributor.

3.22 Shipping data plates. Shipping data plates for each distributor shall be furnished and shall show the silhouette of the distributor (and each section of type II distributor, only), indicating the location and capacity of tiedown provisions, slinging provisions, extraction provisions, suspension provisions, the center of balance and shipping weight. Plates shall conform to MIL-P-514 or contractor's standard plates subject to the approval of the contracting officer. The plates shall be attached to the left side of the distributor and shall show the locations as viewed from the left side. The plates on the sections, (type II distributors only) shall be located in conspicuous protected locations. All plates shall be permanently attached.

3.23 Treatment and painting. The portions of the distributor normally painted shall be cleaned, treated, primed and painted in accordance with the contractor's standard commercial practice. The exterior finishing coat shall be in accordance with MIL-E-52798, forest green color, and the interior coating of the tank shall be in accordance with 3.11.1 for non-toxic characteristics.

3.24 Stenciling instructions. Stenciling instructions shall be provided with each set of technical publications. The instructions shall be provided in card form showing location and wording for tiedown, slinging, suspension, and extraction provisions, tire pressure and the center of gravity for the type I and type II distributor, and the sectionalization storage areas on the type II distributor.

3.25 Lubrication. A lubrication means shall be provided for all moving parts requiring lubrication, Each distributor shall be serviced and run-in with military lubricants conforming to MIL-L-2104, MIL-L-2105, MIL-L-46167, MIL-M-7866, MIL-G-10924, and MIL-G-23827, as applicable. Silicone fluid for hydraulic brakes shall be in accordance with MIL-B-46176.

3.26 Technical publications. Such technical publications as are specified (see 6.2) shall be furnished.

3.27 Special tools. Any nonstandard or special tools required for equipment operation and operator maintenance of the distributor shall be furnished with the distributor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.28 Toolbox. A lockable weather protected storage compartment(s) or toolbox of sufficient size to hold all tools and equipment required for operation and operator maintenance shall be provided.

3.29 Technical information package. The contractor shall complete and submit a Technical Information Package within the time frame specified (see 6.2), depicting the distributor and its components exactly as it will be furnished. The Technical Information Package shall be submitted with all bids and proposals.

3.30 Government-furnished equipment (GFE). The following items shall be furnished by the Government (see 6.3):

(a) Container NSN 7520-00-559-9618 complete with maintenance forms. (The contractor shall furnish the fasteners and install the containers on the distributor.)
(b) Supplemental operating, maintenance and repair parts instructions. (SOMARPI).

3.31 Basic issue items. When specified (see 6.2), each item in the Basic Issue Item List shall be furnished with each distributor.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 Preproduction inspection. The first article (preproduction model) (see 6.2), furnished by the contractor shall be examined (see 4.3.1), and demonstrated (see 4.3.2), to determine compliance with the requirements of this specification. Prior to the examination and demonstration of the distributor, the following shall be performed:

(a) Service the distributor with the lubricants specified.
(b) Break in the distributor as prescribed by the contractor.

4.3.1 Preproduction examination. Prior to the preproduction demonstration, the distributor shall be examined for the defects marked "X" in column 1 of table I. Presence of one or more defects shall be cause for rejection. Prior

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

to the preproduction demonstration the distributor shall be examined and compared with this specification, with the contractor's published brochures, with commercial manuals, and with the completed Technical Information Package. Any discrepancy between the specification, brochures, manuals, or Technical Information Package and the preproduction models shall be cause for rejection. Prior to the preproduction demonstration, the certifications, and certified test reports required by 4.5.2.13 and 4.5.2.14 shall be examined. Incomplete, inaccurate, or otherwise unacceptable certifications, or certified test reports shall be cause for rejection.

4.3.2 Preproduction demonstration. Upon successful completion of the examination specified in 4.3.1, the preproduction model distributor shall be subjected to the demonstrations marked "X" in column 1 of table II. Failure of any demonstration or any demonstration reports shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Individual examination. After successful completion of the demonstration specified in 4.4.2, each distributor shall be examined for the defects marked "X" in column 2 of table I. Presence of one or more defects shall be cause for rejection.

4.4.2 Individual demonstration. Each distributor shall be demonstrated as specified in column 2 of table II. Failure of any demonstration shall be cause for rejection.

4.5 Inspection schedule.

4.5.1 Examination. The examination shall be in accordance with table I.

4.5.2 Demonstrations. Demonstrations shall be conducted in accordance with table II in the sequence listed

TABLE I. Examination schedule.

Preproduction Model(s)	Individual	Defect	Requirement Paragraph
1	2	3	4
X	X	101. Distributor type not as specified.	1.2
X	X	102. Distributor description not as specified.	3.2
X	X	103. Safety characteristics not as specified.	3.6
X	X	104. Sound level or warning plate not as specified.	3.6.1
X	-	105. Dimensions not as specified.	3.7.2
X	X	106. Sectionalization and components not as specified.	3.8

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule (cont'd)

Preproduction Model(s)	Individual	Defect	Requirement Paragraph
1	2	3	4
X	X	107. Tractor section not as specified (examine per scraper specification, MIL-S-52986(ME)).	3.10
X	X	108. Water tanker section not as specified.	3.11
X	X	109. Tank, man hole, and vents not as specified.	3.11.1 thru 3.11.3
X	X	110. Catwalk and ladder not as specified.	3.11.4
X	X	111. Running gear not as specified. (Examine per scraper specification.)	3.11.5
X	X	112. Pump not as specified.	3.12
X	X	113. Plumbing and components not as specified.	3.13
X	X	114. Water distribution system not as specified.	3.14
X	X	115. Hydraulic system not as specified.	3.15
X	X	116. Electrical system not as specified.	3.16 thru 3.16.3
X	X	117. Towing device not as specified.	3.17
X	X	118. Attachments not as specified.	3.18
X	-	119. Transportability not as specified.	3.19
X	X	120. Identification plates not as specified.	3.20
X	X	121. Instruction plates not as specified.	3.21
X	X	122. Shipping data plates not as specified.	3.22
X	X	123. Treatment and painting not as specified.	3.23
X	X	124. Stenciling instructions not furnished.	3.24
X	X	125. Lubrication not as specified.	3.25
X	X	126. Technical publications not as specified.	3.26
X	X	127. Special tools not furnished.	3.27
X	X	128. Toolbox not furnished.	3.28
X	-	129. Technical information package not as specified.	3.29
X	X	130. Government furnished containers not installed on distributor.	3.30

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule (cont'd)

Preproduction Model(s)	Individual	Defect	Requirement Paragraph
1	2	3	4
X	X	131. Basic issue items (if specified) not furnished.	3.31
X	X	132. Parts or components missing.	Section 3
X	X	133. Assembly incomplete or incorrect.	Section 3
X	X	134. Cracked or broken parts or assemblies.	Section 3
X	X	135. Permanent deformation of any part or assembly.	Section 3
X	X	136. Leaks in coolant, fuel, oil lines, or cylinders.	Section 3
-	X	137. Material not of same quality, used on preproduction distributor.	Section 3
X	X	138. Distributor not as specified or certification not availible or not as specified.	Section 3

TABLE II. Demonstration schedule.

Preproduction Models		Individual	Test	Test Paragraph	Requirement Paragraph
1		2	3	4	5
Type I	Type II				
X	X	X	Production run-in	4.5.2.1	Section 3
-	X	-	Sound level	4.5.2.2	3.6.1
X	X	-	Weight	4.5.2.3	3.7.1
X	X	-	ROPS removal	4.5.2.4	3.7.2, 3.19
-	X	-	Sectionalization and Interchangeabilily	4.5.2.5	3.1, 3.8
X	X	-	Parachute suspension provisions	4.5.2.6	3.19.1
X	X	-	Slinging provisions	4.5.2.7	3.19.2
X	X	-	Tiedown provisions	4.5.2.8	3.19.3
X	X	-	Extraction provisions	4.5.2.9	3.19.4
-	X	-	Performance	4.5.2.10	3.2, 3.9, 3.11
X	-	-	Water pumping system	4.5.2.11	3.12 thru 3.15
X	X	-	Airdrop	4.5.2.12	3.19

4.5.2.1 Production run-in. Start and operate each distributor as follows:

Operate the distributor in all gears forward and reverse at maximum speeds commensurate with conditions for one-half hour. Stop and restart the engine not less than five times. Operate all pump and valve controls for five-minute periods. Operate the distributor through not less than 10 full right and 10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

full left turns at the maximum speed commensurate with safe operation. Make not less than five abrupt panic stops from a speed not less than 20 mph using the service brake. Release and reapply the parking brake not less than five times. Turn on all lights for the duration of the run-in. Evidence of any deficiency, need for adjustment or maintenance, malfunction of any control, or evidence of leakage of fuel, lubricants, or hydraulic fluid shall be cause for rejection of the distributor by the Government until corrected to the Government's satisfaction. The Government may require additional run-in after deficiencies are corrected. Any defect found during production run-in shall be prima facie evidence that distributors previously accepted are similarly defective unless evidence satisfactory to the contracting officer, is furnished by the contractor that they are not similarly defective.

4.5.2.2 Sound level. The contractor shall perform sound level tests in accordance with SAE J88 and SAE J919. Certified prior test data is acceptable if available. Nonconformance to the requirements of 3.6.1 shall constitute failure of this demonstration.

4.5.2.3 Weight. The weights of the distributor and the distributor sections (Type II only) shall be measured with a scale calibrated within 6 months of the demonstration. Inability to meet the minimum and maximum weight limits of 3.7.1 shall constitute failure of this demonstration.

4.5.2.4 ROPS/FOPS removal and replacement. The removal and replacement of the ROPS/FOPS canopy shall be demonstrated following the procedures in the contractor's manual. Permanent deformation or damage to any part of the ROPS/FOPS canopy or its mounts, or inability to meet the requirements of 3.7.2 and 3.19 shall constitute failure of this demonstration.

4.5.2.5 Sectionalization and interchangeability. The type II distributor, less ROPS/FOPS, shall be demonstrated for compliance to sectionalization requirements of 3.8 and the interchangeability requirements of 3.1. The demonstrations shall consist of the following:

(a) Sectionalization. This demonstration shall be conducted on a relatively flat unimproved area of sufficient size for disassembly, maneuvering, and reassembly of the distributor. Using hand tools furnished with the distributor (no power tools allowed), separate the distributor into two sections. Drive the powered section under its own power for a distance of 50 feet from the remaining section and steer the powered section at least 45 degrees to the longitudinal axis of the remaining section. Drive and steer the powered section to join with the remaining section and reassemble the two sections into a composite unit using the above hand tools only. Record the time required for the maneuvering and reassembly operation. No chains, cables, hoists, blocking, or other vehicles shall be used to assist in the disassembly, maneuvering, and reassembly operations. Nonconformance to 3.8 shall constitute failure of this demonstration. The sectionalization demonstration will be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

compared to the disassembly and assembly instruction specified in 3.21. In addition, those assemblies or components unique to the type II vehicle, or required as a result of the sectionization feature, shall be evaluated and verified as a part of this test, to include disassembly, examination, and reassembly. Maintenance function, procedures, or tools peculiar to the type II equipment, as well as publications associated with the specific features of sectionization, shall also be evaluated and verified. All errors in publications or procedures shall be corrected by the contractor and submitted to the Government for approval prior to acceptance of the preproduction model of the distributor. During this demonstration, the water distribution functions and maintenance tasks shall be performed following procedures in the technical publications using common tools plus any special tools identified by the contractor.

(b) Interchangeability. This demonstration shall be conducted at any indoor or outdoor site by the contractor. Hoists, cables, chains, and overhead cranes maybe used in this demonstration as required. Separate the tractor section of the distributor from the tanker section. Connect the tractor section to the scraper bowl section of the earthmoving scraper conforming to MIL-S-52986, connecting all air, hydraulic, and electrical lines. Operate the scraper for at least 30 minutes activating all controls including at least one filling and emptying of the bowl using the elevator to fill. Failure to complete the tractor/scraper connection, or any malfunction during operation shall constitute failure of this demonstration.

4.5.2.6 Parachute suspension provisions. The parachute suspension provisions shall be demonstrated to prove conformance to 3.19.1. Apply a force of 1.5 times the limit load as specified in MIL-STD-814 to each of the parachute suspension provisions. Weld failure or permanent deformation of the distributor or suspension provisions shall constitute failure of this demonstration.

4.5.2.7 Slinging provisions. The slinging provisions shall be demonstrated to prove conformance to 3.19.2. Nonconformance to 3.19.2, weld failure, or permanent deformation of the distributor or the slinging provisions shall constitute failure of this demonstration. The demonstration procedure shall be as follows:

(a) Lift the distributor and hold in suspension in its normal travel position using slings that converge not more than 24 feet above the lowest extremity of the distributor. Spreader bars are permitted. Determine the force and angles of application for each provision. Measure the clearance between each sling and the distributor.
(b) Restrain the distributor by anchoring the main frame and subject each slinging provision to a force equal to the working load specified in MIL-STD-209. This force shall be applied in the direction as determined in (a) above. Hold each load for a minimum of 90 seconds.
(c) Repeat (a) and (b) above for each section of the type II distributor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

4.5.2.8 Tiedown provisions. The tiedown provisions shall be demonstrated to prove conformance to 3.19.3. Apply a force equal to the limit load as specified in MIL-STD-814 to each of the tiedown provisions. Weld failure or permanent deformation of the distributor or the tiedown provisions shall constitute failure of this demonstration.

4.5.2.9 Extraction parachute provision. The extraction parachute provision shall be demonstrated to prove conformance to 3.19.4. Apply a force equal to 1.5 times the limit load specified in 3.19.4 to the provision. Weld failure or permanent deformation of the distributor or the extraction parachute provision shall constitute failure of this demonstration.

4.5.2.10 Performance. The distributor shall be demonstrated as follows for a minimum total of 40 hours to prove conformance to 3.9, and 3.12, through 3.14.

(a) Travel - Drive the distributor at maximum speed over a smooth paved surface and over gravel and crushed stone haul roads and unimproved trails. Negotiate the distributor over off-road terrain. Demonstrate the distributor's ability to ford creeks and to cross V-ditches, typical of those along highways. Negotiate mud at least 12-inches deep while steering to both right and left (duck-walk). Immobilize the distributor in the muddy area and demonstrate its ability to withstand being retrieved by towing out or pushing out, both forward and rearward; continue towing the distributor with the engine shut down to a simulated, suitable repair area.

(b) Self-loading - Demonstrate the self-loading ability of the distributor for 10-tank fillings from a water source, 10-feet below the center of the pump inlet.

(c) Water distributing - Demonstrate the fan nozzle capability from all nozzles, distributing a total of 10-tank fulls at maximum flow. Then, demonstrate the individual capability at each nozzle to distribute water, 1/2-tank full at mininum spray pattern and the remaining 1/2-tank full at maximum spray pattern. Manually rotate each nozzle 180° using common hand tools.

Nonconformance to 3.9, 3.12 through 3.14 or any malfunction or breakage of mechanical hydraulic, or compressed air components shall constitute failure of this demonstration.

4.5.2.11 Water pump demonstration. Perform a demonstration of the water pump operational capability for a minimum of 2 hours pumping water at the capacity rated by the manufacturer. Correct all data to standard sea level atmospheric conditions of 29.92-inches of mercury and to the specific weight of water (62.3-pounds per cubic foot) at a temperature of 68° Fahrenheit (F) and compare with manufacturer's rating. Evidence of leakage, malfunction of any component, inability of the pump to operate up to rated capacity or as specified, or nonconformance to 3.12, 3.13, 3.14 or 3.15 shall constitute failure of this test.

4.5.2.12 Airdrop. The distributor shall be subjected to simulated airdrop impact demonstration in accordance with MIL-STD-669 to prove conformance to 3.19. This demonstration will be conducted by the Government at a Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

facility, however, acceptance of the preproduction models will be dependent on the successful completion of this demonstration. The demonstration shall consist of the following:

(a) Rig the machine in accordance with MIL-STD-669 and confirm that the rigged weight and dimensions conform to the requirements of the AFSC Design Handbook DH1-11.
(b) Drop test the machine in accordance with MIL-STD-669.
(c) After the first drop, the machine shall be de-rigged, examined, started, and driven forward and backward a few feet, and all controls shall be actuated.
(d) The machine shall then be sectionalized and reassembled in accordance with the contractor's instructions to ascertain that no damage was done to the sectionalization features by the test drop. (This step is omitted for the type I machine).
(e) Re-rig and drop test the machine a second time in accordance with MIL-STD-669.
(f) After de-rigging, the distributor shall be demonstrated for 8 hours performing tasks in 4.5.2.10.

Failure to meet the weight and dimensional requirements of Design Handbook DH1-11, weld failure, leakage, permanent deformation of any structural member or components, inability to reassemble the components removed for airdrop, inability to disassemble and reassemble the type II distributor, or inability of the distributor to perform its intended functions shall constitute failure of this demonstration.

4.5.2.13 Certification. The contractor shall certify in writing to the contracting officer that the distributor complies with the requirements of speed in 3.9.1, braking in 3.9.2, stability in 3.9.3, fording in 3.9.4, tractor in 3.10, running gear in 3.11.5, and rail shipment in 3.19. If certification is not supplied, these requirements shall be demonstated. Nonconformance shall constitute failure of these demonstrations.

4.5.2.14 Certified test reports. The contractor shall furnish certified test reports to prove compliance with the ROPS/FOPS requirements of 3.10, travel speed requirements of 3.9.1, and electromagnetic radiation requirements of 3.16.2 including MIL-S-52986 for the tractor. If certified test reports are not available, these requirements shall be demonstrated. Nonconformance shall constitute failure of these demonstrations.

4.6 Inspection of packaging. The preservation, packing, and marking shall be examined to determine compliance with MIL-T-3351 (for level A or B) and MIL-STD-1188 (for commercial).

5. PACKAGING

5.1 Preservation. Preservation shall be level A, B, or commercial as specified (see 6.2).

5.1.1 Level A. Each complete distributor, components, and attachments shall be preserved in accordance with the level A preservation and packaging requirements of MIL-T-3351.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Each complete distributor, components, and attachments shall be preserved in accordance with the level B preservation and packaging requirements of MIL-T-3351.

5.1.3 Commercial. Each complete distributor and all items issued with the distributor shall be suitably preserved packed in accordance with MIL-STD-1188 for retail distribution directly to a using customer and in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with carrier rules and regulations applicable to the mode of transportation. In addition, the following specific requirements shall be accomplished. Items with critical surfaces required for fit or function shall be provided protection by the use of preservative coating, volatile corrosion inhibitors, or desiccated packs. Items requiring protection from physical damage to surfaces, or which are fragile by nature shall be protected by wrapping, pack compartmentization, or cartonizing of the individual item. The cooling system shall be filled with a fresh solution of 50 percent water and 50 percent antifreeze, conforming to MIL-A-46153, and a tag attached indicating the temperature to which the cooling system can be subjected to before freezing. The crankcase shall contain the required amount of lubricating oil. A guide shall be furnished indicating the preservation and packing materials to be removed, in detail, and any other servicing required prior to placing the distributor in operation.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Level A. Each complete distributor, preserved as specified in 5.1, shall be packed in accordance with the level A packing requirements of MIL-T-3351, as specified for type II unboxed (mobile) vehicle.

5.2.2 Level B. Each complete distributor, preserved as specified in 5.1, shall be packed in accordance with level B packing requirements of MIL-T-3351, as specified for type II unboxed (mobile) vehicle.

5.2.3 Commercial. Each complete distributor, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188. Commercial packing must protect items against physical and enviromental damage during shipment, handling and storage.

5.3 Marking.

5.3.1 Military. Marking for level A or B protection shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The water distributor covered by this specification is intended for world-wide, earthmoving and construction projects by the Armed forces in engineer troop support use in soil stabilization, soil compacting,

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

dust alleviaton, and limited fire fighting. The tractor section for the distributor is identical to and interchangeable with the scraper covered by MIL-S-52986(ME).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type of water distributor required (see 1.2)
(c) Time frame required for submission of the preproduction models (see 3.3).
(d) Technical publications required (see 3.26).
(e) Time frame for completing and submitting a technical information package (see 3.29).
(f) When basic issue items are to be furnished (see 3.31).
(g) Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Government-furnished equipment. The contracting officer should arrange to furnish the equipment specified in 3.30.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.5).

☆U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/530

Custodian:
Army - ME

Review activity:
Army - AT

User activity:
Army - CE

Preparing activity:
Army - ME

Project 3825-A153

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-D-52987(ME) Distributor, Water, Self-Propelled; Minimum 2500 Gallon, Sectionalized and Non-sectionalized

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.