MIL-T-52944A
22 February 1982
SUPERSEDING
MIL-T-52944
6 December 1977

MILITARY SPECIFICATION

TRUCK, FIREFIGHTING; DRY CHEMICAL AND AFFF,

4 BY 4, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial, diesel-engine-driven, four-wheel, four-wheel-drive truck equipped with a dual agent fire extinguisher system, a remote controlled roof mounted twinned turret for dispensing aqueous film forming foam (AFFF) and dry chemical and equipment cabinets for storage.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

O-D-1407	- Dry Chemical, Fire Extinguishing, Potassium Bicarbonate.
BB-N-411	- Nitrogen, Technical.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Preservation, Packing, Method of
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Mat riel
MIL-E-10062	- Engines: Preparation for Shipment and Storage of.
MIL-F-24385	- Fire Extinguishing Agent, Aqueous Film Forming Foam (AFFF) Liquid Concentrate, Six Percent, For Fresh and Sea Water.
MIL-A-46153	- Antifreeze, Ethylene Glycol, Inhibited, Heavy Duty, Single Package.

STANDARDS

FEDERAL

FED-STD-297	- Rustproofing of Automotive Vehicles.
FED-STD-595	- Colors.

MILITARY

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-281	- Automobiles/Truck, Truck-Tractor, Trailers and Trailer Dollies; Preservation and Packaging of.
MIL-STD-1474	- Noise Limits for Army Material.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION

Federal Motor Vehicles Safety Standards and Regulations.
Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Code of Federal Regulations, Title 45, Subtitle A, Part 1201 - Motor Vehicle Air Pollution Standards.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 412 - Evaluating Foam Fire Equipment Aircraft Rescue and Fire Fighting Vehicles.
No. 414 - Aircraft Rescue and Fire Fighting Vehicles.
No. 1901 - Standard for Automotive Fire Apparatus.

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02110.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The truck shall be a 4 X 4 diesel-engine-driven truck cab-and-chassis. The truck shall be equipped with an equipment storage body. A twin agent, fire extinguisher system shall be installed on the truck, with a roof mounted remote controlled twinned agent turret.

3.2 First article. When specified (see 6.2), the contractor shall furnish a truck for first article inspection and approval (see 4.2). Examination and tests shall be subject to surveillance of the Government inspector.

3.3 Standard truck, components, and accessories. Except as specified, the truck, components, and accessories shall be standard cab ahead of engine or optional items which meet or exceed the requirements of this specification. Such items shall be construed as commercial motor vehicle products, complying with all DOT Federal Motor Vehicle Safety Standards and Regulations applicable, on the date of manufacture.

3.3.1 Treatment and painting. The truck cab, chassis, body, and other equipment, as applicable, shall be cleaned, treated, primed and painted two coats gloss lime yellow, Color No. 13670 of FED-STD-595, in accordance with the fire truck manufacturers standard painting procedures, provided it is equal to MIL-T-704, Type I. The vehicle shall be rust proofed in accordance with FED-STD-297.

3.3.2 Identification marking. The truck shall be identified in accordance with MIL-STD-130. The marking shall be applied to the truck on plates conforming to MIL-P-514, Type I, Style 1, Composition C, of Type I, Grade A, Class 1 material. Each plate shall be attached by screws, bolts, or rivets to the inside of the door on the driver's side of the cab. The following data shall appear in the ownership and nomenclature spaces provided on the identification plate in their respective order and the vehicle registration number provided by the contracting officer.

OWNERSHIP - U.S. ARMY
NOMENCLATURE - TRUCK, FIREFIGHTING, COMBINED AGENT,
DRY CHEMICAL AND AFFF 4 X 4.

3.3.3 Instruction plates. All pumping controls, valves, instruments, and truck operating controls shall be provided with instruction plates designating function and operation. Instruction plates shall conform to MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 material, size as applicable. Each plate shall be attached by screws, bolts, or rivets in a location where the plate shall be both visible and legible.

3.3.4 Drain plugs. All drain plugs installed throughout the truck for the purpose of draining lubricants shall be of the permanent magnet type.

3.3.5 Heavy-duty cooling system. A heavy-duty cooling system shall be furnished that shall maintain engine coolant at a temperature below the boiling point with truck loaded and operated as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.3.6 Towing devices. Towing devices, front and rear, shall conform to commercial standards for the size vehicle used.

3.3.7 Radio noise suppressors. The truck chassis shall be equipped with radio noise suppressors conforming to SAE J552. Electromagnetic radiation from the truck chassis shall be certified within the limits of SAE J551.

3.4 Material. All material shall be as specified herein (see 6.3). Material not specified shall be of the same quality used for the intended purpose in commercial practice. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual component or the overall assembly.

3.5 Performance. The fully equipped truck, shall be capable of performing the following:

(a) Parking brake holding the truck on a 30 percent grade in both ascending and descending positions.
(b) Service brakes holding the truck on a 30 percent grade in both ascending and descending positions.
(c) Service brakes bringing the truck to a stop within a braking distance of 30 feet from a speed of 20 miles per hour (mph) on a dry, smooth level surface free from loose material.
(d) Attaining a maximum speed of not less than 65 mph on dry, level, paved roadway.
(e) Accelerating on a level road from a standing start to a speed of 50 mph in 30 seconds.
(f) Negotiate a 50 percent grade in low speed range traveling both up and down hill.
(g) Operation under all conditions of test without component over-heating in any ambient temperature between 32° F and +125° F.
(h) There shall be no evidence of body distortion, leakage, tire and body contact, malfunction of components, irregular chassis noise, vibration, or sway when subjected to a road test of 100 miles over paved roadway at speeds up to 55 mph; 25 miles over graded unpaved roadway at speeds up to 25 mph; and 25 miles off highway over cross-country terrain at speeds up to 15 mph with ground and grade conditions requiring four-wheel drive.
(i) Operate on a 20 percent side slope in both directions.

3.6 Weights and dimensions. The total gross weight of the truck when fully loaded shall not exceed the published rating of the axle manufacturer and the tire manufacturer. Weight distributions and center of gravity shall conform to the best commercial practices. Overall height of the vehicle shall not exceed 135 inches. Overall length shall not exceed 312 inches. Ground clearance shall be as specified by NFPA 414, part D.

3.6.1 Turning circle. The turning circle shall not be more than 50 feet.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

3.7 Engine. The truck engine shall be a diesel engine, having horsepower, torque, and speed characteristics to satisfactorily meet all vehicle performance requirements specified herein. The engine shall be the manufacturer's current standard type. Engine shall be equipped with a full flow type oil filter.

3.7.1 Governor. Manufacturer's current standard type engine governor shall be furnished, set, and sealed to limit engine to maximum recommended operating speed.

3.7.2 Air pollution control. The truck shall comply with the EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture.

3.7.3 Noise level. The noise level in the area occupied by the operatior within the truck cab shall not exceed 85 dB(A) as specified by Category D of MIL-STD-1474. The exterior noise level shall not exceed 83 dB(A) when measured in accordance with SAE J366.

3.7.4 Electrical system.

3.7.4.1 Electrical equipment. The truck shall be equipped with a 12-volt electrical system. Components shall be located so as not to be adversely affected by engine heat. All electrical components shall be water resistant and designed so that their normal functioning will not be impaired by entrance of water during heavy rains, from road splash, from condensation, or from water spray resulting from other causes. Wiring shall be color coded or numbered for easy identification and secured (except for ignition harness) to the frame and body throughout the truck with fasteners. Means of wiring identification shall be consistent throughout the truck. Wire shall be protected by means of looms or grommets at points of potential abrasion. Wiring shall be neatly run with all excess wire removed. All components shall be designed for operation at 12 volts. The use of 6-volt equipment paired in series with resistors or tapped to the midpoint of the battery is not acceptable. The truck body electical circuits, excluding truck chassis electrical circuits, shall be provided with overload protective devices of the manual or automatic reset, over-load-circuit-breaker type.

3.7.4.2 Starting system. The starting system shall be standard for the type truck furnished. Trucks shall be provided with a safety device to prevent engine starting unless the transmission is in a neutral position.

3.7.4.3 Battery units and electrical circuits. Two 12-volt battery units shall be provided. Both battery units shall be housed and shall be mounted on either a draw-out-type or permanent-type tray to permit accessibility for testing and servicing. The permanent-type tray may be mounted on the running board of the truck, provided it does not protrude beyond the sides of the truck. Provisions shall be made for locking the draw-out-type tray in a retracted position, and battery cables shall be arranged to prevent chafing. Batteries shall be securely held in place by means of removable locking devices

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

and shall be protected against engine and exhaust heat. Battery compartments shall be ventilated to the truck exterior and treated against acid fumes and spillage. The batteries shall be shipped charged and dry. Each battery shall be provided with a polarized receptacle for station charging and shall be located so as to automatically be disconnected when the truck moves forward. The battery circuit shall be provided with a reverse current device to protect the voltage regulator from damage when the batteries are connected in reverse polarity. The receptable shall be of the recessed male type with a spring-loaded cover, and shall be provided with a matching female plug. The batteries shall conform to SAE Number 20T6A or 20T8A. Battery circuits and switching systems shall be provided whereby:

(a) Either battery may be used:

(1) For ignition and lights alone.
(2) For starting, alone.
(3) For starting, ignition and lighting.

(b) Both batteries may be used simultaneously in starting.
(c) Neither the lighting wiring nor the ignition wiring will be connected to both batteries except when both starter switches are operated.
(d) The alternator shall be connected to supply the battery which is being used for ignition and lights.
(e) Wiring shall conform to wiring diagram entitled "Suggested Application of Dual Batteries to Single Ignition Engine" in the appendix of NFPA No. 1901.
(f) Batteries shall be sufficient to start engine after truck has been cold soaked at minus 25° F.
(g) Commercial standard slave receptacle shall be provided at the rear of the truck for emergency power for starting.

3.7.4.4 Electric generating system. The engine shall be equipped with a 12 volt alternator and regulator capable of supplying the built-in DC current requirements of the truck with a minimum rating of 125 amps. Charging rate at 1000 engine rpm shall be minimum of 70 amps. A 3000 watt AC power inverter capable of continuous operation at rated output shall be provided. The inverter shall electrically attach to the vehicle alternator and shall produce constant 60 Hz ±1 Hz power at all engine speeds. The inverter shall have voltage control of ±5 percent no-load to full load. Pulley ratio driving the alternator shall be sized to provide a minimum of 2000 watts of AC power at 1000 engine rpm. A remote control shall be installed to allow starting and stopping of the inverter from the driver's cab position. A voltmeter shall be provided with all control positions to indicate inverter operation. All wires shall be of sufficient gage and shall be properly supported and protected from injury. Two fused, grounded, weatherproof, duel receptacles with spring-loaded covers, shall be electrically wired into the 120 volt AC high output of the inverter. One outlet shall be mounted on each side of the truck. Three Quartz 500 watt minimum lights shall be mounted on the truck. The lights shall be wired into the inverter with individual control switches mounted in the truck cab. One light shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

mounted on the front of the vehicle below the windshield in the center of the cab and one on each top corner of the front side compartments. The side lights shall be mounted on 6 foot manual telescoping type poles. The poles shall retract down into the compartment to the lowest possible height. The lights shall be adjustable for luminescence front to rear but shall not turn in continuous 360° circles.

3.7.4.5 Lighting. All truck lights, reflectors, and wiring shall be standard for the vehicle furnished. Lights and reflectors shall not be mounted on vertical surfaces of rub rails or bumpers. Two automatic backup lights, not less than 4-inch in diameter, shall be installed at rear of the truck.

3.7.4.6 Lights. Lighting equipment shall conform to part D of NFPA 414.

3.7.5 Fuel system. Fuel system shall be standard for the vehicle furnished.

3.7.5.1 Air cleaner. An air cleaner shall be furnished.

3.7.5.2 Fuel tank. The fuel tank shall be the manufacturer's standard. Tank and fill piping shall be so placed as to be protected from mechanical injury.

3.7.6 Exhaust system. Muffler and other portions of exhaust system shall be manufacturer's standard for the chassis. A shield plate shall be installed where necessary to prevent spilled fuel from coming in contact with the exhaust system.

3.7.7 Transmission system. A fully automatic or semiautomatic transmission shall be provided. Input torque capacity of transmission shall be at least equal to the maximum torque delivered by the engine. Transmission shall have not less than four forward speeds and one reverse speed. An electrically operated back-up warning system conforming to SAE J944 shall be installed to operate when transmission is in the reverse mode.

3.7.8 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.7.9 Frame. Chassis frame shall be manufacturer's standard for the truck furnished.

3.7.10 Suspension. Truck shall be equipped with suspension system, with components having a rated capacity at least equal to the load imposed on each member, plus at least 10 percent, measured at the ground, with truck loaded as specified. When suspension is rated at the spring pads, unsprung weight shall be deducted. Truck shall be equipped with hydraulic, double-acting, shock absorbers on the front wheels.

3.7.11 Axles. The axles rated capacity shall be not less than the load imposed, plus 10 percent. Rear axle shall be provided with positive-traction or limited-slip differential.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.7.12 Wheels, rims, tires, and tubes. Truck shall be equipped with single front and single rear wheels. Rim sizes shall be the same for all wheels on the truck. Tire size and ply rating (load range) shall be the same for all tires on the truck. Rim and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished.

3.7.12.1 Tires. Tires shall be tube- or tubeless-type with mud and snow tread. Tires shall be of not less than 100 level quality. Tires shall have a rated capacity at least equal to the load imposed on each tire measured at each wheel, at the ground, with truck loaded as specified. Tire shall be not less than 14 ply rated.

3.7.12.2 Inner tubes. When tube-type tires are furnished, inner tubes shall be of proper size for tires furnished. When mounted on other than drop center rims, tire flaps shall be installed.

3.7.13 Brakes. Brakes shall be standard for the vehicle furnished.

3.7.13.1 Service brakes. Truck shall be equipped with straight air, four-wheel, cam type, combination diaphragm brakes on rear. An air dryer shall be furnished to prevent system freezing.

3.7.13.2 Parking brake. Truck shall be equipped with parking brake, meeting requirements specified herein.

3.7.14 Steering. Truck shall be equipped with power assist steering. Mechanical type steering capability shall be available in event of loss of power assist steering.

3.7.15 Cab. Cab shall be 2 man capacity. Cab shall have upholstered, individual, adjustable, driver's seat and passenger seat designed for use with 30 minute air pack. Interior dome lighting shall be provided. Manufacturer's standard fastenings and seat belts shall be installed on the truck.

3.7.16 Windshield wipers and washers. Truck shall be equipped with windshield wipers and windshield washers. Windshield wipers shall be speed controlled type and shall return to the retracted position out of the line of vision when not in use.

3.7.17 Heater and defroster. Heater and defroster shall be standard for the chassis used.

3.7.18 Controls and operating mechanism. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing.

3.7.19 Front bumper. Manufacturer's standard front bumper shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

3.7.19.1 Brush Guard. A brush guard shall be provided. The brush guard shall be as wide as the widest part of the front fenders, and shall be as high as the hood in the center and not less than 4 inches above the top of the fenders. The guard shall be four-point suspension mounted.

3.7.20 Rear bumper and step. Rear bumper and step shall conform to NFPA 414 requirements. All platforms and steps shall have anti-skid surfaces.

3.7.21 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) An outside rearview mirror shall be mounted on each side of the cab. The mirrors shall be of the West Coast type. The upper mirror shall have a flat reflective area. The lower mirror shall have a convex reflective area. Stick on convey mirrors are not acceptable. The mirror assembly shall be individually adjustable and mounted to minimize obstruction of forward lines vision.

(b) Transmission temperature gage.
(c) Ammeter meter.
(d) Fuel gage.
(e) Oil pressure gage.
(f) Engine temperature gage.
(g) Speedometer with recording odometer.
(h) Dual sunvisors.
(i) Door mounted armrests.
(j) Manufacturer's standard air horns.

3.7.22 Access steps. When the height of the first step, from the ground to the truck is more than 28 inches, a step made of wire rope or other type devise shall be provided. The step when struck by a object shall move without major damage and shall return to a functional position.

3.8 Body. Body shall be either all steel or aluminum construction, with enclosed compartments at both sides. The body shall be free from rough and sharp edges.

3.8.1 Body characteristics. Body characteristics shall be as follows:

(a) All partitions, trays, and shelving shall be furnished with rolled edges.
(b) Each side of the body shall have four compartments sized to store the equipment specified herein.
(c) All doors shall be of box type, reinforced construction having continuous, heavy-duty corrosion-resistant hinges, with stainless steel hinge pins and stainless steel insert sockets. All doors shall be built to insure the carrying off of rain and wash water. Horizontal doors shall be equipped with support chains and the vertical doors shall be equipped with hold-open devices. All doors shall be equipped with recessed "D" ring type door handles, slam action catches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

(d) The curb side shall have not less than three compartments. One compartment shall be sized to store the complete rescue saw with storage chest specified in 3.9.13.
(e) The street side shall have not less than three compartments. Street side horizontal compartments shall be equipped with one shelf with 1-inch retainer. The shelf shall extend the full length of the compartment.
(f) Load compartment floor shall be constructed of safety tread plate. Front part of the floor shall be provided with two drain holes.

3.8.2 Deck lights. Two sealed beam deck lights (spotlights) with waterproof switch, shall be provided, one each mounted at the rear of the truck on top of each side body compartment section. The deck lights shall be adjustable and capable of rotation and vertical movement.

3.8.3 Handrails. A handrail shall be provided for use of personnel in mounting truck.

3.8.4 Warning Devices. Warning lights, siren, public address, and radio amplifier system shall be furnished in accordance with NFPA 414 part D.

3.9 Combined agent fire extinguisher system. A combined agent fire extinguisher system shall be provided and installed in the load space of the service maintenance body. An AFFF and dry chemical dispensing twinned agent turret shall be mounted on the cab roof, with power assist, remote control from within the cab. The twin agents shall be an AFFF firefighting agent and a dry chemical, Purple-K-Powder (P-K-P), firefighting agent. The AFFF agent shall conform to MIL-F-24385. The P-K-P agent shall conform to O-D-1407. The combined agent fire extinguisher system shall consist of an AFFF agent tank, P-K-P agent tank, nitrogen cylinder(s), piping, pressure regulators, controls, twin turret discharge hoses and nozzles, hose reel, and other requirements specified herein. The combined agent fire extinguisher system shall be capable of the following:

(a) Discharging the AFFF active solution, thru 100 feet of hose at normal ambient temperature, within a minimum-maximum range of 45 to 60 gallons per minute (gpm) at 100 pounds per square inch gage (psig) pressure, with a nozzle ground pattern reach of 50 feet and a minimum width of 14 feet.
(b) Discharging the dry chemical P-K-P, at normal ambient temperature within a minimum-maximum range of 5.0 to 8.0 pounds per second at 100 psig pressure, with a nozzle ground pattern minimum-maximum reach of 35 to 40 feet. The combined agent fire extinguisher system shall be capable of operating in any normal ambient temperature above 32° F. The system shall be capable of providing simultaneously, an average flow rate of 55 gpm of AFFF agent and 5.0 pounds per second of dry chemical at any hose length from 25 to 100 feet.
(c) Twinned agent turret shall conform to table in paragraph 7546 of NFPA 414.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:11Z
Check the source to verify that this is the currentversion before use.

3.9.1 Agent tank, AFFF. The AFFF agent tank shall have a capacity of not less than 250 gallons of 6 percent AFFF liquid solution. The tank shall be constructed in accordance with the ASME Boiler and Pressure Vessel Code, section VIII, for a design working pressure of 250 psig. The tank shall be fabricated from material resistant to corrosion by the AFFF agent, or a suitable lining material shall be provided. A fill opening at least 4 inches in diameter and a drain line shall be provided. The fill opening shall be provided with straight through unencumbered access to the tank, without dog-legs or offsets, to permit stirring and gaging of the contents and inspection of the interior. The fill pipe shall extend into the tank to sufficient depth to preclude foaming. A reseating type relief valve, capable of preventing pressures in excess of 110 percent of the design working pressure, shall be provided on the tank. A temperature relief valve set for 212° F ± 10° F shall be installed. A vent line with a valve shall be provided on the top of the tank for blowdown purpose to insure zero pressure before opening the fill cap.

3.9.1.1 Fill cap. The fill cap on the tank shall be provided with a safety vent hole so that cap is pressure venting while at least 3-1/2 threads are still engaged. The fill cap arrangement shall be such that the male threads are a part of the tank and the female threads are a part of the cap. When required, an extension spanner wrench for easy removal of the fill cap shall be supplied.

3.9.1.2 Tank funnel. A suitable funnel shall be provided for easy loading of liquid agent.

3.9.2 Dry chemical agent tank. The P-K-P agent tank shall have a capacity of not less than 1400 pounds of dry chemical. The tank shall be provided with a suitable method of fluidizing the contents to insure proper dispensing of P-K-P and prevent caking. The tank shall be constructed in accordance with the ASME Boiler and Pressure Vessel Code, section VIII, for a design working pressure of 250 psig. The tank shall be fabricated from material resistant to corrosion by the P-K-P agent. The temperature operational requirements shall be as specified in 3.9.1 for the AFFF agent tank. A fill opening, vent line, and relief valve as specified in 3.9.1 shall be furnished. A fill cap as specified in 3.9.1.1 shall be furnished. A suitable funnel shall be provided for easy loading of dry chemical tank.

3.9.3 Nitrogen propellant system. A nitrogen gas propellant system for firefighting agents shall be provided. Nitrogen gas cylinder(s) having adequate capacity and pressure to provide performance requirements specified in 3.9 shall be furnished. The propellant gas cylinder(s) shall be in accordance with DOT requirements and regulations. The fully charged gas cylinder(s) shall be provided with nitrogen conforming to BB-N-411, type I, class 1, grade B. The cylinder(s) shall be provided with a pressure gage indicating the cylinder gas pressure and shall be located within view of the operator for ease in checking. The pressure gage shall indicate at all times the pressure in the nitrogen gas cylinder(s) without opening any valves. A quick-opening valve to release the nitrogen gas and capable of being easily reset shall be provided, and shall be located at the control panel (see 3.9.6). Design and placement of the nitrogen gas cylinder(s) shall be such that provision shall be made for quick and easy

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

replacement after each use. Sufficient nitrogen propellant shall be provided to fully expell all agents and permit complete purging of all piping and hose lines after each use. Safety relief valve shall be provided on nitrogen gas cylinder(s).

3.9.4 Piping. A piping system, with an effective nitrogen gas pressurization to insure proper discharge of the AFFF agent and P-K-P agent, shall be provided. Piping system shall include any additional agent tank fittings and valves required for the pressurization discharge, venting, and flushing of the twin agent fire extinguisher unit. Piping shall be designed to minimize friction losses at the design flow rates. The piping system shall permit depressurization and purging of all lines and tanks without loss of remaining agent. Check valves shall be used to prevent backflow into the gas regulators from the agent tanks. A device shall be used to restrain the agents from entering the hose lines until pressurization takes place. All valves and piping shall be resistant to corrosion by the AFFF agent. No black or galvanized iron, if furnished, shall be in contact with the AFFF. Potential galvanic corrosion points shall be eliminated by proper choice of material. Care shall be taken to prevent loosening of joints or breaking of pipes or connection due to shock and vibration. Approved flex-type hose may be furnished.

3.9.5 Pressure regulator(s). The gas flow rate of the regulator(s) and gas piping system shall effect a pressure level of 80 percent of the working pressure within 10 seconds of cylinder valve operation on both of the agent tanks. Dead end setting of the regulator(s) shall be within 95 to 110 percent of the tank's design working pressure and be capable of handling the full regulator gas flow. The regulator pressure setting shall be adjusted by the manufacturer and sealed in a manner to discourage manipulation in the field.

3.9.6 Controls. Operating controls to pressurize the agent fire extinguisher system shall be located adjacent to the nozzle stowed position at the rear of the truck. A remote pneumatic system, preferably a push button type, shall be mounted on the dash of the vehicle cab for complete pressurization of the system to the nozzle valves from inside the vehicle. Not more than two manual control manipulations (exclusive of discharge nozzles) shall be allowed to pressurize agent units to the discharge nozzles. Operational instruction and product marking plates shall be mounted at the rear of the truck.

3.9.7 Discharge hoses. The discharge hoses shall be a noncollapsible twin hose and shall be 100 feet long. The hose shall be used for the AFFF agent and the P-K-P agent. The twin discharge hose shall be capable of withstanding the full tank pressure with a burst pressure of not less than 600 psig minimum. Discharge hoses shall be mounted on the hose reel (see 3.9.8).

3.9.8 Hose reel. An electric rewind hose reel shall be an integral part of the extinguisher unit. Access to the nozzles shall be within easy reach of a firefighter while standing on the ground. The design shall provide for ease of rapid removal and restowage of the 100 foot length twin agent hoses. A means of restraining the discharge nozzles in a readily accessible stowed position shall be incorporated. The reel shall be equipped with adequate vertical and

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the currentversion before use.

horizontal rollers and guides to reduce hose chafing and friction when on either side of the truck. The reel shall be equipped with friction brake(s) to prevent hose from unreeling when not desired. The discharge hoses shall be capable of being used in incremental payout lengths and shall not be required to pay out the full 100 feet for operational use. The hose reel shall incorporate a manual overide so as to allow a manual rewind of the hose in case of electrical power failure to the electric rewind motor.

3.9.9 Handline nozzles. The handline nozzles shall be twined together for one man operation. The shutoff for each agent shall be either a ball type with hose, shoe handle, or pistol grip and trigger types. Both must be designed for ease of operation. The dry chemical nozzle shall provide a semidiffused pattern with a low discharge recoil characteristic. The dry chemical nozzle shall have a nominal flow rate of not less than 8 lbs/per second and an effective range of not less than 40 feet. The AFFF nozzle shall discharge solution at a nominal rate of at least 60 gpm, with an effective range of not less than 50 feet when in a straight stream position.

3.9.10 Nozzle mounting. The two discharge nozzles shall be mounted side-by-side separated approximately 6 inches, with suitable brackets.

3.9.11 Operation and product markings. Destruction resistant, embossed, plates shall be permanently and legibly marked for identification and use of the extinguisher unit in accordance with MIL-STD-130. The plate shall be permanently mounted at the rear of the truck so that they may be easily read by personnel standing on the ground.

3.9.11.1 Operation markings. A plate or plates shall be marked with the following:

(a) Complete and detailed activating instructions for placing the equipment in operation shall be printed on a contrasting background.
(b) After use instructions and maintenance instructions shall be provided.
(c) A statement shall be shown that the gas cylinder(s) "shall be replaced if the pressure during storage drops below a specified level". (Contractor to insert proper level.)
(d) Storage and maintenance instructions shall include precautions against subfreezing temperature exposure of the equipment.

3.9.11.2 Product markings. The plate shall be marked with the following:

(a) Name and model number of unit.
(b) Name and address of manufacturer.
(c) Serial number of unit.
(d) Contract number and date.

3.9.11.3 Agent refilling table. A table for the AFFF agent shall be provided, indicating the amount of agent necessary to either completely or partially refill the agent tank after use, by measuring the distance in inches from the top of the tank to the remaining level of agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.9.12 Agent identification. Each agent tank or its respective fill cap shall be identified as to its contents near the point of filling.

3.9.13 Fire rescue equipment. The following items of rescue equipment shall be furnished and stowed in the body compartments:

(a) Rescue saw, complete kit, similar or equal to Partner, Model K-1200 or equal.
(b) Aircraft crash rescue tool kit, canvas roll, similar or equal to STEBCO, No. CRK5 or equal.
(c) Hydraulic rescue kit, 10-Ton capacity.
(d) Gasoline-engine driven, hydraulic-powered rescue tool, Hurst Model 32 or equal.

Stowage of the equipment shall be in a manner to prevent damage to equipment and the truck under all conditions specified herein and shall allow for quick and easy remount by personnel dressed in full fire fighting protective clothing.

3.10 Lubrication. Lubrication shall be in accordance with the equipment manufacturer's recommendations. Pressure lubrication shall not damage seals or other parts. All parts requiring lubrication shall be lubricated prior to delivery. A tag to show the type and temperature rating of the lubricant used shall be displayed in the cab on the transmission control level.

3.11 Servicing and adjusting. Prior to acceptance of the truck by the Government inspector, contractor shall service and adjust each truck and its mounted equipment for operational use, including at least the following: Focusing of lights; adjustment of engine; adjustment of electrical and brake system, alignment of front wheels; inflation of all tires; complete lubrication of front wheels; inflation of all tires; complete lubrication of chassis, engine, running rear, and mounted equipment.

3.12 Workmanship.

3.12.1 Steel fabrication. Steel used in the fabrication of equipment shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal. Shearing and chipping shall be done neatly and accurately. All bends of a major character shall be made with controlled means in order to insure uniformity of size and shape.

3.12.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice and all bolts, nuts, and screws shall be tight.

3.12.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter or rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.12.4 Welding. Welding procedure shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.12.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.4 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Initial production inspection (see 4.4).
(c) Inspection of packaging (see 4.7).

4.3 Preproduction inspection.

4.3.1 Examination. The preproduction truck shall be examined as specified in 4.5.1 Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction truck shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.4 Initial production inspection. When specified (see 6.2), one or more trucks will be selected at random by the Government from trucks being produced by production tooling and will be examined as specified in 4.5.1 and tested as specified in 4.5.2 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site selected by the Government. Acceptance of an initial production truck shall not exclude the remaining trucks from the quality conformance inspection and acceptance provisions specified in Section 4. In addition to any test specified as part of the initial production test, the Government reserves the right to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

conduct any and all other tests contained in this specification as part of the initial production test and failure of such additional tests shall have the same effect as failure of those tests specified as initial production tests.

4.4.1 Inspection failure. Failure of an initial production truck to meet any requirement specified herein during and as a result of the examination and tests specified in 4.4 shall be cause for rejection of the initial production truck(s) and shall be cause for refusal by the Government to continue acceptance of production trucks until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on trucks previously accepted and produced under the contract. Any deficiencies found as a result of the initial production inspection will be considered prima facie evidence that all trucks accepted prior to the completion of initial production inspection are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.4.2 Tests. Each truck shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.5 Inspection procedure. Prior to examination or tests, the truck shall be lubricated with military oils and greases for use at the ambient temperature at the inspection site.

4.5.1 Examination. The truck shall be examined as specified herein for the following defects:

101. Material not as specified.
102. Conditions hazardous to the safety of operating or attending personnel.
103. Total gross weight of completed truck in excess of the truck manufacturer's gvw rating when fully loaded.
104. Evidence of alterations to chassis frame reducing designed strength.
105. Engine not as specified, presence of short bends or kinks in fuel lines, or fuel lines improperly located, supported, or shielded; or evidence of leaks in cooling, fuel, exhaust, or lubrication system.
106. Electrical system not as specified.
107. Bumper not directly attached to chassis frame.
108. Towing hooks and rings not provided.
109. Shock absorbers not as specified, or evidence of malfunction.
110. Individual wheel loadings greater than rated spring capacity.
111. Evidence of malfunction of truck drive assembly.
112. Excessive lost motion in steering.
113. Brakes not as specified.
114. Wheels, tires, and tubes not as specified.
115. Cab not as specified.
116. Equipment cabinets, running boards, and rear platform and handrail not as specified.
117. Tank not of specified capacity or construction, improperly located, or not mounted on truck frame, interior of tank not coated as specified, noncompliance with specified piping requirements, or evidence of leakage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

118. Hose reel not as specified.
119. Equipment mounting not as specified.
120. Tank not of specified capacity or construction or improperly located, controls not properly located on pump instrument panel, noncompliance with specified piping arrangements, or evidence of leakage.
121. Truck not lubricated with designated lubricants or tagged as specified.
122. Noncompliance with specified treatment and painting requirements.
123. Identification and instruction plates not provided as required or data incomplete, inaccurate, or not legible.
124. Nonconformance to specified workmanship requirements affecting performance, ease of maintenance, and general appearance.
125. Electromagnetic interference suppression components and network not identical to the approved model.

4.5.2 Tests.

4.5.2.1 Truck weight. The truck shall be weighed to determined curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axle will be computed using the curb weight, and the payload uniformly distributed over the vehicle load area to provide the specified gvw. Calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension, and tires furnished are of adequate capacity to meet specification requirements.

4.5.2.2 Operational tests. The truck shall be loaded with agent and equipment as specified and operated to verify performance requirements specified in 3.5(a) through (i). During these tests, the functioning of the engine, power train, steering, brakes, truck and body lighting systems, controls, and instruments shall be observed for effective operation.

4.5.2.3 Twin agent fire extinguisher unit tests.

4.5.2.4 Agent tanks pressure test. The AFFF agent tank and the P-K-P dry chemical agent tank shall be pressure tested. Each tank shall be pressurized to 150 percent of the design working pressure of 250 psig and the pressure held for 15 minutes. There shall be no evidence of leakage, permanent distortion, or other defects. Openings not subjected to this test shall be plugged. ASME certification may be used.

4.5.2.5 Agent tank relief valve test. Each agent pressure tank relief valve shall be tested to determine conformance to 3.9.1.

4.5.2.6 Discharge hoses pressure test. Discharge hoses with fittings shall be hydrostatically tested to 600 psig pressure for 5 minutes to determine conformance to 3.9.7.

4.5.2.7 Operating characteristics test. Each handline discharge nozzle shall be individually performance tested as specified herein at a hose length of 100 feet. The AFFF shall be discharged at an ambient temperature of 65° F to 85° F. The rate of discharge of active solution shall be within a minimum-maximum

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the currentversion before use.

range of 45 to 60 gpm. The AFFI product, as produced by the specified nozzle in 3.9.9, shall be sampled and tested in accordance with the procedures set forth in the current edition of NFPA Pamphlet No. 412. The resultant AFFF shall have a minimum expansion of 4 with a minimum 25 percent drain time of 2 minutes. The AFFF nozzle shall have performance patterns as specified in 3.9.9. The rate of discharge of the dry chemical powder shall be as specified in 3.9.9. A minimum of 95 percent of the powder contents must be discharged at an overall average rate not less than 4.5 pounds per second. The full contents of each agent tank shall be discharged during the above individual tests. Each agent container shall attain 80 percent of their working pressure within 10 seconds of system activation. The twinned agent turret shall be tested for conformance to requirements of NFPA 414 paragraph 7546.

4.5.2.8 Recharging test. After complete discharge of the agent tanks during tests in 4.5.2.7, the unit shall be fully recharged in order to observe any problems or inadequacies in filling.

4.5.2.9 Noise level. The first article truck shall be tested in accordance with SAE J366 for exterior noise level and paragraph 5 and MIL-STD-1474 for interior noise level. Nonconformance to 3.7.3 shall constitute failure of this test.

4.5.3 Measurement of electromagnetic radiation. To determine conformance to 3.3.7, electromagnetic radiation shall be measured in accordance with SAE J551. When suppressed to conform to 3.3.7, the manufacturer may furnish a certification in lieu of the test that the truck meets the requirements, together with a list of the suppression devices installed. The list shall be sufficiently detailed to allow visual determination that the devices are installed.

4.5.4 Production sample. Upon acceptance of the first article, it shall remain at the manufacturing facility as a production sample, and be the last truck shipped on the contract. The first article shall be reconditioned, including replacement of abnormally worn parts and paint touch-up or repainting prior to delivery to enable it to be accepted as a contract item. The contractor shall maintain the first article in a serviceable condition for the duration of the contract.

4.6 Production truck tests. Each production truck shall be operated and tested as specified in 4.6.1 and 4.6.2.

4.6.1 Operational tests. Each production truck shall be loaded to its rated gvw as specified in 3.6 and operated as follows:

(a) Five miles over paved roads at speeds up to 55 mph.
(b) Five miles over graded dirt roads at speeds up to 25 mph.
(c) Five miles off highway over cross country terrain at speeds up to 15 mph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

During these tests, the functioning of the engine, power train, steering, brakes, truck and body lighting systems, controls, and instruments shall be observed for effective operation.

4.6.2 Twin agent extinguisher test. The twin agent extinguisher unit on each production truck shall be tested in accordance with the requirements specified in 4.5.2.7 for flow rates.

4.7 Inspection of packaging. The preservation, packing and marking of the truck and equipment shall be examined to determine compliance with the Quality Assurance Provisions of MIL-STD-281 and MIL-E-10062 as applicable, for level A or for the specific requirements specified herein for level C.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each complete truck with accessory equipment shall be preserved in accordance with MIL-STD-281, level A (mobile), with the following additions and exceptions.

5.1.1.1 Engine. The engine and engine accessories shall be preserved in accordance with MIL-E-10062, type I, method I, level A. The cooling system shall be preserved by the water and antifreeze procedure except the antifreeze shall conform to MIL-A-46153.

5.1.1.2 Fire rescue equipment. The fire rescue equipment shall be preserved in accordance with the contractor's recommendations that are adequate to prevent deterioration and damage during shipment and indeterminate storage; utilizing the preservation-packaging criteria established in MIL-P-116. Specifically the gasoline engine shall be preserved in accordance with the level A requirements of MIL-E-10062, type I, method I.

5.1.1.3 Equipment. Equipment shall be placed and secured as provided for, except exposed equipment subject to pilferage, damage, or loss shall be prepared as "On vehicle equipment" in accordance with MIL-STD-281.

5.1.2 Level C. Each complete truck and all items issued with the truck shall be suitably preserved to afford protection against deterioration and damage from the contractor to the initial destination. In addition, the following specific requirements shall be accomplished. Items with critical surfaces required for fit or function shall be provided protection by the use of preservative coatings, volatile corrosion inhibitors, or desiccated packs. Items requiring protection from physical damage to surfaces or which are fragile by nature shall be protected by wrapping, pack compartmentization, or cartonizing of the individual item. Exposed equipment subject to easy pilferage or loss shall be placed in secured compartments, truck cab, or in wooden boxes. Wooden boxes when used shall be secured to the truck with metal strapping and in a manner to prevent damage to the painted surfaces of the truck. The cooling system shall be filled with a fresh clean solution of 50 percent water and 50 percent

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:11Z
Check the source to verify that this is the currentversion before use.

antifreeze conforming to MIL-A-46153 and a tag attached indicating the temperature to which the cooling system can be subjected before damage. The crankcase and all other lubrication reservoirs shall be filled to the operating level with the grade of military lubricant designated for use in the temperature range at the shipping destination. A tag shall be attached in a conspicuous location to indicate which military lubricant has been used and its grade and temperature range. A deprocessing guide shall be furnished indicating in detail the preservation material to be removed and other servicing required prior to placing the truck in operation.

5.2 Packing (see 6.4). Each complete truck, preserved as specified in 5.1 shall not require packing.

5.3 Marking (see 6.4). Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Truck covered by this specification is primarily intended for use in rapidly combating aircraft crash fires.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Date of issue of DoDISS applicable to this contract and exceptions thereto (see 2.1.1).
(c) When a first article is required for inspection and approval (see 3.2, 4.2).
(d) Level of preservation required (see 5.1).
(e) When initial production inspection is required (see 4.4).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.4).

6.4 Marking. Levels of packing have not been included as they are not appropriate for this item. For purposes of preservation/packing level marking, the marking shall be A/A or C/A, as applicable.

Custodians:
Army - ME
Air Force - 99

Preparing activity:
Army - ME

Project 4210-0342

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Comma. der
USA Mobility Equipment R&D Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-52944A Truck, Firefighting; Dry Chemical and AFF, 4 by 4, Commercial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.