MIL-T-52984A(ME)

30 August 1984

SUPERSEDING
MIL-T-52984(ME)
19 September 1980

MILITARY SPECIFICATION

TRUCK, FIRE FIGHTING: BRUSH, 1200 GALLON WATER TANK, 6 X 6, COMMERCIAL CHASSIS

This specification is approved for use by the Belvoir Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a diesel-engine-driven (DED), three axle, all wheel drive, fire fighting truck having pump and roll capability to fight brush/grass fires, and the ability to provide support operation on structural fires.

2. APPLICABLE DOCUMENTS

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-P-35	- Passivation Treatment for Corrosion Resisting Steel
VV-F-800	- Fuel Oil, Diesel.
GGG-S-62	- Saw, Chain, Portable, Power.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-L-2104	- Lubricating Oil, Internal Combustion Engines, Tactical Service.
MIL-L-2105	- Lubricating Oil, Gear, Multipurpose.
MIL-E-10062	- Engine, Preparation for Shipment and Storage of.
MIL-G-20241	- Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-A-46153	- Antifreeze, Ethylene Glycol, Inhibited, Heavy Duty, Single Package.
MIL-S-81733	- Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

FEDERAL

FED-STD-H28	- Screw Thread Standard for Federal Service.
FED-STD-297	- Rust proofing of Automotive Vehicles.
FED-STD-595	- Colors.

MILITARY

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-281	- Automobiles, Trucks, Truck-tractors, and Trailer Dollies, Preservation and Packaging of.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1474	- Noise Limits for Army Material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION

Federal Motor Vehicles Safety Standards and Regulations.
Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Code of Federal Regulations, Title 45, Subtitle A, part 1201 - Motor Vehicle Air Pollution Standards.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. The issues of the document which is indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/ASME - Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.
ANSI/AWS D1.1 - Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 414 - Aircraft Rescue and Fire Fighting Vehicles.
No. 1901 - Standard for Automotive Fire Apparatus.

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The truck shall be a three axle, all wheel drive, DED truck cab-and-chassis. The truck shall be fitted with a fire truck body, a 250 gallon per minute (gpm) minimum fire pump driven by an auxiliary diesel engine. A 1200 useable (minimum) gallon (gal) removable water tank, hose beds, booster hose reel; operator's instrument panel for fire pump; and such other equipment and accessories as are specified herein.

3.1.1 Standard truck, components, and accessories. Except as specified herein, the truck, components and accessories shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented and rated in the contractor's sales information, including special or mounted equipment. Sales information shall be limited to specifications and technical material, identical to that furnished to the authorized contractor representative for selection of truck models and components. Sales information and special drawings necessary to identify the required truck and components shall be on file in the engineering offices of the contracting activity prior to delivery of the items. Truck, components, assemblies, and accessories to be provided hereunder are standard or optional commercial products for the purpose of this specification. Such items shall be construed as commercial motor vehicle products, complying with all DOT Federal Motor Vehicle Safety Standards and Regulations applicable, on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified (see 6.2) a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Materials. Materials shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The truck shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the item may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as a corrosion inhibiting sealant conforming to MIL-S-81733 or chromate tape conforming to MIL-G-20241. Protection against any galvanic corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the truck may be newly fabricated from recovered materials to the maximum extent practicable, provided the truck produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the truck.

3.4 Design.

3.4.1 Truck chassis. The truck-chassis shall be a three axle, all wheel drive, front wheel steer, dual rear wheel, conventional type, with three man cab.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.4.2 Weight, ratings, and dimensions.

3.4.2.1 Weight rating. The total gross weight of the complete truck shall not exceed the manufacturer's gross vehicle weight (gvw) rating when fully equipped as specified herein, including all specified fire fighting equipment, serviced with fuel, water and lubricants; loaded with not less than 1200 gal of water in the water tank; not less than a 300 pound (lb) simulated load in each equipment cabinet; rate of hose installed and a crew of three man in the cab weighing not less than 175 lbs each or equivalent deadweight. Weight distribution ratio between the front and rear axle shall be such as to insure positive traction at all wheels and positive steering at the front wheels under all operating conditions specified herein. Weight distribution shall not exceed the manufacturer's rating of individual component.

3.4.2.2 Dimensions. The truck overall dimensions including mounted equipment shall be not more than the following:

a. Width - 8 feet (ft)

b. Length - 26 ft

c. Height - 9 ft

3.4.3 Frame. Chassis frame shall be the manufacturer's standard welded, riveted, or bolted construction, and shall be rated for operation at rated gvw. When operating the fully equipped and loaded truck under conditions specified herein, the frame shall show no evidence of permanent deformation or distortion. Prior to production of the first truck, the contractor shall obtain certification from the original truck chassis manufacturer that:

a. The chassis frame is suitable for the intended operational use and for the mounting of all required firefighting components, specified herein.

b. Any frame modification, including machining, shall be approved and certified by the truck chassis manufacturer.

c. Flame cutting of the frame for modification shall not be allowed.

Certification shall be made available for review by the contracting officer or designated representitive.

3.4.3.1 Angles of approach and departure. The angles of approach and departure shall conform to the angle of departure requirements of NFPA No. 414.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.4.4 Engine. The truck shall be equipped with the manufacturer's current standard liquid cooled, diesel engine rated for fire service use. The engine furnished shall produce the required vehicle performance when operated on fuel conforming to VV-F-800 at an engine speed not more than the manufacturer's recommended operating speed. The engine shall be capable of continuous, warranted operation. At the engine manufacturer's rated governed speed the engine shall develop not less than 200 gross horsepower but not more than 120 percent required to meet the requirements specified herein. Engine net torque ratings and new horsepower rating used in performance prediction shall be determined in accordance with SAE J245 or SAE J270, as applicable.

3.4.4.1 Fuel system. Fuel system shall conform to DOT Motor Carrier Safety Regulations, Section 393.65.

3.4.4.1.1 Fuel tank. The fuel tank shall be sized in accordance with NFPA but shall be not less than 50 gal. Tank and fill piping shall be so placed as to be protected from mechanical injury. Step tanks may be furnished, but side running boards are required as specified.

3.4.4.1.2 Fuel filter. The fuel system shall be provided with a fuel filter either installed at the tank or in the fuel line.

3.4.4.2 Engine cooling system. Unless otherwise specified (see 6.2), the cooling system shall be standard for the truck furnished. Draincocks shall be installed at the low points of the cooling system and at such points as may be necessary to drain the system to prevent freezing. The cocks shall be of a hand-operated type that will remain closed under the most severe operating conditions to be encountered by the truck. A coolant temperature indicator shall be provided on the cab dash panel.

3.4.4.3 Lubrication system. The engine lubrication system shall be the full forced feed type. A low oil pressure warning device shall be provided and located on the cab dash panel. A full flow type oil filter shall be furnished. An oil sampling valve conforming to circle seals controls part number 59-500 or equal shall be installed in the lubrication lines. The valve shall be located to insure that personnel will not be exposed to danger when taking oil samples with the engine running. The location of the valve shall be such that samples taken will be a true representation of oil that is flowing while the engine is running.

3.4.4.4 Governor. Manufacturer's current standard type engine governor shall be furnished and set and sealed to limit engine to maximum recommended operating speed.

3.4.4.5 Exhaust system. The exhaust system shall conform to DOT Motor Carrier Safety Regulations, Section 393.83. A spark arresting muffler or a spark arrester shall be provided. Muffler and tail pipe shall be aluminized steel. The exhaust system discharge shall be directed away from the pump operator's control panel area and tires. The muffler shall be located not closer than 2 ft from the fuel tank, with full shielding for the tank from any part of the exhaust system within 1 ft of the tank and insulation and shielding elsewhere, where needed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.4.4.6 Air pollution control. The truck shall comply with the Federal EPA regulations governing control of air pollution from new motor vehicles and new motor vehicle engines in effect on the date of manufacture.

3.4.4.7 Air cleaner. An air cleaner shall be furnished.

3.4.4.8 Engine hour meter. An engine hour meter of the oil pressure type, having a totalizing mechanism of not less than 9,999 hours, shall be furnished for the truck chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. Engine hour meter shall be mounted on the truck instrument panel.

3.4.4.9 Brake horsepower certification. The contractor shall obtain a certified net brake horsepower curve for the engine being furnished and shall make the certification available for review by the contracting officer or designated representitive.

3.4.5 Electrical equipment. The truck shall be provided with a complete 12-volt negative ground starting and lighting system. Electrical equipment, including all truck lights and wiring shall conform to DOT Motor Carrier Safety Regulations, Sections 393.12, 393.19, 393.20, 393.33, 393.24, 393.25, 393.27 through 393.31, and 393.33, except as specified herein. Reflectors shall conform to DOT Motor Carrier Safety Regulations, Section 393.26. Wiring shall be weatherproof, resistant to moisture and fungus, and color-coded or numbered for ready identification. Wiring identification shall be consistent throughout the truck. Two spare, single pole, 15 ampere (A) breakers shall be furnished for future radio use. The truck chassis electrical circuits and the truck body electrical circuits shall be separate circuits. The truck body electrical circuits, excluding truck chassis electrical circuits, shall be provided with overload protective devices of the manual or automatic reset, overload-circuit-breaker type. All electrical equipment shall conform to MIL-STD-454, requirement 1.

3.4.5.1 Starting system. The starting system shall be standard for the type truck furnished. The ignition system shall be furnished with a keyless switch and a pilot light. Trucks shall be provided with a safety device to prevent engine starting unless the transmission is in a neutral position.

3.4.5.2 Battery system. A dual 12 volt (V) battery system shall be provided. Each battery shall be 12 V and of the sealed cell (maintenance free) type. Each battery shall have a cold crank rating of at least 450 A and a reserve capacity rating of at least 125 minimum as set forth in SAE J537. The battery units may be mounted on a sliding tray in an enclosed compartment and shall be accessible for testing and servicing. The batteries shall be securely held in place on the trays with removable locking devices and shall be protected against engine and exhaust heat and road splash. Provisions shall be made for securely locking the sliding trays in the retracted position. The battery compartments shall be ventilated and treated against acid fumes and spillage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

The battery compartments shall not be mounted on or project onto the side running boards when in the retracted (operating) position. Batteries shall be provided with polarized receptacles for station charging. The receptacles shall be located at the rear of the truck in a manner to disconnect without damage when the truck moves forward. Each receptacle shall be the recessed female type with a spring loaded cover and provided with a matching male plug protected prongs. A carrying handle for the batteries shall be provided. Removable battery compartment covers shall be fitted with lifting handles; finger lift openings are not acceptable. The battery terminals shall be provided with guards to prevent accidental shorting. Battery circuits and switching system shall be provided whereby:

a. Each battery may be used:

   1. For starting alone.
   2. For starting and lighting.
   3. For operation of priming pump.
   4. For operation of electric booster hose reel.

b. Both batteries may be used simultaneously in starting.

3.4.5.2.1 Electric generating system. The engine shall be equipped with 12 V alternator and regulator capable of supplying the built-in direct current (dc) requirements of the truck with a minimum rating of 145 A. Charging rate at 1000 engine revolutions per minute (rpm) shall be minimum of 70 A.

3.4.5.3 Lighting system. All truck lights, reflectors, and wiring shall conform to DOT Motor Carrier Safety Regulations, except as specified herein:

a. DOT identification lamps are required.

b. Clearance and side marker lamps shall be combined and mounted to indicate width of trucks.

c. Overload protective devices shall be of the automatic-reset, overload-circuit-breaker type. The lighting system shall be arranged so that the headlamp circuit or circuits shall not be affected by a short circuit in any of the other circuits.

d. Rear-mounted lights shall be located so that they shall not be obscured by equipment or personnel normally carried on the rear step.

e. Front-turn-signal units shall be single-faced flush mounted. The self-canceling-type controller shall be mounted on the steering column, shall operate a visual indicator, and shall be wired through the ignition system.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the currentversion before use.

3.4.5.3.1 Additional lighting. The following additional lighting shall be provided:

a. Two automotive-type sealed-beam spotlights located on each side of the windshield, with controls extended inside the cab for "on-off" control and movement of the lamp housing through horizontal and vertical angles. Spotlight control handle shall not obscure the driver's vision.

b. Two sealed-beam hose pickup lights. Lights shall be mounted to the outside of the hose bed.

c. Shielded engine-compartment lights arranged to illuminate both sides of the engine. Lights shall be controlled by a switch installed in the cab.

d. Pump control panel lights enclosed within hoods or covers designed to completely illuminate the panel controls, pump, motor and hose reel.

e. Two backup lights, with not less than 5 inch diameter, located at rear of the body. The backup light switch shall be automatically controlled when the transmission is placed in the reverse mode.

f. Stoplights, taillights, rear-turn signal lights, and backup lights shall be flush mounted at the rear of the body.

g. A complete wiring diagram shall be provided with each truck, except when provided in a manual furnished with the truck.

3.4.5.3.2 Warning lights. Warning lights shall conform to NFPA No. 1901. Warning lights shall be as follows:

a. One rotating, 3 unit, sealed beam lamp, mounted centric on top of the truck cab.

b. Two strobe type warning lights mounted on either side of the rear of the truck outside of the hose pickup lights.

c. Two low mounted, 6 inch diameter, flashing lights on the front of the truck, installed on a horizontal plane through the centerline of the headlights.

All warning lights shall have red lenses. The controls for the warning lights shall be independent of other electrical equipment controls and shall be broken down into three groups labelled front, top and rear. Warning lights shall be 12 Volt direct current (Vdc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.4.5.3.3 Light switches. The headlight switch shall be the standard push-pull type. The warning light shall be the single-pole-single-throw, rocker, circuit-breaker type with indicating light for the "on" position. There shall be one switch for each of the groups specified in 3.4.5.3.2. All switches shall be clearly and permanently marked. Indicating lights shall be shielded to prevent glare on the windshield during night driving.

3.4.5.4 Siren and horn. The truck shall be equipped with a Federal Sign and Signal Corporation electronic siren and PA combination Model BA20A, or equal. The electronic siren shall be furnished with a microphone and all wiring applicable to two-way radio. A single 6 inch diameter (dia) speaker shall be mounted behind the truck grill. Controls for the siren shall be mounted for easy access for the driver and passenger.

3.4.6 Front bumper and towing devices. A heavy-duty, full width, front bumper and two tow hooks shall be provided at the front of the truck. The two front tow hooks shall be mounted to the frame or rigid members which are attached to the frame. Two recessed, 3 inch inside dia, towing rings, or comparable U-bolts, shall be provided at the rear of the truck, and mounted directly to the chassis side rails.

3.4.7 Brush guard. A brush guard shall be provided. The brush guard shall be as wide as the widest part of the front fenders, and shall be as high as the hood in the center and not less than 4 inches above the top of the front fenders. The brush guard shall be four-point suspension mounted.

3.4.8 Suspension. Truck shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, plus at least 10 percent, measured at the ground, with truck loaded to specified gvw. When suspension is rated at the spring pads, unsprung weight shall be deducted. Truck shall be equipped with hydraulic, heavy duty, double-acting, shock absorbers on the front. The chassis manufacturer's standard auxiliary rear springs shall be furnished.

3.4.9 Truck drive assembly. The entire propulsion train between the engine and the drive wheels shall have a torque capacity at least equal to the maximum torque developed by the engine through the intervening speed and torque ratios.

3.4.9.1 Transmission. The vehicle shall be provided with a standard heavy duty, manual, five (5) speed transmission. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.9.2 Transfer case. A two-speed type transfer case shall be provided. Unless the transfer case is equipped with devices which compensate for differential torque and speeds between front and rear axles, the transfer case shall provide for driver selection of rear axle or all wheel drive. When furnished, interaxle compensating devices shall provide for positive transfer of power to all driving axles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.4.9.3 Axles. The front and rear axles shall have a rated capacity of not less than 110 percent of the load imposed. Rear axle shall be provided with positive traction or limited slip differential.

3.4.9.3.1 Drive hubs. Drive hubs for disengaging front wheels from power train shall be provided for cab operation except for trucks equipped with inter-axle compensating devices between front and rear axles.

3.4.10 Steering mechanism. Provisions shall be made for rapid adjustment of lost motion in the steering mechanism. The steering wheel shall be of ample size, shall not interfere with any other projecting equipment or operation of the vehicle, and shall be mounted on a rigid and sturdy column. Front wheels shall have a cramping angle of not less than 28 degrees right and left at the wheel on the inside of the turning circle. The truck shall be equipped with a power-assisted steering mechanism of the hydraulic type. The mechanism shall preserve, to the maximum practicable extent, the features of directional stability inherent in the manually operated steering mechanism, shall permit manual steering in the event that failure of the hydraulic system occurs, and shall be effective at all vehicle speeds.

3.4.11 Brakes. Certification shall be obtained from the brake manufacturer that the brakes are properly sized for the gvw of the truck. The certification shall be made available to the contracting officer or designated representitive.

3.4.11.1 Service brakes. The truck shall be equipped with straight-air, all-wheel, self-energizing-type service brakes. Service brakes shall control and hold the truck, loaded as specified in 3.8, on a 30 percent grade. Under all conditions of loading, service brakes shall stop the truck within 30 ft from a speed of 20 miles per hour (mph) on dry hard level surfaces free from loose material. The brake mechansim shall be accessible for exterior adjustment. Brake lines shall be anchored to the chassis and protected from damage. Two methods shall be provided to prevent system freezing. All brakes shall conform to the latest DOT requirements.

3.4.11.2 Parking brake. The truck shall be provided with a parking brake. The parking brake shall be the self-energizing air-release type. The parking brake shall be controlled by a push-pull-type control on the cab dashboard. The air system when charged to not less than 100 psi shall not leak more than 25 percent in 24 hours.

3.4.12 Wheels, rims, tires and tubes. Truck shall have single front and dual rear wheels. Rim and tire ratings shall conform to Tire and Rim Association Recommendations. Tires shall be tube type of not less than 100 level quality with standard commercial mud and snow tread. Steel belted radial tires shall be furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association Recommendations. All tires furnished on the truck shall be of the same size. The rated individual tire capacity at 60 mph highway conditions shall be not less than the maximum wheel loading imposed with truck

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

loaded to rated gvw. Wheel and tire assemblies shall be dynamically balanced at simulated speeds up to 60 mph. A spare wheel or rim, with spare tire, shall be furnished and stowed in the hose bed for shipment. Disk type wheels shall be provided. Tire tracking front to rear shall be the same.

3.4.13 Cab. The cab shall provide unobstructed seating for three men. The engine and driver's compartment shall be separated by an insulated firewall. Cab shall have upholstered, full-width adjustable seat. Cab shall be provided with boots for all levers and controls extending to the exterior of the cab. The cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, and with at least the curb side door equipped with external, key operated lock. Safety grips shall be provided on each side of the cab to assist personnel in climbing into the truck cab. Fastenings and three pairs of seat belts, and arm rests shall be furnished. Tinted safety glass shall be provided throughout the cab. Dual sun visors shall be furnished. A dome light shall be provided. The seat shall be upholstered over deep air foam cushions with first grade Naugahyde, or equal, suitable for fire service.

3.4.13.1 Windshield wiper and washer. Windshield wipers shall be mounted to facilitate clear vision. Wiper assemblies shall include features to permit speed control and return of the wiper blade to a retracted position out of the line of vision when not in use. The windshield cleaning system shall include a device that will spray the path of the wiper blades with water or cleansing solution. The cleansing solution reservoir shall have a minimum capacity of 2 quarts. The windshield wiping/cleaning system shall conform to SAE J198.

3.4.13.2 Heater and defroster. A hot water heater shall be provided. Heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to floor and to defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

3.4.14 Controls and operating mechanism. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from driver's compartment when dressed in fire fighting clothes. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.4.15 Back-up warning device. The fire truck shall be provided with an automatically activated, audible, pulsating, signaling warning device, electrically operated to caution personnel when fire truck is in reverse gear operation. Back-up warning device shall conform to SAE J944.

3.4.16 Tool stowage space. Stowage space of sufficient size to accomodate jack, handtools, anti-skid chains, emergency reflective triangles, and reflectors shall be furnished for retaining equipment during truck operation. Storage space for these tools may be furnished inside the cab.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.4.17 Body. The truck shall be equipped with a body which shall incorporate a fire pump housing and stowage bin, fire pump operator's control panel, removable water hose bed, equipment cabinets, rear platform, booster hose reel and fire fighting equipment. The body shall be fabricated from high strength material and shall be of welded construction. The body shall be reinforced at all points where clamps and hangers are attached. The body shall be free from rough and sharp edges. The body shall be furnished with flexable mud flaps and fenderetts to reduce tire splash in wet weather.

3.4.18 Handrails and grabrails. The rear platform shall be provided with two vertical grabrails to assist personnel in climbing onto the rear platform. A horizontal handrail shall be provided at the rear platform and not more than 66 inches above the rear platform. The handrails and grabrails shall be 1-1/4 inch minimum dia chromium-plated brass, chromium-plated steel, or polished stainless steel tubing. All handrails and grabrails shall be of the nontwist type.

3.4.19 Rear platform and running boards. The truck shall be provided with a rear platform and running boards. The rear platform shall have a load-carrying capacity of not less than 500 lbs. The rear platform length shall be equal to the width of the truck. The platform shall be not less than 18 inches in width, from front to rear, in front of the hose reel compartment. Rear platform shall have rounded corners, and shall be flanged downward at least 2 inches. The side running boards shall extend from the rear of the cab to the side equipment cabinets. Running boards shall have a load-carrying capacity of not less than 500 lbs. The rear platform and running boards shall have a non-slip tread surface. The running boards and rear platform shall be located at the same height from ground level. The rear platform and running boards shall be 22 inches +2 inches -0 inch, above ground level, with the truck loaded as specified in 3.4.2.1.

3.4.20 Steps. Steps shall be provided to assist personnel in gaining access to various fire fighting body components.

3.4.21 Buzzer. A buzzer shall be installed in the cab and a weatherproof pushbutton on one of the rear handrail supports to provide for a signaling device from the rear platform to the truck cab.

3.5 Maintainability.

3.5.1 Maintenance support. Assemblages or support elements such as technical manuals, repair parts, special tools, or lubrication charts, as specified (see 6.5 and 6.6) shall be adequate to perform the intended function of assisting or conducting maintenance operations.

3.5.2 Ease of maintenance. All major assemblies, including pumps, transmission, hose reels, water tank, and similar items, shall be arranged for individual removal and replacement without major disassembly or removal of other components of the truck body. Covers or plates which must be removed for component adjustment or maintenance shall be equipped with quick-disconnect fasteners. Drain outlets shall be located for accessibility.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.6 Human factors. The characteristics of the truck shall provide for operation by personnel ranging from the small man, clothed, through the large man, arctic coated, in accordance with SAE J 833 and J 925. Universal symbols in accordance with SAE J 1500 shall be used throughout.

3.6.1 Noise level. The personnel noise level in the truck cab, or at the pump operator's station, or at any other occasionally occupied station shall not exceed 85 dB(A) as specified in MIL-STD-1474 paragraph 5.1.1.1 category D when tested in accordance with 4.5.2.6. If technical infeasibility is established via MIL-STD-1474 paragraph 5.1.1.2 or the means of reduction is too costly, the written permission of the procuring activity shall be requested to exceed the 85 dB(A) limit.

3.7 Safety. All exposed parts which are subject to high operating temperatures, or which are energized electrically shall be insulated, fully enclosed or guarded. All rotating, reciprocating or moving parts which are of such nature or so located as to be a hazard to operating or maintenance personnel shall be fully enclosed or guarded. Fire lighting equipment, when mounted on the truck, shall be located and positioned so as not to present a safety hazard to personnel. Surfaces of the truck which are to be used as walkways, working areas, or steps, shall be provided with non-skid surfaces.

3.8 Performance. The fully equipped truck and equipment loaded as specified shall be capable of performing the following:

a. Parking brakes holding the truck on a 30 percent grade, in both ascending and descending positions, with the fire pump operating and discharging 80 percent of the water tank capacity at a flow rate of not less than 100 gpm at a pressure of not less than 100 psi through the 1-1/2 inch hose.

b. Service brakes holding the truck on a 30 percent grade in both ascending and descending positions.

c. Service brakes bringing the truck to a stop within a braking distance of 30 ft from a speed of 20 mph on a dry, smooth, level surface free from loose material.

d. Maintaining a maximum speed of not less than 55 mph on dry, level, paved roadway.

e. Accelerating on a level road from a standing start to a speed of 35 mph in 25 seconds.

f. Maintaining a sustained speed when ascending a 30 percent grade in low speed range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

g. There shall be no evidence of body distortion, water leakage, tire and body contact, malfunction of components, irregular chassis noise, vibration or sway when subjected to road test of 100 miles over paved roadway at speeds up to 55 mph; 25 miles over graded dirt roadway at not less than 25 mph; and 25 miles off highway over cross-country terrain at speeds up to 15 mph with ground and grade conditions requiring all wheel drive.

h. Negotiating side slopes up to 15 percent on a surface reasonably hard and free from loose material.

3.9 Environmental operation requirements.

3.9.1 Temperature. The truck and equipment shall be capable of starting and performing in any temperature from plus (+) 125° F to minus (-) 25° F.

3.9.2 Altitude. The truck and equipment shall deliver its rated pumping capacity at 100 psi net pump pressure and 100 gpm at any elevation from sea level to 2000 feet at the temperatures specified in 3.9.1. When specified (see 6.2), modification kits shall be provided and installed for utilization of trucks and equipment at specified elevations above 2000 feet.

3.10 Fire pump. The fire pump shall be a centrifugal pump that is driven by an auxiliary diesel engine. The pump impeller shaft shall be of corrosion resistant steel. The impeller suction inlets and all other portions of the pump coming into contact with the water shall be resistant to the corrosive effect of salt water. All pump-shaft glands or mechanical seals shall be adequate for service under operating conditions specified herein. The pump shall withstand a hydrostatic pressure of 350 psig for a period of 10 minutes. Drain cocks, push-pull or rotary turn type, accessible at the pump operator's position and arranged so that the open and closed position is clearly indicated, shall be provided to drain the pump and all water-carrying lines. Drain cocks shall be of the water service type and shall be equipped with positive stops. Pump drain lines shall be furnished and shall completely drain and discharge to a point not above the bottom of the chassis frame. All threaded connections shall be NPT and shall conform to FED-STD-H28. The pump, when drafting at a minimum lift of 10 ft through 20 ft of 3 inch suction hose shall:

a. Deliver 100 percent rated capacity at 150 psig discharge pressure at less than the manufacturer's recommended governed speed of the engine.

b. Deliver 70 percent of rated flow at 200 psig discharge pressure at less than the manufacturer's recommended governed speed of the engine.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

c. Deliver 50 percent of rated flow at 250 psig net pump pressure.

d. Deliver each flow rate specified above at an additional 10 percent discharge gage pressure.

e. The pump, when dry, shall take suction and discharge water within 30 seconds, with a lift of 10 ft through 20 ft of 3 inch suction hose.

f. The pumping requirements specified herein shall be accomplished at all altitudes up to 2000 feet above sea level and in any ambient temperatures from +125° F to -25° F without evidence of overheating, vapor lock, excessive vibration or any other malfunction. When operation above 2000 feet altitude (see 6.2), is required special provisions may be made.

g. The fire pump shall also deliver not less than 250 gpm from the water tank and shall maintain the rate of flow for not less than 80 percent of the rated capacity of the tank.

3.10.1 Auxiliary engine. The fire pump shall be furnished with an electric start, air cooled diesel engine. The engine shall start from the main truck battery. A start button shall be furnished on the pump panel and in the cab accessible to the driver. Fuel for the engine shall be supplied from the main truck fuel tank. The pump and engine shall be mounted as a single unit at the left rear of the truck on the same platform with the booster reel.

3.10.1.1 Priming device. The priming device shall be provided, complete with all necessary valves, and levers operated from the pump control panel. The priming device shall develop a vacuum of 22 inches of mercury (Hg) at an altitude up to 1000 ft above sea level.

3.10.2 Suction connections. The fire truck shall be provided with two gated 2-1/2 inch full flow type suction connections; one located to take water from the tank and one to take water from an auxiliary source. The valves shall be the pump manufacturer's standard corrosion-resistant, balanced ball type for quarter-turn operation. The valves shall be operated and locked by means of an individual control handle as a single-handed operation from the operator's panel. The valves shall be fitted with a female swivel and a rocker lug plug. The suction connections shall be equipped with a removable and accessible strainer; shall have a machined end with mirror finish to permit hand tight connections; shall provide a seat for suction hose gaskets, and shall be threaded with American National fire hose coupling thread (NH). All piping from the suction connection shall be 3 inch inside dia.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.10.3 Discharge connections. The fire truck shall be provided with one 2-1/2 inch discharge connection located on the pump operator's control panel, two 1-1/2 inch discharge connections located one in each of the 1-1/2 inch transverse hose beds, and one discharge connection to the booster reel. All discharge connections shall have machined ends with a mirror finish to permit hand tight connections. The connection shall provide a seat for discharge hose gaskets, and shall be threaded with NH threads. The 2-1/2 inch connection shall be fitted with a 2-1/2 x 1-1/2 NH adapter with 1-1/2 inch gasketed cap and chain. The discharge connections shall be provided with a single discharge pressure gage located on the fire pump operator's control panel. The discharge valves shall be the pump manufacturer's standard valve, and shall be balanced, corrosion resistant, ball type for quarter-turn operation. The 2-1/2 inch valves shall be operated and locked by means of an individual control handle as a single-handed operation. Discharge connections shall be provided with drain valves of at least 3/4-inch inside dia for draining hose lines with the pump discharge gates closed. Push-pull or rotary turn type drain valves shall be of the water service type and shall be equipped with positive stops. Drain-valve controls shall be located adjacent to the discharge connections. Drain lines shall be concealed behind the pump panels and shall discharge to a point not above the bottom of the chassis frame. Each discharge connection, pressure gage, and drain shall be identified by a related numbering system as well as function.

3.10.4 Relief valve. A relief valve shall not be provided.

3.10.5 Pressure rating. The pump shall withstand not less than 350 psig hydrostatic pressure on the discharge side for 10 minutes.

3.10.6 Fire pump operator's control panel. The fire truck shall be equipped with a stainless steel fire pump operator's control panel located at the rear of the truck. The panel shall have a nonglare finish. The pump pressure and suction gages shall be not less than 3-1/2 inches dia liquid filled or single Bourdon type, with throttling valves or restrictive devices to eliminate pulsating of gages. The pump pressure and suction gages shall be accessible to the operator. All gages shall return to zero reading upon equipment shut-down. All valve operating handles and other controls shall be operable by personnel wearing heavy gloves. All extended controls and handles shall be noninterfering, firmly supported, and realinable. Panel shall include at least the following:

a. Pump pressure gage - 30 inch Hg (vacuum) to 600 psi.

b. Pump suction gage - 30 inch Hg (vacuum) to 600 psi.

c. All pump discharge and suction valve controls.

d. Tank suction valve control and instructions.

e. Primer device control and instructions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

f. Illumination of all instruments and controls with nonglare lighting.

g. Engine start and stop control.

h. Water tank level gages, electronic type, shall be installed in the cab and on the pump panel.

i. All other pump panel mounted drains and controls mentioned herein.

j. Discharge valve and throttle handles shall be of black extreme temperature resisting plastic, brass, or stainless steel. All gage rims and other exposed metal shall be chromium plated or stainless steel.

k. A discharge pressure gage shall be installed in the cab for use during pump and roll. The gage shall be equipped with a throttling device to eliminate pulsating and shall be not less than 3-1/2 inches dia. The gage shall be visible to both the driver and assistant driver.

l. Instruction plates specified in 3.21.

All controls, valves drains, and gages shall be identified as to their function and shall have a related identification number. All instruments and switches shall be identified as to their function.

3.11 Water tank. A removable water tank of not less than 1200 useable gal capacity shall be provided. The water tank shall be fabricated of high-strength corrosion resistant stainless steel that has been passivated in accordance with QQ-P-35, with a yield point of 50,000 psi and shall be free of mill scale either by a pickling treatment or sand blasting. Longitudinal and transverse surge partitions conforming to NFPA No. 1901 shall be provided in the tank. The water tank shall be provided with a sump, and shall be mounted on the truck frame. The water tank shall be capable of discharging 80 percent of full capacity with the fire truck on a 30 percent grade, heading upgrade and also heading downgrade. The top shall be removable, gasketed to prevent leakage, or provided with a manhole to permit access to the tank interior for cleaning. The top shall support not less than 200 lbs per square ft of surface area. The top retaining fasteners shall not come in contact with the water. The tank drain shall be located at the low point of the tank to provide complete drainage. The water tank drain shall discharge directly to a point not above the bottom of the chassis frame. The tank shall have a nonsplash combination overflow and vent pipe of not less than 3 inch nominal pipe size, directed to the ground at the rear of the rear axle, and extending below the bottom of the truck frame.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.11.1 Tank filler opening. The tank shall have an accessibly located filler opening not less than 144 square inches and shall be provided with a tight, gasketed, hinged cap having a spring-type hold-down catch. The tank fill opening shall be provided with a removable strainer. A 2-1/2 inch line from the pump to the tank shall be provided for filling the tank, with a valve control located on the pump panel.

3.11.2 Tank piping. All piping shall be of corrosion-resistant metal, or shall be galvanized. The pipeline may incorporate a flexible, reinforced, noncollapsible connections to take up vibration. A quick-opening tank to pump shutoff valve shall be provided with control extended to the pump operator position. The tank piping shall provide for discharging the water in the tank through the fire pump discharge manifold at a flow rate of not less than 250 gpm. The tank suction pipeline, valves, and fittings shall withstand not less than 120 psi working pressure. The piping between the pump, booster reel and transverse hose beds shall be not less than 1-1/2 inch inside dia and shall incorporate 1-1/2 inch quick opening valves with controls extended to the pump operator's panel. The discharge piping, valves, and fitting between the pump booster reel and transverse hose bed shall withstand not less than 500 psi working pressure. A complete piping diagram shall be provided. All drain lines shall discharge to a point not above the bottom of the chassis frame. The piping system shall provide the capability of removing all water from the water tank when operating upgrade or downgrade on a 30 percent grade.

3.11.3 Tank mounting. The tank shall be supported on sills to cushion shock and transfer the load to the truck frame. The tank shall be so mounted to the chassis that it can be removed.

3.11.4 Tank level gage. A water tank level gage shall be furnished and located on the fire pump operator's control panel. The gage shall be of the electronic type. Another water tank level gage shall be installed in the truck cab visible to the driver and passenger.

3.12 Hose bed. A hose bed shall be provided with the capability of stowing not less than 400 ft of 1-1/2 inch, double-jacketed, cotton, rubber-lined, fire hose. The hose bed interior shall be free of all projections, sharp or rough edges which might chafe or tear fire hose or hinder its placement or removal. The hose bed sides and end shall be flanged and reinforced to withstand not less than 200 lbs horizontal pull at any point on top edge without permanent deformation. The hose bed floor shall be of slatted well-seasoned, select grade oak, or other hardwood having equal characteristics. The slats shall run the full length of the hose bed, and shall be spaced to provide ventilation for the hose. The hose bed floor assembly shall be removable. The interior of the hose bed shall be free from all projecting nuts, sharp angles, or brackets. Exposed bolt or rivet heads shall be of the oval type. Two folding, spring loaded, chromium-plated toe steps shall be furnished; one shall be located on the right, and one on the left, at the rear of water tank or body to permit easy access to the hose bed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.12.1 Transverse hose beds. Two transverse hose beds shall be located over the top of the pump area. Each transverse bed shall have the capability of stowing not less than 200 ft of 1-1/2 inch double-jacketed, cotton, rubber-lined, fire hose. Hose payout or removal openings shall be provided on each side of the truck with hose rollers installed in the bottom and both sides of each transverse bed opening to prevent hose interference or snagging. Two 1-1/2 inch swivel type discharge connections shall be provided to allow hose to be removed to either side of the truck. The bottom of the transverse hose beds shall be of slatted, well-seasoned hardwood or aluminum. Discharge gate controls for each hose bed shall be located at pump control panel, and shall be suitably identified. The hose beds shall be identified as transverse hose bed No. 1 and No. 2. Hose bed No. 1 shall be located towards the front of the vehicle. Each hose bed shall be provided with a center mount swivel type discharge connection to permit hose to be removed from either side of the truck. It is required that the discharge connections be located away from any hose bed to permit hose attachment to, or removal from, the connections without side wall interference.

3.13 Equipment cabinets. All equipment cabinets and cabinet doors shall be the manufacturer's standard box type construction and shall be watertight. The cabinets shall be the maximum size practical. Cabinets shall be framed of welded- or bolted-in structural members for strength and resistance to damage. Cabinet doors shall be double panel construction and shall be attached with full length corrosion-resistant, piano hinges. All vertically hinged doors shall have spring-type, hold-open devices. Each cabinet door shall be provided with recessed "D" ring type chromium-plated handles, operable with heavy-gloved hands, with weather-resistant latches. Maximum corrosion resistant materials shall be utilized in cabinet fabrication and hardware. Doors shall be fully gasketed and weather-stripped with neoprene and all cabinet seams shall be complete welds. Drip rails or flanged cover plates shall be provided to deflect rain water from entering cabinets. Provisions shall be incorporated to permit flushing and cleaning inside of cabinet. Each cabinet shall be illuminated. Cabinet lights shall be controlled automatically by individual door switch, with an indicating light, located on the truck instrument panel. Cabinet tops and wheelhousing tops shall run continuously on each side of the truck and shall be of antiskid surface. All equipment cabinets specified herein shall be a minimum of 1/8-inch aluminum with 3/16-inch aluminum doors. Cabinets shall not be flush with the running boards or wheel skirting.

3.13.1 Cabinet arrangement. The streetside and curbside cabinets shall be identical and shall both run the full length of the water tank. One cabinet on each side shall be located aft of the rear wheels. Two cabinets shall be located ahead of the rear wheels. The cabinets adjoining the rear wheels shall have vertically hinged doors with the hinges located on the door edge toward the front of the truck. The forwardmost cabinet on either side shall have drop-down doors. The forewardmost cabinets on either side shall be sized to accommodate the stowage of not less than 5 fire rakes, 5 long-handled shovels and 5 long-handled forrest fire beaters. However, these tools shall not be furnished with the truck.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.13.2 Hose reel compartment. A rear hose reel compartment shall be furnished. The hose reel specified in 3.14 shall be mounted to the right at the rear of the truck. Access to the hose reel shall be from the rear of the truck. There shall be sufficient width to permit access to the hose reel for servicing and removal and hose payout. The hose reel shall be illuminated and the lighting shall be controlled by the switch specified in 3.13. Hose rollers shall be installed on both sides and bottom of the hose reel to prevent hose interference or snagging. The hose shall be mounted on a common platform with the auxiliary engine and pump. Mounting shall be to the truck frame or frame extensions.

3.14 Booster hose reel. A booster hose reel shall be provided and installed as specified in 3.13.2. The reel shall be an electrical rewind type. The rewind control switch shall be a push type, spring loaded, button. One electric rewind control switch shall be installed and located near the hose reel. The switch shall be suitably identified. The hose reel shall be equipped with 150 ft, in three 50 ft lengths, of 1 inch, 800 psi, rubber chemical hose, jointed with smooth full-flow type, 2300 psi couplings. A 1 inch brass hose nozzle of the combination straight stream and adjustable fog type shall be furnished. The nozzle shall be equipped with ball shut-off and click-stop nozzle settings. The nozzle shall be of the pistol grip type. Nozzle tip shall be fitted with a rubber or synthetic rubber-ring. The nozzle shall permit preselection of any nozzle setting prior to turning on the nozzle, and shut-off at any nozzle setting. The nozzle shall provide settings for straight stream and minimum fog settings of 30 degrees, 60 degrees, and 90 degrees. The nozzle shall have a discharge capacity of not less than 20 gpm for straight stream and not less than 22 gpm for fog (spray). The hose reel shall have a friction brake payout to prevent over-travel. The hose reel shall also have provisions for manual hand-crank rewind, with the hand-crank facing toward the fireman standing at the rear of the truck. The hose reel shall be connected to the discharge manifold of the fire pump with a 1-1/2 inch inside dia galvanized steel pipe-line having a flexible section to take up vibration, and shall have an operation valve with handle extended to the left side of the truck on the pump operator's panel. The discharge pipe-line, and fittings between the pump and booster reel shall withstand not less than 500 psi working pressure. Drain line shall discharge at a point not above the bottom of the chassis frame.

3.15 Communication equipment. When specified (see 6.2), a radio communication system, or a space approximately 1-1/2 ft long x 1-1/2 ft wide x 1 ft high for installation of communication equipment, shall be provided.

3.15.1 Radio noise suppressors. The truck chassis shall be equipped with radio noise suppressors conforming to SAE J552. Electromagnetic radiation from the truck chassis shall be within the limits of SAE J551.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

3.16 Electromagnetic interference. Unless otherwise specified (see 6.2), the electromagnetic interference emission and susceptability characteristics of the truck shall be certified to SAE J551.

3.17 Lubrication. Unless otherwise specified (see 6.2), the truck shall be lubricated prior to delivery with lubricants designated for use in the -25° F to +125° F temperature range. The truck shall operate as specified herein when serviced with military oils conforming to MIL-L-2104 and MIL-L-2105 and designated for use in the temperature range specified herein (see 6.7). A tag shall be attached to the transmission control level to indicate the temperature range, and the lubricant grade used.

3.17.1 Drain plugs. All drain plugs installed throughout the truck for the purpose of draining lubricants shall be of the permanent magnet type.

3.18 Servicing and adjusting. Prior to acceptance of the truck by the Government inspector, contractor shall service and adjust each truck and its mounted equipment for operational use, including at least the following: focusing of lights; adjustment of engine; adjustment of electrical and brake system; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, running gear and mounted equipment; servicing of cooling system with a solution of antifreeze and water in equal parts by volume, and servicing of windshield washer reservoir with water and appropriate additives.

3.19 Painting. Unless otherwise specified (see 6.2), the truck cab, chassis body and other equipment, as applicable, shall be cleaned, treated, primed, and painted three coats gloss lime-yellow, color No. 13670 of FED-STD-595 in accordance with the manufacturer's standard commercial practice, but not less than equal to MIL-T-704. All tread plates shall be painted aluminum color. The vehicle shall be rust-proofed in accordance with FED-STD-297.

3.20 Identification marking. The truck shall be identified in accordance with MIL-STD-130. The marking shall be applied to the truck on plates conforming to MIL-P-514, type I, style 1, composition C, of type I, grade A, class 1 material. Each plate shall be attached by screws, bolts, or rivets to the inside of the door on the driver's side of the cab. The following data shall appear in the ownership and nomenclature spaces provided on the identification plate in their respective order:

OWNERSHIP - U.S. ARMY

NOMENCLATURE - TRUCK, FIRE FIGHTING: BRUSH, TANK,

6 X 6, COMMERCIAL CHASSIS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.21 Instruction plates. All pumping controls, valves, instruments, and truck operating controls shall be provided with instruction plates designating function and operation. Instruction plates shall conform to MIL-P-514, type III, composition C, of type I, grade A, class 1 material, size as applicable. Each plate shall be attached by screws, bolts, or rivets in a location where the plate shall be both visible and legible.

3.22 Contractor-furnished components. The following equipment components shall be furnished, installed and stowed aboard each truck:

a. One 12 ft aluminum roof-type ladder.

b. One combination adjustable wrench for hydrant and spanner.

c. One portable, floating-type, gasoline-engine-driven, self-priming pump, with a rating of not less than 120 gpm. The pump shall include all equipment components required for line service use, except hose and nozzle.

d. One chain saw conforming to GGG-S-62, type II, style 1, class B, with repair and maintenance kit.

3.23 Interchangeability. All parts having the same part number shall be functionally and dimensionally interchangeable. Interchangeable parts are defined as two or more like parts possessing such functional and physical characteristics as to be equivalent in performance and durability, and capable of being exchanged one for the other without alteration of the parts themselves or of adjoining parts, except for adjustment, and without selection for fit or performance.

3.24 Workmanship.

3.24.1 Castings and forgings. All parts, components, and assemblies of the truck which include castings and forgings shall be clean of harmful extraneous material such as sand, dirt, sprues, scale and flux. Rework shall be limited to procedures which do not reduce mechanical properties or affect function.

3.24.2 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame-cutting, using tips suitable for the thickness of the steel, may be employed instead of shearing. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid over-heating. Heated steel shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.24.3 Bolted connections. Boltholes shall be accurately formed and shall have burrs removed. Washers or lockwashers shall be provided where necessary. Matching thread areas securing bolts conforming to SAE J429 or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt. All fasteners shall be correctly torqued and shall have full thread engagement. Bolts shall protrude not more than two full threads.

3.24.4 Riveted connections. Rivets shall fill the holes completely. The upset rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member, and shall be in accordance with SAE J492.

3.24.5 Welders and welding.

3.24.5.1 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

ANSI/ASME - Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.
ANSI/AWS D1.1 - Structural Welding Code, Section 5, Qualification.

Certification shall be made available for review by the contracting officer or designated representitive. Contractors who make only horizontal welds need not qualify welders for "all position welding". Subject to approval by the Government, the contractor's standard welder qualification may be substituted in lieu of the above codes provided that the contractor's procedure is equivalent to the above codes. The contractor shall be responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with ANSI/ASME or ANSI/AWS codes.

3.24.5.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing, and other foreign matter. Parent materials, weld filler metals and fabrication techniques shall be as required to enable the truck to conform to the examination and test requirements specified in section 4. Parts to be joined by fillet welds shall be brought into as close contact as possible and in no event shall be separated by more than 3/16-inch unless appropriate bridging techniques are used. Unless otherwise specified (see 6.2), the welding process used in fabrication of the truck shall be at the option of the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

3.24.5.3 Aluminum welding. The aluminum surfaces of parts to be welded shall be free from scale, paint, grease, oxide film, and other foreign matter. Cleaning with a wire brush shall be accomplished with a corrosion-resistant (stainless steel) wire brush only. The welding shall be done by the inert gas, shielded arc method. Welds may be ground, filed, buffed, or chipped but shall not be hammered, and shall be free from discontinuities such as base metal cracks adjacent to or behind welds, cracks in weld metal, undercutting of base metal, lack of fusion with parent metal or between parts, lack of penetration, lack of prescribed fit, or splatter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and service conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article truck shall be examined as specified in 4.5.1. The examination shall be conducted after all of the tests specified in 4.5.2 have been completed. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article truck shall be tested as specified in 4.5.2, except the pump test shall be conducted for compliance to 3.10. Failure of any test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection failure. Failure of a first article truck to meet any requirement specified herein during and as a result of the examination and tests specified shall be cause for rejection of the first article truck and shall be cause for refusal by the Government to accept production trucks until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies.

4.4 Quality conformance inspection.

4.4.1 Examination. Each truck shall be examined for defects specified in 4.5.1. presence of one or more defects shall be cause for rejection.

4.4.2 Tests. Each truck and component shall be tested as specified in 4.5.2.1, 4.5.2.1.1 and 4.5.2.4. The road test specified in 4.5.2.4 shall be reduced by one half the required milage. Failure of any test shall be cause for rejection.

4.5 Inspection procedure. Prior to examination or tests, the truck shall be lubricated with military oils and greases for use at the ambient temperature at the inspection site.

4.5.1 Examination. The trucks shall be examined as specified herein for the characteristics listed in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule (requirements).

Number	Characteristic	Requirement Paragraph
Major		
101.	Truck not as specified.	3.1
102.	Materials not as specified.	3.3
103.	Materials are not corrosion resistant or treated to be made corrosion resistant for the applicable storage and operating environment.	3.3.1
104.	Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.	3.3.1.1
105.	Contractor does not have documentation available for identification of material, material finishes or treatments.	3.3.1.2
106.	Used, rebuilt or remanufactured components, pieces or parts incorporated in the truck.	3.3.2
107.	Truck chassis not as specified.	3.4.1
108.	The truck manufacturer's gross vehicle weight (gvw) rating for the truck chassis not as specified.	3.4.2.1
109.	Dimensions not as specified.	3.4.2.2
110.	The chassis frame not as specified.	3.4.3
111.	Angles of approach and departure not as specified.	3.4.3.1
112.	Engine not as specified.	3.4.4
113.	Engine fuel system not as specified.	3.4.4.1
114.	Fuel tank(s) not as specified.	3.4.4.1.1
115.	Fuel filter not installed.	3.4.4.1.2
116.	Engine coolant system not as specified.	3.4.4.2
117.	Lubrication of the engine not as specified.	3.4.4.3
118.	Engine governor not as specified.	3.4.4.4
119.	Exhaust system not as specified.	3.4.4.5
120.	Air pollution control not as specified.	3.4.4.6
121.	Engine hour meter not as specified.	3.4.4.8
122.	Brake horsepower certification not furnished by contractor as specified.	3.4.4.9
123.	Electrical equipment not as specified.	3.4.5
124.	Starting system not as specified.	3.4.5.1
125.	Battery units and electrical circuits not as specified.	3.4.5.2
126.	Electrical generating system not as specified.	3.4.5.2.1
127.	Lighting system not as specified.	3.4.5.3
128.	Additional lighting not as specified.	3.4.5.3.1
129.	Warning lights not as specified.	3.4.5.3.2
130.	Light switches not as specified.	3.4.5.3.3
131.	Siren and horn not as specified.	3.4.5.4

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule (requirements). - Continued

Number	Characteristic	Requirement Paragraph
132.	Front bumper and towing device not as specified.	3.4.6
133.	Brush guard not as specified.	3.4.7
134.	Suspension system not as specified.	3.4.8
135.	Truck drive assembly not as specified.	3.4.9
136.	Transmission not as specified.	3.4.9.1
137.	Power take-off not as specified.	3.4.9.1.1
138.	Transfer case not as specified.	3.4.9.2
139.	Drive axle not as specified.	3.4.9.3
140.	Steering mechanism not as specified.	3.4.10
141.	Brakes not as specified.	3.4.11
142.	Service brakes not as specified.	3.4.11.1
143.	Parking brakes not as specified.	3.4.11.2
144.	Wheels, rims, tires and tubes not as specified.	3.4.12
145.	Cab not as specified.	3.4.13
146.	Windshield wiper and washer not furnished as specified.	3.4.13.1
147.	Heater and defroster not as specified.	3.4.13.2
148.	Controls and operating mechanism not as specified.	3.4.14
149.	Backup warning device not as specified.	3.4.15
150.	Tool stowage space not as specified.	3.4.16
151.	Body not as specified.	3.4.17
152.	Handrail and grabrails not as specified.	3.4.18
153.	Rear platform and runing boards not as specified.	3.4.19
154.	Steps not as specified.	3.4.20
155.	Buzzer not as specified.	3.4.21
156.	Maintenance support assemblages or elements not adequate.	3.5.1
157.	Ease of maintenance not as specified.	3.5.2
158.	Human factors not as specified.	3.6
159.	Noise level not as specified.	3.6.1
160.	Safety not as specified.	3.7
161.	Fire pump not as specified.	3.10
162.	Priming device not furnished as specified.	3.10.1.1
163.	Suction connections not furnished as specified.	3.10.2
164.	Discharge connections not furnished as specified.	3.10.3
165.	Relief valve provided.	3.10.4
166.	Controls not as specified.	3.10.6
167.	Water tank not as specified.	3.11
168.	Tank filler opening not as specified.	3.11.1
169.	Tank piping not as specified.	3.11.2
170.	Tank mounting not as specified.	3.11.3
171.	Tank level gage not as specified.	3.11.4
172.	Hose bed not as specified.	3.12

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule (requirements). - Continued

Number	Characteristic	Requirement Paragraph
173.	Equipment compartment not as specified.	3.13
174.	Booster hose reel not as specified.	3.14
175.	Communication equipment not furnished as specified.	3.15
176.	Truck chassis not equipped with radio noise suppressors as specified.	3.15.1
177.	Truck not lubricated before delivery as specified.	3.17
178.	Drain plugs not as specified.	3.17.1
179.	Truck not serviced and adjusted as specified.	3.18
180.	Instruction plates not made and furnished as specified.	3.21
181.	Other specified components not furnished by contractor.	3.22
182.	Interchangeability of parts having the same part number not as specified.	3.23
183.	Casting and forgings not as specified.	3.24.1
184.	Metal fabrication not as specified.	3.24.2
185.	Bolted connections not formed and burrs removed as specified.	3.24.3
186.	Riveted connections not as specified.	3.24.4
187.	Welders not certified for welding as specified.	3.24.5.1
188.	Welded surface not prepared for welding as specified.	3.24.5.2
189.	Aluminum welding not as specified.	3.24.5.3
Minor		
201.	Painting not as specified.	3.19
202.	Identification marking not as specified.	3.20

4.5.2 Tests.

4.5.2.1 Pumps. The pumps shall be tested for two hours as specified by NFPA 19Q1. Data shall be collected every 15 minutes. All gages shall be checked for accuracy of 10 percent of total gage range.

4.5.2.1.1 Hydrostatic. The entire pump, including the suction chamber and all piping, shall be tested to a hydrostatic pressure of 350 psi for 10 minutes. Nonconformance to 3.10.5 shall constitute failure of this test. This test shall be conducted after all tests specified in 4.5.2.4 have been completed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

4.5.2.2 Truck weight. The truck shall be weighted to determine curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axle will be computed using the curb weight, the operator weight at 175 pounds, and the payload uniformly distributed over the vehicle load area, to provide the specified gvw. Calculated imposed loads on front and rear axle will be utilized to ascertain that the suspension, and tires furnished are of adequate capacity to meet specification requirements.

4.5.2.3 Environment tests.

4.5.2.3.1 Test for ambient temperature and altitude conditions. When specified (see 6.2), the contractor shall perform a pumping test of the first article under actual or simulated conditons of the specified altitude above sea level and an ambient temperature of 125° F. When pumping at heights above 2000 feet altitude is required, certification is required from the contractor that the vehicle will perform as specified in 3.4.4.2. The pumping test shall consist of the following:

a. Test the suction and priming.

b. The pumping test shall be for 3 hours consisting of 2 hours at rated capacity at 150 psi discharge gage pressure, 1/2 hour at 70 percent of rated capacity at 200 psi discharge gage pressure, and 1/2 hour at 50 percent of rated capacity at 250 psi discharge gage pressure. The test shall be conducted with 20 feet of 6 inch suction hose and a suction lift of not less than 10 feet.

Nonconformance to 3.9 shall constitute failure of this test.

4.5.2.4 Road tests. The loaded truck, including filled water tank, filled fuel tanks, lubricants, a 1500 pound evenly distributed simulated load, and a crew of three men, weighing not less than 175 pounds each or equivalent dead weight, shall be tested as follows:

a. 100 miles over paved roads at maximum traffic speeds up to 55 mph.

b. 15 miles over graded dirt roads at speeds up to 30 mph.

c. Service brakes shall be applied during runs a. and b. above.

d. All lights, siren, horn, speedometer, hourmeter, controls, and instruments pertaining to the truck engine shall be tested.

e. The airbrake system shall be tested for conformance to 3.4.11.2.

Nonconformance shall constitute failure of these tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

4.5.2.5 Electromagnetic interference. The truck shall be tested as specified in SAE J 551. The manufacturer may furnish a certification in lieu of the test that the truck meets the requirements, together with a list of the suppression devices installed. Nonconformance to 3.15.1 and 3.16 shall constitute failure of this test.

4.5.2.6 Noise levels. The truck shall be tested in accordance with SAE J366 for exterior noise level, and paragraph 5 of MIL-STD-1474 for personnel noise levels. Non conformance to 3.6.1 shall constitute failure of this test.

4.6 Inspection of packaging. The preservation, packing and marking of the truck and equipment shall be examined to determine compliance with the quality assurance provisions of MIL-STD-281 and MIL-E-10062, as applicable.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each complete truck with furnished equipment shall be preserved in accordance with MIL-STD-281, level A (mobile), with the following additions and exceptions.

5.1.1.1 Engine. The engine and engine accessories shall be preserved in accordance with MIL-E-10062, type I, method I, level A. The cooling system shall be preserved by the water and antifreeze procedures, except the antifreeze shall conform to MIL-A-46153.

5.1.1.2 Fire truck equipment. The fire truck equipment shall be preserved in accordance with the contractors recommendations that are adequate to prevent deterioration and damage during shipment and indeterminate storage, utilizing the preservation-packaging criteria established in MIL-P-116. Specifically the gasoline engine on the portable pump shall be preserved in accordance with the level A requirements of MIL-E-10062, type I, method I.

5.1.1.3 Equipment. Equipment shall be placed and secured as provided for except exposed equipment subject to pilferage, damage or loss shall be prepared as "On vehicle equipment" in accordance with MIL-STD-281.

5.1.2 Level C. Each complete truck and all items issued with the truck shall be suitably preserved to afford protection against deterioration and damage from the contractor to the initial destination. In addition, the following specific requirements shall be accomplished. Items with critical surfaces required for fit or function shall be provided protection by use of preservative coatings, volatile corrosion inhibitiors, desiccated packs. Item requiring protection from physical damage to surfaces or which are fragile by nature shall be protected by wrapping pack compartmentalization, or cartonizing of the individual item. Exposed equipment subject to easy pilferage or loss shall be placed in secured compartments, truck cab, or in wooden boxes when practical. Wooden boxes, when used, shall be

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the currentversion before use.

secured to the truck with metal strapping and in a manner to prevent damage to the painted surface of the truck. Items such as ladders that are to large to place in compartments, truck cab or impractical to place in a wood box shall be secured in place using metal strapping. The cooling system shall be filled with a fresh clean solution of 50 percent antifreeze conforming to MIL-A-46153 and a tag attached indicating the temperature to which the cooling system can be subjected before damage. The crankcase and all other lubrication reservoirs shall be filled to the operating level with the grade of military lubricant designed for use in the temperature range at the shipping destination. A tag shall be attached in a conspicuous location to indicate which military lubricant has been used and its grade and temperature range. A deprocessing guide shall be furnished indicating in detail the preservation material to be removed and other servicing required prior to placing the truck in operation.

5.2 Packing. Packing (see 6.8), each complete truck, preserved as specified in 5.1 shall not require packing.

5.3 Marking. Marking (see 6.8), shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The truck is intended for initial attack in combating structural, forest, brush, grass, or similar natural cover fires.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. When a first article is required for inspection and approval, and numbers of trucks required (see 3.2).

c. When engine cooling system is other than specified (see 3.4.4.2).

d. When altitude modification kits are required (see 3.9.2).

e. Whether communication equipment or space is required (see 3.15).

f. When electromagnetic interference requirements shall be other than as specified (see 3.16).

g. When lubrication other than as specified is required (see 3.17).

h. When truck exterior is to be treated and painted other than as specified (see 3.19).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

i. When the welding process will not be at the option of the contractor (see 3.24.5.2).

j. When altitude and high temperature pumping test shall be performed on the first article model (see 4.5.2.3.1).

k. Level of preservation required (see 5.1).

6.3 First article. When a first article inspection is required, the item will be tested and should be a preproduction model. The first article should consist of one or more truck assemblies. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article.

6.4 Definitions. The following definitions shall apply throughout this specification.

6.4.1 Ambient temperature. The temperature of the astmosphere measured at the intake side of the engine cooling radiator.

6.4.2 Excessive surging. Excessing surging shall be defined as any movement of the water or fuel that would cause the operator of the vehicle to lose control during acceleration, deceleration or any maneuver of the vehicle.

6.5 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each truck.

6.6 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of trucks.

6.7 Lubricants. The contracting officer should furnish a list of military lubricants applicable to the truck covered by this specification as contained in the Federal Supply Catalog, Department of Defense Section, Identification List C9100-IL, for FSC group 91.

6.8 Marking. Levels of packing have not been included as they are not appropriate for this item. For purposes of preservation/packing level marking, the marking shall be as required by the customer.

Custodians:
Army - ME

Review activities:
Army - CE

Preparing activity:
Army - ME

Project 4210-A180

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir R&D Center
ATTN: STRBE-DS
Ft. Belvoir, VA 22060

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-52984A(ME)	Truck, Fire Fighting: Brush, 1200 Gallon Water Tank, 6 X 6, Commercial Chassis

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:11Z
Check the source to verify that this is the current version before use.