MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, SCHOTTKY TTL,
AND-OR-INVERT GATES MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/74B, dated 28 October 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, add the following new case outlines:

"2 C-2 (20 terminal, .350" x .350"), square chip carrier package

"X C-2A (20 terminal, .350" x .350"), square chip carrier package".

1.3, Thermal resistance, junction-to-case (θ_{JC}), delete and substitute the following:

"Thermal resistance, junction-to-case (θ_{JC}):
Cases A, B, C, D, 2, and X - - - - - -(See MIL-M-38510, appendix C)".

PAGE 4

TABLE II, MIL-STD-883 test requirements: Delete "Initial electrical parameters (pre burn-in) and substitute "Interim electrical parameters".

TABLE II, Group A test requirements, Class S: Delete "10,11".

TABLE II, Additional electrical subgroups for group C periodic inspections: Delete in its entirety.

PAGE 5

4.2b: Delete "Initial" and substitute "Interim" (two places).

4.4.3c: Delete in its entirety.

PAGES 9 AND 10

TABLE III, pin designations, delete and substitute the following:

"

Cases														
2,X 1/	2	3	4	6	8	9	10	12	13	14	16	18	19	20
A,B,C,D	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	1A	2A	2B	2C	2D	2Y	GND	1Y	1C	1D	NC	NC	1B	V_{CC}

"

PAGE 10

Bottom of table, add footnote 1/ as follows:

"1/ Cases 2 and X pins not designated are NC."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:12Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - SH, OS
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1067)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:12Z
Check the source to verify that this is the current version before use.