Qualification requirements have been removed for device type 02

MIL-M-38510/75B
AMENDMENT 1
20 OCTOBER 1987

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, SCHOTTKY TTL,
EXCLUSIVE-OR GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/75B, dated 27 November 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, add the following new case outline:

"2 C-2 (20-terminal, .350" x .350"), square chip carrier package
X C-2A (20-terminal, .350" x .350"), square chip carrier package"

1.3, thermal resistance, junction-to-case (θ_{JC}), delete and substitute the following:

"Thermal resistance, junction-to-case (θ_{JC}):
Cases A, B, C, D, E, F, 2, and X - - - - - - (See MIL-M-38510, appendix C)

PAGE 5

3.6, delete second sentence in its entirety.

TABLE II, group A test requirements, class B devices: Add "10, 11".

TABLE II, additional electrical subgroups for group C periodic inspections: Delete in its entirety.

PAGE 9

FIGURE 3, note 3: Delete "5.5 V" and substitute "5.0 V". Make this same change on page 10.

PAGE 13

TABLE III, terminal designations, delete and substitute as follows:

"

Cases														
A,B,C,D	1	2	3	4	5	6	7	8	9	10	11	12	13	14
2, X 2/	2	3	4	6	8	9	10	12	13	14	16	18	19	20
	1A	1B	1Y	2A	2B	2Y	GND	3Y	3A	3B	4Y	4A	4B	V_{CC}

"

Make these same changes on pages 14 and 15.

PAGE 15

Following footnote 1/, add footnote 2/ as follows:

"2/ Cases 2 and X pins not designated are NC."

The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
7	7
8	Reprinted without change

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:12Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1062)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:12Z
Check the source to verify that this is the current version before use.

Pin number			Pin name		Pin name
Case			Device type 01		Device type 02 1/
2 and X	E and F	A, B, C, and D	2	A, B, C, and D	E and F
1	1	1	NC	1A	1A
2	2	2	1A	1B	1B
3	3	3	1B	1Y	1Y
4	4	4	1Y	2A	1C, 2C
5	5	5	NC	2B	2A
6	6	6	2A	2Y	2B
7	7	7	NC	GND	2Y
8	8	8	2B	3Y	GND
9	9	9	2Y	3A	3Y
10	10	10	GND	3B	3A
11	11	11	NC	4Y	3B
12	12	12	3Y	4A	3C, 4C
13	13	13	3A	4B	4Y
14	14	14	3B	V_{CC}	4A
15	15		NC		4B
16	16		4Y		V_{CC}
17			NC		
18			4A		
19			4B		
20			V_{CC}		

1/ Qualification requirements removed for this device type

FIGURE 1. Terminal connections.

Supersedes page 7 of MIL-M-38510/75B of
27 November 1985

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:12Z
Check the source to verify that this is the current version before use.

Device type 01

INPUTS		OUTPUT
A	B	Y
L	L	L
L	H	H
H	L	H
H	H	L

$Y = \overline{A}B + A\overline{B}$

Device type 02 1/

INPUTS			OUTPUT
A	B	C	Y
L	L	L	L
L	H	L	H
H	L	L	H
H	H	L	L
L	L	H	H
L	H	H	L
H	L	H	L
H	H	H	H

Positive logic: $Y = A\overline{B}\overline{C} + \overline{A}B\overline{C} + \overline{A}\overline{B}C + ABC$

1/ Qualification requirements removed for device type 02.

FIGURE 2. Truth tables and logic equations.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:12Z
Check the source to verify that this is the current version before use.