MILITARY SPECIFICATION

ADSORBER, VAPOR, SYNTHETIC SOLVENT DRY CLEANING UNITS

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers single and double unit vapor adsorbers.

1.2 Classification.- The vapor adsorbers shall be of the following sizes as specified (see 6.2).

Size 1 - 1-1/2 gallon adsorption capacity, single unit.
Size 2 - 4 gallon adsorption capacity, single unit.
Size 3 - 8 gallon adsorption capacity, double unit.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

CC-M-636 - Motor, Alternating-Current, (Fractional Horsepower)
CC-M-641 - Motor, Alternating Current, (Integral Horsepower, 200 HP and Smaller)
QQ-C-390 - Copper Alloy Castings (Including Cast Bar)
QQ-N-281 - Nickel-Copper-Alloy, Bar, Plate, Rod, Sheet, Strip, Wire, Forgings, and Structural and Special Shaped Sections
QQ-N-288 - Nickel-Copper-Alloy and Nickel-Copper-Silicon Alloy Castings

MILITARY

MIL-T-152 - Treatment, Moisture - and Fungus Resistant, of Communications, Electronic, and Associated Electrical Equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

MIL-L-3153 - Laundry and Dry Cleaning Machinery and Equipment (for Fixed Installations), Preparation for Delivery of

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130 - Identification Marking of U.S. Military Property
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

Standard ICl-1965 - Industrial Controls

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th St., New York, N. Y. 10017.)

UNDERWRITERS' LABORATORIES, INC. (UL)

Standard 508 - Industrial Control Equipment

(Application for copies should be addressed to Underwriters' Laboratories, Inc., 1285 Walt Whitman Road, Melville, Long Island, N. Y. 11746; 207 E. Ohio St., Chicago, Ill. 60611; or 1655 Scott Blvd., Santa Clara, Calif. 95050.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Standard No. 32 - Dry Cleaning Plants

Standard No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch St., Boston, Mass. 02110.)

AMERICAN WELDING SOCIETY (AWS)

Standard Qualification Procedures of The American Welding Society

(Application for copies should be addressed to the American Welding Society, United Engineering Center, 345 E. 47th St., New York, N. Y. 10017.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel

Code - Welding Qualifications

(Application for copies should be addressed to The American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, N. Y., 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167- Standard Specification for Corrosion-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.

A176- Standard Specification for Corrosion-Resisting Chromium Steel, Plate, Sheet, and Strip.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

3. REQUIREMENTS

3.1 First article.- When specified (see 6.2), before production is commenced, a sample vapor adsorber shall be submitted or made available

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production item.

3.2 Standard product.- Each vapor adsorber covered by this specification shall be the regular commercial product of the manufacturer except for changes necessary to comply with this specification.

3.3 Codes and standards.-

3.3.1 NFPA.- The vapor adsorber shall conform to NFPA Standard No. 32 - Drycleaning Plants, Class IV, and the installation of the electrical components shall conform to NFPA Standard No. 70 - National Electrical Code for equipment for general use.

3.3.2 UL.- Electrical controls shall conform to UL Standard 508 - Industrial Control Equipment - for use in ordinary locations. The complete vapor adsorber or other electrical components shall conform to UL requirements, as applicable, for use in ordinary locations.

3.3.3 NEMA.- Motor controllers shall conform to performance requirements of NEMA Standard No. ICl-1965.

3.4 Certification.- Prior to approval of the preproduction sample, or if none is submitted, prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative, that the complete vapor adsorber or individual electrical components he proposes to furnish meet the requirements specified in 3.3.1, 3.3.2, and 3.3.3, as applicable.

3.4.1 NFPA.- Acceptable evidence of meeting the requirements of 3.3.1 shall be the manufacturer's certified statement that the vapor adsorber conforms to NFPA Standards No. 32 and 70.

3.4.2 UL.- Acceptable evidence of meeting the requirements of 3.3.2 shall be the UL label or a UL listing of the complete vapor adsorber or the individual electrical components, or certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that the vapor adsorber or electrical components conform to applicable UL Standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

3.4.3 NEMA.- Acceptable evidence of meeting the requirements of 3.3.3 shall be the manufacturer's certified statement that the motor controllers conform to NEMA Standard No. ICl-1965. A tag or label attached to the controller(s) stating the component conforms to this standard is acceptable evidence.

3.5 Materials.- Materials not definitely specified, shall be of the quality normally used for the purpose in commercial practice.

3.5.1 Corrosion-resistant metals.- Corrosion-resistant metals used in the fabrication of the vapor adsorber shall conform to 3.5.1.1, 3.5.1.2, or 3.5.1.3.

3.5.1.1 Corrosion-resisting steel.- The corrosion-resisting steel shall conform to ASTM Standard Specification A167- or A176-, as applicable.

3.5.1.2 Nickel-copper-alloy.- The nickel-copper-alloy shall conform to QQ-N-281 or QQ-N-288.

3.5.1.3 Copper alloy castings.- The copper alloy castings shall conform to alloy numbers G1, G5, G6, or G7 of QQ-C-390.

3.5.2 Materials for fasteners.- Rivets, bolts, screws, nuts, and washers shall be of carbon or alloy steel, except where brass or corrosion-resistant metal is to be fastened, in which case they shall be of brass or corrosion-resistant metal respectively. Where dissimilar metals are fastened, bolts, rivets, screws, and nuts shall be of corrosion-resisting metal. Electrodes or welding rods used for welding shall deposit material compatible with the base metal.

3.5.3 Pipe, tube, fittings and valves.- Unless otherwise specified herein, pipe, tube, valves, and fittings used for solvent, water, air, and steam lines shall comply with accepted plumbing practices for their intended use. All piping shall be designed for a minimum operating pressure of 125 pounds per square inch (psi).

3.5.4 Conduit, fittings, and electric wire.- Electrical conduit shall be rigid or flexible steel, metallic conduit, or electrical tubing. All electrical wire shall be heat resistant grade, thermoplastic insulated.

3.6 Design and construction.- The vapor adsorber shall be designed to pull solvent laden air from the dry cleaning machine exhaust, the recovery tumbler, and the various floor pickups, through a ducting inlet when a vapor adsorber motor driven fan is energized. The solvent laden air shall be directed to a carbon bed. When the carbon bed becomes saturated, the vapor adsorber shall be stripped by introducing live steam into the bottom of the carbon bed. The solvent and water vapors shall be condensed into a liquid that flows through a solvent-water separator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

The water shall drain to a waste outlet and the solvent recovered from a solvent outlet, ready for reuse. The adsorber shall exhaust clean vapor free air to the atmosphere through a ducting outlet. The vapor adsorbers shall be designed to recover (after initial stripping) the following amount of solvent when tested as specified in 4.4.2.

Size 1 - 1-1/2 gallons ± 1/4 gal. - for one hour of stripping
Size 2 - 4 gallons ± 1 gal. - for one hour of stripping
Size 3 - 8 gallons ± 2 gal. - for one hour of stripping

The tank shall be constructed of heavy gauge welded steel protected internally by epoxy or phenolic coating. Tanks shall be circular in shape with domed heads. The double tank (size 3) construction shall permit the adsorption cycle to take place in one tank while the other tank is in the recovery cycle. All metal surfaces of attachments that come in contact with solvent vapor shall be given a protective coating or shall be fabricated from corrosion-resistant metal. When operationally tested as specified in 4.4.1, the assembly shall have:

(a) Complete and proper interrelationship.
(b) No leaks.
(c) No undue vibration or noise.
(d) No overheating of parts (i.e. bearings).
(e) Starting and stopping devices that operate smoothly.
(f) No structural failures.

3.6.1 Electrical system.- The electrical system shall conform to requirements of 3.6.1.1 through 3.6.1.3.

3.6.1.1 Electrical characteristics.- The electrical components of the system shall be designed for operation on the voltage, frequency, and number of phases specified (see 6.2).

3.6.1.2 Wiring.- Wiring shall be provided between all electrical components mounted on the machine, with materials specified in 3.5.4, as applicable. All wiring shall terminate in a junction box with provisions for extending beyond the machine.

3.6.1.3 Motors.- Motors shall conform to the requirements of CC-M-636 or CC-M-641, and to the following requirements:

(a) All motors shall have windings impregnated to resist moisture.
(b) Motors shall have the proper starting characteristics and ample power with a reasonable factor of safety for their intended operation under full-load conditions without exceeding the permissible temperature rise.
(c) Motors shall be equipped with ball bearings, except that motors of less than 1/2 horsepower for horizontal applications may have sleeve bearings. Motor bearings shall be of the permanently lubricated type or shall have adequate and accessible means for lubrication.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

3.6.2 Attachment lines and outlets.- The following attachment lines and outlets shall be provided with each vapor adsorber:

Recovered solvent outlet
Water inlet lines
Waste water outlet
Inlet ducting line
Outlet ducting line
Steam lines

The sizes shall be in accordance with manufacturers commercial practice, providing the final assembly meets the solvent recovering capacity for the size vapor adsorber specified.

3.6.3 Fan.- The vapor adsorber motor driven fan shall be rated to deliver the required air flow through the carbon bed. The fan shall meet electrical system requirements of 3.6.1.

3.6.4 Lint cylinder.- The lint cylinder shall be located in an accessible position between the carbon tank and various machines or floor pick-up, to remove the large particles of lint or dirt that may be picked up from the air duct. The lint filter shall be a foam disc or lint bag.

3.6.5 Accessories.- Each vapor adsorber shall be provided with adjustment and shut off valves as required for steam, water, and vapor. The adsorbers shall also be provided with pressure gauges, steam trap, steam separator, dampers, dampered floor pickups, and other accessories, as required, to make a complete unit.

3.6.6 Moisture and fungus resistance treatment.- When specified (see 6.2), electrical control components shall be moisture and fungus resistant treated with materials conforming to and applied as specified in MIL-T-152.

3.7 Electromagnetic compatibility.- When specified (see 6.2), equipment shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.4.3).

3.8 Finish.- Unless otherwise specified (see 6.2), the vapor adsorbers shall be finished according to the manufacturer's standard practice except components to be painted shall have a color corresponding to No. 24172 of FED-STD-595.

3.8.1 Metallic-coating thickness.- When galvanizing or other protective metallic coating is used, the thickness of the coating shall be in accordance with the manufacturer's standard commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

3.8.2 Finish of exposed corrosion-resistant metals.- When used, corrosion-resisting steel, cast bronze, and nickel-copper alloy metal shall be free from scale. Exposed corrosion-resisting steel and nickel-copper alloy metal surfaces shall be finished in accordance with the manufacturers standard finish.

3.9 Name and data plates.- For Military procurements, each vapor adsorber shall be marked for identification in accordance with MIL-STD-130. For civil agency procurements, the plates may be in accordance with the manufacturer's standard practice, provided they are legibly and permanently marked with the manufacturer's name or trademark of such known character that the source of manufacture of the machine may be readily determined, and contain the type or model and size of the machine and the electrical characteristics, as applicable.

3.10 Equipment manual.- The supplier shall furnish with each adsorber an equipment manual. Manual contents and additional distribution shall be as specified in the contract or order (see 6.2).

3.11 Workmanship.- The completely fabricated vapor adsorber shall be free from defects such as splits, punctures, tears, dents, creases, deteriorations, or malformations. The spacing and extent of welds, rivets, bolts, and screws shall be such as to insure fastening without bulging. There shall be no sharp edges, burrs, projections, or other defects which may cause personal injury.

3.11.1 Application of finish.- The finish applied to the end item shall be continuous, smooth, adherent, without discoloration or foreign material imbedded, and contain no sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, cracks, scratches, pours, pits, or orange peel. No rust, rough grinds, trim marks, or toolmarks shall show through the coating.

3.11.2 Welders and welding.-

3.11.2.1 Welders.- The welders, performing the welding on subassemblies, assemblies, and on the end item, shall be certified welders and have passed the qualification test as prescribed by either the "Standard Qualification Procedures of the American Welding Society" or "Welding Qualification of the American Society of Mechanical Engineers" code. The supplier shall furnish the Government with a list of names of his welders who are certified and have passed the test of either referenced codes and he shall certify that the welding of this equipment was performed by the welders included on the list.

3.11.2.2 Welding and brazing.- The surfaces of parts to be welded or brazed shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be continuous, sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and flux (when flux is used) shall be removed from the finished welds.

3.11.3 Soldering.- Soldering shall be complete and adherent, have all flux or residue removed, and contain no pin holes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

3.11.4 Bolts, nuts, screws, studs and other threaded fasteners.- Threaded fasteners shall not be broken, stripped, fractured, or loose.

3.11.5 Rivets.- Rivets shall be driven to completely fill the holes, with full size heads neatly finished and in full contact with the surface of the members.

3.11.6 Electrical wiring.- Wiring shall not be cut, abraded, or have excessive insulation stripped and shall be properly and tightly joined at terminals. Wiring shall have adequate slack to provide strain relief.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.- When a preproduction sample is required it shall be examined for defects listed in table I and tested as specified in 4.4.1, 4.4.2, and when required, 4.4.3 except the functional test of 4.4.2 shall not be required if requirements of the functional test waiver of 4.3.3.2 have been satisfied. The presence of any visual defect or failure to pass the applicable tests shall be cause for rejection of the preproduction sample.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified,or qualified in this specification or applicable purchase document.

4.3.2 In-process inspection.- Examination shall be made during the manufacturing process for coating of internal surfaces of the tank as specified in 3.6, when applicable,to establish that no deviation is made from indicated requirements. Whenever nonconformance is noted correction shall be made to affected items and process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

4.3.3 End item inspection.- The lot shall consist of all vapor adsorbers of the same size offered for inspection at one time. The sample unit shall be one completely fabricated vapor adsorber.

4.3.3.1 Visual examination.- The completely assembled end item shall be examined for defects in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I.- Classification of defects

Examine	Defect	Classification Major	Classification Minor
Finish	Not finished, plated, or coated (where required)	X	
	Finish not in accordance with manufacturer's standard practice		X
(Enamel or paint where applicable)	Area of no finish	X	
	Discoloration or foreign material imbedded in finish		X
	Not adherent, i.e., flakes off easily		X
	Rusted, scratched, or abraded area		X
	Sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, cracks, or peel		X
(Metallic finish where applicable)	Not smooth continuous coating, not tightly adherent, i.e., flaking, porous, pitted, or corroded area		X
	Uncoated area (base metal shows), blisters, lumps, drops, flux, or drips, scratches, abrasions, or nicks or foreign material imbedded in finish		X
	Any evidence of peeling or flash spots		X
	Rough grind or tool marks showing through coating		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Design	Any characteristic not in accordance with the specified requirements	X	
Construction	Any component or attachment missing or not specified type	X	
	Split, punctured, torn, dented, creased, deteriorated, or malformed	X	
	Component misplaced or not in proper alignment	X	
	Component loose		X
	Sharp burr, sliver, or sharp edge	X	
	Any functioning component that is inoperative or will not function as intended	X	
	Any functioning component that requires abnormal force to operate		X
	Component not connected or joined as specified	X	
	Valve, switch, gage, et cetera, not mounted in a manner that affords protection against accidental damage		X
	Any adjustable assembly that cannot be adjusted	X	
	Any assembly not properly adjusted		X
	Enclosure panels fitted over parts requiring frequent adjustment or servicing not removable	X	
	Any component not properly assembled or secured	X	
Welding and brazing (where applicable)	Incomplete, burn holes, fractured, or not fused	X	
	Slag inclusion, undercut, not smooth and uniform, or deposits of scale and flux not removed		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Soldering (where applicable)	Incomplete or not adherent	X	
	Not clean (flux or residue not removed) or contains pin holes		X
Bolts, nuts, screws, studs and other threaded fasteners	Broken, stripped, fractured, e.g., seal or packing nut stripped or loose	X	
	Threaded fasteners loose		X
Rivets (where applicable)	Broken, not peened, or not peened sufficiently	X	
	Rivets loose		X
Electrical equipment	Wire not as specified	X	
	Wiring cut or abraded, excessive insulation stripped, not properly joined, or loose at terminal	X	
	Not inclosed in specified conduit, incomplete, or not approved type (when applicable)	X	
	Adequate slack not provided, strain relief or support clip missing		X
Pipe, tubing, fittings, and valves	Improperly connected or installed, will not provide a seal where required	X	
	Threads stripped	X	
Gages and instruments	Not properly mounted or calibrated, inoperative or no means for adjustment (where required)	X	
Lubrication (where applicable)	Lubrication fitting not accessible for servicing (when applicable)		X
	Lubrication fitting defective		X
Identification marking	Missing, incomplete, illegible, not specified type or size, not in proper location, not affixed in prescribed manner		X
Equipment manuals	Missing, incomplete; illegible, not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

4.3.3.2 Testing of the end item.- When a preproduction sample is not required, the initial production unit shall be tested as specified in 4.4.2 and 4.4.3 (when applicable). Any nonconformance shall be cause for rejection of the lot. The functional test (see 4.4.2) shall be witnessed by a representative of the Government prior to acceptance, unless satisfactory evidence is produced that this item has satisfactorily passed this test either in the manufacturer's plant or in a commercial application. The Government reserves the right to check-test such items to determine validity of the evidence produced. The test outlined in 4.4.1 shall be performed on each production unit. Any nonconformance shall be cause for rejection of the unit.

4.3.3.3 Codes and standards compliance.- Proof of compliance with the requirements of 3.3.1, 3.3.2, 3.3.3, and 3.11.2.1 shall be available to the Government representative.

4.3.4 Examination of preparation for delivery.- Examination shall be made to determine that preservation, packaging, packing, and marking are in accordance with MIL-L-3153.

4.4 Tests.-

4.4.1 Operational tests.- The vapor adsorber shall be connected to the specified power source (see 3.6.1.1) and operationally tested for a sufficient time to determine compliance with the following requirements of 3.6. Any nonconformance shall constitute failure of this test.

(a) Assembly of components
(b) Leaks
(c) Undue vibration or noise
(d) Overheating of parts i.e. bearings
(e) Smooth operation of starting and stopping devices
(f) Structural failures

4.4.2 Functional test.- After complete installation to the cleaning unit, the vapor adsorber shall be connected to power, water and steam and operated for a sufficient time to determine compliance with operational and solvent recovery requirements of 3.6, and as established in all other paragraphs of this specification. The tests for solvent recovery shall be performed in accordance with the normal operating instructions provided in the manufacturer's equipment manual (see 3.10) for the applicable size vapor adsorber. Nonconformance to paragraph 3.6 and other applicable paragraphs constitute failure of this test.

4.4.3 Electromagnetic compatibility test.- When applicable, the preproduction sample or initial unit of production equipped for the reduction of radio interference in accordance with 3.7 shall be tested

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserives the right to witness tests performed by the supplier or his private testing organization. The supplier shall furnish the contracting officer, for approval, the interference control plan, the EMI/EMC test plan, and the electromagnetic test report required in MIL-STD-461. Upon approval of the test report by the contracting officer and provided all other requirements of the specification are met, the preproduction sample or the initial unit of production, as applicable, shall be used as a model for all production units.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking.- Preservation, packaging, packing and marking for level A, B, or C shall be in accordance with MIL-L-3153 (see 6.2).

6. NOTES

6.1 Intended use.- The vapor adsorbers covered by this specification are intended for use in fixed installations in conjunction with dry cleaning units using perchlorethylene as a solvent.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification
(b) Size required (see 1.2)
(c) First article.- When a preproduction sample is required (see 3.1)
(d) Electrical characteristics required (voltage, frequency, and number of phases) (see 3.6.1.1)
(e) When moisture and fungus resistance treatment is required (see 3.6.6)
(f) When electromagnetic compatibility is required (see 3.7)
(g) Finish, when other than specified (see 3.8)
(h) Manual contents and distribution (see 3.10)
(i) Selection of applicable levels of preservation and packaging and packing (see 5.1)

6.3 When drawings are required for installation purposes, request that successful bidder furnish drawings showing exact dimensions of the item, overall floor space requirement, location of hold down bolts, location of the inlet and cutlet lines, the point where electrical connection is to be made, and the electrical characteristics of the motor and other electrical equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

6.4 When the supplier is to furnish supervision of installation or demonstration service of items, the location, approximate date, the person or office to report to, and any accommodations or services to be supplied by the installation or agency, shall be stated.

6.5 Successful commercial operation.- Invitation for bids should specify that no item of equipment shall be acceptable unless the manufacturer has had equipment of approximately the same type and design as that specified operating successfully in a commercial institutional drycleaning establishment for at least one year. Equipment installed for test purposes in a manufacturer's plant or laboratory shall not come within the category of successful commercial operation.

6.6 Electromagnetic compatibility.- When applicable, the contracting officer should submit a copy of the interference control plan, the EMI/EMC test plan, and the test report required (see 4.4.3) to the Commanding General, U.S. Army Electronics Command, ATTN: AMSEL-RD-GF, Fort Monmouth, N. J., 07703 for approval.

6.7 Supersession data.- This specification includes the requirements of IP/DES-S-57-7 dated 24 November 1967.

Custodians:

Army - GL
Navy - YD
Air Force - 45

Preparing activity:

Army - GL

Project No. 3510-0176

Review activities:

Army - MD, EL
Air Force - 45, 85

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
Adsorber, Vapor, Synthetic Solvent Dry Cleaning Units MIL-A-43657

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.