INCH-POUND

MIL-B-43648B
9 February 1990
SUPERSEDING
MIL-B-43648A
10 September 1982

MILITARY SPECIFICATION

BAGS, TOOL, ENVELOPE TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers envelope type tool bags of various sizes.

1.2 Classification. The tool bags shall be of the following sizes, as specified (see 6.2).

Size 1	- 3 inches by 7-1/2 inches
Size 2	- 9-1/2 inches by 18 inches
Size 3	- 12 inches by 18 inches
Size 4	- 10-1/8 inches by 20-1/4 inches

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 5140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-203	- Paper, Kraft, Untreated
DDD-L-20	- Label: For Clothing, Equipage And Tentage (General Use)
PPP-B-636	- Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items: Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-3-59	- Bag Tool Envelope Type; Size 1
5-3-60	- Bag Tool Envelope Type; Size 2
5-3-61	- Bag Tool Envelope Type; Size 3
5-3-62	- Bag Tool Envelope Type, Size 4; Assembly

(Copies of drawings required by contractors are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shall be as specified on the applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirement of this specification.

3.3 Construction. The construction shall conform in all respects to the drawings listed in 2.1.2 and shall be as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

3.3.1 Stitches, seams and stitchings. All seams and stitching, except bartacking shall conform to FED-STD-751, type 301 with 8 to 10 stitches per inch.

3.3.1.1 Type 301 stitching. Ends of stitching shall be backstitched or overstitched not less than 1 inch (1/2 inch for box and box-x stitching) except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewed.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, except presewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box and box-x stitching) back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box and box-x stitching), continue over the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Bartacks. Bartacks shall be as specified on the applicable drawing and as follows:

Length ± 1/16	Width ± 1/32	Stitches per bartack
3/4 inch	1/8 inch	42

Bartacks shall be free from thread breaks and loose stitching.

3.3.1.3 Automatic stitching. Automatic machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.3.1.4 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

3.3.1.5 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.3.2 Setting of end clips. Webbing shall be inserted the full depth of the clip. The clips shall be securely attached without cutting the webbing and the webbing shall be flat at the point of entrance.

3.3.3 Setting of snap fasteners. A hole shall be prepunched to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

3.3.4 Setting of rivets. Rivets shall be securely set and neatly headed.

3.3.5 Marking. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on the applicable drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.3.6 Location marks. Location marks shall not be drilled except for locating snap fasteners. Printed markings shall not be more than 1/32 inch in width.

3.3.7 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the tool bag.

3.3.8 Replacement of defective components. During the spreading, cutting and manufacturing process, components of the tool bag having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

3.4 Workmanship. The tool bag shall conform to the quality of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the thread conforms to the requirement specified in 3.3.1.5.

4.4.2 In-process inspection. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, to the lot in-process, and to the operation. Parts which cannot be corrected shall be removed from production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

a. Dimensional examination of parts for which a cut length or size is specified to determine conformance with specified dimensions.

b. Visual examination of cut parts to remove parts containing material defects and damages (see 3.3.8).

c. Visual examination of subassemblies to determine if prepunched holes for receiving snap fasteners are in conformance with 3.3.3.

d. Visual examination of the steel stiffener used on the size 4 bag to determine if it is phosphate coated (see Drawing 5-3-62).

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tool bags. The sample unit shall be one tool bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet)	101	
Webbing or tape	Any hole, cut, tear, or smash	102	
	Not firmly and tightly woven	103	
	Edges frayed or scalloped	104	
	Multiple floats		201
	Abrasion mark, slub, or broken end or pick		202
	Cut ends of nylon webbing not fused		203
Hardware (general)	Broken or malformed failing to serve intended purpose, corroded area, burr, or sharp edge	105	
	Finish omitted or not as specified:		
	-on brass		204
	-on steel components	106	
	Area of partial or no finish		205
	Any required component improperly installed causing failure to serve intended purpose	107	
	Not assembled as specified	108	
	Size or type not as specified	109	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Rivets and caps	Not securely clinched so that they may become disengaged from body; or clinched excessively tight, cutting material	110	
End clips	Not securely clinched; webbing not flat at point of insertion; clinched excessively tight, cutting webbing		206
Snap fasteners	Any fastener not functioning properly i.e., fails to snap closed, provide a secure closure, or open freely	111	
	NOTE: The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material	112	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use		207
	Clinched loosely to the degree that components can be expected to become detached during use	113	
	NOTE: Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
	Incorrect style	114	
	More than three splits in eyelet or button barrels		208

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Slide fastener	Not functioning properly, failing to effect a secure closure, or to open freely	115	
NOTE:	The slide fastener shall be fully closed and opened to determine if fastener operates smoothly and provides a secure closure.		
	Slider jams or fails to interlock scoops	116	
	Thong omitted	117	
	Fastener tape cut or torn	118	
Open seam	1/2 inch or less		209
	More than 1/2 inch	119	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching		210
NOTE:	Raw edge not securely caught in stitching shall be classified as an open seam		
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type	120	
Bartacks	Any bartack omitted	121	
	Any bartack not as specified or not in specified location		211
	Loose stitching, incomplete or broken		212

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitch tension	Loose, resulting in a loose bobbin or top thread		213
	Excessively tight, resulting in puckering of material		214
Stitches per inch	One stitch less than minimum specified		215
	Two or more stitches less than minimum specified	122	
	One or more stitches in excess of maximum specified		216
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams, or in turning corners shall be classified as follows: (a) Within the minor defect classification - no defect. (b) Within the major defect classification - minor defect.		
Stitching ends	Not secured as specified		217
Thread breaks, skipped stitches or runoffs	Not overstitched as specified		218
	NOTE: Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Rows of stitching	Any row missing except on box and box-x stitching	123	
	On box and box-x stitching: -one row of stitching omitted		219
	-two or more rows of stitching omitted	124	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Components and assembly	Any component part omitted or not as specified or any required operation omitted (unless otherwise classified herein)	125	
	Needle chews	126	
	Any mend, darn, patch, or splice	127	
Binding	Loosely applied but not exposing raw edge of material		220
	Loosely applied exposing raw edge of material	128	
Marking	Omitted, illegible, incorrect, or misplaced		221
Location markings	Drilled	129	
	Printed marking more than 1/32 inch in width		222
Cleanness	Any spot or stain clearly noticeable		223
Thread ends	Not trimmed to 1/4 inch maximum length		224

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of tool bags. The sample unit shall be one tool bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as: incomplete closure of container flap, improper taping, loose strapping, or inadequate stapling. Bulged or distorted container.
Content	Weight of contents exceeds 65 pounds. Number of bags per bundle is more or less than specified. 1/

1/ For this defect, one bundle shall be examined from each shipping container in the sample.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Each bag shall be securely fastened with its respective closing device. Five bags of one size shall be alternately reversed end for end and stacked in a neat bundle. Each bundle shall be securely cross-tied with cotton tape or twine.

5.1.2 Commercial preservation. The tool bags shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Bags of one size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be uniformly arranged to form an even and balanced pack applicable to the particular size bag within the shipping container. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5. The weight of contents of each shipping container shall not exceed 65 pounds. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Bags of one size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conform-ing to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. The Level A unit packs shall be uniformly arranged to form an even and balanced pack applicable to the particular size bag within the shipping container. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III, as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Tool bags, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), tool bags, packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV, of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tool bags are used as components of various tool sets, kits or equipment to store and to protect the tools from damage and the elements.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Size required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Levels of preservation and packing (see 5.1 and 5.2).
f. Type and class of unit load required (see 5.2.1).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
h. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Container, utility
Pouch, satchel

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

Custodian:

Army - GL

User activities:

Army - AV
Navy - MC

Civil agency coordinating activity:

GSA - FSS

Preparing activity:

Army - GL

(Project 5140-0091)

☆U.S. GOVERNMENT PRINTING OFFICE: 1990 - 704-034/30374

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-43648B	BAGS, TOOL, ENVELOPE TYPE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.