INCH-POUND

MIL-B-43663C
23 July 1992
SUPERSEDING
MIL-B-43663B
8 August 1989

MILITARY SPECIFICATION

BAGS, TOOL, SATCHEL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers satchel tool bags fabricated from cotton and nylon duck cloth.

* 1.2 Classification. The tool bags shall be of the following types, as specified (see 6.2).

Type I	-	2 pockets, slide fastener closure, 2 nylon webbing handles
Type II	-	1 compartment, strap fastening closure, cotton webbing handgrip and shoulder strap
Type III	-	1 compartment, 2 nylon webbing handles, 2 leather retaining straps, masonite reinforced bottom, with rigid steel frame

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-50083	-	Bag, Plastic, Folded Garment
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items: Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams and Stitching

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-3-219	-	Bag, Tool, Satchel, Type I; Assembly and Sections
2-3-220	-	Type I Details
2-3-305	-	Bag, Tool, Satchel, Type II; Assembly, Complete
2-3-306	-	Type II Details
2-3-307	-	Type II Details and Sections
2-3-308	-	Type II Sections

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

2-3-525	-	Bag, Tool, Satchel, Type III; Assembly and Sections
2-3-526	-	Bag, Tool, Satchel, Type III; Layout and Sections
2-3-527	-	Lower Closure Frame
2-3-528	-	Upper Closure Frame
2-3-529	-	Press-Board

* (Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shall be as specified on the applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. The construction shall conform in all respects to the drawings listed in 2.1.2 and all the subsidiary drawings and parts lists pertaining thereto, and as specified therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

* 3.3.1 Stitches, seams, and stitching. All seams and stitching, for type I and II bags, shall be stitch type 301 with 8 to 10 stitches per inch, conforming to FED-STD-751. All seams and stitching, for the type III bag, shall conform to the requirements of the applicable drawings.

3.3.1.1 Type 301 stitching. Ends of all stitching, except box and box-x, shall be back stitched or overstitched 1 inch minimum except where ends are turned under or caught in other stitching. On box and box-x stitching, all ends shall be back stitched or overstitched 1/2 inch minimum. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, except presewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box and box-x stitching) back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch for box and box-x stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for box and box-x stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be back stitched

3.3.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three or more tying, overlapping or back stitches are used to secure the ends of stitching.

3.3.1.3 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a maximum length of 1/4 inch.

3.3.1.4 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.2).

3.3.2 Setting of end clips. Webbing shall be inserted the full depth of the clip. The clips shall be securely attached without cutting the webbing and the webbing shall be flat at the point of entrance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

3.3.3 Setting of rivets. Rivets shall be securely set and neatly headed.

3.3.4 Marking. The identification marking shall be applied in the location shown on the applicable drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on the applicable drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.3.5 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32 inch in width.

3.3.6 Repairs. Except as otherwise specified, repairs such as mends, darns, patches or splices shall not be made to the tool bag.

3.3.7 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

* 3.4 Workmanship. The finished tool bag shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to the requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect test such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. Any nonconformance shall be cause for the rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that all materials conform to the requirements specified on the drawings.

* 4.4.2 In-process inspection. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, to the lot in process, and to the operation. Parts which cannot be corrected shall be removed from production.

a. Visual and dimensional examinations of the cut parts to determine that they are properly cut with respect to size and material requirements specified on drawings, that location marks and notches on the parts are located correctly, and that parts containing material defects and damages have been removed (see 3.3.7).

b. Visual examination to determine that the corner reinforcements (type II bag) are given a phosphate treated zinc plate prior to enameling.

c. Visual examination to determine that the handle reinforcement (type II bag) is given a zinc plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

d. Visual examination to determine if the thread has been lubricated by any means for compliance with 3.3.1.4.

* 4.4.3 End item visual examination. The end items shall be examined for the applicable defects listed in table I. The lot size shall be expressed in units of tool bags. The sample unit shall be one tool bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be: for type I tool bags, 6.5 for major defects and 15 for total (major and minor combined) defects; for type II and type III tool bags, an AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet)	101	
Webbing or tape	Any hole, cut, tear, or smash	102	
	Not firmly and tightly woven	103	
	Edges frayed or scalloped	104	
	Multiple floats		201
	Abrasion mark, slub, or broken end or pick		202
	Cut ends of nylon webbing not fused		203
Hardware (general)	Broken or malformed failing to serve intended purpose, corroded area, burr, or sharp edge	105	
	Finished omitted or not as specified:		
	- on brass		204
	- on steel components	106	
	Area of partial or no finish		205
	Any required component improperly installed causing failure to serve intended purpose	107	
	Not assembled as specified	108	
	Size or type not as specified	109	
	Rivets and caps not securely clinched so that they may become disengaged from body; or clinched excessively tight, cutting material	110	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Hardware (general) (cont'd)	End clips not securely clinched; webbing not flat at point of insertion; clinched excessively tight, cutting webbing		206
Slide fastener	Not functioning properly, failing to effect a secure closure, or to open freely and fully	111	
	NOTE: The slide fastener shall be fully closed and opened to determine if the fastener operates smoothly and provides a secure closure.		
	Not specified type or size	112	
	Any portion of fastener broken, bent, missing or not aligned	113	
	Slider jams or fails to interlock scoops	114	
	Thong omitted	115	
	Fastener tape cut or torn	116	
Seams and stitching:			
Open seam	1/2 inch or less		207
	More than 1/2 inch	117	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching		208
	NOTE: Raw edge not securely caught in stitching shall be classified as an open seam.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Seams and stitching: (cont'd)			
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type	118	
Stitch tension	Loose, resulting in a loose bobbin or top thread		209
	Excessively tight, resulting in puckering of material		210
Stitches per inch	One stitch less than minimum specified		211
	Two or more stitches less than the minimum specified	119	
	One or more stitches in excess of the maximum specified		212
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams, or in turning corners shall be classified as follows: (a) Within the minor defect classification - no defect (b) Within the major defect classification - minor defect		
Stitching ends	Not secured as specified		213
Thread breaks, skipped stitches or runoffs	Not overstitched as specified		214
	NOTE: Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as an open seam.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Seams and stitching: (cont'd)			
Rows of stitching	Any row missing except on box and box-x stitching	120	
	On box and box-x stitching:		
	- One row of stitching omitted		215
	- Two or more rows of stitching omitted	121	
Components and assembly	Any component part omitted or not as specified or any operation omitted or not as specified unless otherwise classified herein)	122	
	Any needle chew	123	
	Any mend, darn, patch, splice, or other unauthorized repair	124	
Binding	Loosely applied but not exposing raw edge of material		216
	Loosely applied exposing raw edge of material	125	
Marking	Omitted, illegible, incorrect, or misplaced		217
Location markings	Drilled	126	
	Printed marking more than 1/32 inch in width or not covered by component part		218
Cleanness	Any spot or stain clearly noticeable		219
Thread ends	Not trimmed to 1/4 inch maximum length		220

* 4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of tool bags. The sample unit shall be one tool bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

* 4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Weight of contents exceeds 65 pounds

* 4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

5.1.1.1 Type I bag. Each bag, with fastener closed, shall have one side and the top pushed inward lengthwise against the base and the opposite side. The latter side is to be folded down with the handles inside the resulting flat-folded bag. The two ends of the flattened bag should form protruding angles with no unnecessary distortions along the slide fastener length. The knocked-down bag shall measure approximately 25 by 7-1/4 by 1 inches. Each bag shall be unit packed in a plastic bag conforming to A-A-50083.

5.1.1.2 Type II bag. Each bag with the carrying strap coiled and placed in the bag, shall have the closing straps securely fastened. Each bag shall be unit packed in a plastic bag conforming to A-A-50083.

5.1.1.3 Type III. Each bag, with straps fastened, shall have the handle and closure frame portion collapsed over the base of the bag. The width of the flattened bag shall be 8-3/4 inches. Each folded bag shall be unit packed in a close-fitting and end-opening fiberboard box conforming to style RSC, type CF (variety SW), class domestic, grade 200 of PPP-B-636. Each box shall be closed in accordance with method IV of the appendix of PPP-B-636.

5.1.2 Commercial preservation. Each tool bag shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Types I and II bags. Tool bags of one type only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The weight of the contents shall not exceed 65 pounds. Each box shall be closed, waterproofed and reinforced in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.1.2 Type III bags. Tool bags, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container as specified in 5.1.1.1, except the box liner shall not be required. Each shipping container shall be closed, waterproofed and reinforced as specified in 5.1.1.1. The weight of contents of each shipping container shall not exceed 65 pounds. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing.

5.2.2.1 Type I and II bags. Tool bags of one type only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW), or SF, class

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

domestic, grade 275 of PPP-B-636. The weight of the contents shall not exceed 65 pounds. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.2 Type III bag. Tool bags, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container as specified in 5.2.2.1, except the box liner shall not be required. Closure and weight of contents of each shipping container shall be as specified in 5.2.2.1.

5.2.2.3 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Tool bags, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), bags, packed as specified in 5.2.2 and 5.2.3 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tool bags are intended to be used as components of various tool sets, kits or equipment, to store and to protect the tools from damage and the elements.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Type required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Levels of preservation and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

f. Type and class of unit load required (see 5.2.1.1 and 5.2.1.2).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.3).
h. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Container, fabric
Pouch
Sack

6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this specification based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activity:

GSA - FSS

User activities:

Army - AV
Navy - MC

Preparing activity:

Army - GL

(Project 5140-0107)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-43663C	1992 July 23

3. DOCUMENT TITLE

BAGS, TOOL, SATCHEL

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:58Z
Check the source to verify that this is the current version before use.