MIL-F-43640(GL)
8 May 1969

MILITARY SPECIFICATION

FOOD CONTAINERS, DELIVERY AND STORAGE: ALUMINUM

1. SCOPE

1.1 Scope.- This specification covers two types of aluminum food containers.

1.2 Classification.- The aluminum food containers shall be of the following types as specified (see 6.2).

Type I - Platter (30 x 12-1/2 x 3/4 inches)

Type II - Utility (26 x 15-1/2 x 8 inches)

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 - Box, Fiberboard.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.

MILITARY

MIL-A-8625 - Anodic Coatings, For Aluminum Alloys.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized and Containerized Unit Loads 40" x 48" Pallets, Skids, Runners, or Pallet-Type Base.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:54Z
Check the source to verify that this is the current version before use.

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal, shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

Specification B 209-68 -Aluminum- Alloy Sheet and Plate.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19106).

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment.

Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, P. O. Box 1468, Ann Arbor, Michigan 48106).

NATIONAL CLASSIFICATION BOARD

National Motor Freight Classification.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N.W., Washington, D.C. 20036.)

UNIFORM CLASSIFICATION BOARD

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies).

3. REQUIREMENTS

3.1 First article.- Unless otherwise specified (see 6.2), before production is commenced, a sample platter or utility container covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:54Z
Check the source to verify that this is the current version before use.

3.2 Standard product.- The food containers delivered under this specification shall be the manufacturer's standard commercially current product, except for any changes necessary to comply with specification requirements.

3.3 NSF Standard.- Food containers shall conform to the applicable requirements of NSF Standard No. 2.

3.3.1 NSF Certification.- The supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the food containers he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 2 as follows:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished food containers shall be submitted prior to approval of the preproduction sample, if one is submitted, or prior to approval of the first shipment, or

(2) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the food containers are being procured, indicating that the food containers have been tested and conform to NSF Standard No. 2 shall be submitted prior to the approval of the preproduction sample, if one is submitted, or prior to commencing production.

3.4 Materials.- Materials not definitely specified shall be of the quality normally used by the manufacturer for his food containers provided the completed item complies with all provisions of this specification.

3.4.1 Aluminum sheet.- Aluminum sheet shall conform to alloy 5005-H32 or 5050-0 of ASTM B-209-68, as specified herein.

3.5 Design and construction.- The aluminum platter and utility container shall be designed with a half round open bead not less than 9/16 inch in diameter and as illustrated in figure 1. The bead shall be used for carrying or supporting the platter or utility container. The bead may be flanged-out at the ends to facilitate handling and shall be not less than 11/16 inch wide.

3.5.1 Platter.- The platter shall be formed or drawn seamless from a single piece of 5005 aluminum alloy specified in 3.4.1. The platter shall be 30 inches long by 12-1/2 inches wide by 3/4 inches deep with a tolerance of plus or minus 1/16 inch applicable to these dimensions. The metal thickness shall be minimum 0.050 inch prior to fabrication. The bottom of the platter shall be reinforced by embossing or by a stiffening member or by any other means. The platter shall not deflect more than 1/4 inch or be permanently deformed when tested as specified in 4.5.2.

3.5.2 Utility container.- The container shall be formed or drawn seamless from a single piece of 5050 aluminum alloy specified in 3.4.1. The container shall be 26 inches long by 15-1/2 inches wide by 8 inches deep with a tolerance of 1/16 inch applicable to these dimensions. The metal thickness shall be minimum 0.050 inch prior to fabrication. The container sides, ends, and bottom

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:54Z
Check the source to verify that this is the current version before use.

shall be reinforced by embossing or stiffening or by any other means used by the manufacturer. The container shall have tapered ends and sides for nesting. The container shall nest without binding and shall not be scratched on the exterior surface of the container being removed and the interior surface of the remaining container when tested as specified in 4.5.1. The container loaded with 75 pounds shall not deflect more than 1/4 inch or be permanently deformed when tested as specified in 4.5.2.

3.6 Finish.- The food containers shall be anodized in accordance with type II, class 1 of MIL-A-8625. There shall be no evidence of discoloration, pits, or stains.

3.7 Marking for identification.- The food containers shall be permanently marked with the manufacturer's name, trade name, or trademark of such known character as to be readily identifiable with the manufacturer. The surface opposite the markings shall show no signs of penetration or unevenness nor shall the marking cause distortion of any part of the item where marked.

3.8 Workmanship.- Kinks and bends shall be removed from sheet metal prior to fabrication of the food containers. The platter and utility container shall be clean and not contain any rough or sharp edges, burrs, slivers, or scratches, and shall be free from rough grind, die, or trimming marks. The finished items shall not be fractured, buckled, dented, punctured, or malformed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.- When a preproduction sample is required it shall be examined for defects listed in table I, dimensions specified, and tested in accordance with 4.5.1 and 4.5.2. Failure to pass the tests in 4.5.1 and 4.5.2 shall be cause for rejection of the preproduction sample. The presence of any defects listed in table I or any dimension not within specified requirements shall be cause for rejection of the preproduction sample.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:54Z
Check the source to verify that this is the current version before use.

4.3.2 End item inspection.- The inspection lot shall consist of all platters or utility containers offered for inspection at one time. The sample unit shall be one completely fabricated platter or utility container.

4.3.2.1 Visual examination.- Examination shall be made of the food container for the defects in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I.- Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not as specified.		X
	Evidence of discoloration, pits, or stains.	X	
Construction and workmanship (general)	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks.	X	
	Any component fractured, buckled, kinked, dented, punctured, or malformed.	X	
	Not one piece construction.	X	
	Half round open bead not provided.	X	
	Not fabricated of aluminum.	X	
Utility container	Not reinforced at the sides, ends, and bottom.	X	
Platter	Not reinforced at bottom.	X	
Marking	Missing, incomplete, or illegible.		X
	Surface opposite marking shows penetration or unevenness (when applicable).		X

4.3.2.2 Dimensional examination.- Inspection shall be made of the end items to determine compliance with dimensions specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects, expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end item.- The end items shall be tested as specified in 4.5.1 and 4.5.2. The inspection level shall be S-2 with an AOL of 6.5 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:54Z
Check the source to verify that this is the current version before use.

4.3.3 Examination of preparation for delivery.- An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored as specified in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

TABLE II.- Examination of preparation for delivery

Examine	Defect
Markings (exterior and interior containers)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Contents (exterior and interior containers)	More or less than required.

4.3.3.1 Examination of shipping containers.- When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with PPP-B-636.

4.4 Standard compliance.- Proof of compliance with NSF requirements of 3.3 shall be made available to the Government representative.

4.5 Tests.-

4.5.1 Nesting test.- Two empty utility containers shall be nested for storage. The top nested container shall be listed by the ends or sides for removal. The exterior of the container being removed and the interior of the remaining container shall be examined to determine compliance with 3.5.2. Inability of the utility container to meet the nesting and scratching requirements specified shall constitute failure of the test.

4.5.2 Deformation test.- The platter or utility container shall be uniformly loaded with a minimum of 75 pounds and supported at the sides, then ends, for a period of not less than 10 minutes each. Items shall be examined for deflection and deformation to determine compliance with requirements of 3.5.1 and 3.5.2. Inability of the platter or utility container to meet the deflection and deformation requirements specified shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:54Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.- Twelve platters or six utility containers shall be nested and packaged in a snug-fitting fiberboard box conforming to style optional, type CF, variety SW, or type SF, class domestic of PPP-B-636. Prior to packaging, the platters shall be slip-sheeted with wax paper. Box closure shall be in accordance with the appendix of PPP-B-636.

5.1.2 Level C.- The food containers shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Twenty-four platters or twelve utility containers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636.

5.2.2 Level B.- Twenty-four platters or twelve utility containers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to Style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2) the shipping container shall be a grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix thereto. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Level C.- Food containers, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Rules, as applicable.

5.3 Palletization.- Unless otherwise specified (see 6.2) food containers packed as specified shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.4 Marking.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:54Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.- The utility container and platter covered by this specification are intended for use in transporting and storage of meat, poultry, fish, and vegetables in commissary stores. The utility container is intended for use with the sizes 1 and 2 racks, delivery and storage covered by MIL-R-43567 and the platter is intended for use with all sizes of racks in MIL-R-43567.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) First article.- When a preproduction sample is not required (see 3.1).
(d) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard is required for level B packing (see 5.2.2.1).
(f) When palletization is not required (see 5.3).

Custodian:

Army - GL

Review activity:

Army - MD

Preparing activity:

Army - GL

Project No. 7330-A353


Source: https://assist.dla.mil -- Downloaded: 202610-21T21:54Z
Check the source to verify that this is the current version before use.

FOOD CONTAINERS, ALUMINUM

FIGURE - 1



PLATTER, MEAT AND PRODUCE



UTILITY LUG

Source: https://assist.dla.mil -- Downloaded: 202640-21T21:54Z
Check the source to verify that this is the current version before use.