MIL-T-43660

8 August 1969
(see 6.-)

MILITARY SPECIFICATION

TAGGING MACHINES, LAUNDRY MARKING

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers machines for attaching thermoplastic backed laundry marking tags.

1.2 Classification.- Tagging machines shall be of the following types, as specified (see 6.2):

Type I - Manually operated.

Class 1 - For table mounting.

Type II - Air-operated.

Class 1 - For table mounting.

Class 2 - Pedestal mounted.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601 - Box, Wood, Cleated Plywood.
PPP-B-621 - Box, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, and Waterproofing; With Appropriate Test Methods.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal, shall apply.

UNDERWRITERS' LABORATORIES, INC. (UL)

Standard No. 508 - Industrial Control Equipment (1967).

Electrical Construction Materials List.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, Illinois 60611; 1285 Walt Whitman Road, Melville, Long Island, New York 11746; 1655 Scott Blvd., Santa Clara, California 95050.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Standard No. 70 - National Electrical Code (1968)

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, Massachusetts 02110.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.,

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Association, Attn: Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 First article.- Unless otherwise specified (see 6.2), before production is commenced, a sample of the finished tagging machine shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product.- The laundry tagging machines covered by this specification shall be regular commercial products of the manufacturer except for any changes necessary to comply with this specification.

3.3 Codes and standards.-

3.3.1 NFPA.- The electrical wiring shall conform to NFPA Standard No. 70 for general use.

3.3.2 UL.- Electrical control equipment shall conform to UL Standard No. 508. Other electrical components shall be UL approved under label service or re-examination service for use in nonhazardous locations.

3.3.3 Certification.- Prior to approval of the preproduction sample, or if none is submitted, prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative, that the tagging machine wiring and components he proposes to furnish meet the requirements specified in 3.3.1 and 3.3.2.

3.3.3.1 NFPA.- Acceptable evidence of meeting requirements of 3.3.1 shall be the manufacturer's certified statement that the tagging machine electrical wiring conforms to NFPA Standard No. 70.

3.3.3.2 UL.- Acceptable evidence of meeting requirements of 3.3.2 shall be the UL label on the components; a UL listing of the electrical components

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

in the Electrical Construction Materials List; or certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that the electrical components conform to applicable UL standards.

3.4 Materials.- Materials not definitely specified shall be of the quality normally used by the manufacturer for tag attaching thermosetting machines provided the completed item complies with all provisions of this specification.

3.5 Design.- The type I and II laundry tagging machines shall be designed to attach precut thermoplastic backed tags (see 6.3) measuring approximately 5/8 inch by 2-1/4 inches to natural and synthetic garments by heat and pressure, and the tags shall be capable of being removed from garments without the use of solvents (see 4.4.1). The heating head shall be designed to maintain a temperature between 270 Fahrenheit (F.) and 280 F. (see 4.4.1). The machine shall be controlled by a master "on" and "off" switch, thermostat, and timer. A pilot light shall be provided to indicate when the head is being heated. A ready-light may be furnished to indicate when the operating temperature is reached. The timer shall provide for the heat sealing cycle and shall release the heating head upon completion of the cycle. The heat sealing cycle shall average 10 seconds and shall be manually adjustable from 0.0 seconds to 30 seconds. The heating head operating assembly shall operate without binding at operating temperature (see 4.4.1).

3.6 Construction.-

3.6.1 Heating head platen.- Unless otherwise specified (see 6.2) the heating head shall be 1-3/4 inches ± 1/2 inch wide by 3-1/4 inches ± 1/2 inch long. The stationary platen shall be made of heat-resistant materials. The heating head and platen shall be provided with a polytetrafluoethylene cover or equal. The pressure between the heating head and platen shall be 10 pounds per square inch (psi), with means for adjusting the pressure within ± 10 percent.

3.6.2 Type I, class 1.- The type I, class 1 tagging machine shall be a manually operated machine suitable for table mounting.

3.6.3 Type II, class 1 and 2.- The type II, class 1 and 2 machines shall be air-operated. Class 1 shall be for table mounting and class 2 shall be pedestal mounted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

3.6.3.1 Operation.- The type II, class 1 and 2 machines shall be air-operated either by hand controls or by foot pedal. The operation shall be fully automatic through a cycle of closing, pressure application, timing, and reopening.

3.6.3.2 Air-operated system.- Type II machines shall have the necessary pipe, tubing, fittings, cylinder, valves, air filter, and water separator device assembled to comply with accepted plumbing practices. Pressure control shall be adjustable and a direct reading air-pressure gauge shall be furnished. In addition, the inlet air supply connection shall be furnished with a manually operated shutoff valve. The air line and cylinder shall be designed to withstand a minimum of 80 psig without leakage when tested as specified in 4.4.2.

3.6.4 Accessories.- The machines shall be provided with a metal holder for boxed tags, a garment holding or work platform device, and a means for checking operating temperature. The type II machine shall be furnished with a safety guard around the garment holding or work platform area.

3.6.5 Electric cord and plug.- The machine shall be provided with a 3-wire cord and attachment plug. The cord shall be a minimum of 7 feet long.

3.7 Electrical characteristics.- Unless otherwise specified (see 6.2), the machine shall be for use on a 120 volt, single-phase, 60 hertz, alternating current, power source.

3.8 Lubrication.- Provision shall be made for the lubrication of all moving parts. Instructions for lubricating shall be furnished in the equipment manual specified in 3.9.

3.9 Equipment manuals.- The supplier shall furnish with each laundry tagging machine, an equipment manual. Manual contents and additional distribution shall be as specified in the contract or order (see 6.2).

3.10 Finish.- The laundry tagging machine shall be finished in accordance with the manufacturer's commercial practice, except the color of painted parts shall correspond to Number 24172 of FED-STD-595.

3.11 Marking for identification.- The laundry tagging machine shall be marked for identification in accordance with the manufacturer's commercial practice.

3.12 Workmanship.- The completely fabricated item shall be free from defects such as fractures, splits, punctures, tears, dents, creases, bows, miscasts, or malformations. There shall be no sharp edges, burrs, or slivers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

3.12.1 Application of finish.- The finish applied to the end item shall be continuous, smooth, adherent, have no imbedded foreign matter and contain no sags, runs, drips, creeps, laps, bubbles, or streaks. No rust or toolmarks shall show through the coating.

3.12.2 Threaded fasteners.- Threaded fasteners shall not be broken, stripped, fractured, or loose.

3.12.3 Rivets.- Rivets shall be driven to completely fill the holes, with full size heads neatly finished and in full contact with the surface of the members, and shall not be loose.

3.12.4 Electrical wiring.- Wiring shall not be cut, abraded or have excessive insulation stripped, and shall be securely joined at terminals. Wiring shall have adequate slack to provide strain relief.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.- When a preproduction sample is required, it shall be examined for defects in table I, specified dimensions, and tested as specified in 4.4.1, and when applicable, 4.4.2. The presence of any visual defect, any dimension not within the specified requirements, or failure to pass the tests shall be cause for rejection of the preproduction sample.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection.- In accordance with 4.1, above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

4.3.2 End item inspection.- A lot shall consist of all laundry tagging machines of one type and class offered for inspection at one time. The sample unit shall be one completely fabricated laundry tagging machine.

4.3.2.1 Visual examination.- The completely assembled end item shall be visually examined for defects classified in table I. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I.- Visual examination

Examine	Defect	Classification Major	Classification Minor
Finish	Not color specified.		X
Design and construction	Not provided with means for checking operating temperature.	X	
	Metal holder for boxed tags missing.		X
	Garment holding devices or work platform missing.	X	
	Heating head or platen cover missing or not as specified.	X	
	Heating head temperature not adjustable.	X	
	Pressure control not adjustable.	X	
	Operating assembly of heating head not adjustable.	X	
	Safety guard missing.	X	
	Operating assembly of heating head binds.	X	
	Operating assembly not properly adjusted.		X
Workmanship	Fracture, split, puncture, tear, dent, crease, bow, miscast, malformation, sharp edge, burr, or sliver.	X	
Application of finish	Not continuous, smooth, or adherent, evidence of sags, runs, drips, creeps, laps, bubbles, streaks or rust.	X	
	Toolmark shows through coating.		X
Threaded fasteners	Broken, stripped, fractured or loose.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

TABLE I.- Visual examination (cont'd)

Examine	Defect	Classification Major	Classification Minor
Electrical equipment	Wiring cut, abraded, not properly joined.	X	
	Adequate slack not provided or insulation excessively stripped.	X	
Lubrication	Provisions for lubrication missing.	X	
Identification marking	Missing, illegible.		X
Equipment manual	Missing, incomplete, illegible.	X	

4.3.2.2 Dimensional examination.- Inspection shall be made of the end item for compliance with dimensions specified. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.3.2.3 Testing of end item.- When a preproduction sample is not required, the first unit of production shall be tested as specified in 4.4.1. Any nonconformance shall be cause for rejection of the lot. The test in 4.4.1, and when applicable, 4.4.2, shall be performed on each lot offered for acceptance. The inspection level shall be S-2 with an AQL of 2.5 expressed in terms of defects per hundred units.

4.3.3 Code and standard compliance.- Proof of compliance with the requirements of 3.3 shall be made available to the Government representative.

4.3.4 Examination of preparation for delivery.- An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. The defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

TABLE II.- Examination of preparation for delivery

Examine	Defect
Marking	Missing; incorrect, illegible; of improper size, location, sequence or method of application.
Material	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components, such as blocking and bracing inadequate.

4.3.4.1 Examination for closure and strapping of shipping containers.- Examination for defects in closure and strapping of shipping containers shall be in accordance with the appendix of the applicable container specification.

4.4 Test.-

4.4.1 Operation and performance test.- The laundry tagging machine shall be electrically energized in a location having an ambient temperature of 70 F. plus or minus 2 F. The pilot light shall be checked to determine it lights while the head is heating and goes out when operating temperature has been reached. When a ready light is provided it shall indicate when the operating temperature has been reached as specified in 3.5. The temperature of the sealing surface of the heating head shall be checked at three points to determine compliance with 3.5, and any temperature not within the specified range shall constitute failure of this test. The machine shall be operated for 5 minutes using thermoplastic backed laundry tags on natural and synthetic garments to determine compliance with 3.5 Any nonconformance with the requirements of 3.5 shall constitute failure of these tests.

4.4.2 Air pressure test.- The air line and cylinder shall be tested with 80 pounds per square inch gauge air pressure. The pressure shall be maintained a minimum of ten minutes to determine that no leaks are present. Any nonconformance with the requirements of 3.6.3.2 shall constitute failure of the test.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.- Parts free to move on each tagging machine shall be secured to prevent movement while in transit. The equipment manual shall be placed in a paper or plastic envelope and secured to the machine.

5.1.2 Level C.- Tagging machines shall be packaged to afford adequate protection against damage during shipment from the supply source to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Each tagging machine, packaged as specified in 5.1, shall be packed in a fiberboard, nailed wood or cleated plywood shipping container, conforming to grade V2s, style RSC of PPP-B-636, except that weight and dimensional limitations shall not be exceeded; class 2, style 2 or 4 of PPP-B-621; or overseas type of PPP-B-601. For fiberboard shipping containers, voids within the container shall be filled and the contents shall be secured by means of fiberboard inserts; and the container waterproofed by means of tape in accordance with the appendix of PPP-B-636. For all other containers, contents shall be secured by anchoring or cushioned and blocked and braced with lumber; and waterproofed in accordance with MIL-STD-1186. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

5.2.2 Level B.- Each tagging machine, packaged as specified in 5.1, shall be packed as specified in 5.2.1 except that shipping containers shall conform to type CF (variety SW) or SF, class domestic, style RSC of PPP-B-636; class 1, style 2 or 4 of PPP-B-621; or domestic type, style A or B of PPP-B-601; and waterproofing shall not be required.

5.2.3 Level C.- Tagging machines, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification rules or National Motor Freight Classification rules, as applicable.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The tagging machines covered by this specification are intended for use in attaching thermoplastic backed tags to garments in laundries.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and class of machine required (see 1.2).
(c) First article.- When a preproduction sample is not required (see 3.2).
(d) When size of platen and heating head is other than specified (see 3.6.1).
(e) Electrical requirements, if other than specified (see 3.7).
(f) Manual contents and distribution (see 3.9).
(g) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Tags specified in 3.5 should be the manufacturer's standard tags and should be furnished by the supplier of the tagging machine for verification testing when required.

6.4 Supersession data.- This specification includes the requirements of Interim Purchase Description, IP/DES S-55-7 dated 14 November 1967.

Custodians:

Army - GL
Navy - YD

Review activities:

Army - EL

User activities:

Army - SM
Navy - MC

Preparing activity:

Army - GL

Project No. 3510-0177

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER

2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional

b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional

c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional

8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES (Mr. D. Juppino)
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:57Z
Check the source to verify that this is the current version before use.