6 January 1977
SUPERSEDING
MIL-W-43644(GL)
23 May 1969

MILITARY SPECIFICATION

WRAPPING, CONVEYING, WEIGHING AND LABELING SYSTEMS, MEAT AND PRODUCE; AUTOMATIC, SHRINK FILM AND STRETCH FILM

This specification is approved for use by the Natick Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers electrically operated, fully automatic, stretch film and shrink film wrapping, conveying, weighing and labeling systems, for meat and produce.

1.2 Classification. The stretch and shrink film wrapping, conveying, weighing and labeling systems covered by this specification shall be of the following systems and speeds as specified (see 6.2).

System II - Shrink film

High speed	-	Not less than 30 packages per minute
Medium speed	-	Not less than 22 packages per minute

System III - Stretch film

High speed	-	Not less than 40 packages per minute
Medium speed	-	Not less than 28 packages per minute

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
GG-M-1807	-	Motor, Alternating Current, Fractional and Integral Horsepower (500 Horsepower and Smaller)
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-650	-	Crates, Wood, Open and Covered
PPP-T-60	-	Tape: Packaging, Waterproof

MILITARY

MIL-C-104	-	Crates, Wood: Lumber and Plywood Sheathed, Nailed and Bolted
MIL-P-116	-	Preservation-Packaging, Methods Of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-W-40614	-	Wrapping Machines, Meat and Produce, Automatic Shrink Film
MIL-S-43147	-	Scale Systems, Prepackaged Food

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

UNDERWRITERS LABORATORIES INC.

Electrical Appliance and Utilization Equipment List

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 333 Pfingsten Road, Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, LI, NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050 or 2602 Tampa East Blvd., Tampa, FL 33619.)

NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION (NEMA)

Standard ICS - Industrial Controls and Systems

(Application for copies should be addressed to the National Electrical Manufacturer's Association, 155 East 44th Street, NY, NY 10017.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Standard No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies shall be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies shall be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2) the contractor shall furnish a sample of the required wrapping, conveying, weighing and labeling system for first article inspection and approval (see 4.2 and 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

* 3.2 Standard product. The automatic wrapping, conveying, weighing and labeling system shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features to comply with the requirements of this specification. Modification to add features shall not incorporate different parts unless such parts are used on other commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable in all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

* 3.3 Code and standards.

* 3.3.1 NFPA. The automatic wrapping, conveying, weighing and labeling system shall be wired to be employed in accordance with NFPA Standard No. 70.

* 3.3.2 UL. The applicable components of the units shall conform to applicable Underwriters Laboratory (UL), standards.

3.3.3 NEMA. Motor controllers, switches, relays and time delays shall conform to performance requirements of NEMA Standards Publication No. ICS.

* 3.3.4 Certification. Prior to approval of the first article or if none is submitted, prior to approval of this first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the automatic wrapping, conveying, weighing and labeling system he proposes to furnish meet the requirements specified in 3.3.1, 3.3.2 and 3.3.3.

* 3.3.4.1 NFPA. Acceptable evidence of meeting requirements of 3.3.1 shall be the manufacturer's certified statement that the automatic wrapping, conveying, weighing and labeling system are wired to be employed in accordance with NFPA Standard No. 70.

* 3.3.4.2 UL. Acceptable evidence of meeting requirements of 3.3.2 shall be the UL label, a listing in the UL "Electrical Material List" or certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that the wiring, fittings and conduit conform to the applicable UL standards.

* 3.3.4.3 NEMA. Acceptable evidence of meeting the requirements of 3.3.3 shall be the manufacturer's certified statement that the motor controllers, switches, relays and time delays, conform to NEMA Standard Publication No. ICS. A tag or label attached to these items stating these components conform to this standard is acceptable evidence.

3.4 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer in his commercial wrapping, conveying, weighing and labeling system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

3.5 Design and construction. Each wrapping, conveying, weighing and labeling system shall be an integrated unit, fully automatic, and electrically operated. When specified (see 6.2), the unit shall be equipped with a portable package accumulator bin. The overall dimensions of the systems shall be not greater than the following:

Shrink film system II - 209 inches wide, 42 inches deep and 72 inches high

Stretch film system III - 258 inches wide, 96 inches deep and 72 inches high

3.5.1 System II.

3.5.1.1 System II, high speed. The completely assembled integrated system II, high speed unit shall wrap, convey, weigh and label not less than 30 packages per minute for wrapping meat or produce without binding, failure, or malfunction when tested as specified in 4.4.1.

3.5.1.2 System II, medium speed. The completely assembled integrated system II, medium speed unit shall wrap, convey, weigh and label not less than 22 packages per minute for wrapping meat or produce without binding, failure or malfunction when tested as specified in 4.4.1.

3.5.1.3 System II, wrapping machine. The system II, wrapping machine shall conform to MIL-W-40614.

3.5.1.4 System II, package sizes. The system II, package sizes shall conform to the requirements of MIL-W-40614.

3.5.1.5 System II, scale. The system II, scale system shall conform to type I, style A of MIL-S-43147. The scale system shall handle not less than 30 packages per minute, when tested in conjunction with a high speed wrapping machine conforming to MIL-W-40614 and not less than 22 packages per minute, when tested in conjunction with a medium speed wrapping machine conforming to MIL-W-40614.

3.5.2 System III.

3.5.2.1 System III, high speed. The completely assembled integrated system III, high speed unit shall wrap, convey, weigh and label not less than 40 packages per minute for wrapping meat or produce without binding, failure or malfunction when tested as specified in 4.4.1.

3.5.2.2 System III, medium speed. The completely assembled integrated system III, medium speed unit shall wrap, convey, weigh and label not less than 22 packages per minute for wrapping meat or produce without binding, failure or malfunction when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

3.5.2.3 System III, wrapping machine. The system III wrapping machines shall be capable of automatically feeding, measuring, cutting, wrapping and heat-sealing plastic on each package without the use of a shrink tunnel. Each machine shall have a rigid frame, electric motor drive, package conveyor, heat-sealing belt, cold film cut-off, package elevator and film roll holder(s). The wrapping machine shall be capable of accommodating the attachment of a type I, style A, automatic scale as specified in 3.5.2.11, that is capable of weighing, computing, conveying, printing, identifying, dispensing and affixing labels to packaged items. The scale system shall be capable of operating independently from the wrapping machine and shall be provided with adjustable legs. The parts of each machine likely to come in contact with meat or produce shall be corrosion-resisting steel, aluminum, polystyrene, nylon or teflon, as applicable. The machines shall have a film stretching mechanism which simultaneously grips and stretches the film around all four sides of the package.

* 3.5.2.4 System III, film roll holders. The system III, film roll holders for the high speed wrapping machine shall be designed to accommodate at least one film roll. The machine shall be supplied with either of two belt settings, narrow or wide as specified (see 6.2). The film width capacity for the narrow belt setting shall be 11 inches to 18 inches and for the wide belt the setting shall be 14 inches to 19-3/4 inches. The film width capacity of the medium wrapping machine shall be 9 inches minimum to 20 inches maximum.

* 3.5.2.5 System III, controls. The system III controls shall be located so that the operator does not have to move from his normal operating position in order to change package sizes.

* 3.5.2.6 System III, motors. The system III motors shall conform to CC-M-1307.

* 3.5.2.7 System III, electrical characteristics. Unless otherwise specified (see 6.2) each system III high and medium speed wrapping machine shall operate on a nominal 208 volts, 3-phase, 60 Hz or 240 volts, 1-phase, 60 Hz power source.

* 3.5.2.8 System III, lubrication. The system III machines shall have lubrication means for all moving parts as applicable. Seals shall be provided to prevent leakage of lubricants. When applicable, lubricating fittings shall be readily accessible. At time of delivery, the machines shall be completely lubricated with the manufacturer's standard lubricant.

* 3.5.2.9 System III, lubricating chart. System III lubricating chart shall be furnished by the manufacturer and attached to each machine as applicable. The instructions on the chart shall indicate the grade of lubricant to be used and the parts to be serviced periodically.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

* 3.5.2.10 Package sizes. The high speed wrapping machine for the completely assembled integrated system III shall be capable of wrapping packages of the following sizes:

Length:	5-1/2"	minimum	to	12-1/2" maximum
Width:	3-1/2"	minimum	to	8-7/8" maximum
Height:	3/8"	minimum	to	4-3/4" maximum

The medium speed machine for the completely assembled integrated system III shall be capable of wrapping packages of the following sizes:

Length:	5-1/2	minimum	to	12-1/2" maximum
Width:	3-1/2"	minimum	to	9-1/2" maximum
Height:	3/8"	minimum	to	4-3/4" maximum

* 3.5.2.11 Scale system. The required scale system for the completely assembled integrated system III shall conform to type I, style A of MIL-S-43147. The scale system shall handle not less than 40 packages per minute, when tested in conjunction with a high speed wrapping machine and not less than 28 packages per minute using a medium speed wrapping machine, as applicable.

* 3.6 Finish. The stretch film wrapping machines for the completely assembled integrated system III shall be finished in accordance with the manufacturer's standard commercial practice. Painted coatings shall be smooth, adherent and free of blisters, runs, imbedded foreign matter, and areas of no coating.

* 3.7 Marking for identification. Marking for identification for stretch film wrapping machine for the completely integrated system III shall be in accordance with the manufacturer's standard commercial practice and shall include manufacturer's name, date of manufacture and model number.

3.8 Workmanship. The completed assembled integrated system III unit shall be free from defects such as fractures, dents, creases, bows, deteriorations, or malformations. There shall be no sharp edges, burrs, or slivers.

3.8.1 Welding and brazing. The surfaces of parts to be welded or brazed shall be free from oxide, scale, paint, grease, and other foreign matter. Welds or brazes shall be continuous, sound, smooth, and free from porosity, cracks, incomplete fusion, undercuts, and deformation of material.

3.8.2 Bolts, nuts, screws, studs, and other threaded fasteners. Threaded fasteners shall not be broken, stripped, fractured, or loose.

3.8.3 Driving of rivets. Rivets shall be driven to completely fill the holes, neatly finished, and in full contact with the surface of the mating members.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

3.9 Performance. The performance of the completely assembled wrapping, conveying, weighing and labeling system when tested as specified in 4.4.1 shall operate, wrap packages, convey, weigh and label in a refrigerated preparation room at an ambient temperature of 50°-55°F as follows:

(1) Using pulp, styrofoam and clear plastic trays, approximately 8 inches wide, 5 inches long and 1 inch high filled with a wooden filler to approximately 7 inches wide, 4 inches long and 4 inches high, the system shall wrap, convey, weigh and label packages automatically at speeds indicated in 4.4.1 with no jamming.

(2) The wrapper shall snuggly wrap the packages with no tearing of the film.

(3) The machine shall seal end folds on the package to produce a fusion of interfaces of the film.

(4) The package overwrap shall be fed or dispensed smoothly with no tearing, wrinkling, or snarling of the film.

3.10 Warning label. Warning label for each system shall be permanently and legibly marked with the following statement:

TO BE USED WITH WRAPPING MATERIALS APPROVED FOR USE WITH FOOD AND FOOD PRODUCTS.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First article inspection. The first article, when supplied, shall be examined for the defects listed in table I, dimensions specified, and tested as specified in accordance with 4.4.1.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

4.3.2 Standards compliance. Proof of compliance with the requirements of 3.3 shall be made available to the Government representative.

* 4.3.3 In process inspection.

4.3.3.1 In process examination. Inspection shall be made of the following processes to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to affected items and processes.

* 4.3.3.1.1 Welding and brazing. Prior to welding or brazing, the surfaces to be welded or brazed shall be examined for compliance with the requirements of 3.8.1.

* 4.3.3.1.2 Driving rivets. Prior to finishing, all rivets shall be examined for compliance with the requirements of 3.8.3.

* 4.3.4 End item inspection. The lot shall consist of all like wrapping, conveying, weighing, and labeling systems offered for inspection at one time. The sample unit shall be one completely fabricated wrapping, conveying, weighing, and labeling system.

4.3.4.1 Visual examination. Examination shall be made of the wrapping, conveying, weighing, and labeling system for the defects listed in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

	Examine	Defect	Classification Major	Classification Minor
*	Finish	Not finished in accordance with manufacturer's standard commercial practice		X
		Painted surface coating not smooth or adherent, not free of blisters, runs, imbedded foreign matter or areas of no coating		X
		Rust, rough grinds, toolmarks show through finish		X
		Not continuous and smooth, areas of no coverage		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship	Any part missing or not specified type	X	
	Component misplaced or not in proper alignment	X	
	Sharp burr, sliver, or sharp edge	X	
	Component loose		X
	Component not connected or joined properly	X	
Wiring	Cut, abraded, not enough slack	X	
	Excessive stripping of insulation, loose terminals		X
Welding and brazing	Missing, incomplete, burn holes, fractured, or not fused	X	
	Slag inclusion, undercut, not smooth and uniform, or deposits of scale and flux or other foreign material not removed		X
Rivets, bolts, nuts, screws and threaded fasteners	Missing, broken, stripped, or fractured	X	
	Threaded fastener loose		X
	Rivets not securely set	X	
Marking	Missing, incomplete, not legible, not as specified		X
Operation	Wrapping machine does not produce a tight wrap	X	
Lubrication (where applicable)	Not lubricated where required	X	
	Fitting not accessible for servicing		X
Lubricating chart	Lubrication chart missing, incomplete, not legible	X	

4.3.4.2 Dimensional examination. Examination shall be made for dimensions specified. Any deviation from specified requirements shall be considered a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

* 4.3.4.3 Testing of the end item. Each wrapping, conveying, weighing, and labeling system shall be tested as specified in 4.4.1. Any nonconformance to specified requirements shall be cause for rejection.

* 4.3.5 Packaging inspection. An examination shall be made to determine that preservation-packaging, packing and marking complies with section 5. Defects will be as specified in table III. The lot shall be all wrapping, conveying, weighing and labeling systems offered for inspection at one time. The sample unit shall be one system fully prepared for delivery except that shipping container need not be closed. The inspection level shall be S-2 and the AQL shall be 4.0 expressed in terms of defects per hundred units.

TABLE II. Packaging inspection

Examine	Defect
Marking (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence or method of application
Materials	Components missing, damaged or otherwise defective
Preservation	Preservative improperly applied or missing
Workmanship	Barrier material missing or not secured as specified Bulged or distorted containers
Contents	Wrapping machine equipment parts or special tools (if applicable) missing

4.3.5.1 Inspection of interior and exterior containers. When containers are required to be in accordance with PPP-B-636, PPP-C-650 or MIL-C-104, examination for defects in closure, waterproofing and reinforcing, as required, shall be in accordance with the applicable container specification.

4.4 Tests.

* 4.4.1 Operation and capacity test. The wrapping machine for the applicable wrapping, conveying, weighing and labeling system shall be loaded and threaded with applicable film. In addition, pulp, styrofoam and clear plastic trays, filled with a wooden filler of approximate dimensions, 4 inches wide by 7 inches long and 4 inches high, shall be fed into the machine for wrapping. These items shall be processed through the complete wrapping, conveying, weighing, and labeling cycle to determine compliance with the process capacity and performance requirements of 3.5.1.1, 3.5.1.2, 3.5.2.1, 3.5.2.2 and 3.9, as applicable. Each type of tray (pulp, styrofoam and clear plastic) shall be continuously fed for a period of 30 minutes. Inability of the assembly to meet the above requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

* 5.1.1 Level A.

* 5.1.1.1 Disassembly. Any removable components of each machine shall be disassembled in order to reduce cube and prevent damage while in transit. Care shall be exercised to avoid disassembly where the function of the item may be impaired or where special tools, calibration, or technical personnel may be needed for reassembly at the point of use.

* 5.1.1.2 Preservation.. Exposed, uncoated ferrous metal surfaces of each machine and disassembled components shall be cleaned process C-1 of MIL-P-116 and thoroughly dried. All cleaned and dried surfaces which will be in contact with food shall be coated with type P-14 preservative of MIL-P-116. The air compressor shall be preserved in accordance with the industry's practice.

* 5.1.1.3 Protection of preservatives. Surfaces from which preservative compound might be removed by contact with packaging and packing materials shall be covered or wrapped with greaseproof barrier-material conforming to type I or II, grade A, class 1 or 2 of MIL-B-121. The barrier-material shall be secured with tape conforming to type III or IV of PPP-T-60, cord or twine, or be heat-sealed when applicable.

* 5.1.1.4 Intermediate packaging. Parts of each machine that are free to rotate shall be securely fastened in a fixed position to prevent movement or vibration while in transit. Disassembled components shall be packaged in a snugfitting fiberboard box conforming to style optional, grade V2s, V3s or V4s of PPP-B-636. Fiberboard inserts or other cushioning material shall be used to separate and immobilize the contents of the box. Each box shall be securely closed in accordance with method IV as specified in the appendix of the box specification.

* 5.1.2 Commercial. Machines shall be preserved-packaged to afford adequate protection against corrosion deterioration and physical damage during shipment from supply source to receiving activity.

* 5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Each system consisting of the machines with detached components preserved-packaged as specified in 5.1, shall be packed in a crate conforming to type I, class 1 or 2, style a of MIL-C-104. Alternatively, each syste consisting of the machines with detached components may be packed in a crate conforming to type V, style A, class 1 of PPP-C-650 provided the maximum net load and maximum inside dimensions specified in PPP-C-650 are not exceeded. Crates used to pack machines conforming to PPP-C-650 shall be waterproofed, closed and strapped in accordance with the appendix thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B packing. Each system consisting of the machines with the detached components, preserved-packaged as specified in 5.1, shall be packed as specified in 5.2.1, except made from 50 pound minimum basis weight (24 by 36-500) kraft paper or 0.004-inch minimum thickness polyethylene film conforming to type I of L-P-378.

* 5.2.3 Commercial packing. Each system consisting of the machines with the detached components, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

* 5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

* 6.1 Intended use. The wrapping, conveying, weighing and labeling systems covered by this specification is intended for use in commissaries to automatic wrap, convey, weigh and label meat and produce items.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) System and speed required (see 1.2).
(c) When a first article is required (see 3.1).
(d) When a package accumulator bin is required (see 3.5).
(e) Whether narrow or wide belt setting is required (see 3.5.2.4).
(f) Electrical requirements if different (see 3.5.2.7).
(g) When contractor is to furnish supervision of the installation of the system. 1/
(h) When contractor is to demonstrate operation and service of the system. 1/
(i) Selection of the applicable levels of preservation-packaging, and packing (see 5.1 and 5.2).

1/ If either (g) or (h) is required, the location, approximate date, the person or office to report to, the normal duty hours and commercial telephone number, and any accommodation or service to be supplied by the installation or agency will be stated.

* 6.3 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically cited in the contract in accordance with the applicable regulations of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

* 6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

* 6.5 Marginal notations. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issues were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Review activities:

Army - SM, MD

Preparing activity:

Army - GL

Project No. 3540-A101

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R253

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DOD 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Natick Research and Development Command
Attn: DRXNM-TD
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:55Z
Check the source to verify that this is the current version before use.