MIL-C-50952(AR)
7 July 1977
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

CABLE ASSEMBLY, SPECIAL PURPOSE ELECTRICAL, TRAINING 5W1, 5W5, 5W6E1, 5W7, AND LEAD, ELECTRICAL TRAINING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of cable, entitled Cable Assembly, Special Purpose Electrical, Training, 5W1, 5W5, 5W6E1, 5W7, and Lead, Electrical Training which is used with the Sprint Warhead Section Trainer Type X: XM213 and Type W: XM214.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-W-81044	- Wire, Electric, Crosslinked Polyackene Insulated, Tin Coated Copper, Lightweight.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 1115

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8800546	- Bag, Packing, Ammunition for Cable Assembly.
8808362	- Packing and Marking for Storage and Shipments.
8883538-4	- Bag, Packing, For Repair Parts.
8883538-9	- Bag, Packing, For Repair Parts.
9241413	- Cable Assembly, S.P. Electrical, 5W7 Training.
9248225	- Cable Assembly, S.P. Electrical, Branched: 5W5 Training.
9248227	- Cable Assembly, S.P. Electrical, Branched: 5W1 Training.
9280839	- Lead, Electrical Training.
9281720	- Cable Assembly, S.P. Electrical, 5W6E1, Training.
9283133	- Marking and Packing for Fiberboard Box for Cable Assembly, S.P. Electrical, Branched: 5W1, Training.
9287510	- Packing and Marking for Box, Fiberboard, for Cable Assembly, 5W5 and 5W5, Training.
EL-9241413	- Equipment List.
EL-9248225	- Equipment List.
EL-9248227	- Equipment List.
EL-9280839	- Equipment List.
EL-9281720	- Equipment List.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The cables shall comply with all requirements specified on the drawings (dwgs) 9248227, 9248225, 9281720, 9241413, and 9280839, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:04Z
Check the source to verify that this is the currentversion before use.

3.5 Circuit resistance.

3.5.1 Cable assembly: 5W1. The circuit resistance between the points shown in Table I shall be less than 0.100 ohms, and those shown in Table II shall be less than 0.500 ohms when tested as specified in 4.4.1.

Table I

Circuit Resistance

From	To
P1-53	P3-29
P2-1	P1-1
P2-2	P3-12
P2-4	P1-4
P2-5	P1-5
P2-6	P1-6
P2-7	P1-33
P2-9	P1-9
P2-10	P1-10
P2-11	P1-12
P2-12	P1-11
P2-13	P1-28
P2-14	P3-31
P2-16	P3-11
P2-17	P1-32
P2-18	P1-19
P2-19	P1-18
P2-20	P1-20
P2-21	P1-51

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Table I (Continued)

From	To
P2-22	P1-22
P2-23	P1-23
P2-24	P1-24
P2-25	P1-25
P2-26	P1-27
P2-27	P1-26
P2-28	P1-13
P2-29	P3-1
P2-30	P3-3
P2-31	P1-31
P2-32	P3-5
P2-33	P3-6
P2-34	P1-35
P2-35	P1-34
P2-36	P1-36
P2-37	P1-37
P2-38	P1-38
P2-39	P1-50
P2-40	P1-2
P2-41	P1-39
P2-42	P1-41
P2-43	P1-43
P2-44	P1-45

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Table I (Continued)

From	To
P2-45	P1-44
P2-46	P1-42
P2-47	P3-2
P2-48	P3-4
P2-49	P1-40
P2-50	P1-55
P2-51	P1-49
P2-53	P3-8
P2-54	P3-7
P2-55	P1-52
P3-30	P4-53
P5-1	P4-1
P5-3	P4-3
P5-4	P4-4
P5-6	P4-6
P5-8	P3-10
P5-9	P4-40
P5-10	P4-39
P5-11	P4-12
P5-12	P4-27
P5-13	P4-20
P5-16	P4-47
P5-17	P4-28

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Table I (Continued)

From	To
P5-18	P4-7
P5-19	P4-19
P5-20	P3-9
P5-21	P4-38
P5-22	P4-43
P5-23	P4-45
P5-24	P4-33
P5-25	P4-52
P5-26	P4-46
P5-27	P4-13
P5-28	P4-24
P5-29	P4-25
P5-30	P4-30
P5-31	P4-9
P5-32	P4-34
P5-33	P4-35
P5-34	P4-14
P5-35	P4-18
P5-37	P4-21
P5-38	P4-8
P5-39	P4-31
P5-40	P4-49
P5-41	P4-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Table I (Continued)

From	To
P5-42	P4-11
P5-43	P4-26
P5-44	P4-22
P5-45	P4-41
P5-46	P4-55
P5-47	P4-54
P5-48	P4-32
P5-49	P4-50
P5-51	P4-29
P5-52	P4-37
P5-53	P4-15
P5-54	P4-16
P5-55	P4-48

Table II

Circuit Resistance

From	To
P2-3	P1-3
P2-8	P1-8
P2-8	P5-15
P5-5	P4-36
P5-7	P4-10
P5-7	P5-50
P5-15	P1-8

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Table II (Continued)

From	To
P5-36	P4-36
P5-36	P5-5
P5-50	P4-10

3.5.2 Lead, electrical training. The circuit resistance between the points shown below shall be less than 0.100 ohms when tested as specified in 4.4.1.

From	To
P2	P1-1
P2	P1-2
P2	P1-3
P2	P1-4
P2	P1-5
P2	P1-6
P2	P1-7
P2	P1-8

3.6 Insulation resistance.

3.6.1 Cable assembly: 5W1. The insulation resistance between each isolated pin and all other pins and connector shell tied together, as shown in Table III, shall not be less than 50 megohms when tested as specified in 4.4.2. Test voltage shall be 500 ± 50 volts direct current, with current limited to a maximum of 10 milliamperes.

Table III

Insulation Resistance

P2-1,2,3,4,5,6,7,8,9,10,11,12,13,14,16,17,18,19,20,21,22,23, 24,25,26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,43,44, 45,46,47,48,49,50,51,53,54 and 55.

P5-1,3,4,5,6,7,8,9,10,11,12,13,15,16,17,18,19,20,21,22,23, 24,25,26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,42, 43,44,45,46,47,48,49,50,51,52,53,54 and 55.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

3.6.2 Lead, electrical training. The insulation resistance between each isolated pin and all other pins and connector shell tied together as shown below shall not be less than 50 megohms when tested as specified in 4.4.2. Test voltage shall be 500 + 50 volts direct current, with current limited to a maximum of 10 milliamperes.

P1-9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,25,26,27, 28,29,30 and 31.

3.7 Conductor. All conductors assembled into the cables shall have conformed to MIL-W-81044. Objective quality evidence substantiating conformance shall be made available to the Government representative.

3.8 Soldering. All soldering shall be in conformance with MIL-STD-1460.

3.9 Workmanship.

3.9.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.9.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.9.3 Burrs. Parts shall be free from burrs.

3.9.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.9.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.9.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:04Z
Check the source to verify that this is the current version before use.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 2 complete assemblies (see dwgs 9248227, 9248225, 9281720, 9241413 and 9280839) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table IV. Tests shall be conducted in order specified in Table IV.

Table IV

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics/defects (see 4.3.2.1)		X
2.*,**Circuit resistance (see 3.5)		X
3.**Insulation resistance (see 3.6)		X

*Units tested for first article may be used as part of the deliverable production quantity after all first article tests have been successfully completed.
**Applicable to the 5W1 Cable Assembly and Lead Electrical Training only.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor defects/characteristics table (see Table V and Table VI), and inspected for all defects/characteristics in the applicable classification. Any defects/characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of defects/characteristics in each classification need not be followed as long as all defects/characteristics inspections are performed.

Table V
Major Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table VI
Minor Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of defects/characteristics (see 3.2). Critical, major and minor defects/characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Cable assembly, special purpose (SP) electrical, branched: 5W1 training (see dwg 9248227) before sleeving.

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
101.	Soldering not in compliance with MIL-STD-1460 (see 3.8)	Manual/Visual
102.	Inability to engage mating connector	Gage
103.	Bent pin or foreign matter in pin socket, as applicable (after mating)	Visual
104.	Serialization improper or missing (see 3.4)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.2 Cable assembly, SP electrical, branched: 5W1 training (see dwg 9248227).

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
101.	Components damaged, missing, loose, improper or improperly assembled	Manual/Visual
102.	Incorrect length from a point to main key in connector (4 places)	Gage
103.	Improper profile	Visual
104.	Tape placement of color not in compliance with note on dwg	Visual
105.	Excessive shrinkage of sleeving (see note on dwg)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

106.	Marking missing, improper, illegible or improperly positioned	Visual
107.	Serialization improper or missing (see 3.4)	Visual

Minor:

201.	Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.3 Cable assembly, SP electrical, branched: 5W5 training (see dwg 9248225), before sleeving.

Categories	Characteristics/Defects	Method of Inspection

Critical: None defined.

Major:

101.	Inability to engage mating connector	Gage
102.	Bent pin for foreign matter in pin socket (after mating)	Visual

Minor:

201.	Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.4 Cable assembly, SP electrical, branched: 5W5 training (see dwg 9248225).

Categories	Characteristics/Defects	Method of Inspection

Critical: None defined.

Major:

101.	Components damaged, missing, loose, improper or improperly assembled	Visual/Manual
102.	Incorrect length-overall	Gage
103.	Improper profile	Visual
104.	Tape placement or color not in compliance with note on drawing	Visual
105.	Excessive shrinkage of sleeving (see note on drawing)	Visual
106.	Marking missing, improper, illegible or improperly positioned	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

	107.	Serialization improper or missing (see 3.4).....Visual
Minor:		
	201.	Jacket or molding damaged.....Visual
	202.	Protective caps missing.....Visual
	203.	Evidence of poor workmanship (see 3.9).....Visual

4.3.2.1.5 Cable assembly, SP, electrical, 5W6E1, training (see dwg 9281720 and 5W7 training (see dwg 9241413) before sleeving.

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
	101. Inability to engage mating connector	Gage
	102. Bent pin or foreign matter in pin sockets (after mating)	Visual
	103. Soldering not in compliance with MIL-STD-1460 (see 3.8)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.6 Cable assembly, SP, electrical, 5W6E1, training (see dwg 9281720 and 5W7 training (see dwg 9241413).

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
	101. Component damaged, missing, loose, improper or improperly assembled	Visual/Manual
	102. Incorrect overall length	Gage
	103. Improper profile	Visual
	104. Tape placement or color not in compliance with note on drawing	Visual
	105. Excessive shrinkage of sleeving (see note on drawing)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

106.	Marking missing, improper, illegible or improperly positioned	Visual

Minor:

201.	Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.7 Lead, electrical training (see dwg 9280839) before sleeving.

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
101.	Soldering not in compliance with MIL-STD-1460 (see 3.8)	Manual/Visual
102.	Inability to engage mating connector	Gage
103.	Bent pin or foreign matter in pin socket (after mating)	Visual
Minor:	None defined.	

4.3.2.1.8 Lead, electrical training (see dwg 9280839).

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
101.	Components damaged, missing, loose, improper or improperly assembled	Visual/Manual
102.	Incorrect length-overall	Gage
103.	Improper profile	Visual
104.	Tape placement or color not in compliance with note on drawing	Visual
105.	Excessive shrinkage of sleeving (see note on drawing)	Visual
106.	Marking missing, improper, illegible or improperly positioned	Visual
Minor:		
201.	Jacket or molding damaged	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

202. Protective caps missing.....Visual
203. Evidence of poor workmanship (see 3.9).....Visual

4.3.2.1.9 Preparation for delivery (see 5).

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
	101. Packaging, packing and marking not in accordance with applicable drawing or requirement	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.9)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. *Circuit resistance	Major

*Applicable to the 5W1 Cable Assembly and Lead, Electrical Training.

This test is not destructive and samples so tested may be returned to the lot.

4.3.3.1 Circuit resistance. Each 5W1 Cable Assembly and Lead, Electrical Training shall be tested in accordance with 4.4.1. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major defects/characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-9241413, 9281720, 9248225, 9248227 and 9280839). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor defects/characteristics and tests. Acceptance inspection equipment for minor defects/characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Circuit resistance. The circuit resistance of the cable assembly shall be measured in accordance with Tables I and II with approved measuring equipment, requirements shall be as specified in 3.5.

4.4.2 Insulation resistance. The insulation resistance of the cable assembly shall be measured with approved insulation resistance measuring equipment in accordance with Table III, requirements shall be as specified in 3.6.

5. PREPARATION FOR DELIVERY

5.1 *Preservation and packaging, lead, electrical training. The cable assembly shall be packed and packaging marked in accordance with dwg 8883538-9 and 8808362.

5.2 *Preservation and packaging 5W1. The cable assembly shall be packed and packaging marked in accordance with dwg 9283133 and 8808362.

5.3 *Preservation and packaging 5W5. The cable assembly shall be packed and packaging marked in accordance with dwg 9287510.

5.4 *Preservation and packaging 5W6E1. The cable assembly shall be packed and packaging marked in accordance with dwgs 8883538-4 and 8808362.

5.5 *Preservation and packaging 5W7. The cable assembly shall be packed and packaging marked in accordance with dwgs 8800546 and 8808362.

*When Level C packaging and packing is specified (see 6.1) the moisture barrier may be omitted.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:04Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 thru 5.5).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2260B dated 29 April 1974.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No. 1115-A066

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.