MIL-C-50963A(AR)
1 February 1979
SUPERSEDING
MIL-C-50963(MU)
21 October 1971

MILITARY SPECIFICATION

CABLES, for M15 WARHEAD SECTION SUBASSEMBLY

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers two types of electrical cables which are used in the M15 Pershing warhead section subassembly.

1.2 Classification.- Electrical cables covered by this specification shall be of the following types:

Type I (radio frequency coaxial cables):

2W4, 2W5, 2W6, 2W7, 2W20, 2W21, 3W9, and 3W10.

Type II (wiring harnesses):

4W36, 4W67, 4W70, and 4W118.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents.- The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 1135

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

* STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.
MIL-STD-1460 - Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure for.

DRAWINGS (see 6.5)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

8800545 - Bag, Packing, Ammunition, for Cable Assembly.
8800546 - Bag, Packing, Ammunition, for Cable Assembly.
8861967 - Carton, Packing, Ammunition, for Wiring Harness: 4W36.
8861968 - Bag, Packing, Ammunition, for Wiring Harness, Branched: 4W70.
10560567 - Cable Assembly, Radio Frequency: 2W4.
10560568 - Cable Assembly, Radio Frequency: 2W5.
10560569 - Cable Assembly, Radio Frequency: 2W6.
10560570 - Cable Assembly, Radio Frequency: 2W7.
10560571 - Cable Assembly, Radio Frequency: 2W20.
10560572 - Cable Assembly, Radio Frequency: 2W21.
10560573 - Cable Assembly, Radio Frequency: 3W9.
10560574 - Cable Assembly, Radio Frequency: 3W10.
10560677 - Wiring Harness, Branched: 4W70.
10561496 - Cable Assembly, Special Purpose, Electrical: 4W118.
10564995 - Wiring Harness, Branched: 4W36.

US ARMY MISSILE RESEARCH AND DEVELOPMENT COMMAND

10560676 - Wiring Harness: 4W67.

PUBLICATIONS (see 6.5)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

Inspection Equipment Lists:

EL-10560567	EL-10560571	EL-10560676
EL-10560568	EL-10560572	EL-10560677
EL-10560569	EL-10560573	EL-10561496
EL-10560570	EL-10560574	EL-10564995

QAI-PA-1 - Quality Assurance Instructions for Reporting Data on Nuclear Weapons.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:04Z
Check the source to verify that this is the current version before use.

Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

3. REQUIREMENTS

3.1 Materials and components.- Materials shall conform to applicable specifications and drawings. Each component shall conform to all dimensions and tests specified on the component drawing. The contractor shall have available verifiable proof (i.e., objective evidence (see 6.2)) that materials and components were fabricated, inspected, and tested under controllable conditions as set forth in the contractor's quality control or inspection procedures.

3.2 Assembly.- The cable assemblies shall comply with all requirements specified on the following drawings (dwg.):

Type I - 10560567 (2W4), 10560568 (2W5), 10560569 (2W6) 10560570 (2W7), 10560571 (2W20), 10560572 (2W21), 10560573 (3W9), and 10560574 (3W10).

Type II - 10564995 (4W36), 10560676 (4W67), 10560677 (4W70), and 10561496 (4W118).

The cable assemblies shall also comply with all requirements specified herein and with the requirements of applicable specifications to the extent specified on the drawings and herein.

3.3 First article.- When specified, the contractor shall submit sample cables for first article inspection and approval (see 4.3 and 6.1.1).

3.4 Continuity and resistance.- Each Type I cable shall exhibit continuity between the center terminal of each connector and between the shell of each connector. The resistance of the center conductor (as measured between the center terminals) and the resistance of the shield (as measured between the connector shells) shall be as specified in Table I. The Type II cables (except the 4W70 cable) shall exhibit continuity between connected terminals, and the resistance shall be not greater than 1.0 ohm (refer to applicable drawing for wiring list). The continuity and resistance of the 4W70 cable shall be as specified in Table IA. Testing shall be as specified in 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I

Cable Assembly	Resistance (ohms, max.) Center Conductor	Shield
2W4	0.30	0.02
2W5	0.30	0.02
2W6	0.30	0.02
2W7	0.35	0.02
2W20	0.30	0.02
2W21	0.30	0.02
3W9	1.70	0.09
3W10	1.70.	0.09

TABLE IA

4W70 Wiring Harness		
From	To	Resistance (ohms, max.)
P1 shell	P3-B	0.03
P1 shell	P3-H	0.03
P1 center cond.	P3-A	0.03
P2 shell	P3-D	0.08
P2 shell	P3-F	0.08
P2 center cond.	P3-E	0.06
P3-C	P3-G	0.05

3.5 Insulation resistance.- The insulation resistance of the Type I cables shall be not less than 1000 megohms. The insulation resistance of the Type II cables shall be not less than 200 megohms. After humidity testing, the insulation resistance of the 4W67, 4W70, and 4W118 cables shall be not less than 20 megohms, and the insulation resistance of the 4W36 cable shall be not less than 5 megohms. There shall be no evidence of insulation breakdown or other damage during this test. Testing shall be as specified in 4.5.2.

3.6 Dielectric strength.- The Type I and Type II cables shall be subjected to a high-potential alternating current at a frequency of 60 hertz (Hz). The Type I and Type II cables shall show no indication of dielectric breakdown as evidenced by flashover (surface discharge), sparkover (air discharge), breakdown (puncture discharge), or inability to attain or maintain the high potential. Testing shall be as specified in 4.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

3.7 Capacitance.- The capacitance of the Type I and the 4W70 cables shall be as specified in Table II. In addition, the actual capacitance value in picofarads (pf) for each cable shall be recorded (see 3.12.1). Testing shall be as specified in 4.5.4

TABLE II

Cable	Limits (pf)	Test identification number (see 3.12.1) 1/
2W4	11.0 - 15.0	060001
2W5	11.0 - 15.0	060002
2W6	16.0 - 20.0	060003
2W7	18.5 - 22.5	060004
2W20	14.5 - 18.5	060005
2W21	14.5 - 18.5	060006
3W9 2/	82.0 - 94.0	060007
3W10 2/	80.0 - 92.0	060008
4W70 P1	49.0 - 59.0	060009
4W70 P2	121.0 - 147.0	060010

1/ Not required for the pull test and for environmental tests (high temperature, low temperature, and humidity).

2/ After the environmental tests, the capacitance limits of the 3W9 cable shall be 78.0 - 98.0 pf, and the capacitance limits of the 3W10 cable shall be 76.0 - 96.0 pf.

3.8 Pull test.- The coaxial connectors of the Type I and the 4W70 cables shall withstand a pull force of 12 ± 0.5 pound for a minimum period of 10 seconds. There shall be no evidence of connector separation, pin retraction, or other damage during this test. After testing, the cables shall comply with the requirements of 3.4, 3.5, and 3.7. Testing shall be as specified in 4.5.5.

3.9 High temperature.- The cables shall withstand a high temperature of 160° ± 5°F, for a minimum period of 4 hours, without evidence of cracking, swelling, distortion, or other damage. While at the high temperature (at the end of the high-temperature exposure period), the cables shall comply with the requirements of 3.4. After this test (at room temperature), the cables shall comply with the requirements of 3.4, 3.5, and 3.7 (if applicable). Testing shall be as specified in 4.5.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

3.10 Low temperature.- The cables shall withstand a low temperature of -33° ± 3°F, for a minimum period of 4 hours, without evidence of cracking, swelling, distortion, or other damage. While at the low temperature (at the end of the low-temperature exposure period), the cables shall comply with the requirements of 3.4. After this test (at room temperature), the cables shall comply with the requirements of 3.4, 3.5, and 3.7 (if applicable). Testing shall be as specified in 4.5.7.

3.11 Humidity.- The cables shall withstand a relative humidity of 95 ± 5 percent and a temperature of 105° ± 5°F without evidence of cracking, swelling, distortion, or other damage. After this test (at room temperature), the cables shall comply with the requirements of 3.4, 3.5, and 3.7 (if applicable). Testing shall be as specified in 4.5.8.

3.12 Serialization.

3.12.1 4W70 and Type I cables.- A six-letter serial code shall be assigned to each 4W70 and each Type I cable. The contractor shall obtain these serial codes by means of a letter addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR-QAN-R, Dover, New Jersey 07801. The letter of request shall include: (a) the list of cables requiring data feedback (see Table II), (b) contract number or procurement request order number, and (c) number of serial codes required (unused codes must be returned). In addition to normal inspection records, the contractor shall provide data feedback (see 6.1.2) in conformance with Quality Assurance Instruction QAI-PA-1. The data required to be coded, and the test identification numbers, are specified in 3.7.

3.12.2 4W36, 4W67, and 4W118 cables.- A serial number shall be assigned by the contractor to each 4W36, 4W67, and 4W118 cable. In no event shall serial numbers be duplicated on different cables of the same designation. Six-letter serial codes shall not be used on these cables.

3.13 Soldering.- All soldering shall be in accordance with MIL-STD-1460.

3.14 Workmanship.- All parts and accessories shall be constructed, assembled, and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness, marking, cleaning, and freedom of the parts from burrs and sharp edges which may affect performance or result in injury during handling. All parts shall be free of chips, dirt, grease, rust, and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspections.- The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3)
2. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission.- When the contract requires first article inspection, the contractor shall submit one cable of each designation being produced to the testing facility designated in the invitation for bids or request for proposal.

4.3.2 Inspection and testing to be performed.- The first article inspection samples shall be inspected, as applicable, for the defects specified in 4.4.2.1, using inspection methods contained therein, and for all requirements of Section 3, which are listed in Table III, using the test methods specified in 4.5. Inspection and testing shall be performed with the acceptance inspection equipment specified in 4.4.4. The cables shall be tested in the order specified in Table III. If any cable fails to comply with the applicable requirements, the first article samples, of the type where the failure occurred, shall be rejected. The Government reserves the right to terminate its inspections upon any failure of the first article samples to comply with the stated requirements. This series of tests is considered destructive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE III. First article tests.

Test	Requirement paragraph
1. Continuity and resistance	3.4
2. Insulation resistance	3.5
3. Dielectric strength	3.6
4. Capacitance (Type I and 4W70 cables only)	3.7
5. Pull test (Type I and 4W70 cables only)	3.8
6. High temperature	3.9
7. Low temperature	3.10
8. Humidity	3.11

4.4 Quality conformance inspection.

4.4.1 Inspection lot.- A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot, and a batch shall mean an inspection batch for the purposes of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.4.2 Product inspection examination.- A sample shall be selected at random from each inspection lot (cables of one designation) in accordance with the major defect or the minor defect table as applicable (see Table IV). Any defect found in the sample, selected for the major or minor classification, shall reject the lot. Critical defects shall require 100 percent inspection of all items in the inspection lot. If any critical defect is found in an item, the item shall be removed from the lot. The sequence of inspections for the classification of defects need not be followed so long as all the defect inspections are performed.

TABLE IV. Inspection lot sampling.

Major Defect Table		Minor Defect Table	
Lot Size	Sample Size	Lot Size	Sample Size
1-30	all	1-30	all
31-45	29	31-45	27
46-60	35	46-60	30
61-75	38	61-75	33
76-95	42	76-95	35
96-130	46	96-130	37
131-180	50	131-180	39
181-250	52	181-250	41
251-400	54	251-400	42
401 and over	56	401 and over	44

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.4.2.1 Classification of defects.- Critical, major, and minor defects are defined in MIL-STD-105.

4.4.2.1.1 Cable Assembly, Radio Frequency: 2W4, 2W5, 2W6, 2W7, 2W20, 2W21, 3W9, and 3W10 (see dwg. numbers listed in 3.2, Type I cables).

Categories		Defects	Method of Inspection
Critical:	None defined.		
Major:			
	101.	Length, min	Gage
	102.	Ability of connector to engage and disengage with mating connector (2 places)	Manual/Gage
	103.	Connector pin missing or damaged (2 places)	Visual
	104.	Connector improper (2 places)	Visual
	105.	Soldering improper (inspect during assembly)(see 3.13)	Visual
Minor:			
	201.	Insulation cut or damaged (exposing cable shield)	Visual
	202.	Protective cap missing or improper (2 places)	Visual
	203.	Connector strain relief improper (2 places)	Visual
	204.	Marking missing improper or illegible	Visual
	205.	Evidence of poor workmanship (see 3.14)	Visual

4.4.2.1.2 Wiring Harness, Branched: 4W36 (see dwg. 10564995); Wiring Harness: 4W67 (see dwg. 10560676); Wiring Harness, Branched: 4W70 (see dwg. 10560677); and Cable Assembly, Special Purpose, Electrical: 4W118 (see dwg. 10561496).

Categories		Defects	Method of Inspection
Critical:	None defined.		
Major:			
	101.	Overall length, min. (except the 4W70 cable)	Gage
	102.	Length of branches on 4W70 cable, min. (3 branches)	Gage
	103.	Length of branches on 4W36 cable, min. (8 branches)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

104.	Ability of connectors to engage and disengage with mating connectors	Manual/Gage
105.	Keyway orientation of connectors improper (4W36 and 4W67 only)	Visual
106.	Connectors improper	Visual
107.	Grounding wire (at rear end of J2 connector) missing or improper (4W118 cable only)	Visual
108.	Connector pin or socket missing or damaged	Visual
109.	Height of pins in connector (see 6.4)	Visual
110.	Depth of sockets in connector (see 6.4)	Visual
111.	Soldering improper (inspect during assembly)(see 3.13)	Visual

Minor:

201.	Insulation cut or damaged (exposing cable shield)(4W70 cable only)	Visual
202.	Cable sleeving cut or damaged exposing inner conductors (except 4W70 cable)	Visual
203.	Protective caps missing or improper	Visual
204.	Connector strain relief improper (2 places)(4W70 cable only)	Visual
205.	Potting missing or improper	Visual
206.	Marking missing, improper, or illegible	Visual
207.	Evidence of poor workmanship (see 3.14)	Visual

* 4.4.2.1.3 Packaging of Cables (see Section 5).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:		
101.	Cable improperly preserved, packaged, packed, and marked (see applicable paragraph in Section 5)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection testing.- The contractor shall perform all of the tests specified in Table V. The tests shall be performed in the listed sequence. None of these tests is considered destructive, and samples so tested shall be returned to the lot.

TABLE V. Quality conformance tests.

Test	Test classification
1. Continuity and resistance	Major
2. Insulation resistance	Major
3. Capacitance (Type I and 4W70 cables only)	Major
4. Pull test (Type I and 4W70 cables only)	Major

4.4.3.1 Continuity and resistance (see 3.4), insulation resistance (see 3.5), capacitance (see 3.7), and pull test (see 3.8).- Each cable shall be subjected to these tests (see applicable paragraph in 4.5). If any cable fails to comply with the applicable requirements, it shall be classified defective and shall be removed from the lot.

4.4.4 Acceptance inspection equipment.

4.4.4.1 Major defects and tests.- Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration procedures as specified in the following equipment lists (EL):

EL-10560567	EL-10560571	EL-10560676
EL-10560568	EL-10560572	EL-10560677
EL-10560569	EL-10560573	EL-10561496
EL-10560570	EL-10560574	EL-10564995

When either of the following conditions exists, the contractor shall design required equipment or specify suitable commercial equipment: (a) if any deviation from equipment or procedures, as specified in the EL, is desired or (b) the code "CD" is listed in the "Part or Identifying Number" column in the EL (see 6.1.2). The contractor shall obtain approval of such designs, operating instructions, and special calibration procedures prior to use on the contract (see 6.3).

4.4.4.2 Minor defects and tests.- Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.- The tolerances specified in this specification are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used. Unless otherwise specified, the tests shall be conducted at room temperature (77° ± 10°F). NOTE: During environmental tests, cable connectors shall be protected by mating connectors or by suitable protective caps.

4.5.1 Continuity and resistance.- The continuity and resistance of each cable shall be measured by means of a Government-approved resistance measuring device which is capable of accurately measuring low resistances in the range specified in 3.4. The cables shall comply with the requirements of 3.4 during this test.

4.5.2 Insulation resistance.

4.5.2.1 Type I cables.- The insulation resistance of each Type I cable shall be measured by using a Government-approved insulation resistance tester at an applied voltage of 1600 ± 100 volts direct current (VDC). The measurements shall be made between the center terminal and the connector shell on either one of the cable connectors. The test voltage shall be applied instantaneously and maintained for a period of 5 to 30 seconds. If an acceptable insulation resistance value is maintained (or increasing) within this time period, the test voltage may be removed. The Type I cables shall comply with the applicable requirements of 3.5 during this test.

4.5.2.2 Type II cables.- The insulation resistance of each Type II cable shall be measured by using a Government-approved insulation resistance tester at an applied voltage of 500 ± 50 VDC. The measurements shall be made between each connector terminal and all other electrically isolated terminals and connector shells tied together as one terminal (refer to applicable Type II cable drawing for wiring list or diagram). The test voltage shall be applied instantaneously, and the insulation resistance shall be measured after a 10-second application of the test voltage. The Type II cables shall comply with the applicable requirements of 3.5 during this test.

4.5.3 Dielectric strength.

4.5.3.1 Type I cables.- The Type I cables shall be subjected to a high potential of 1600 ± 100 volts root mean square (rms) for a minimum period of 10 seconds. The test potential shall be applied between the center terminal and the connector shell on either one of the cable connectors. The test potential shall be applied either instantaneously or at a uniform rate from zero to 1600 volts (within a 5-second period). A Government-approved test setup shall be used, and suitable means

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

shall be provided to indicate the occurrence of dielectric breakdown in the event it is not visually evident in the cable. The Type I cables shall comply with the applicable requirements of 3.6 during this test.

4.5.3.2 Type II cables.- The Type II cables shall be subjected to a potential of 500 ± 50 volts rms for a minimum period of 10 seconds. The test potential shall be applied between each connector terminal and all other electrically isolated terminals and connector shells tied together as one terminal (refer to applicable Type II cable drawing for wiring list or diagram), and the test voltage shall be applied instantaneously. A Government-approved test setup shall be used, and suitable means shall be provided to indicate the occurrence of dielectric breakdown in the event it is not visually evident in the cable. The Type II cables shall comply with the applicable requirements of 3.6 during this test.

4.5.4 Capacitance.- The capacitance of the 4W70 and the Type I cables shall be measured by use of a Government-approved capacitance bridge at a frequency of 1000 Hz. The capacitance measurements of the Type I cables shall be made between the center terminal and the connector shell on either one of the cable connectors. The capacitance measurements of the 4W70 cable shall be made between the center terminal and the connector shell of connectors P1 and P2. The cables shall comply with the requirements of 3.7 during this test.

4.5.5 Pull test.- The coaxial connectors of the 4W70 and the Type I cables shall be subjected to an axial pull force, along the longitudinal axis of the cable, using a Government-approved pull fixture. The cables shall comply with the requirements of 3.8 during this test.

4.5.6 High temperature.- The cable shall be placed into a test chamber, and the temperature of the chamber shall be raised to 160°F. The cable shall remain at this temperature for a minimum period of 4 hours and then tested as specified in 3.9 at the end of the high-temperature exposure period. The cable shall then be removed from the test chamber, allowed to stabilize at room temperature, and then tested for the applicable requirements of 3.9. The cable shall comply with all requirements of 3.9 during this test.

4.5.7 Low temperature.- The cable shall be placed into a test chamber, and the temperature of the chamber shall be lowered to -33°F. The cable shall remain at this temperature for a minimum period of 4 hours and then tested as specified in 3.10 at the end of the low-temperature exposure period. The cable shall then be removed from the test chamber, allowed to stabilize at room temperature, and then tested for the applicable requirements of 3.10. The cable shall comply with all requirements of 3.10 during this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.8 Humidity.- The cable shall be placed into a dry oven and conditioned at a temperature of 105°F for a minimum period of 24 hours. At the end of this conditioning period, the cable shall be transferred to a humidity chamber having a temperature of 105°F and a relative humidity of 95 percent. The cable shall remain in this chamber for a minimum period of 96 hours. Following this exposure period, the cable shall be removed from the humidity chamber and allowed to stabilize at room temperature for a minimum period of 4 hours. The cable shall comply with the requirements of 3.11 during this test.

* 5. PACKAGING

5.1 Cables for interplant shipments (see 6.2).

5.1.1 Preservation, packaging, packing, and marking.- Preservation, packaging, packing, and marking shall be in accordance with MIL-STD-1188 or as specified in the contract or purchase order.

5.2 Cables for spare parts.

5.2.1 Preservation, packaging, and marking.- Preservation, packaging, and marking shall be in accordance with the applicable drawings listed in Table VI.

TABLE VI

Cable	Packaging drawing
2W4	8800546
2W5	"
2W6	"
2W7	"
2W20	"
2W21	"
3W9	8800545
3W10	"
4W36	8861967
4W67	8800546
4W70	8861968
4W118	8800545

5.2.2 Packing and marking.- Packing and marking shall be in accordance with MIL-STD-1188 or as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

* 6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

6.1.1 Procurement requirements.- (a) Title, number, and date of this specification, (b) whether procurement is for cables for spare parts or for interplant shipments (see 6.2), (c) selection of methods of packaging or packing (see Section 5), and (d) first article sample requirements.

6.1.2 Data requirements.- Data specified in 3.7, and contractor engineering documentation specified in 4.4.4.1, will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated into the contract.

6.2 Definitions.

6.2.1 Objective evidence.- Records of the contractor's quality control and inspections which can be verified.

6.2.2 Interplant shipments.- Shipments from a supply source to a receiving activity for subsequent incorporation into the next assembly during end item production.

6.3 Acceptance inspection equipment.- The contractor shall obtain approval of equipment designs, operating instructions, and calibration procedures from Commander, US Army Armament Research and Development Command, Attn: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 Inspection of connectors.

6.4.1 Height of pins.- In the event a pin does not appear to be the same relative height of adjacent pins, a gage shall be used to determine the variation from normal height. Reject any connector that has a pin that varies by more than 0.040 inch maximum from the normal pin height of the individual connector. The normal height of the individual connector pins shall be determined by calculating the average height from measurements taken of pins adjacent to the pin that appears to be defective. The forward metal edge of the connector shall be used as the reference surface for all measurements.

6.4.2 Depth of sockets.- In the event a socket does not appear to be the same relative depth of adjacent sockets, a gage shall be used to determine the variation from normal depth. Reject any connector that has a socket that varies by more than 0.040 inch maximum from the normal socket depth of the individual connector. The normal depth of the individual connector sockets shall be determined by calculating the average depth from measurements taken of sockets adjacent to the socket that appears to be defective. The forward metal edge of the connector shall be used as the reference surface for all measurements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

6.5 Drawings and publications.- Drawings and publications listed in Section 2 of this specification under the heading of US Army Armament Research and Development Command (ARRADCOM) may also include drawings and publications prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings and publications. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.6 Changes from previous issue.- The margins of this specification are marked with asterisks to indicate where major changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

(Project 1135-A246)

Preparing Activity:
Army-AR

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-50963A CABLES, FOR M15 WARHEAD SECTION SUBASSEMBLY

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.