MIL-F-50869E (AR)
9 September 1985
SUPERSEDING
MIL-F-50869D (AR)
22 July 1981

MILITARY SPECIFICATION

FUZE PIBD, M550, LESS SPITBACK ASSEMBLY, METAL PARTS FOR AND LOADING, ASSEMBLING AND PACKAGING

This specification is approved for use by the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the metal parts and loading, assembling and packaging for one type of fuze designated as Fuze, PIBD, M550, less spitback Assembly.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-B-2427	-	Box, Ammuntion Packing, Wood Nailed
MIL-C-5541	-	Chemical Conversion Coatings on Aluminum and Aluminum Alloys
MIL-A-8625	-	Anodic Coatings, for Aluminum and Aluminum Alloys

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

MIL-D-14978 - Detonator, Stab, M55
MIL-P-19644 - Plastic Molding Material (Polystrene Foam, Expanded Bead)
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specifications For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspections by Attributes
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

2.1.2 Other Governemt documents, drawings and publications. The following other Governemnt documents form a part of this specification to extent specified herein:

DRAWING (SEE6.8)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

PRODUCT AND PACKING DRAWINGS

8796522 - Marking, Diagram and Sealing for Wood Packing Boxes
8799112 - Marking Diagram and Sealing
8886360 - Fuze, PIBD, M550 Less Spitback
9280921 - Packing and Marking for Fiberwood Box for Fuze, PD, M550, Less Spitback
9287615 - Cartridge, 40mm, Test Vehicle for Fuze, M550

(Copies of specifications, standards, handbooks and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Other publications. The following documents form a part of this specification to the extend specified herein. Unless otherwise indicated, the issue in effect on date of initiation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Goverment Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 110-119 (latest revision)".)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B 117-64 - Standard Method of Salt Spray (fog) Testing
ASTM-D1474-68 - Indentation Hardness of Organic Coatings, test for

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specifications shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg.) 8886360 and with all requirements specified in applicable specifications.

3.3 Contamination and distortion of Lexan parts. Extreme care should be taken throughout all phases of manufacture to avoid contracting "Lexan" parts with certain solvent materials and vapors which may attack the "Lexan" material. Specific information on "Lexan" destructive solvents may be obtained from the General Electric Co., Chemical and Metallurigical Division, Pittsfield, MA.

3.4 Transportation vibration. The fuze shall be safe and operable.

3.5 Jolt and jumble. The fuze shall withstand the requirements of MIL-STD-331 without becoming hazardous to anyone handling it.

3.6 X-ray examination of sample fuze assemblies.

3.6.1 Prior to jolt and jumble testing. The sample fuze assemblies shall be x-rayed and shall not be armed or partially armed (as evidenced by by the detonator moving any degree from the safe position) or have any part missing. (i.e. detent, detent spring, setback pin, setback pin retainer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

3.6.2 After jolt and jumble testing. The sample fuze assemblies shall be x-rayed and shall not be armed or partially armed (as evidence by the rotor overriding the setback pin) or the setback pin retracted.

3.7 Functioning. The fuze shall function high order as evidence by the spitback functioning high order or when disassembled, the rotor had moved to the full arm position and detonator output was in correct position.

3.7.1 Safety. There shall be no premature burst (see 6.7) or evidence thereof in any of the firings.

3.8 Non-functioning.

3.8.1. Hard target (as applicable). The fuze shall not function as evidence by the spitback not functioning high order. (Detonator firing to be reported for informational purposes only).

3.8.2 Soft target (as applicable). The fuze shall not function as evidence by the detonator not functioning high order.

3.9 First article testing. This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in contract.

3.10 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIOS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions opf MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (see 4.3)
b. Quality Conformance Inspection (see 4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawings	Quantity	
Body Fuze	8886356	25	(5 for salt spray)
Pin Setback	9276568	25	
Spring Setback	9276673	25	
Pin Firing	8864598	25	
Ogive	8886350	25	(5 for salt spray)
Centerplate	9266693	25	
Rotor Assembly	8886363	50	
Verge Assembly	8886365	50	
Pinion Assembly	8886368	50	
Escapment Assembly	8886357	50	
Hammerweight Assembly	8864599	50	
Centerplate Assembly	9266692	50	
Rotor and Gear Sector Assembly	9219871	25	
Fuze Assemblies	8886360	474	

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078 and the following:

4.3.3.1 Functioning. If the combined total of fuzes not functioning exceeds seven (7) or exceeds four (4) in either phase or one (1) premature burst occurs, the first article sample shall be rejected.

4.3.3.2 Non-functioning, hard target or soft target (as applicable). Accept if one (1) or less fuzes function and reject if four (4) or more fuzes function. If two (2) or three (3) fuzes function, an additional fifty (50) fuzes shall be subjected to this test. If a total of four (4) or more fuzes function in the cumulative sample, the first article sample shall be rejected. If one (1) premature burst occurs in any sample, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
	Fuze Assembly and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body Fuze (Dwg. 8886356)				
	Examination for defects	25		3.2	4.4.2.4
	Salt Spray	5		3.2	4.5.1
	Pin Setback (Dwg. 9276568)				
	Examination for defects	25		3.2	4.4.2.6
	Spring Setback (Dwg. 9276673)				
	Examination for defects	25		3.2	4.4.2.7
	Push Test of simulated setback pin	25		3.2	4.5.2
	Verification of heat treat	*		3.2	4.5.3
	Firing Pin (Dwg. 8864598)				
	Examination for defects	25		3.2	4.5.2.8

NOTES: * Three (3) setback springs showing the lowest push force of simulated setback pin.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
	Fuze Assembly and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Ogive (Dwg. 8886350)				
	Examination for defects	25		3.2	4.4.2.10
	Salt Spray	5		3.2	4.5.1
	Centerplate (Dwg. 9266693)				
	Deflection test	25		3.2	4.5.6
	Rotor Assembly (Dwg. 8886363)				
	Examination for defects	50		3.2	4.4.2.13
	Stake of detonator	50		3.2	4.5.12
	Verge Assembly (Dwg. 8886365)				
	Examination for defects	50		3.2	4.4.2.14
	Torque test	50		3.2	4.5.4
	Disassembly test	50		3.2	4.5.5
	Pinion Assembly (Dwg. 8886368)				
	Examination for defects	50		3.2	4.4.2.15
	Push off test	50		3.2	4.5.7
	Torque test (when applicable)	50		3.2	4.5.8
	Hammerweight Assembly (Dwg. 8864599)				
	Security of stake	50		3.2	4.5.20

NOTES:

Source: https://assist.dla.mil - Document created 2026-01-26 04:03
Check the source to verify that this is the current version before use.

TABLE I First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER
	Fuze Assembly and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Escapement Assembly (Dwg. 8886357)				
	Examination for defects	50		3.2	4.4.2.16
	Arming	50		3.2	4.5.10
	Arming delay time	50		3.2	4.5.9
	Non-arming	50		3.2	4.5.11
	Pull test of spring setback	50		3.2	4.5.13
	Centerplate Assembly (dwg. 9266692)				
	Arming	50		3.2	4.5.14
	Push out test of hammerweight assembly	*37		3.2	4.5.15
	Separation test of hammerweight pin	*37		3.2	4.5.16
	Retention check of firing pin	50		3.2	4.5.17
	Rotor and Gear Sector Assembly (Dwg. 9219871)				
	Static push test	25		3.2	4.5.18
	Fuze Assembly (Dwg. 8886360)				
	Examination for defects	50		3.2	4.4.2.22
	Air pressure of crimped joint	50		3.2	4.5.19
	X-ray examination, prior to jolt and jumble test	24		3.2	4.5.21.1
	Jolt test	12		3.2	4.5.22

NOTES: *Hammerweight assemblies on each of the three (3) legs.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z.
Check the source to verify that this is the current version before use.

TABLE I First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
	Fuze Assembly and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Jumble test	12		3.2	4.5.22
	X-ray examination after jolt and jumble test	24		3.2	4.5.21.2
	Transportation vibration	400		3.2	4.5.23
	Functioning	300*			
	a. Gravel pad	150	4.3.3.1	3.2	4.5.24
	b. Steel plate	150	4.3.3.1	3.2	4.5.24
	Non-functioning, hard target or soft target (as applicable)	50* 50 if required	4.3.3.2	3.2	4.5.25

NOTES: * After completion of the transportation vibration test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Each inspection lots shall contain:

a. Detonators from one interfix lot number from one manufacturer.

b. Metal parts from one interfix lot number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886356
4.4.2.1	Body Fuze				NEXT HIGHER ASSEMBLY 8886355
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter setback spring cavity		.40%	3.2	Gage
102.	Depth set back spring cavity		.40%	3.2	Gage
103.	Diameter setback pin cavity		.40%	3.2	Gage
104.	Depth setback pin cavity		.40%	3.2	Gage
105.	Salt spray	*	*	3.2	4.5.1
Minor					
201.	Poor workmanship		.65%	3.10	Visual

NOTES: * Sampling and rejection shall be in accordance wtih MIL-C-5541.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9276568
4.4.2.2	Pin Setback				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Length large end to flange, min		100%	3.2	Gage
102.	Diameter body small end, max		.40%	3.2	Gage
Minor					
201.	Poor workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Spring Setback		9276673
			NEXT HIGHER ASSEMBLY 8886357

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
		See 4.4.3.2			
Critical	None defined				
Major					
101.	Diameter between tangs		.40%	3.2	Gage
102.	Tange broken, bent or missing		.40%	3.2	Gage
103.	Push test of simulated setback pin	125*	.40%	3.2	4.5.2
Minor					
201.	Length, max		.65%	3.2	Gage
202.	Poor workmanship		.65%	3.10	Visual

NOTES: * Per heat treat batch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50869E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Firing Pin		8864598
			NEXT HIGHER ASSEMBLY 8864596

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Profile of firing pin point		.40%	3.2	Gage
102.	Length from point to shoulder		.40%	3.2	Gage
Minor					
201.	Poor workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Ogive				8886350
					NEXT HIGHER ASSEMBLY 8886360
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Salt spray	*	*	3.2	4.5.1
102.	Spherical radius	See 4.4.3.2	.40%	3.2	Gage
Minor					
201.	Color incorrect		.65%	3.2	Visual
202.	Protective finish with bare spot exposing base metal except rack marks		.65%	3.2	Visual
203.	Wall thickness		.65%	3.2	Gage
204.	Poor workmanship		.65%	3.10	Visual

NOTES: * Sampling and rejection shall be in accordance with MIL-A-8625

Source: https://assist.dla.mil -- Downloaded: 20260-26104:032
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Centerplate		9266693
			NEXT HIGHER ASSEMBLY 9266692

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Deflection test	50	1-2	3.2	4.5.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886363
4.4.2.7	Rotor Assembly				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Detonator stake missing		.40%	3.2	Visual
102.	Detonator inverted		.40%	3.2	Visual
103.	Detonator above flush		.40%	3.2	Visual
104.	Descernible bulge on detonator		.40%	3.2	Visual
105.	Stake of detonator	125	1-2	3.2	4.5.12
Minor					
201.	Poor workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886365
4.4.2.8	Verge Assembly				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Bearing diameters		.40%	3.2	Gage
102.	Thickness of verge		.40%	3.2	Gage
103.	Outside diameter of verge		.40%	3.2	Gage
104.	Distance from shoulder of arbor to end of bushing		.40%	3.2	Gage
105.	Depth of cutout on verge		.40%	3.2	Gage
106.	Torque test	125	1-2	3.2	4.5.4
107.	Disassembly test	125	1-2	3.2	4.5.5
Minor					
201.	Lubricant missing		.65%	3.2	Visual
202.	Poor workmanship		.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886368
4.4.2.9	Pinion Assembly				NEXT HIGHER ASSEMBLY 8886357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Bearing diameters		.40%	3.2	Gage
102.	Starwheel thickness		.40%	3.2	Gage
103.	Concentricity of OD of starwheel with bearing diameters		.40%	3.2	Gage
104.	Torque test (when applicable)	125	1-2	3.2	4.5.8
105.	Push off test	125	1-2	3.2	4.5.7
Minor					
201.	Poor workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Escapement Assembly		8886357
			NEXT HIGHER ASSEMBLY 8886355

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Arms less than 190 miliseconds (delay time)		100%	3.2	4.5.9
2.	Rotor in armed position		100%	3.2	Visual/Probe
3.	Non-arming test		100%	3.2	4.5.11
4.	Pin, setback missing or retracted		100%	3.2	Visual/Probe
Major					
101.	Spring, setback missing		100%	3.2	Visual/Probe
102.	Arms in less than 220 miliseconds (delay time)		100%	3.2	4.5.9
103.	Arming test	125	1-2	3.2	4.5.10
104.	Pull test of spring setback		100%*	3.2	4.5.13
Minor					
201.	Face of posts above flush after stake		.65%	3.2	Visual
202.	Poor workmanship		.65%	3.10	Visual

NOTES: * Acceptable alternate to this test is 100% inspection verifying presence of spring setback and setback pin when installing escapement assembly into body fuze.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886357
4.4.2.11	Escapement Assembly, Immediately Prior to Insertion Into Body Assembly				NEXT HIGHER ASSEMBLY 8886355
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Setback spring missing		100%	3.2	Visual/Probe
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8864599
4.4.2.12	Hammerweight Assembly				NEXT HIGHER ASSEMBLY 9266692
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101.	Security of stake	50	1-2	3.2	4.5.20
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9266692
4.4.2.13	Centerplate Assembly				NEXT HIGHER ASSEMBLY 8886355
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Arming test	50	1-2	3.2	4.5.14
Minor					
201.	Poor workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9219871
4.4.2.14	Rotor and Gear Sector Assembly				NEXT HIGHER ASSEMBLY 8886363
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Static push test	50	1-2	3.2	4.5.18
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Fuze Assembly, Less Spitback		8886360
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Rotor in armed position		100%	3.2	Visual/Probe
Major					
101.	Outside diameter		.40%	3.2	Gage
102.	Diameter between crimped joint		.40%	3.2	Gage
103.	Air pressure test of crimped joint	125	3-4	3.2	4.5.19
104.	X-ray examination, prior to jolt and jumble test	108	0-1	3.6.1	4.5.21.1
105.	X-ray examination, after jolt and jumble test	108	0-1	3.6.2	4.5.21.2
106.	Jolt test	12	0-1	3.5	4.5.22
107.	Jumble test	96	0-1	3.5	4.5.22
Minor					
201.	Marking misleading or unidentifiable		.65%	3.2	Visual
202.	Poor workmanship		.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9280921
4.4.2.16	Unsealed Outer Fiber Box				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Marking of bag misleading or unidentifiable		.40%	3.2	Visual
102.	Bag improperly sealed		.40%	3.2	Visual
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-50869E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Unsealed Inner Box				9280921
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201.	Incorrect number of trays		.65%	3.2	Visual
202.	Incorrect number of fuzes		.65%	3.2	Visual
203.	Fuze inverted		.65%	3.2	Visual
204.	Plastic film missing		.65%	3.2	Visual
205.	Improper strapping		.65%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9280921
4.4.2.18	Sealed Fiber Box				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201.	Contents loose		.65%	3.2	Manual
202.	Box damaged		.65%	3.2	Visual
203.	Improper sealing		.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Dimensional control of plastic parts. In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (see Note 1) a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification, As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in applicable paragraphs after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective parts shall be removed from production, If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request. Contractor design of gages and test equipment required to perform inspections listed herein shall be forwarded to Commander. ARDC, Dover, NJ 07801-5001, ATTN: AMSMC-QAF-I for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to ARDC, Dover, NJ 07801-5001, ATTN: AMSMC-QAF-S. If there is a change in material, or in the cycle time, or if the cavity is reworked, or a new cavity is used, a ne curing time shall be established and approved.

4.4.3.2 Dimensional conrotl of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the current version before use.

least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.4.3.3 Check test for deterioration of detonators. If the total time between original acceptance of any lot and the assembly of that lot into the fuze exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in MIL-D-14978 immediately before the detonator lot is assembled into the fuze. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the fuze (see 6.6). The test shall be conducted at Government expense without cost to the contractor who loaded the detonator or the contractor assembling the detonator into the fuze and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while detonator lot was under the responsibility of either contractor. The Contracting Officer shall arrange to have the contractor reimbursed for the expense incurred in the performance of check tests.

4.4.3.4 Pushout-test of hammerweight assembly on centerplate assembly. Forty-two (42) centerplate assemblies shall be selected from each lot and the hammerweight assembly on each of the three legs of each assembly shall be subjected to this test. If two (2) or more hammerweight assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the currentversion before use.

4.4.3.5 Seperation test hammerweight on centerplate assembly. Forty-two (42) centerplate assemblies shall be selected from each lot and the hammerweight pins on each of the three legs of each assembly shall be subjected to this test. If two (2) or more hammerweight pins fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected.

4.4.3.6 Retention check of firing pin spring on centerplate assembly. After completion of test specified in 4.4.3.5, the forty-two (42) centerplate assemblies shall be subjected to this test. If two (2) or more assemblies fail to comply with the drawing requirement, the lot shall be rejected.

4.4.3.7 Verification of heat treat of spring setback. After completion of the push test of simulated setback pin, the three (3) setback springs exhibiting the lowest push test force shall be subjected to this test. If any setback spring fails to comply with the requirement specified on the applicable drawing, the heat treat batch represented by the sample shall be rejected.

4.4.3.8 Transportation vibration. Only those fuze assemblies selected for the functioning and non-functioning tests shall be subjected to this test.

4.4.3.9 Functioning. After completion of the transportation vibration test, beginning with the first lot produced and continuing until three (3) consectutive lots have been accepted under the criteria of this paragraph, three hundred (300) fuzes with loaded spitback assemblies shall be assemblied into rounds with inert loaded cup and skirt assemblies and subjected to this test. One hundred and fifty (150) each shall be fired to impact against vertical mild steel plate 1/2 inc. thick and a horizontal gravel pad as specified in 4.5.20. If the combined total of fuzes not functioning exceeds nine (9) or exceeds five (5) in either phase or one (1) premature burst occurs, the lot shall be rejected.

4.4.3.10 Functioning, regular production. After three (3) consectutive lots have met the criteria of 4.4.3.9, the following shall apply:

Gravel: Eighty (80) fuzes shall be selected for this test. Accept if two (2) or less fuzes fail to function and no premature burst occurs and reject if five (5) or more fuzes fail to function or if one (1) premature burst occurs. When three (3) or four (4) fuzes fail to function in the first sample of eighty (80) an additional eighty (80) fuzes shall be subjected to this test. If a total of six (6) or less in the cumulative sample of one hundred sixty (160) fuzes fail to function and no premature burst occurs, the lot shall be accepted. If a total of seven (7) or more in the cumulative sample fail to function or if one (1) premature burst occurs, the lot shall be rejected. The test shall be performed as specified in 4.5.24.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

Plate: Eighty (80) fuzes shall be selected for this test. Accept if two (2) or less fuzes fail to function and no premature burst and reject if five (5) or more fuzes fail to function or if one (1) premature burst occurs. When three (3) or four (4) fuzes fail to function in the first sample of eighty (80) an additional eighty (80) fuzes shall be subjected to this test. If a total of six (6) or less in the cumulative sample of one hundred sixty (160) fuzes fail to function and no premature burst occurs, the lot shall be accepted. If a total of seven (7) or more in the cumulative sample fail to function or if one (1) premature burst occurs, the lot shall be rejected. The test shall be performed as specified in 4.5.24.

4.4.3.11 Non-functioning. After completion of the transportation vibration test fifty (50) fuzes with loaded spitback assemblies shall be assembled into rounds with inert loaded cup and skirt assemblies and subjected to this test. Accept if one (1) or less fuzes function and no premature burst occurs, and reject if four (4) or more fuzes function. If two (2) or three (3) fuzes function in the first sample of fifty (50), an additional fifty (50) fuzes, assembled as above shall be subjected to this test. Accept if a total of three (3) fuzes function and no premature burst occurs, in the cumulative sample of one hundred (100). If a total of four (4) or more fuzes function in the cumulative sample of one hundred (100), the lot shall be rejected. The test shall be performed as specified in 4.5.25.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in the Tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-47078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Salt Spray. This test shall be conducted in accordance with ASTM-B-117. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.2 Push test of simulated setback pin into spring setback. The spring setback shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied to a simulated setback pin. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.3 Verification of heat treat of spring setback. The spring setback shall be subjected to the Knoop hardness reading in accordance withe ASTM-D-1474. This test is a destructive test. Parts so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the currentversion before use.

4.5.4 Torque test of verge assembly. The verge assembly shall be placed in an approved fixture and the torque specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.5 Disassembly test of verge assembly. The verge assembly shall be placed in an approved fixture and the disassembly force specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.6 Deflective test of centerplate. The centerplate shall be placed in an approve fixture and the force specified on the applicable drawing shall be applied. This is a destructive test. Parts so tested shall not be returned to the lot.

4.5.7 Push off test of pinion assembly. The pinion assembly shall be placed in an approved fixture and the load specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.8 Torque test of pinion assembly (when applicable). The pinion assembly shall be placed in an approved fixture and the torque specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.9 Arming delay time of escapement assembly. The escapement assembly shall be placed in an approved fixture and rotated at the speed specified on the applicable drawing. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.10 Arming of escapement assembly. The escapement assembly shall be placed in an approved fixture and rotated at the arming speed specified on the applicable drawing. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.11 Non-arming of escapement assembly. The escapement assembly shall be placed in an approved fixture and rotated at the non-arming speed specified on the applicable drawing. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.12 Stake of detonator on rotor assembly. The rotor assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.5.13 Pull test of spring setback on escapement assembly. The escapement assembly shall be placed in and approved fixture and the force specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.14 Arming of centerplate assembly. The centerplate assembly shall be placed in an approved fixtured and rotated at the arming speed specified on the applicable drawing. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.15 Pushout test of hammerweight assembly on centerplate assembly. The centerplate assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied to the hammerweight pin. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.16 Separation of hammerweight assembly on centerplate assembly. The centerplate assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied to the hammerweight pin. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.17 Retention check of firing pin spring on centerplate assembly. This test may be performed manually. The requirement specified on the applicable drawing shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.18 Static push test of rotor and gear sector assembly. The rotor and gear sector assembly shall be placed in an approved fixture and the force specified on the apllicable drawing shall be applied. This is a destructive test. Parts so tested shall not be returned to the lot.

4.5.19 Air pressure test of fuze crimped joint. The fuze shall be placed in an approved fixture and a measured quantity of air applied to produce the required air pressure specified on the applicable drawing. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.20 Security of stake of hammerweight assembly. The hammerweight assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. This is a destructive test. Parts so tested shall not be returned to the lot.

4.5.21 X-ray of fuze assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

4.5.21.1 Prior to jolt and jumble testing. Armed or partially armed fuze assemblies shall be determined by x-ray equipment or any other method satisfactory to the Contracting Officer. This test shall be conducted in two (2) phases:

a. From the top of the fuze assembly down.
b. From the side.

4.5.21.2 After jolt and jumble testing. Armed or partially armed or setback pin retracted shall be determined by x-ray equipment or any other method satisfactory to the Contracting Officer. This test shall be conducted in two (2) phases:

a. From the top of the fuze assembly down.
b. From the side.

4.5.22 Jolt and jumble testing. The fuze shall be tested with the procedures specified in Test 101.1 and Test 102.1 of MIL-STD-331. These tests are destructive tests. Parts so tested shall not be returned to the lot.

4.5.23 Transportation vibration. The fuzes packed in their regular shipping containers shall be tested in accordance with Test 119 of MIL-STD-331. Simulated fuzes may be used to insure a full box. Parts subjected to subsequent tests shall not be returned to the lot.

4.5.24 Functioning. The fuze shall be assembled with a loaded spitback assembly then assembled as a cartridge in accordance with Dwg. 9287439.

Gravel: The cartridge shall be fired from a M203 launcher to impact at approximately 200 meters from the launcher on a six inch thick loose gravel pad. The gravel pad used shall have a 1/2 inch maximum stone size.

Plate: The cartridge shall be fired from a M203 launcher to impact at 125 feet from the launcher on a vertical mild steel plate 1/2 inch thick.

4.5.25 Non-functioning.

4.5.25.1 Hard target (as applicable). The fuze shall be assembled with a loaded spitback assembly then assembled as a cartridge in accordance with Dwg. 9287439. The cartridge shall be fired from a M203 launcher against a vertical target of 16 gauge steel sheet backed by 5/8 inch plywood sheet placed forty four (44) plus or minus (±) one (1) feet from point of fire.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

4.5.25.2 Soft target (as applicable). The fuze shall be assembled with a loaded spitback assembly then assembled as a cartridge in accordance with Dwg. 9287439. The cartridge shall be fired from a M203 launcher against a vertical soft target approved by the Procuring Agency, placed forty four (44) plus or minus (±) one (1) feet from piont of fire.

5. PACKAGING.

5.1 Preservation. Preservation shall be in accordance with Dwg. 9280921.

5.1.1 Packing. Packing shall be Level B unless otherwise specified. Level B packing shall be in accordance with Dwg. 9280921. Level A will be the same as Level B packing except that a wooden box complying with MIL-B-2427 shall be substituted for the fiberboard box specified on Dwg. 9280921.

5.2 Marking.

5.2.1 Level A and Level B. Marking for Level A packaging shall be in accordance with Dwgs. 9280921 and 8796522. Marking for Level B packaging shall be in accordance with Dwgs. 9280921 and 8799112 and Code of Federal Regulations, Title 49, Parts 100-199.

5.3 Unitization. Unitization shall be in accordance with instructions issued by the procuring agency.

5.4 Shipping. When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES.

6.1 Intended use. The component covered by this specification is intended for use with Cartridge, 40mm, HEDP, M433.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078(AR). Submit equipment designs as required to Commander, ARDC, ATTN: AMSMC-QAF-I(D), Dover, NJ 07801-5001. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examination or tests to Commander, ARDC, ATTN: AMSMC-QAF-S(D), Dover, NJ 07801-5001.

6.5 Submission of test data. In addition to the normal distribution of record, when the fuzes are procured by ARDC(R), one copy of all ballistic data and ammunition data cards shall be forwarded to Commander, ARDC, ATTN: AMSMC-QAF-S(D), Dover, NJ 07801-5001.

6.6 Cost or check test. The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the detonator assembly. The tests shall be conducted at Governement expense without cost to the contractor who loaded the detonator assembly of to the contractor assembling the detonator assembly in the fuze; and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as direct result of carelessness in handling, storage, etc., permitted while the detonator assembly lot was under jurisdiction of either contractor.

6.7 Premature burst. A premature burst is considered to have occurred if the round functions in the gun bore or in flight.

6.8 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by and identified as, Englewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.9 Changes from previous issue. Astericks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A468)

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-50869E	FUZE PIBD, M550, LESS SPITBACK ASSEMBLY, METAL PARTS FOR LAP

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required *interpretation*, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.