INCH-POUND

MIL-F-50950C (AR)
06 January 1993
SUPERSEDING
MIL-F-50950B
30 July 1980

MILITARY SPECIFICATION

FUZE, GRENADE, GP: M223

This Specification is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, quality assurance provisions, and preparation for delivery for the fabrication of parts, assembling and packing of one type of fuze designated as Fuze, Grenade, GP: M223, (See 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-D-14978 - Detonator Stab, M55, Loading, Assembling and Packing
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U S Army ARDEC, ATTN SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A FSC 1330
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.9)

U.S. Army Armament Research and Development Command

Product and Packaging Drawings

9206125	- Box, Polypropylene, Inner, for Fuze, General Purpose Grenade: M223
9206126	- Box, Fiber, Outer, for Fuze, General Purpose Grenade: M223
9215350	- Fuze, General Purpose Grenade: M223
9329425	- Fuze, General Purpose Grenade: M223, Inert

PUBLICATIONS

Code of Federal Regulations

Title 49 - Transportation, parts 100-199

(The code of Federal Regulations is available from the superintendent of Documents, US Government Printing Office, Washington, D.C. 20402. Orders should specify "49 CFR 100-199 (latest revision)").

(Copies of other Government documents, drawing, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM)

ASTM B 117-73	- Standard Method of Salt Spray (Fog) Testing
ASTM E 290	- Semi-Guided Bend Test for Ductility of Metallic Materials
ASTM A 666	- Austenitic Stainless Steel, Sheet Strip, Plate, and Flat Bar for Structural Applications

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA. 19103).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts. The parts and assemblies shall comply with all requirements specified on Drawing 9215350, all associated drawings and with all requirements specified in applicable specifications.

3.3 First article testing. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3.2).

3.4 Torque to unthread arming screw on fuzes procured for M42/46 and M77 grenades.

3.4.1 Torque to unthread arming screw, M42/46 grenade. With safety clip removed, the maximum torque required to rotate the arming screw out of the slide shall be 1.0 inch-ounce when tested as specified in 4.5.10.2.1.

3.4.2 Torque to unthread arming screw, M77 grenade. With the safety clip removed, the maximum torque required to rotate the arming screw out of the slide shall be 1.0 inch-ounce for any individual reading when tested as specified in 4.5.10.2.2. The sample mean must be within 0.0 and 0.8 inch-ounces and the sample shall have a range no greater than 0.9 inch-ounce. In addition, the average of the sample means for any fuze lot shall not exceed 0.500 inch-ounce.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

3.5 Lubrication. Details of the proposed procedure for lubricating the weight (Dwg. 9215355) to be used by the contractor shall be submitted in writing to the Government Technical Agency and written approval received prior to initiation of production. The proposed procedure shall include materials, process and equipment to be used by the contractor, detailed method of control including limits for time, temperature, concentration and all other information pertinent to the processes. Approval of process, materials, or equipment implies no guarantee of acceptance of the results obtained.

3.6 Workmanship. All parts and assemblies shall be fabricated, finished, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous, however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Housings	9215357	50 (Same 50 for compressive force test)
Slides	9215359	50
Weights	9215355	50
Arming Screws	9215354	50
Arming Screws and Weight Assemblies	9215352	(Same 50 for Salt Spray)
Arming Springs	9215360	50 (Same 50 for Load Test)
Covers	9215366	50 (10 for Direction of Grain Test)
Safety Clips	9215356	50
Slide Assemblies	9215358	50 (Same 50 for Removal Force Test of Safety Pin and Force Test of Crimp of Detonator)
Cover Specimens (from material stock used for producing covers)	9215366	6
M223 Fuzes (packed as intended for regular production)	9215350	50 (Same 50 for Pull Test, Torque Test and Fuze Arming Test)

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE Fuze, Grenade, GP: M223	SHEET 1 OF 3	DRAWING NUMBER See below
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Housing (Dwg. 9215357) Examination for defects Compressive force test	 50(a),100% 50, 100%	 3.2 3.2	 4.4.2.1 4.5.1
	Slide (Dwg. 9215359) Examination for defects	 50(a),100%	 3.2	 4.4.2.2
	Arming Screws (Dwg. 9215354) Examination for defects Salt spray test	 50, 100% 50, 100%	 3.2 3.2	 4.4.2.3 4.5.5
	Weight (Dwg. 9215355) Examination for defects	 50(a),100%	 3.2	 4.4.2.4

NOTES

a. All tooling and cavities used for production shall be represented in this sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Fuze, Grenade, GP: M223	2 OF 3	See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Arming Spring			
	(Dwg. 9125360)			
	Examination for defects	50	3.2	4.4.2.6
	Load test	50	3.2	4.5.4
	Safety Clips			
	(Dwg. 9215356)			
	Examination for defects	50	3.2	4.4.2.7
	Slide Assemblies			
	(Dwg. 9215358)			
	Examination for defects	50	3.2	4.4.2.8, 4.4.2.9
	Removal force test of safety pin, coiled	50	3.2	4.5.8
	Force test of crimp detonator	50	3.2	4.5.9
	Distance to safety pin, max.	50	3.2	4.5.7
	Cover specimen from material stock to be used for producing cover			
	(Dwg. 9215366)			
	180 degree bend test	6	3.2	4.5.2
	Arming screw and weight assembly			
	(Dwg. 9215352)			
	Threading load test	50	3.2	4.5.6

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Fuze, Grenade, GP: M223	SHEET 3 OF 3	DRAWING NUMBER See below
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Cover (Dwg. 9215366)			
	Examination for defects	50(a),100%	3.2	4.4.2.5
	Direction of grain test	10	3.2	4.5.3
	M223 Fuze picked as intended for regular production (Dwg. 9215350)			
	Examination for defects	50	3.2	4.4.2.11
	Pull test for removal of safety clip	50	3.2	4.5.10.1
	Torque test to unthread arming screw	50	3.4.1	4.5.10.2.1
			3.4.2	4.5.10.2.2
	Fuze Arming test	50	3.2	4.5.10.3

NOTES

a. All tooling and cavities used for production shall be represented in this sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition each inspection lot shall contain:

a. Housings of one lot interfix number from one manufacturer.

b. Slides of one lot interfix number from one manufacturer.

c. Weights of one lot interfix number from one manufacturer.

d. Arming screws of one lot interfix number from one manufacturer.

e. Covers of one lot interfix number from one manufacturer.

f. Detonators of one lot interfix number from one manufacturer. (See 4.5.12).

g. Arming springs of one lot interfix number from one manufacturer.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels cited in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:04Z
Check the source to verify that this is the currentversion before use.

TABLE II. Attributes sampling inspection

Lot Size	INSPECTION LEVELS					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150001 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality assurance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.12). When required, the contractor shall demonstrate that the effectiveness of the proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Housing	1 OF 1	9215357
			NEXT HIGHER ASSEMBLY: 9215352

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Compressive force test	Level III	3.2	4.5.1
102	Diameter of outer holes in flange, max. (2 places)	Level III	3.2	Gage
103	Profile from bottom to top of angled surface (4 places)	Level III	3.2	Gage
104	Height from base to top surface of tunnel roof, min.	Level III	3.2	Gage
105	Total tunnel length as measured between roof ends	Level III	3.2	Gage
106	Height from base to top of rectangular (safety clip) cutout, max.	Level III	3.2	Gage
107	Height from base to inside roof of cavity	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Slide	1 OF 1	9215359
			NEXT HIGHER ASSEMBLY: 9215350

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Cricital	None defined			
Special				
a	Diameter of middle (arming screw) hole counterbore	100%	3.2	Gage
b	Depth of middle (arming screw) hole counterbore	100%	3.2	Gage
Major				
101	Width across ears, min.	Level III	3.2	Gage
102	Symmetry of width across ears with width of body	Level III	3.2	Gage
103	Depth of rectangular recess in underside	Level III	3.2	Gage
104	Width of rectangular recess	Level III	3.2	Gage
105	True position of largest (detonator) hole	Level III	3.2	Gage
106	True position of middle (arming screw) hole	Level III	3.2	Gage
Minor				
201	Diameter of detonator flash hole, max.	Level V	3.2	Gage
201	Mold or cavity identification marking missing or incorrect	Level V	3.2	Visual
203	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Screw, arming	1 OF 1	9215354
			NEXT HIGHER ASSEMBLY: 9215352

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Salt spray test	4.5.5	3.2	4.5.5
102	Length of point below flange, min.	Level II	3.2	Gage
103	Diameter of counterbore, min.	Level II	3.2	Gage
104	Concentricity of counterbore with outside	Level II	3.2	Gage
105	Depth of counterbore, min.	Level II	3.2	Gage
106	Outside diameter at counterbore end, min.	Level II	3.2	Gage
107	Length from thread to counterbore end	Level II	3.2	Gage
108	Profile of point, to and including flange	Level II	3.2	Gage
109	Pitch diameter of thread	Level II	3.2	Gage
110	Major diameter of thread	Level II	3.2	Gage
111	Length from flange to counterbore end of threads	Level II	3.2	Gage
112	Flange thickness, min.	Level II	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Weight	1 OF 1	9215355
			NEXT HIGHER ASSEMBLY: 9215352

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width of rectangular portion	Level II	3.2	Gage
102	Length of rectangular portion	Level II	3.2	Gage
103	True position of outside diameter of cylindrical portion	Level II	3.2	Gage
104	Depth of smaller diameter counterbore	Level II	3.2	Gage
105	Pitch diameter of thread	Level II	3.2	Gage
106	Minor diameter of thread	Level II	3.2	Gage
107	True position of thread pitch diameter	Level II	3.2	Gage
108	Total height	Level II	3.2	Gage
Minor				
201	Height of rectangular portion, min.	Level V	3.2	Gage
202	Mold or cavity identification symbol missing or incorrect	Level V	3.2	Visual
203	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Cover	1 OF 1	9215366
			NEXT HIGHER ASSEMBLY: 9215350

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	180 degrees Bend test	4.5.2	3.2	4.5.2
102	Direction of grain test	4.5.3	3.2	4.5.3
103	Straightness of bottom surface	Level III	3.2	Gage
104	Height of center tab	Level III	3.2	Gage
105	Width of center tab	Level III	3.2	Gage
106	Symmetry of width of center tab	Level III	3.2	Gage
107	True position of center semi-circular cutout including slot length to center tab at max material condition	Level III	3.2	Gage
Minor				
201	Inside diameter between diagonally opposite tabs, max. (2 places)	Level V	3.2	Gage
202	Evidence of crack in any bend	Level V	3.2	Visual
203	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Spring, Arming	1 OF 1	9215360
			NEXT HIGHER ASSEMBLY: 9215350

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter in free state	Level III	3.2	Gage
102	Length in solid state, max.	Level III	3.2	Gage
103	Length in free state, min.	Level III	3.2	4.5.4
104	Load test	Level III	3.2	4.5.15
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Clip, Safety	1 OF 1	9215356
			NEXT HIGHER ASSEMBLY: 9215352

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width of material	Level III	3.2	Gage
Minor				
201	Free state gap, as noted, max. (after removal of pin)	Level V	3.2	Gage
202	Length from larger diamond datum to end of loop	Level V	3.2	Gage
203	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Slide Assembly (Prior to assembly of detonator)	1 OF 1	9215358
			NEXT HIGHER ASSEMBLY: 9215350

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Distance to safety pin, max.	100%	3.2	4.5.7
Major				
101	Removal force test of safety pin	Level III	3.2	4.5.8
102	Safety pin protrusion exceeds permitted amount	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Slide Assembly	1 OF 1	9215358
			NEXT HIGHER ASSEMBLY: 9215350

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Force test of crimp of detonator	Level II	3.2	4.5.9
102	Height of slide in detonator area including any crimp material, max.	Level II	3.2	Gage
103	Detonator above flush	Level II	3.2	Gage
104	Detonator missing or inverted (green end of detonator showing through top to hole)	Level II	3.2	Visual
105	Damaged safety pin	Level II	3.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Housing Assembly	1 OF 1	9215352
			NEXT HIGHER ASSEMBLY: 9215350

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Threading load test of arming screw in the weight	100%	3.2	4.5.6
Major				
101	Freedom of movement of weight and arming screw assembly	Level III	3.2	4.5.11
102	Height to bottom or arming screw flange, min. in condition noted	Level III	3.2	Gage
103	Arming screw point damaged	Level III	3.2	Gage
Minor				
201	Looped end of safety clip not surrounding safety pin hole in tunnel roof (indicating reversed assembly)	Level V	3.2	Visual
202	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Fuze, General Purpose Grenade: M223	1 OF 2	9215350
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Depth from bottom of cover to point of arming screw, max., in condition noted	100%	3.2	Gage
2	Safety pin missing or damaged	100%	3.2	Gage
3	Slide assembly protruding from housing indicating armed or partially armed condition	100%	3.2	Gage
4	Cover tabs (4) not seated on flange of housing or cover loose	100%	3.2	Gage
5	Safety clip missing or double ends not protruding beyond end of housing tunnel	100%	3.2	Gage
6	Area of housing tunnel roof containing safety pin hole missing	100%	3.2	Gage
7	Area of housing tunnel roof which covers detonator missing	100%	3.2	Gage
Major				
101	Test for minimum force for removal of safety clip	Level III	3.2	4.5.10.1

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Fuze, General Purpose Grenade: M223	2 OF 2	9215350
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
102	Torque test to unthread arming screw, M42/46 grenade	Level III	3.4.1	4.5.10.2.1
103	Torque test to unthread arming screw, M77 grenade	(a)	3.4.2	4.5.10.2.2
104	Fuze arming test	Level III	3.2	4.5.10.3
105	True position of outer holed	Level III	3.2	Gage
106	Part(s) missing or damaged (excluding safety pin)	Level III	3.2	Visual
107	Arming screw point damaged (when viewed through cover cutout)	Level III	3.2	Visual
108	Any portion of material exposed beyond tab	Level III	3.2	Visual
109	White marking missing (PN 9215350-1)	100%	3.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual
202	Test for maximum force for remvoal of safety clip	Level V	3.2	4.5.10.1

NOTES

a. Four assembled fuzes, with safeties intact, shall be randomly selected from a consecutively produced quantity not to exceed three thousand (3000).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Sleeve, Polypropylene, With Bag, Inner Pack (Prior to insertion into barrier bag)	1 OF 1	9206125
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Sleeve damaged, contents exposed	Level III	3.2	Visual
Minor 201	Contents loose	Level V	3.2	Manual

NOTES

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Sealed Barrier Bag	1 OF 1	9206125
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Barrier bag waterproofness destroyed by separation of heat seal, or rip, tear or puncture	Level III	3 2	Visual
Minor				
201	Marking incomplete, incorrect or illegible	Level V	3.2	Visual
202	Evidence of poor workmanship	Velev V	3.6	Visual

NOTES

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Box, Fiber, Outer (Sealed)	1 OF 1	9206126
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Box damaged - contents exposed	Level III	3.2	Visual
102	Sealing strip missing, incomplete or badly wrinkled	Level III	3.2	Visual
Minor				
201	Contents loose	Level V	3.2	Manual
202	Marking incomplete, incorrect or illegible	Level V	3.2	Visual
203	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Slide Assembly, Inert	1 OF 1	9327873
			NEXT HIGHER ASSEMBLY: 9327872

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Inert marking missing, incomplete, illegible or wrong color	100%	3.2	Visual
2	Dot or stripe missing	100%	3.2	Visual
Major				
101	Force test of crimp of detonator	Level III	3.2	4.5.9
102	Height of slide in detonator area including any crimp material, max.	Level III	3.2	Gage
103	Detonator above flush	Level III	3.2	Gage
104	Detonator missing or inverted (green end of detonator showing through to top of hole)	Level III	3.2	Visual
105	Damaged safety pin	Level III	3.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-F-50950C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Fuze, General Purpose Grenade: M223, Inert	1 OF 2	9327872
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Inert marking missing, incomplete, or illegible (2 places)	100%	3.2	Visual
2	Dot missing	100%	3.2	Visual
Major				
101	Depth from bottom of cover to point of arming screw, max, in condition noted	Level III	3.2	Gage
102	Safety pin missing or damaged	Level III	3.2	Visual
103	Slide assembly protruding from housing indicating armed or partially armed condition	Level III	3.2	Visual
104	Cover tabs (4) not seated on flange of housing or cover loose	Level III	3.2	Visual/Manual
105	Test for minimum force for removal of safety clip	Level III	3.4.1	4 5.10.1
106	Torque test to unthread arming screw	Level III	3 4.1	4.5.10 2.1
107	Fuze arming test	Level III	3.4.1	4 5 10.3
108	True position of outer holes	Level III	3.4.1	Gage
109	Safety clip missing or double ends not protruding beyond end of housing tunnel	Level III	3.4.1	Visual
110	Part(s) missing or damaged (excluding safety pin)	Level III	3.4.1	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.16	Fuze, General Purpose Grenade: M223, Inert	SHEET 2 OF 2	9327872
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
111	Arming screw point damaged (when viewed through cover cutout)	Level III	3.4.1	Visual
112	Any portion of material exposed beyond tab	Level III	3.4.1	Visual
Minor				
201	Test for maximum force for removal of safety clip	Level V	3.2	4.5.10.1
202	Evidence of poor workmanship	Level V	3.6	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Compressive force test of housing. The total height of the housing shall be measured and recorded. The same housing shall be mounted in an approved fixture and the load, as specified on the applicable drawing, shall be applied and removed. The total height of the same housing shall be re-measured and compared with the original measurement for compliance with the applicable requirement. All inspection equipment used shall be approved in accordance with the provisions of 4.4.4. (Destructive Test).

4.5.2 180 degrees bend test of bend test specimen from material stock to be used for producing covers.

4.5.2.1 Sampling lots. For purpose of sampling, a lot shall consist of all sheets or strips of the same thickness, class, condition of temper, and finish rolled from the same heat, and heat treated at the same time. In case the heat cannot be identified, a lot shall consist of not more than 50 pieces of the same class, condition of temper, finish, and thickness. If coils are used, specimens for this test shall be taken from each coil of material stock to be used for producing covers.

4.5.2.2 Sampling. Two transverse bend test specimens shall be taken from each lot of flat sheets and strips. One transverse bend test specimen shall be taken from each end of each coil. Otherwise, the two specimens shall not be taken from the same piece.

4.5.2.3 Test procedure. The size of the test specimens shall be as specified in ASTM E 290. Each of the specimens selected shall be oriented such that the axis of the bend test is at an angle around a diameter determined as specified in ASTM A 666. Bending shall be performed by using the methods and procedures specified in ASTM E 290. After bending to achieve a 180 degree bend angle, each specimen shall be visually examined. If any specimen shows any cracking in the area of the bent portion, the quantity of material represented by the failing specimen shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.3 Direction of grain test of cover.

4.5.3.1 Coiled stock. Observation shall be made to determine that the die orientation for stamping the covers, in relation to the direction of feed of the material from the coil, is in accordance with the requirement shown on the applicable drawing. Deviation from the requirement shall be cause for rejection of all the covers thus produced. This determination shall be made at the start of production and a minimum of once per week of production, or portion thereof, unless otherwise directed by the Contracting Officer.

4.5.3.2 Strip stock from sheets. Twenty-five (25) strips from each lot shall be selected and subjected to this test prior to producing covers. Each of these strips shall be tested for direction of grain using any method satisfactory to the Contracting Officer. Having thus determined the grain direction of the strip, observation shall then be made to determine that the die orientation for stamping the covers in relation to the direction of feed of the strip and the direction of the grain of the strip, is in accordance with the requirement specified on the applicable drawing.

If any strip has grain direction contrary to the required direction for processing through the cover stamping die, the quantity of strips represented by the failing sample shall be rejected.

4.5.4 Free length of arming spring. The arming spring shall be mounted in an approved fixture in accordance with 4.4.4 and compressed to the specified height. Free length shall be measured after release from fixture.

4.5.5 Salt spray test of arming screw. The arming screw shall be subjected to the salt spray test using the procedures specified in ASTM B 117-73. The exposure time shall be 96 hours. This is a destructive test. Parts so tested shall not be returned to the lot.

4.5.5.1 Batch-type process. When the parts are produced in a batch-type process, ten (10) arming screws shall be selected from each batch and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specified requirement, the batch represented by the failing part shall be rejected. The test shall be performed using equipment in accordance with 4.4.4.

4.5.5.2 Continuous-type process. When the parts are produced in a continuous-type process, five (5) arming screws shall be selected from each four (4) hours of production, or portion thereof, and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specified requirement, the parts represented by the sample shall be rejected. The test shall be performed using equipment in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.5.3 Lot plan. Ten (10) arming screws shall be selected from each lot and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specified requirement, the lot represented by the failing sample shall be rejected. The test shall be performed using equipment in accordance with 4.4.4.

4.5.6 Thread load test of arming screw and weight. After assembling the arming screw to the weight, the assembly shall be placed in an approved inspection device. The assembly shall be brought to the specified dimension and the load applied in the direction shown. Failure of the thread engagement to withstand the load specified on the applicable drawing shall cause the inspection device to initiate a signal indicating a failing assembly. Such failing assemblies shall be ejected to a locked container. Provisions shall be made for the use of masters and calibration checks to verify the accuracy of the equipment. Failure of any fixture to respond properly when each master is used or each calibration check is performed, shall cause the production from that fixture, since the last acceptable check was conducted, to be rejected. Each fixture shall be similarly qualified for use at the start of production of each operating shift and whenever any adjustment or repair is made to fixture. If an alternate test method is desired for assuring the adequacy of threads, the test method and inspection equipment to be used will be forwarded for approval.

4.5.7 Distance to safety pin, max. Each assembly shall be inspected for the applicable drawing requirement by a suitable fixture. This fixture may be an integral part of the assembly machine. Any part failing to meet the drawing requirement shall cause the fixture to initiate a signal indicating a failing assembly. Such failing assemblies shall be ejected to a reject container. Provisions shall be made for the use of masters and calibration checks to verify the accuracy of the equipment. Failure of the fixture to respond properly when each master is used or each calibration check is performed shall cause the production from that machine since the last acceptable check was conducted to be rejected. Each fixture shall be similarly qualified for use at the adjustment or repair is made to a fixture.

NOTE: Inspection Equipment, Operating and Calibration Instructions submitted for approval in accordance with 4.4.4 shall indicate a calibration frequency for the fixture and masters used for this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.8 Removal force test of safety pin of slide assembly. The test shall be performed on assemblies which have passed Critical Defect 1 of 4.4.2.8. The slide assembly shall be mounted in an approved fixture in accordance with 4.4.4 and a removal force as specified on the applicable drawing shall be applied. After application of the load, the safety pin must successfully pass the requirement of Critical Defect 1 of 4.4.2.8.

WARNING: The following tests are conducted on assemblies containing an explosive component. Test barricades (where used), procedures, and equipment shall have prior approval.

4.5.9 Force test of crimp of detonator of slide assembly. The slide assembly shall be mounted in an approved fixture and the load specified on the applicable drawing shall be applied. The load shall be applied at the rate specified on the drawing. After the load is removed, the assembly shall be inspected to assure that the applicable drawing requirement has been met. the test shall be performed using equipment in accordance with 4.4.4 and the method used shall not cause damage to any slide assembly. Slide assemblies which pass this test may be returned to the lot.

4.5.10 Pull test for removal of safety clip from fuze, torque test to unthread the arming screw of fuze and fuze arming test.

4.5.10.1 Safety clip removal. The fuze shall be mounted in an approved fixture in accordance with 4.4.4 and the safety pin shall be removed. The safety clip shall then be pulled free from the fuze. If the removal force fails to comply with the requirement specified on the applicable drawing, the fuze shall be classed defective but shall be identified and retained in the sample.

4.5.10.2 Torque test to unthread arming screw on fuzes procured for M42/46 and M77 grenades.

4.5.10.2.1 Torque test to unthread arming screw, M42/46 grenade. After testing as specified in 4.5.10.1, the same fuzes shall be subjected to this test. Using the same fixture to prevent the slide from arming, the torque required to rotate the arming screw out of the slide shall be measured using equipment approved in accordance with 4.4.4. If the torque exceeds the amount specified in 3.4.1 the fuze shall be classed defective.

4.5.10.2.2 Torque test to unthread arming screw, M77 grenade. After testing as specified in 4.5.10.1, the same fuzes shall be subjected to this test. A one pound (1 lb) weight will be attached to the fuze through its housing and the slide shall be secured to prevent arming. The test will be conducted using a fixed torque

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

watch from which this fuze/weight will be suspended. The torque required to rotate the arming screw out of the slide shall be measured using equipment approved in accordance with 4.4.4. If any sample of fuzes fails to meet any requirement of 3.4.2 the fuzes represented by the sample shall be rejected.

4.5.10.3 Fuze arming test. After testing as specified in 4.5.10.2, the same assemblies shall be subjected to this test. While maintaining the armed arming screw free of the slide, the fixture device for preventing slide movement shall be withdrawn permitting the slide to move to the armed position. Fuzes failing to comply with the specified arming distance, as measured with equipment approved in accordance with 4.4.4, shall be classed defective and identified.

4.5.10.4 Disposition. Fuzes passing all the above tests may be returned to the lot providing the following provisions are accomplished: The slide shall be returned to the unarmed position, the arming screw shall be rotated to the unarmed position, and the safety clip shall be properly reassembled to the fuze. The length and diameter of the safety pin shall be verified for compliance with Dwg. 9215255. The safety pin shall then be reassembled to the fuze. The maximum height of the safety pin, as measured from the bottom of the cover, shall not exceed the maximum dimension specified on Dwg. 9215350. Both these verification checks shall be performed using equipment approved in accordance with 4.4.4. The reassembled fuze shall then be subjected to, and must pass all the critical defect inspection requirements of 4.4.2.11 prior to being returned to the lot.

4.5.11 Freedom of movement of weight and arming screw assembly in housing. This test shall be performed in the following manner. With the safety clip removed, the housing assembly shall be turned downward. The weight and arming screw assembly shall be allowed to fall out freely. Any weight and arming screw assembly (see Dwg. 9215352) which does not freely fall from the housing shall be classified defective.

4.5.12 Check test for deterioration of detonators (see MIL-D-14978). If the total time between original acceptance of any detonator lot and the assembly of that lot into the slides exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in MIL-D-14978 immediately before the detonator lot is assembled into the slides. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the slides (see 6.7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.13 Dimensional control of stamped parts. In place of the normal sampling associated with Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control to the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion or production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing the contractor presents objective evidence to the Contracting Officer to substantiate the request.

4.5.14 Dimensional control of cast parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the contracting Officer, a sample of at least three (3) parts (as cast) from each cavity shall be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of 5000 parts. Individual cavity identification must be provided.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test specified above. The contractor may request a change of inspection frequency providing the contractor presents objective evidence to substantiate the request to the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.15 Load test of arming spring. The arming spring shall be mounted in an approved fixture in accordance with 4.4.4 and the load to compress the spring to the height specified on the applicable drawing shall be observed.

5. PACKAGING

5.1 Preservation and packaging. Level C. The fuze shall be preserved and packaged in accordance with Dwg. 9206125.

5.2 Packing. Level C. The fuze, preserved and packaged as specified in 5.1, shall be in accordance with Dwg. 9206126.

5.3 Marking. Marking shall be in accordance with Dwgs. 9206125 and 9206126 and Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping. When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The M223 fuze is intended to be used with M42/46 GP, Grenades and the M77, GP Grenade.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.2).

6.3 Submission of inspection procedures and equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to: Commander, U.S. Army Research, Development and Engineetring Center, ATTN: SMCAR-QAR-I, Picatinny Arsenal, N.J. 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Inspection lots. It is noted that the size of inspection lots of components, assemblies or items of delivery may differ from the actual quantities contractually scheduled for delivery.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria per MIL-STD-1168 and sampling provisions of this specification are maintained.

6.5 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination the characteristic may be measured or gaged to determine acceptability.

6.5.1 Submission of results of contractor-conducted examinations and tests. Data shall be submitted in accordance with data item on the DD Form 1423 for the contract.

6.6 Submission of ballistic test data and ammunition data cards. In addition to the normal distribution of records, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to Commanding Officer, ARDEC, Picatinny Arsenal, N.J. 07806-5000, ATTN: SMCAR-QAR-Q.

6.7 Cost of check test. The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the detonator assemblies. The tests shall be conducted at Government expense without cost to the contractor who loaded the detonator assemblies, or to the contractor assembling the detonator assemblies into the slides; and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the detonator assembly lot was under the jurisdiction of either contractor.

6.8 Barricades. The contractor shall employ proper barricades and safety procedures when examinations or tests are conducted on assemblies containing an explosive component.

6.9 Drawings. Drawings listed in section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, U.S. Army Research and Development Command (ARRADCOM) or U.S. Army Armament Research and Development Center (ARDC) drawings. Technical data orginally prepared by these activities is not under the cognizance of ARDEC.

6.10 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

6.11 Subject term (key word) listing.

M42, M46, M77
Housing assembly
Slide assembly
Detonator stab, M55
Torque test to unthread arming screw
Arming test

6.12 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AC69)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1 The preparing activity must complete blocks 1, 2, 3, and 8 In block 1, both the document number and revision letter should be given

2 The submitter of this form must complete blocks 4, 5, 6, and 7

3 The preparing activity must provide a reply within 30 days from receipt of the form

NOTE This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	MIL-F-50950C	930106

3 DOCUMENT TITLE: FUZE, GERNADE, GP M223

4 NATURE OF CHANGE (Identify paragraph number and include proposed rewrite if possible Attach extra sheets if needed)

5 REASON FOR RECOMMENDATION

6 SUBMITTER

a NAME (Last First Middle Initial)	b ORGANIZATION
c ADDRESS (Include Zip Code)	d TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7 DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY

a NAME	b TELEPHONE (Include Area Code)
U S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial: 201-724-6627 (2) AUTOVON: DSN-880-6627
c ADDRESS (Include Zip Code) ATTN SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike Suite 1403 Falls Church VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.