# MILITARY SPECIFICATION

## FILLING KIT FOR 16XPM-05 BATTERY ASSEMBLY, TRAINING

### 1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of filling kit for 16XPM-05 Battery Assembly for Atomic Demolition Charge.

### 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipment
8861697 - Bag, Packing Ammunition, For Battery Filler Kit
9207801 - Filling Kit for 16XPM-05 Battery Assembly, Training



Source: https://assist.dla.mil -- Downloaded: 202640-26T04:04Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The filler kit shall comply with all requirements specified on the drawing (dwg) 9207801, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not Applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation

4.3.1.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection, examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II) and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

TABLE I

Major Characteristics

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-16 | all | 28-29 | 23 | 52-56 | 31 | 132-156 | 39 |
| 17 | 16 | 30-31 | 24 | 57-62 | 32 | 157-191 | 40 |
| 18 | 17 | 32-34 | 25 | 63-69 | 33 | 192-244 | 41 |
| 19-20 | 18 | 35-36 | 26 | 70-76 | 34 | 245-334 | 42 |
| 21 | 19 | 37-40 | 27 | 77-86 | 35 | 335-519 | 43 |
| 22-23 | 20 | 41-43 | 28 | 87-97 | 36 | 520-1120 | 44 |
| 24-25 | 21 | 44-47 | 29 | 98-112 | 37 | over-1120 | 45 |
| 26-27 | 22 | 48-51 | 30 | 113-131 | 38 | | |

TABLE II

Minor Characteristics

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-9 | all | 14-16 | 12 | 28-33 | 16 | 77-121 | 20 |
| 10 | 9 | 17-18 | 13 | 34-41 | 17 | 122-273 | 21 |
| 11 | 10 | 19-22 | 14 | 42-54 | 18 | over 273 | 22 |
| 12-13 | 11 | 23-27 | 15 | 55-76 | 19 | | |

4.3.2.1 Classification of characteristic (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Filling kit for 16XPM-05 battery assembly, training (see 9207801).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined | | |
| Major: | | |
| 101 | No components missing or damaged. . . . . | Visual |
| 102 | Contents properly packed. . . . . | Visual/Manual |
| Minor: | | |
| 201 | Marking. . . . . | Visual |
| 202 | Workmanship (see 3.3). . . . . | Visual/Manual |

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5.1)

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined | |
| Major: | | |
| 101 | Preservation, packaging, packing and marking in accordance with MIL-STD-1169. . . . . | Visual/Manual |
| Minor: | None defined | |

4 3.2.1.3 Bag, packing ammunition for battery filler kit (see dwg 88616

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined | |
| Major: | | |
| 101 | Bottom of boxes secured by tape. . . . . | Visual |
| 102 | Length of bag before packing, min. . . . . | *Measure |
| 103 | Width of bag before packing, min. . . . . | *Measure |
| 104 | Proper heat seal. . . . . | Visual/Manual |
| 105 | Properly packed. . . . . | Visual/Manual |
| 106 | Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116. . . . . | Visual |
| 107 | No cracks or holes in bag. . . . . | Visual |
| 108 | Material (see 3.1). . . . . | Visual |

* Measure with suitable scale

| | | |
|---|---|---|
| Minor: | | |
| 201 | Marking. . . . . | Visual |
| 202 | Workmanship (see 3.3). . . . . | Visual/Manual |

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 88C8362 and 5.2)

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined | |
| Major: | | |
| 101 | Gross load weight. . . . . | *Measure |
| 102 | Contents tight in package. . . . . | Manual |
| 103 | Correctly packed. . . . . | Visual/Manual |
| 104 | Material (see 3.1). . . . . | Visual |

* Determine weight with suitable scale

| | | |
|---|---|---|
| Minor: | | |
| 201 | Marking. . . . . | Visual |
| 202 | Workmanship (see 3.3). . . . . | Visual/Manual |

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:04Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. Not applicable
4.3.4 Acceptance inspection equipment. Not applicable
4.4 Test Methods. Not applicable

5. PREPARATION FOR DELIVERY

5.1 Production Items.
5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.1.1.1 Level A. The filler kit shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).
5.1.1.2 Level C. The filler kit shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).
5.1.2 Packing.
5.1.2.1 Levels A and C. The filler kit shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).
5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).
5.2 Repair parts.
5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.2.1.1 Level A. The filler kit shall be packaged in accordance with dwg 8861967 and 8808362 using the specified moisture barrier.
5.2.1.2 Level C. The filler kit shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.
5.2.2 Packing.
5.2.2.1 Level A and C. The filler kit shall be packed in accordance with dwg 8861967 and 8808362.
5.2.3 Marking. Marking shall be as specified in accordance with dwg 8861967 and 8808362 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.
6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 17801, ATTN: SMUPA-QA-N-I.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 6140-A325

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:04Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-F-50965(MU) Filling Kit for 16XM-05 Battery Assembly, Training

ORGANIZATION

| CITY AND STATE | CONTRACT NUMBER |
|---|---|
| | |

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

| SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE |
|---|---|
| | |

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:04Z
Check the source to verify that this is the current version before use.