MIL-F-51156A
6 November 1969
SUPERSEDING
MIL-F-51156(MU)
25 October 1963

MILITARY SPECIFICATION

FLAME THROWER, MECHANIZED, MAIN

ARMAMENT, APC-MOUNTED, M10-8

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a flame thrower in an armored personnel carrier.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

U-T-30	-	Talcum Powder, Palin and Borated.
TT-W-572	-	Wood Preservative, Water Repellent.
VV-G-76	-	Gasoline, Automotive.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Sheet, Stock and Cut Shapes.
PPP-P-150	-	Paper, Shredded, Waxed.
PPP-P-291	-	Paperboard, Wrapping, Cushioning.
PPP-T-60	-	Tape; Pressure-Sensitive Adhesive, Waterproof - For Packaging and Sealing.
PPP-T-76	-	Tape; Pressure-Sensitive Adhesive Paper, Water Resistant, (For Carton Sealing).

FSC 1040

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	-	Preservation, Methods of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-T-704	-	Treatment and Painting of Material.
MIL-B-2427	-	Box, Ammunition Packing, Wood, Nailed.
MIL-H-5606	-	Hydraulic Fluid, Petroleum Base, Aircraft and Ordnance.
MIL-V-13811	-	Varnish, Waterproofing, Electrical, Ignition.
MIL-C-51158	-	Cupola, Flame Gun, M8.
MIL-P-51159	-	Pressure Control Unit, For M10-8 Mechanized Flame Thrower.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL81-1-9052	-	Flame Thrower, Mechanized, Main Armament, APC-Mounted, M10-8.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL81-1-9052 or on the subsidiary drawings shall conform to the specifications thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the flame thrower shall conform to the specifications and drawings listed on Drawing DL81-1-9052 and subsidiary drawings.

3.2 Assembly. The flame thrower shall be assembled in accordance with Drawing E81-1-9052.

3.3 Performance.

3.3.1 Pressure drop. The fuel tanks shall be filled with thickened fuel and the gasoline tank filled with approximately two gallons of gasoline conforming to Specification VV-G-76 (commercial). The air bottles shall be charged to 3000 pounds per square inch gage (psig). Valves shall be opened to pressurize entire system. The pressure in the system at time of charging shall be recorded and the flame thrower allowed to stand for 5 hours. The pressures and ambient temperature shall be recorded and corrected to standard conditions of temperature and pressure. The fuel and air systems shall have no external leakage evident at any pressure and coupling connections when tested in accordance with 4.2.4.1. A system leakage of 100 psig maximum, after temperature and pressure correction will be considered permissible to compensate for internal component leakage.

3.3.2 Functioning. The flame thrower, after being accepted for above test, shall function as follows when tested as specified in 4.2.4.2:

(a) The cupola shall traverse freely 360 degrees without binding and interference and the flame gun shall elevate 55 degrees minimum and depress 11 degrees minimum.

(b) The flame gun igniters shall be selective, instantaneous and continuous ignition.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(c) The flame gun shall have a minimum range of 150 yards when elevated 20 degrees ± 2 degrees above horizontal.

(d) The pintle valve shall not leak and the pressure within the fuel system shall not drop below 260 psig during firing.

3.4 Flexible tube. The flexible tube (Drawing C81-1-7584) shall not distort to leak under a hydrostatic pressure of 550 ± 10 psig, for 5 or 6 minutes, when tested as specified in 4.2.4.3.

3.5 Check valve (Drawing B81-1-9129).

3.5.1 Endurance. The valve shall be in a vertical position (arrow pointed down) and a pressure of 550 ± 10 psig at 70° ± 5°F applied to the inlet end. The outlet shall be vented to the atmosphere for 5 to 6 seconds which will constitute one cycle. The valve shall be cycled 400 times. The above shall be repeated except that the temperature shall be 125° ± 5°F for 400 cycles and -40° to - 45°F for 400 cycles. The valve shall function when tested as specified in 4.2.4.4(a).

3.5.2 Functioning. The valve shall operate at a pressure of 550 ± 10 psig and have a flow rate of 45 ± 5 gallons per minute (gpm) when tested as specified in 4.2.4.4(b).

3.5.3 Leakage. The valve shall not leak under a pressure of 1200 ± 50 psig, submerged in water to a depth of 1 to 2 inches over the body of the valve for 5 to 6 minutes, when tested as specified in 4.2.4.4(c).

3.6 Hoses.

3.6.1 High pressure. The high pressure hose shall not leak under a hydrostatic pressure of 5000 ± 50 psig for 5 to 6 minutes when tested as specified in 4.2.4.5(a).

3.6.2 Medium pressure. The medium pressure hose shall not leak under a hydrostatic pressure of 500 ± 10 psig for 5 to 6 minutes when tested as specified in 4.2.4.5(b).

3.7 Pneumatic vent assembly. The pneumatic vent (Drawing C81-1-9245) shall not leak under a hydrostatic pressure of 550 ± 10 psig for 5 to 6 minutes when tested as specified in 4.2.4.6.

3.8 Fuel tube and adapter, fuel tube. The fuel tube (Drawing C81-1-7560) and adapter (Drawing C81-1-9075) shall not leak under a hydrostatic pressure of 550 ± 10 psig for 5 to 6 minutes when tested as specified in 4.2.4.7.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

3.9 CO_2 cabinet (Drawing E81-1-9125).

3.9.1 Control valve. The valve shall function and fully open when tested as specified in 4.2.4.8(a).

3.9.2 Assembly. The complete cabinet assembly, less the pressure control assembly (Drawing E81-1-9104), shall function when the control handle is pulled, discharging the CO_2 from both cylinders when tested as specified in 4.2.4.8(b).

3.10 Shut off valve. The valve (Drawing B81-1-9048) shall function and not leak when subjected to the following hydrostatic pressures for 60 to 65 seconds:

(a) 4500 psig.

(b) 3000 psig.

The valve shall be opened and closed three times and then shall be held for 5 minutes at both pressures when tested as specified in 4.2.4.9.

3.11 Workmanship. The flame thrower shall be free from contamination (foreign matter, oil, and grease) and damage, cracks, or deformation) which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the valves, CO_2 cabinets, hoses, fuel tubes, electric cables and pneumatic vent assemblies of one interfix number, produced by one manufacturer, under essentially the same manufacturing conditions.

4.2.2 Sampling.

4.2.2.1 Nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105. For CO_2 cabinets and check valve endurance test use level S-2.

4.2.3 Inspection procedure.

4.2.3.1 For examination. Each flame thrower and the level A preparation for delivery shall be examined in accordance with the list of defects. If any item contains any defect listed in 4.2.3.3, that item shall be rejected.

4.2.3.2 For nondestructive tests. Sample components shall be tested in accordance with 4.2.4 as applicable and MIL-STD-105. For CO_2 cabinets and check valve endurance test use an AQL of 2.5 percent defective.

4.2.3.3 List of defects:

(a) Flame thrower, mechanized, main armament, apc-mounted, M10-8 (Dwg E81-1-9052).

	Acceptance standards
1. Component missing or incorrectly assembled	
2. Protective finish missing	
3. Functioning	4.2.4.2
4. Empty CO_2 cabinets	
5. Seal missing from CO_2 cabinet	
6. Workmanship (3.11)	

(b) Preparation for delivery (section 5).

1. Blocking, bracing or anchoring incorrect or insufficient to prevent movement
2. Openings not processed as specified
3. Container closures incorrect
4. Loose pack
5. Marking incorrect, missing or illegible

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.2.4 Tests.

4.2.4.1 Pressure drop. The assembled flame thrower loaded and charged with required fuel and air pressure shall be checked for leakage after the required period of time.

4.2.4.2 Functioning. The flame thrower shall be functioned as follows:

(a) Traverse and cupola the required degrees in each direction 3 complete turns. Lower and elevate the gun 3 complete cycles.

(b) Discharge and ignite the gasoline, four 3-second bursts.

(c) Elevate the gun the required degrees above horizontal and with nil wind conditions or a tail wind not in excess of 5 miles per hour. The gun shall be fired six 3-second bursts of flame, pausing between bursts to allow the system to stabilize.

(d) The flame gun trigger shall be fully depressed and released, and a check made to insure that the pintle valve opens and closes with each burst.

4.2.4.3 Flexible tube. Using hydraulic oil conforming to MIL-H-5606, the tube shall be subjected to the specified pressure and time.

4.2.4.4 Check valve.

(a) Endurance. The valve shall be subjected to the specified pressure, time cycles, and temperatures, using nitrogen or air.

(b) Functioning. The valve shall be subjected to the specified pressure and have the specified flow rate when a flowmeter is attached to the outlet end of the valve. It shall be cycled 10 times venting the outlet end to the atmosphere. Hydraulic oil (see 4.2.4.3) shall be used as test fluid.

(c) Leakage. The valve shall be subjected to the specified pressures, using air or nitrogen, submerged in water for the required period of time.

4.2.4.5 Hoses.

(a) High pressure. The hose shall be subjected to the specified pressure, using water, for the required period of time.

(b) Medium pressure. The hose shall be subjected to the specified pressure, using water, for the required period of time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.2.4.6 Pneumatic vent. The vent shall be subjected to the specified pressure, using water, for the required period of time.

4.2.4.7 Fuel tube and adapter fuel tube. The fuel tube and adapter shall be subjected to the specified pressure, using water, for the required period of time.

4.2.4.8 CO_2 cabinet.

(a) Control valve. The valve shall be mounted on a suitable adapter and fixture. The handle shall be pulled to ascertain that the valve opens easily and fully.

(b) Assembly. The complete cabinet with two cylinders installed shall be securely mounted on a suitable base. The control handle shall be pulled.

4.2.4.9 Shut off valve. The valve shall be subjected to the specified pressure, using oil or water, for the required period of time.

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. The components of the flame thrower shall be cleaned and dried in accordance with MIL-P-116, using cleaning process C-1 and the most applicable of drying procedures listed thereon.

5.2 Preservating and packaging. Levels shall be as specified (see 6.1).

5.2.1 Level A.

5.2.1.1 Unit preservation and packaging.

(a) Preservatives and packaging methods. Unless otherwise specified herein, the preservatives, including the application thereof and packaging methods cited herein shall conform to MIL-P-116.

(b) Repainting. Damaged portions of painted areas shall be treated and repainted in accordance with the applicable requirements of MIL-T-704, type A, except that the color of the finish coat of paint shall conform to the requirements as shown on the applicable drawings.

(c) Unpainted surfaces. Unless otherwise specified herein, all exposed unpainted surfaces, including threaded areas shall be coated with type P-1 preservative.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:05Z
Check the source to verify that this is the currentversion before use.

(d) Nameplates, data and instruction plates. Nameplates, date and instruction plates shall be coated with electrical ignition waterproofing varnish, conforming to MIL-V-13811.

5.2.1.2 Unit preservation and packaging (flame thrower assemblies and components.)

(a) Flame gun cupola. The flame gun cupola shall be preserved and packaged in accordance with the level A requirements of MIL-C-51158.

(b) Pressure control unit. The pressure control unit shall be preserved, packaged and packed in accordance with the level A requirements of MIL-P-51159.

(c) Fire extinguisher cabinet and fire extinguishers with tube assemblies and spray nozzles. The support (Dwg C81-1-9160) and bracket (Dwg C81-1-9147) shall be removed from the fire extinguisher cabinet; and the tube assembly (Dwg C81-1-9223) and spray nozzle shall be removed from each of the two fire extinguishers. The fire extinguishers shall then be secured in place within the fire extinguisher cabinet with the locking yoke (Dwg C81-1-9131). The two tube assemblies and spray nozzles shall be packaged together in accordance with method III. The unit container shall conform to PPP-B-636, type CF, class weather-resistant, and shall be closed in accordance with the appendix to the box specification. The removed support and angle shall be individually cushion wrapped in either grade A, greaseproof barrier material conforming to MIL-B-121 or in cushioning wrapping paperboard, conforming to PPP-P-291 securing the wraps in place with pressure sensitive tape conforming to either PPP-T-76 or type III, class I of PPP-T-60. The fire extinguisher cabinet, with the fire extinguishers secured therein and the removed components shall be packaged in a class 2, style 4 nailed wood box, conforming to PPP-B-621 providing the necessary internal blocking or bracing to preclude any movement therein. Before applying internal blocking or bracing, filler pads fabricated from type SF, class weather resistant, grade optional fiberboard conforming to PPP-F-320, shall be placed between the top, bottom, sides, and ends of the box and the fire extinguisher cabinet. The box shall be closed in accordance with the applicable requirements of the box specification. The box shall not be strapped.

(d) Fuel tank. Each fuel tank shall be filled with type P-9, preservative oil and drained, coating unpainted exposed areas around openings into tank with the same type of preservative oil.

(e) Air tank. Each tank shall be charged to 5 psig with dry nitrogen and openings sealed with metal caps. A tag conforming to requirements of MIL-STD-129 shall be affixed to each tank, indicating that tanks have been charged to 5 psig with dry nitrogen and to discharge same, carefully remove metal caps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(f) Flexible tube, fuel tube adapter, fuel tube and inlet tube. The internal surfaces and all unpainted external surfaces shall be coated with type P-9, preservative oil. The tubes shall then be wrapped with grade C greaseproof barrier material, conforming to MIL-B-121, securing the wrap in place with pressure-sensitive tape conforming to either PPP-T-76, or type III, class 1 of PPP-T-60.

(g) Tank mounting beams. All unpainted areas shall be coated with type P-1 preservative.

(h) Flame gun shroud. The internal surfaces and all unpainted external surfaces shall be coated with type P-9, preservative oil. The shroud shall then be wrapped in grade C greaseproof barrier material conforming to MIL-B-121, securing wrap in place with pressure-sensitive tape conforming to either PPP-T-76 or type III, class 1 of PPP-T-60.

(i) Clamps. The clamps not used in packing assembly (see 5.3) shall be packaged in accordance with method III. The unit container shall conform to PPP-B-636, type CF, class weather-resistant, and shall be closed in accordance with the appendix to the box specification.

(j) Clamp gaskets. The clamp gaskets not used in packing assembly (see 5.3) shall be sprinkled with talc conforming to U-T-30, and packaged in accordance with method III, in such manner as to prevent distortion of gaskets. The unit container shall conform to PPP-B-636, type CF, class weather-resistant, and shall be closed in accordance with the appendix to the box specification.

(k) Hose. The hose fittings shall be coated with type P-9, preservative oil and then wrapped with grade A or C greaseproof barrier material, conforming to MIL-B-121; securing the wraps in place by either tying or taping.

(l) Hardware. The hardware not used in the packing assembly (see 5.3) shall be packaged in accordance with method III, except the bolts used for installing the right, left, and center mounting beams in the carrier shall be coated with type P-10, type 1, grade 30 preservative oil and packaged in accordance with method IC-1. The unit container shall conform to PPP-B-636, type CF, class weather-resistant, and shall be closed in accordance with the appendix to the box specification.

(m) Technical manuals. Technical manuals shall be packaged in accordance with method IC-1 or IC-3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

5.2.1.3 Intermediate packaging. Components and technical manuals unit preserved and packaged as specified in 5.2.1.2(i) through 5.2.1.2(m) shall be intermediately packaged together in a V3c, style RSC-SL fiberboard box conforming to PPP-B-636. In addition to the closure requirements specified, the box seams and corners including the manufacturer's joint shall be taped. As an alternate, pressure-sensitive tape conforming to PPP-T-76 may be used. Prior to box closure, internal cushioning material conforming to either PPP-C-843 or PPP-P-150, shall be used as required to make a tight intermediate package.

5.2.2 Level C.

5.2.2.1 Flame thrower assemblies and components.

(a) Flame gun cupola. The flame gun cupola shall be preserved and packaged in accordance with the level C requirements of Specification MIL-C-51158.

(b) Pressure control unit. The pressure control unit shall be preserved, packaged and packed in accordance with the level C requirements of MIL-P-51159.

(c) Other assemblies and components. Other assemblies and components, such as fire extinguishers, fuel and air tanks, flexible tubes, adapters, fuel tubes, inlet tubes, tank mounting beams, clamps, gaskets, hardware, technical manuals, etc., shall be cleaned and dried as specified in 5.1 and preserved and packaged in accordance with the manufacturer's instructions for immediate use.

5.3 Packing. Levels shall be as specified (see 6.1).

5.3.1 Level A.

5.3.1.1 Flame thrower assemblies and components.

(a) Flame gun cupola. The flame gun cupola shall be packed in accordance with the level A requirements of MIL-C-51158.

(b) Other assemblies and components. The other assemblies and components processed as specified in 5.1 and 5.2 shall be packed in a type II, class 1 or 2, style A wood crate, conforming to MIL-C-104. The crate and all wood parts shall be completely immersed for a minimum of 3 minutes in a water-repellent wood preservative, conforming to composition A of TT-W-572. Prior to packing the assemblies in the treated crate, the crate shall meet

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

the dryness of preservative requirement specified in MIL-B-2427. These assemblies and components shall be blocked, braced, or anchored to the skid base of the crate in accordance with the appendix to the crate specification and the following:

(1) The left mounting beam, center mounting beam and right mounting beam shall be bolted to the skid base of the crate with carriage bolts of the same diameter as those used when installing beams in personnel carrier. The bolts must be of sufficient length to pass through the beam leg, floor member and either the wood sleeper or wood skid. Sleepers used shall conform to the appendix requirements of the crate specification. Flat washers shall be used when the tie down holes have a much greater diameter, than those normally provided for bolts. In addition, lock washers shall be used.

(2) The fuel tank shall be bolted to the left, center, and right mounting beams in the same pattern as they would be mounted in the carrier. The air tanks shall then be mounted to the fuel tanks. The fuel tanks shall be connected with each other in the same manner as when installed, using the required coupling clamp seals and coupling clamps. All remaining fuel tank openings shall be closed off with plastic plugs held in place with coupling clamps, coating unpainted surfaces of the plugs and clamps with type P-1 preservative compound.

(3) The boxes pressure control unit, and the boxed fire extinguisher cabinet with fire extinguishers shall be secured to the skid base of the crate in accordance with the applicable requirements as specified in 5.3.1.1(b).

(4) Components intermediately packaged as specified in 5.2.1.2 shall be secured to the skid base of the crate in accordance with the applicable requirements as specified in 5.3.1.1(b).

(5) The connecting tubes and the flame gun shroud shall be secured to the skid base of the crate in accordance with the applicable requirements as specified in 5.3.1.1(b).

5.3.2 Level C.

5.3.2.1 Flame thrower assemblies and components.

(a) Flame gun cupola. The flame gun cupola shall be packed in accordance with the level C requirements of MIL-C-51158.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(b) Other assemblies and components. Other components and assemblies processed as specified in 5.1 and 5.2 shall be packed in such manner as to insure carrier acceptance and safe delivery to first domestic destination for immediate use. Containers shall comply with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of specification.
(b) Level of packaging and packing required.

6.2 Components specifications. The following specifications are components of and are required for the manufacture of the mechanized flame thrower:

MIL-T-51157(MU) - Tank, Fuel and Air; for M10-8 Flame Thrower.
MIL-C-51158(MU) - Cupola, Flame Gun, M8.
MIL-P-51159(MU) - Pressure Control Unit; for M10-8 Mechanized Flame Thrower.

6.3 Caution. Due to the hazards inherent in testing with thickened fuel, suppliers are hereby notified that every precaution possible should be taken for the safety and protection of personnel testing the items.

Custodians:

Army - MU

User activity:

Navy - MC

Preparing activity:

Army - MU(EA)

Project No. 1040-0071

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

TO DETACH FORM - CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.