MILITARY SPECIFICATION

LAUNCHER, ROCKET, 66MM,

FOUR TUBE, M202

1. SCOPE

1.1 This specification covers one type of launcher.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-117	-	Bags, Sleeves and Tubing,-Interior Packaging.
MIL-A-2550	-	Ammunition and Special Weapons, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Table for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-810	-	Environmental Test Methods.
MIL-STD-1168	-	Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL147-1-100	-	Launcher, Rocket, 66MM, Four Tube, M202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement function should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL147-1-100 or on subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the launcher shall conform to the specifications and drawings listed on Drawing DL147-1-100 and subsidiary drawings.

3.2 Assembly. The launcher shall be assembled in accordance with Drawing E147-1-100.

3.3 Nonfunctioning.

3.3.1 Front cover assembly and handle interlock. When the front cover is closed or open and swinging free, the handle assembly shall not be able to become unlatched. When the front cover is opened and latched, the handle assembly shall be free to open and latch when tested as specified in 4.4.4.1. When the handle release button is depressed, the handle shall be disengaged and may be returned to stowed position. When the handle assembly is in its stowed position, and latched, the front cover assembly shall be disengaged from its fully opened and latched position.

3.3.2 Trigger safety. When the safety button on the handle is positioned so that the "S" shows, the trigger shall be incapable of functioning. The trigger safety button shall require a 1 to 4 pound force to slide from safe to fire position and from fire to safe position when tested as specified in 4.4.4.2.

3.3.3 Safety guide tube and firing pin cam. The trigger shall not function when trigger safety is in the fire position and firing mechanism is collapsed to any position beyond 1 inch from fully extended position. Points of three firing pins shall extend outward from firing mechanism housing a maximum of 0.075 inch and one firing pin shall be retracted in the housing when tested as specified in 4.4.4.3.

3.4 Extension shaft engagement into safety guide tube. The extension shaft shall enter the safety guide tube smoothly without excessive drag or binding when tested as specified in 4.4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

3.5 Trigger function. The trigger shall function at not less than 8 pounds nor more than 18 pounds pull when tested as specified in 4.4.4.5.

3.6 Springs. Springs shall not break or take a permanent set when tested as specified in 4.3.3.3.

3.7 Firing pin. Each assembled firing pin (Drawing C147-1-73) shall free fall through a gage having a hole diameter of 0.374 ± 0.0005 inch when tested as specified in 4.4.4.6. Gage height shall be 1 1/8 inches minimum. Gage shall include a minimum width slot for the cam follower to fall through.

3.8 Firing pin tension. Force required to collapse each firing pin into housing shall be between 7 1/2 and 11 pounds when tested as specified in 4.4.4.7.

3.9 Sight. The sight shall operate, move smoothly and freely without binding when tested as specified in 4.4.4.8.

3.10 Outer tube.

3.10.1 Destructive. There shall be no cracks or leaks when the tube is subjected to an external hydrostatic pressure of 20 to 25 pounds per square inch gage (psig) and then no cracks when subjected to an internal hydrostatic pressure of 1500 ± 50 psig for a minimum period of 5 seconds when tested as specified in 4.4.4.9.(a). Pressure shall then be increased until burst.

3.10.2 Nondestructive. There shall be no cracks or permanent deformation in excess of that permitted by the drawing dimensions when the tube is subjected to an internal pressure of 700 ± 20 psig applied for a minimum of 5 seconds when tested as specified in 4.4.4.9(b).

3.11 Clip latch. The clip and round assembly shall not be able to be inserted or extracted from the launcher without depressing the clip latch when tested as specified in 4.4.4.10.

3.12 Functioning.

3.12.1 Empty clip. Four primers shall function when tested as specified in 4.4.4.11(a).

3.12.2 Loaded clip. The rockets shall impact on a 7 1/2 by 7 1/2 foot by 1 inch wood target 200 meters from point of launch when tested as specified in 4.4.4.11(b). In preproduction testing of two clips (eight rockets),

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

seven rockets shall hit the target. In regular production testing of one clip (four rockets), three rockets shall hit the target. Aiming point shall be center of target.

3.13 Vibration. The launcher shall not be damaged and shall meet the requirements of 3.3.1, 3.3.2, 3.12.2 and 3.14 after testing as specified in 4.3.3.1.

3.14 Trigger cycle. The launcher trigger shall activate the firing pins and conform to 3.5 when tested as specified in 4.3.3.2.

3.15 Cable assembly.

(a) Destructive. The swaged balls on the cable shall not move or separate from the cable nor shall any wire strand break when subjected to a tension load of 225 pounds minimum when tested as specified in 4.4.4.12(a).

(b) Nondestructive. The swaged ball on the cable shall not move or separate from the cable nor shall any wire strand break when subjected to a tension load of 150 ± 5 pounds when tested as specified in 4.4.4.12(b). No assembly subjected to this test shall be used in production.

3.16 Pawl assembly. The spring swaged into pin shall not slip or separate when subjected to a tension load of 2 to 3 pounds when tested as specified in 4.4.4.13.

3.17 Retraction of firing mechanism. The return spring shall partially retract the firing mechanism a minimum of 3/8 inch into launcher when the extension shaft and keys are lined up with the shaft ratchet and safety guide slots when tested as specified in 4.4.4.14.

3.18 Rear cover. When the rear cover latch is opened, cover shall freely move to fully opened position and return to closed latched position when tested as specified in 4.4.4.15.

3.19 Lever detent. The welded detent rivet shall not separate or slip or the weld crack when a 1000 ± 25 pound load is applied as specified in 4.4.4.16. No assembly subjected to this test shall be used in production.

3.20 Handle support. The brazed pin shall not separate or slip when a 750 ± 20 pound load is applied as specified in 4.4.4.17. No assembly subjected to this test shall be used in production.

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:05Z
Check the source to verify that this is the current version before use.

3.21 Preproduction. Prior to the start of regular production, a preproduction sample of launchers shall be produced in accordance with this specification for examination and test (see 4.3).

3.22 Workmanship. The launcher shall be free from foreign matter (oil, grease or dirt) and damage such as cracks, burrs, dents, excess epoxy, excess paint, voids in painted surfaces, gaps in epoxy joints and deformation which could affect its intended use, and shall comply with the workmanship requirements of MIL-A-2550.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)

(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 10 launchers, 10 of each spring five outer tubes and two launcher tube assemblies shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.3.2.1 For examination and nondestructive tests.

(a) Launcher and components. The sample launchers and components shall be examined and tested in accordance with the classification of defects (4.4.3.5) and list of defects (4.4.3.6). The AQL's do not apply. The sample launchers shall be sequentially tested in accordance with 4.3.3.1, 4.3.3.2, 4.4.4.1, 4.4.4.2 and 4.4.4.11(b).

(b) Functioning. Two clips shall be fired from each of two sample launchers when tested as specified in 4.4.4.11(b).

4.3.2.2 For destructive tests. The sample springs and outer tubes shall be tested in accordance with 4.3.3.3 and 4.4.4.9.

4.3.3 Tests. Tests shall be conducted as follows:

4.3.3.1 Vibration. The test samples shall consist of two unpackaged launchers with loaded clips inserted in the carrying configuration. The samples shall be tested in accordance with method 514, table 514-I, equipment category (h), procedure XI, part 2, test type-bounce, loose cargo of MIL-STD-810, except that the time shall be 11 minutes of which 6 minutes shall be on one side and 5 minutes on any other side.

4.3.3.2 Trigger cycling. The extension and retraction of the firing pins shall be measured before and after completion of test. An empty clip shall be inserted into the launcher, fully extended, and the trigger pulled four times. Collapse clip into launcher, this constitutes one cycle. Repeat as above until trigger has been pulled 4000 times (1000 cycles). Measure the extended firing pins after each 250 cycles (see 3.3.3). Every 250 cycles inspect ends of clip for burrs or cracks which could damage launcher tubes. Replace clip as required.

4.3.3.3 Springs. The springs shall be extended or flexed in a manner representative of actual functioning for 100 cycles. If a spring breaks or fails to return to its original condition prior to this, it is defective.

4.3.4 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.3.2 to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of launcher, no more than one interfix number from one manufacture of the following component is permitted.

Outer tube

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests.

(a) Except as provided in paragraph (b) following, sampling shall be conducted in accordance with MIL-STD-105.

(b) For testing in accordance with 4.4.4.11(b), sampling shall be conducted in accordance with MIL-STD-105, level S-4.

4.4.2.2 For destructive tests.

(a) Outer tube. Fifteen outer tubes shall be randomly selected from each lot.

(b) Cable assembly. Sampling shall be conducted in accordance with MIL-STD-105, inspection level S-4.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive tests.

(a) Except as provided in paragraph (b) following and in paragraph 4.4.3.3, the sample launchers and the level A preparation for delivery shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

(b) MIL-STD-105, level S-4, sample of launchers shall be tested in accordance with 4.4.4.11(b). The acceptance number is zero.

(c) Evidence of compliance with the required bonding techniques on E147-1-99 and E147-1-100 shall be determined by visual examination of the squeeze out of epoxy bonding agent from bonded joints. Gaps in the squeeze-out of no longer than 1/4 inch are permitted so long as any two gaps are separated by at least 3/4 inch squeeze-out of epoxy, except that no gaps are permitted along closure strip bonded joints. Cleaning or removal of excess epoxy from the tube and bulkhead joint is permitted before or after curing at the option of the contractor, provided that the assembly is Government inspected prior to and after epoxy removal. Cleaning or removal of excess eqoxy from the closure strip and tube interface is permitted to obtain a smooth flush joint.

4.4.3.2 For destructive tests.

(a) Outer tube. The sample tubes shall be tested in accordance with 4.4.4.9(a). The acceptance number is zero.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

(b) Cable assembly. The sample cable assemblies shall be tested in accordance with 4.4.4.12(a). The acceptance number is zero.

4.4.3.3 List of defects. Each launcher and each component noted in the list of defects shall be inspected for those defects. If any launcher or component contains any defect listed in 4.4.3.6, that launcher or component shall be rejected.

4.4.3.4 For critical defects. Each item in the lot shall be tested for critical characteristics listed in the classification of defects.

4.4.3.5 Classification of defects.

(a) Launcher, rocket, 66MM, multishot, M202 (Drawing E147-1-100).

Categories	Defects	Acceptance standards
Critical:		
1	Functioning	4.4.4.11(a)
2	Front cover assembly and handle interlock functioning incorrect	4.4.4.1
3	Trigger safety functioning incorrect	4.4.4.2
4	Extension shaft engagement into safety guide tube	4.4.4.4
5	Trigger function	4.4.4.5
6	Sight	4.4.4.8
7	Firing pin tension	4.4.4.7
8	Retraction of firing mechanism	4.4.4.14

(b) Firing pin (Drawing C147-1-73).

Categories	Defects	Acceptance standards
Critical:		
1	Free fall through gage	4.4.4.6

(c) Ratchet assembly (Drawing D147-1-43).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Pawl assembly pull test	4.4.4.13

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.4.3.5 Classification of defects (continued).

(d) Tube, outer (drawing C147-1-92).

Categories	Defects	Acceptance standards
Critical:		
1	Cracks or permanent deformation	4.4.4.9(b)

(e) Cable (Drawing B147-1-127).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 0.15 percent defective	
101	Move or separation	4.4.4.12(b)

(f) Preparation for delivery (section 5)

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Bag not sealed	
102	Loose pack	
103	Seams or joints not sealed	
104	Container incorrect	
105	Strapping loose or missing	
106	Marking illegible or incorrect	
107	Glue or adhesive in area of front cover handle toggle key	
108	Accessories missing	
109	Spare clip retainer missing	

4.4.3.6 List of defects.

(a) Launcher, rocket, M202 (Drawing E147-1-100).

(1)	Firing pin protrusion (0.075 max) incorrect	4.4.4.3
(2)	Clip latch incorrect	4.4.4.10
(3)	Rear cover	4.4.4.15

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

following actions:

(b) Tube assembly launcher (Drawing E147-1-99).

(1) Tube location incorrect (both ends)
(2) Perpendicularity
(3) Parallelism (DLB5220-A50-9646)*
(4) Detent pin location (DLB5220-A50-9776)*
(5) Rear bulkhead location (4.441 dimension)

*Inspection gage drawing number.

(c) Firing pin mechanism assembly (Drawing C147-1-71).

(1) Alignment pin stick out 0.310 + .040 incorrect
(2) Pins lubricated and roll free

4.4.4 Tests. Test shall be conducted as follows:

4.4.4.1 Front cover assembly and handle interlock. After final paint touch-up, perform the following tests.

(a) When the front cover is closed and again when open and swinging free, attempt to open the handle assembly from its stowed and locked position.

(b) When the front cover is opened and latched, open and latch the handle assembly.

(c) Repeat (a) and (b) for a total of 10 times.

(d) The trigger handle must be fully collapsed, the interlock tripped, and the handle latched into place before the front cover is released and can be closed. The front cover must be unlatched, the interlock tripped and the handle cover locked into position before the trigger handle is automatically released from its stowed position.

4.4.4.2 Trigger safety. After final paint touch-up, perform the following test. Insert an empty clip into launcher and extend to firing position. With the safety button on the handle as specified, attempt to squeeze trigger by hand. Use a spring gage tester to determine force required to slide the safety button from safe to fire position 10 times, and squeeze trigger each time.

4.4.4.3 Safety guide tube and firing pin cam. After final paint touch-up, perform the following test. With the trigger safety button in fire position, insert and extend an inert clip, attempt to function the trigger with the clip in two positions: 3/4 extended, and fully extended. Firing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

pin extension shall be measured at fully extended position. Measurement shall be taken after functioning trigger one time.

4.4.4.4 Extension shaft engagement into safety guide tube.

(a) Insert and extend inert clip.
(b) Pull trigger.
(c) Push detent and collapse clip 2 to 3 inches.
(d) Extend clip.
(e) Repeat steps (b), (c) and (d), three additional times.

4.4.4.5 Trigger function. After final paint touch-up, perform the following test procedure.

(a) Insert and extend inert clip.
(b) Move trigger safety to "S" position.
(c) Attach spring gage tester to trigger approximately 1/2 inch above lower tip of trigger handle and pull down at an angle of approximately 20 degrees to the longitudinal axis of launcher. This action rotates the "just fired" firing pin onto the safing ramp. Record force required.
(d) Move trigger safety to "F" position.
(e) Attach spring gage tester as in (c) above. Pull trigger and record force needed to fire pin.
(f) Repeat steps (b), (c), (d), and (e) three additional times.

4.4.4.6 Firing pin. Place each assembled firing pin into gage and allow it to free fall completely through the gage.

4.4.4.7 Firing pin tension. After final paint touch-up, push each firing pin into housing, which has been assembled into firing mechanism, and record force required to compress spring to just above fully retracted position. Firing pins shall move freely throughout their full travel with no binding dragging or hangup.

4.4.4.8 Sight. After final paint touch-up, perform the following test procedure.

(a) Raise sight to operating position and check detent for engagement.
(b) With sight lock fully depressed, assure that lock will not override adjustment plate end tabs.
(c) Depress sight adjustment plate lock and rotate to operating position.
(d) Open and close lens cover. Check for detent engagement.
(e) Depress sight adjustment plate lock and rotate sight to closed position.
(f) Lower sight to closed position and check for detent engagement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.4.4.9 Outer tube.

(a) Destructive. The tube shall be placed in a suitable fixture and subjected to the specified pressures for the required time and then burst. Record burst pressure.

(b) Nondestructive. The tube shall be placed in a suitable fixture and subjected to the specified pressure for the required time.

4.4.4.10 Clip latch. Slowly insert an empty clip assembly into launcher without depressing clip latch. Clip shall enter launcher approximately 1/2 inch before clip latch restricts movement. Depress clip latch, and fully insert clip. From fully collapsed position, apply a steady slow pull at an approximate rate of 6 inches per second on bail handle at end of clip; the clip shall extend from launcher and lock into firing position. To remove clip assembly, collapse into launcher, remove clip retainer, extend clip assembly by bail handle, push clip latch, and extract clip.

4.4.4.11 Functioning.

(a) Empty clip. Insert empty clip, with four primers installed, into launcher. When launcher is ready to fire, pull trigger four times. The mechanism shall operate and initiate the four primers.

(b) Loaded clip. Insert loaded clip into launcher. When launcher is ready to fire, function trigger four times. The mechanism shall operate, and the specified number of rockets shall hit the specified target. (See 6.2 and 6.3.)

4.4.4.12 Cable assembly.

(a) Destructive. Secure one end of the swaged balls in a stationary fixture, grip the other ball at end of cable and apply specified load for 5 seconds, then increase tension until destruction. Record load required to destroy cable.

(b) Nondestructive. Secure one of the swaged balls in a stationary fixture, grip the other ball at end of cable and apply specified load for 5 seconds.

4.4.4.13 Pawl assembly. Attach a spring gage tester into loop of spring and secure pin in a stationary fixture. Apply specified load along longitudinal axis.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

4.4.4.14 Retraction of firing mechanism. After final paint touch-up, insert and extend inert clip and place launcher in horizontal position. Remove clip retainer and observe to see that firing mechanism retracts the specified distance from the primer manifold.

4.4.4.15 Rear cover. After final paint touch-up insert inert clip, close and latch rear cover, open cover latch, move cover to full open position, close and latch cover. Repeat opening and latching five times.

4.4.4.16 Lever detent. After welding, use a suitable fixture with a 3/8 inch diameter hole. Apply the specified load to end of 0.125 inch diameter rivet and hold for 5 seconds.

4.4.4.17 Handle support. After brazing, apply specified load to exposed end of pin and hold for 5 seconds.

5. PREPARATION FOR DELIVERY.

5.1 Packaging, level A.

5.1.1 Cleaning. The launcher and components thereof shall be cleaned in accordance with process C1 of MIL-P-116.

5.1.2 Launcher (Drawing E147-1-100). One launcher shall be packaged in accordance with Drawing D147-1-189.

5.1.3 Sling (Drawing D147-1-181). One sling shall be packaged in accordance with Drawing D147-1-189.

5.1.4 Special tools and ear plugs. The special tools, consisting of one Disk Set, Boresighting (Drawing C147-1-177) and one wrench-screwdriver combination (Drawing C147-1-190) shall be packaged together with one box of 24 plugs, ear, noise protection (FSN 6516-299-8289) in accordance with preservation method IC-3 of MIL-P-116, except that preservation is not required. The bag shall conform to type I or II, class B, style optional of MIL-B-117 and have inside dimensions of 4 by 8 inches. The special tools and ear plugs, packaged, shall be secured to the launcher in accordance with Drawing D147-1-189.

5.1.5 Technical publications. Applicable technical publications shall be packaged in accordance with preservation method IC-3 of MIL-P-116. The bag shall conform to type I or II, class B, style optional of MIL-P-117 and have inside dimensions of 10 by 12 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

5.2 Packing, level A. One launcher, packaged as specified in 5.1.2, shall be packed in accordance with Drawing D147-1-189.

5.3 Marking. In addition to any special marking required in the contract or order, interior packages shall be marked in accordance with MIL-STD-129 and shipping containers shall be marked in accordance with Drawing D147-1-164.

5.4 Palletization. When specified in the contract or order, the launcher, packed in accordance with 5.2, shall be palletized in accordance with Drawing D147-1-163.

6. NOTES

6.1 Intended use. This item is intended to launch rockets to neutralize hard, soft or jungle type targets and is man-portable for field use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Preproduction:

(1) Time allowed for supplier's submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when applicable.
(3) Time required for the Government to notify supplier whether to proceed with production.

(c) The M74 rocket and clip will be Government furnished when applicable.
(d) Palletization when required.

6.3 Caution. Due to the hazards attending live firing, suppliers are advised to take all necessary precautions to protect personnel while testing.

Custodian:

Army - MU

Preparing activity:

Army-MU(EA)

Project No. 1055-A049

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-TS-S
Edgewood Arsenal, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.