MIL-M-50803C (AR)
26 January 1979
SUPERSEDING
MIL-M-50803B (PA)
13 August 1976

MILITARY SPECIFICATION

* MOTOR, ROCKET, METAL PARTS FOR, DEMOLITION KIT, CRATERING: M180

This specification is approved for use by U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of metal parts for one type of rocket motor designated as Rocket Motor Metal Parts for Demolition Kit, Cratering, M180.

2 APPLICABLE DOCUMENTS

2.1 Issues of Documents. - The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-I-6868 - Inspection Process, Magnetic Particle
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

FEDERAL

Fed Test Method Std 151 - Metals, Test Methods

MILITARY

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

FSC: 1340

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil - Downloaded: 2023-10-27T04:37
Check the source to verify that this is the current version before use.

* DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9328030 - Rocket Motor Metal Parts

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. - The parts shall comply with all requirements specified on Drawing 9328030 and associated drawings and with all requirements specified in applicable standards and specifications.

3.3 Magnetic Particle Inspection. - Motor Assembly Weld. - The motor assembly weld shall show no evidence of voids, slag deposits, cracks or crack like indications.

3.4 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, rust, grease and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspections. - The responsibility for inspections shall comply with MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.2 Classification of Inspections. - The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First Article Inspection

* 4.3.1 Sumbission. - The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing No.	Quantity
Head, Rocket	9244407	5
Plate, Retainer, Rocket	9244408	5
Conduit, Detonator Wires	9244422	5
Body, Protector, Rocket	9244426	5
Retainer, Protector Rocket	9244427	5
Nozzle, Motor Case	9244439	5
Case, Motor	9244440	5
Rocket Motor Case Assembly	9244441	5
Flange, Rocket	9244447	5
Support, Blasting Cap	9244449	5
Plug, Head	9285387	5
Flat, Conduit	9329708	5
Tube, Conduit	9329709	5

4.3.2 Inspections to be Performed. - See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the currentversion before use.

* TABLE 1 FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE MOTOR, ROCKET, METAL PARTS FOR, DEMOLITION KIT, CRATERING: M180	SHEET 1 OF 2			DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Head, Rocket (Dwg. 9244407) Examination for Defects	5	-	3.2	4.4.2.1
	Plate, Retainer, Rocket (Dwg. 9244408) Examination for Defects	5	-	3.2	4.4.2.2
	Conduit, Detonator Wires (Dwg. 9244422) Examination for Defects	5	-	3.2	4.4.2.3
	Body, Protector, Rocket (Dwg. 9244426) Examination for Defects	5	-	3.2	4.4.2.4
	Retainer Protector, Rocket (Dwg. 9244427) Examination for Defects	5	-	3.2	4.4.2.5
	Nozzle, Motor Case (Dwg. 9244439) Examination for Defects	5	-	3.2	4.4.2.6
	Case, Motor (Dwg. 9244440) Examination for Defects	5	-	3.2	4.4.2.7
	Rocket Motor Case Assembly (Dwg. 9244441) Examination for Defects	5	-	3.2	4.4.2.8

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	CONTINUATION SHEET				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Flange, Rocket (Dwg. 9244447) Examination for Defects	5	-	3.2	4.4.2.9
	Support Blasting Cap (Dwg. 9244449) Examination for Defects	5	-	3.2	4.4.2.10
	Plug, Head (Dwg. 9285387) Examination for Defects	5	-	3.2	4.4.2.11
	Flat, Conduit (9329708) Examination for Defects	5	-	3.2	4.4.2.12
	Tube, Conduit (9329709) Examination for Defects	5	-	3.2	4.4.2.13

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation. - See MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling Plans. - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
#4.4.2.1	Head, Rocket		9244407
			NEXT HIGHER ASSEMBLY
			9328030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of center hole		0.40%	3.2	Gage
102	True position of center hole with datum A		0.40%	3.2	Gage
103	Minimum perfect thread		0.40%	3.2	Gage
104	Diameter of O ring groove		0.40%	3.2	Gage
105	True position of O ring groove with datum A		0.40%	3.2	Gage
106	Large outside diameter		0.40%	3.2	Gage
107	Thickness of outer portion		0.40%	3.2	Gage
108	Hardness Test		100%	3.2	4.5.2
Minor					
201	Pitch diameter of tapped holes		0.65%	3.2	Gage
202	Minor diameter of tapped holes		0.65%	3.2	Gage
203	True position of tapped holes		0.65%	3.2	Gage
204	Contour and location of O ring groove		0.65%	3.2	Gage
205	Total thickness of head		0.65%	3.2	Visual
206	Protective finish missing or damaged		1.00%	3.5	Visual
207	Evidence of poor workmanship				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244408
*4.4.2.2	Plate, Retainer, Rocket				NEXT HIGHER ASSEMBLY 9328030
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of center hole		0.40%	3.2	Gage
102	True position of center hole		0.40%	3.2	Gage
103	Outside diameter, max.		0.40%	3.2	Gage
104	Thickness of plate		0.40%	3.2	Gage
105	Diameter of propellant charge holes		0.40%	3.2	Gage
106	True position of 15 equally spaced holes		0.40%	3.2	Gage
107	True position of 28 equally spaced holes		0.40%	3.2	Gage
108	True position of 8 equally spaced holes		0.40%	3.2	Gage
109	True position of 21 equally spaced holes		0.40%	3.2	Gage
110	Depth of undercut		0.40%	3.2	Gage
Minor					
201	Countersink on center hole improper or missing		0.65%	3.2	Visual
202	Chamfer missing or propellant charge holes		0.65%	3.2	Visual
203	Protective finish missing or damaged		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50803C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244422
*4.4.2.3	Conduit, Detonator Wires				NEXT HIGHER ASSEMBLY 9328030
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
Minor					
201	Welding improper		0.65%	3.2	Visual
202	Protective finish missing or damaged		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
*4.4.2.4	Body, Protector, Rocket		9244426
			NEXT HIGHER ASSEMBLY 9328030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width of retaining ring groove		0.40%	3.2	Gage
102	Runout of flange face with datum A		0.40%	3.2	Gage
103	Total length		0.40%	3.2	Gage
104	True position of holes		0.40%	3.2	Gage
105	Location of retaining ring groove		0.40%	3.2	Gage
106	Length of booster assembly cavity		0.40%	3.2	Gage
107	Length to thread undercut, min.		0.40%	3.2	Gage
108	True postion of P.D. of threads with datum A		0.40%	3.2	Gage
109	P.D. of threads		0.40%	3.2	Gage
110	Small inside diameter		0.40%	3.2	Gage
111	Large inside diameter (I.D.)		0.40%	3.2	Gage
112	Small outside diameter (O.D.)		0.40%	3.2	Gage
113	Runout of small O.D. with datum A		0.40%	3.2	Gage
114	Runout of large O.D. with datum A		0.40%	3.2	Gage
115	Thickness of flange		0.40%	3.2	Gage
116	Diameter of retaining ring groove		0.40%	3.2	Gage

NOTES:

10

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
*4.4.2.4	CONTINUATION SHEET		9244426
			NEXT HIGHER ASSEMBLY 9328030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Diameter of large hole		0.65%	3.2	Gage
202	Improper countersink on small I.D.		0.65%	3.2	Gage
203	Thread undercut diameter		0.65%	3.2	Gage
204	Diameter of small holes		0.65%	3.2	Gage
205	Improper radius groove on flange		0.65%	3.2	Gage
206	Protective coating missing or damaged		0.65%	3.2	Visual
207	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.5	Retainer Protector Rocket				9244427
					NEXT HIGHER ASSEMBLY 9328030
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter (P.D.) of threads		0.40%	3.2	Gage
102	Major diameter of threads		0.40%	3.2	Gage
103	Thread length		0.40%	3.2	Gage
104	Runout of P.D. of threads		0.40%	3.2	Gage
Minor					
201	Diameter of holes		0.65%	3.2	Gage
202	Chamfers missing		0.65%	3.2	Visual
203	Protective finish missing or damaged		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRD[illegible]-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 7[illegible] Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Nozzle, Motor Case		9244439
			NEXT HIGHER ASSEMBLY 9244441

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Small I.D.		0.40%	3.2	Gage
102	Large I.D.		0.40%	3.2	Gage
103	Small wall thickness		0.40%	3.2	Gage
104	Large wall thickness		0.40%	3.2	Gage
105	True position of large I.D. with datum A		0.40%	3.2	Gage
Minor					
201	Overall length		0.65%	3.2	Gage
202	Chamfer at small diameter		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-28T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.7	Case, Motor		9244440
			NEXT HIGHER ASSEMBLY
			9244441

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth of cavity from head end to start of shoulder at nozzle end		0.40%	3.2	Gage
102	Overall length		0.40%	3.2	Gage
103	O.D. at nozzle end		0.40%	3.2	Gage
104	Contour of nozzle end		0.40%	3.2	Gage
105	Wall thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
*4.4.2.8	Rocket Motor Case Assembly		9244441
			NEXT HIGHER ASSEMBLY 9328030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Hardness test		100%	3.2	4.5.3
102	Magnetic particle inspection		100%	3.3	4.5.4
103	I.D. at weld bead		0.40%	3.2	Gage
104	True position of I.D. at weld bead with datum D		0.40%	3.2	Gage
105	Perpendicularity at nozzle face with datum A		0.40%	3.2	Gage
106	TIR of I.D. of nozzle face with datum A		0.40%	3.2	Gage
107	Diameter of retaining ring groove		0.40%	3.2	Gage
108	True postion of retaining ring groove diameter with datum B		0.40%	3.2	Gage
109	Width of retaining ring groove		0.40%	3.2	Gage
110	I.D. of Motor Case		0.40%	3.2	Gage
111	True position of head end I.D. with datum A		0.40%	3.2	Gage
112	I.D. at head end of Motor Case		0.40%	3.2	Gage
113	O.D. of Motor Case		0.40%	3.2	Gage
114	True position of throat diameter with datum D		0.40%	3.2	Gage
115	Diameter of throat		0.40%	3.2	Gage
116	O.D. of flange at head end		0.40%	3.2	Gage
117	True position of nozzle end I.D. with datum D		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9244441
4.4.2.8	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY 9328030
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Depth of slot in flange from head end		0.65%	3.2	Gage
202	10° and 15° chamfers missing on I.D. of head end		0.65%	3.2	Visual
203	Radius at forward edge of retaining ring groove missing		0.65%	3.2	Visual
204	Overall length		0.65%	3.2	Visual
205	Nut, Welding (3) missing or improper		0.65%	3.2	Visual
206	Protective finish missing or improper		0.65%	3.2	Visual
207	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244447
*4.4.2.9	Flange, Rocket				NEXT HIGHER ASSEMBLY 9328030
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large O.D.		0.40%	3.2	Gage
102	Large diameter of mating warhead		0.40%	3.2	Gage
103	Small diameter of mating warhead		0.40%	3.2	Gage
104	Diameter of body, protector hole, max.		0.40%	3.2	Gage
105	Runout of large diameter of mating warhead with datum A		0.40%	3.2	Gage
106	Runout of small diameter of mating warhead with datum A		0.40%	3.2	Gage
107	Runout of small I.D. with datum A		0.40%	3.2	Gage
108	Total thickness		0.40%	3.2	Gage
109	Depth of body, protector flange cavity		0.40%	3.2	Gage
110	Depth of large diameter of mating warhead		0.40%	3.2	Gage
111	Depth of small diameter of mating warhead		0.40%	3.2	Gage
Minor					
201	Diameter of large holes		0.65%	3.2	Gage
202	Diameter of small hole		0.65%	3.2	Gage
203	True position of holes and slot		0.65%	3.2	Gage
204	Protective finsih missing or damaged		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 which is Obsolete

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.10	Support, Blasting Cap		9244449
			NEXT HIGHER ASSEMBLY 9328030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	P.D. of threads		0.40%	3.2	Gage
102	Minor diameter of threads, max		0.40%	3.2	Gage
103	True position of P.D. of threads with datum A		0.40%	3.2	Gage
104	Small O.D. (datum A)		0.40%	3.2	Gage
105	I.D. of blasting cap cavity		0.40%	3.2	Gage
106	Runout of small I.D. with datum A		0.40%	3.2	Gage
107	Length of thread cavity		0.40%	3.2	Gage
108	Diameter of O ring groove		0.40%	3.2	Gage
109	Runout of O ring groove with datum A		0.40%	3.2	Gage
110	Total length		0.40%	3.2	Gage
111	Contour and location of O ring groove		0.40%	3.2	Gage
Minor					
201	Distance from large end to shoulder		0.65%	3.2	Gage
202	Diameter of undercut (when applicable)		0.65%	3.2	Gage
203	Width of undercut (when applicable)		0.65%	3.2	Gage
204	Protective finish missing or damaged		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.11	Plug, Head		9285387
			NEXT HIGHER ASSEMBLY
			9328030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location and contour of O ring groove		0.40%	3.2	Gage
102	Minimum perfect thread		0.40%	3.2	Gage
103	Diameter of O ring groove		0.40%	3.2	Gage
104	Outside diameter		0.40%	3.2	Gage
105	Pitch diameter of threads		0.40%	3.2	Gage
106	Minor diameter of threads, max.		0.40%	3.2	Gage
107	Total length		0.40%	3.2	Gage
108	Thickness of flange		0.40%	3.2	Gage
Minor					
201	Minor diameter of threads, min.		0.65%	3.2	Gage
202	Improper countersink		0.65%	3.2	Visual
203	Protective finish missing or damaged		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://easist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.12	Flat, Conduit	1 OF 1	9329708
			NEXT HIGHER ASSEMBLY 9244422

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height		0.40%	3.2	Gage
102	Radius		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Width		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50803C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.13	Tube, Conduit		9329709
			NEXT HIGHER ASSEMBLY 9244422

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Wall thickness		0.40%	3.2	Gage
104	Distance from outside diameter to flat surface		0.40%	3.2	Gage
Minor					
201	Distance from end to angle		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check for updates to this form/standard before use.

4.4.3 Testing

4.4.3.1 Testing. - Testing and examination of the samples for First Article and Quality Conformance are completely described in the First Article and Quality Conformance table.

* 4.4.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods and Procedures

4.5.1 Materials, Components and Processes. - Compliance with all requirements of section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies and materials) have been inspected and, tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and Mechanical Inspections. - The visual, manual, and mechanical inspections and tests shall verify compliance with the requirements of sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table 1.

4.5.2 Hardness Test. - Each Rocket Head shall be subjected to a hardness test with a Rockwell Hardness Tester in accordance with Federal Test Method Standard No. 151, Method 243.1. If any Rocket Head fails to meet the requirements specified, it shall be classed defective.

4.5.3 Hardness Test. - Each Motor Case Assembly shall be subject to a hardness test with a Rockwell Hardness Tester in acordance with Federal Test Method Standard No. 151, Method 243.1. If any Rocket Motor Case Assembly fails to meet the requirement specified, it shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the currentversion before use.

4.5.4 Magnetic Particle Inspection. - Each Rocket Motor Case Assembly shall be subjected to magnetic particle inspection in accordance with MIL-I-6868 using the continuous wet, flourescent method. If any Rocket Motor Case Assembly fails to meet the requirement specified, it shall be classed defective.

* 5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging. - Packaging shall be Level B in accordance with MIL-STD-1169.

5.2 Packing. - Packing shall be Level B in accordance with MIL-STD-1169.

5.3 Marking. - Marking shall be Level B in accordance with MIL-STD-1169.

6. NOTES

6.1 Intended Use. - The metal parts covered by this specification are used in the Rocket Motor Assembly which is a major component of the Demolition Kit, Cratering: M180.

6.2 Ordering Data. - See MIL-A-48078.

6.3 Submission of Designs for Approval. - See MIL-A-48078. Submit equipment designs, as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-Q, Dover, New Jersey 07801.

6.4 Changes from Previous Issue. - The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from Revision B dated 13 August 1976 have been made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.5 Drawings. - Drawings listed in Section 2 of this specification under the heading U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal Drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Source: https://assist.dla.mil -- Downloaded: 2021-07-12T07:03Z
Check the source to verify that this is the current version before use.