MIL-M-50974C(AR)
19 MARCH 1983
SUPERSEDING
MIL-M-50974B
23 March 1979

MILITARY SPECIFICATION

MOTOR-DETONATOR ASSEMBLY, ROCKET, LOADING, ASSEMBLING AND PACKING (FOR DEMOLITION KIT, CRATERING: M180)

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions for the loading, assembling and packing of Rocket Motor-Detonator Assembly for Demolition Kit, Cratering: M180.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.1), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-585	-	Box, Wood, Wirebound.
PPP-B-601	-	Boxes, Wood, Cleated Plywood.
PPP-B-621	-	Box, Wood, Nailed and Lock Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-C-843	-	Cushioning Material, Cellulosic.
QQ-S-781	-	Strapping, Steel, and Seals.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-117	-	Bag, Sleeve and Tubing, Interior Packaging.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.5)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9244401 - Rocket Motor-Detonator Assembly. (Sheets 1 and 2)
9329725 - Packing and Marking For Box, Fiberboard For Rocket Motor Assembly or Rocket Motor and Detonator Assembly.
9329726 - Packing and Marking For Box, Packing For Box, Fiberboard For Rocket Motor and Detonator Assembly or Rocket Motor Assembly.
9340544 - Packing and Marking For Box, Packing, For Box, Fiberboard, For Rocket Motor and Detonator Assembly or Rocket Motor Assembly.

PUBLICATIONS

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 100-199 (latest revision).")

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B 117 (Part 10) - Salt Spray (Fog) Testing.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Rocket motor-detonator assembly. The rocket motor-detonator assembly shall comply with all requirements specified on Drawing (Dwg.) 9244401, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Pull test of butt splice. The butt slice shall show no evidence of slippage of the leads when the splice is subjected to a minimum static load of eight (8) pounds when tested as specified 4.5.3.

3.5 Water resistance (time delay electric blasting cap). The blasting cap shall function satisfactorily after being subjected to water immersion specified in 4.5.4.

3.6 Functioning time (time delay electric blasting cap).

3.6.1 Minus 40°F. The blasting cap, following temperature-conditioning, shall function high order on the first attempt in not less than 0.380 seconds and not more than 0.520 seconds after electrical initiation when tested as specified in 4.5.5.

3.6.2 Plus 130°F. The blasting cap, following temperature-conditioning, shall function high order on the first attempt in not less than 0.380 seconds and not more than 0.520 seconds after electrical initiation when tested as specified in 4.5.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

3.7 Welding. All welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration, and soundness of deposit representative of good welding practice. The process shall be such as to prevent warpage and distortion. There shall be no crack in or near welded areas.

3.8 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.9 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. External threads shall be full, complete and undamaged for their entire length. All soldering shall be performed in a thorough, workmanlike manner with no evidence of burning or charring. Paintings and coatings on all parts and assemblies shall be restored when such have been removed or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Part Description	Drawings	Quantity	
Rocket-Motor Detonator Assembly	9244401	10	
Clamp, Conduit	9244410	10	
Conduit, Detonator Wires	9244422	10	
Splice, Butt, Firing Circuit	9244425	10	
Body, Protector, Rocket	9244426	10	
Retainer, Protector, Rocket	9244427	10	
Flange, Rocket	9244447	10	
Support, Blasting Cap	9244449	10	
Blasting Cap, Electric, Time Delay	9244456	30	
Detonator Assembly	9329588	10	
Fiberboard Box (Interior)	9329725	1	(See Note)
Fiberboard Box (Exterior)	9329726	1	(See Note)

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

NOTE: Applicable when rocket-motor detonator assembly requires shipment from loading plant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE: Rocket Motor-Detonator Assembly		SHEET 1 OF 3		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rocket Motor Detonator Assembly (Dwg. 9244401)				
	Examination for Defects	10		3.3	4.4.2.9
	Resistance of installed circuit (Note 5 on Dwg.)	10 (a)		3.3	4.5.2
	Clamp, Conduit (Dwg. 9244410)				
	Examination for Defects	10		3.2	4.4.2.1
	Conduit, Detonator Wires (Dwg. 9244422)				
	Examination for Defects	10		3.2	4.4.2.2
	Salt Spray Test	10 (a/b)		3.2	4.5.1
	Splice, Butt, Firing Circuit (Dwg. 9244425)				
	Inspect for all drawing requirements	10		3.2	Gage/Visual

NOTES: a. This test shall be performed on the assemblies subjected to the examination for defects.
b. If any part shows evidence of corrosion (red rust, white salts), it shall be classed defective.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE: Rocket Motor-Detonator Assembly		SHEET 2 OF 3		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body, Protector, Rocket (Dwg. 9244426)				
	Examination for Defects	10		3.2	4.4.2.3
	Salt Spray Test	10(a/b)		3.2	4.5.1
	Retainer, Protector, Rocket Dwg. 9244427)				
	Examination for Defects	10		3.2	4.4.2.4
	Salt Spray Test	10(a/b)		3.2	4.5.1
	Flange, Rocket (Dwg. 9244447)				
	Examination for Defects	10		3.2	4.4.2.5
	Salt Spray Test	10(a/b)		3.2	4.5.1
	Support, Blasting Cap (Dwg. 9244449)				
	Examination for Defects	10		3.2	4.4.2.6
	Salt Spray Test	10(a/b)		3.2	4.5.1
	Blasting Cap, Electric, Time Delay (Dwg. 9244456)				
	Examination for Defects	10		3.2	4.4.2.7

NOTES: a. This test shall be performed on the parts subjected to the examination for defects.
b. If any part shows evidence of corrosion (red rust, white salts), it shall be classed defective.

DRD:R-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-M-50974C(AR)

PARAGRAPH	TITLE: Rocket Motor-Detonator Assembly		SHEET 3 OF 3		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Water Resistance Functioning	10		3.5	4.5.4
	Low temperature Functioning	10		3.6.1	4.5.5
	High temperature Functioning	10		3.6.2	4.5.6
	Detonator Assembly (Dwg. 9329588)				
	Examination for Defects	10		3.2	4.4.2.8
	Pull test of splices	10(a)		3.4	4.5.3

NOTES: a. This test may be performed on the assemblies subjected to the examination for defects.

DRDA:R-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each lot shall contain:

a. Booster assemblies of one lot interfix number from one manufacturer.
b. Rocket Motor assemblies of one lot interfix number from one manufacturer.
c. Rocket cable assemblies of one lot interfix number from one manufacturer.
d. Time delay electric blasting caps of one lot interfix number from one manufacturer.
e. Detonator assemblies of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Clamp, Conduit	1 OF 1	9244410
			NEXT HIGHER ASSEMBLY: 9244401

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Radius of clamping surface		0.40%(a)	3.2	Gage
102	Thickness		0.40%(a)	3.2	Gage
103	Location of holes		0.40%(a)	3.2	Gage
104	Diameter of holes		0.40%(a)	3.2	Gage
Minor					
201	Angle		0.65%(a)	3.2	Gage
202	Width		0.65%(a)	3.2	Gage
203	Total length		0.65%(a)	3.2	Gage
204	Protective finish missing or damaged (bare spot)		0.65%	3.2	Visual
205	Poor workmanship		1.0%	3.9	Visual

NOTES: a. See 4.5.7 for alternate method of sampling.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Conduit, Detonator Wires				9244422
					NEXT HIGHER ASSEMBLY 9244401
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test	(a)	--	3.2	4.5.1
102	Total length		0.40%	3.2	Gage
Minor					
201	Welding improper or poor welding workmanship		0.65%	3.7	Visual
202	Protective finish (Passivation) missing or damaged		0.65%	3.2	Visual
203	Paint missing or damaged (bare spot)		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.9	Visual

NOTES: a. Five (5) samples shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If one sample shows evidence of corrosion or salt deposits, the lot shall be rejected.

DRDL:R-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.3	Body, Protector, Rocket		9244426
			NEXT HIGHER ASSEMBLY 9329588

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width of retaining ring groove		0.40%	3.2	Gage
102	Runout of flange face with datum A		0.40%	3.2	Gage
103	Total length		0.40%	3.2	Gage
104	True position of holes		0.40%	3.2	Gage
105	Location of retaining ring groove		0.40%	3.2	Gage
106	Diameter of booster assembly cavity		0.40%	3.2	Gage
107	Depth to thread undercut, min.		0.40%	3.2	Gage
108	True position of pitch diameter of threads with datum A		0.40%	3.2	Gage
109	Pitch diameter of threads		0.40%	3.2	Gage
110	Diameter of center hole		0.40%	3.2	Gage
111	Large inside diameter		0.40%	3.2	Gage
112	Smaller outside diameter		0.40%	3.2	Gage
113	Runout of smaller outside diameter with datum A		0.40%	3.2	Gage
114	Runout of larger outside diameter with datum A		0.40%	3.2	Gage
115	Thickness of flange		0.40%	3.2	Gage
116	Diameter of retaining ring groove		0.40%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.3 Cont'd.	Body, Protector, Rocket				9244426
					NEXT HIGHER ASSEMBLY 9329588
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
117	Diameter of flange		0.40%	3.2	Gage
118	Salt spray test	(a)	--	3.2	4.5.1
Minor					
201	Diameter of blasting cap wires hole		0.65%	3.2	Gage
202	Thread undercut diameter		0.65%	3.2	Gage
203	Either countersink on center hole missing		0.65%	3.2	Visual
204	Radius on flange missing		0.65%	3.2	Visual
205	Protective finish mising or damaged (bare spot)		0.65%	3.2	Visual
206	Paint on prohibited surface		0.65%	3.2	Visual
207	Poor workmanship		1.0%	3.9	Visual

NOTES: a. Five (5) bodies shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If one sample shows evidence of corrosion or salt deposits, the lot shall be rejected.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Retainer, Protector, Rocket	1 OF 1	9244427
			NEXT HIGHER ASSEMBLY 9329588

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test	(a)	--	3.2	4.5.1
102	Pitch diameter of threads		0.40%	3.2	Gage
103	Major diameter of threads		0.40%	3.2	Gage
104	Length of thread		0.40%	3.2	Gage
105	Runout of pitch diameter of threads		0.40%	3.2	Gage
106	Outside diameter, min.		0.40%	3.2	Gage
107	Inside diameter booster retainer shoulder (1.25)		0.40%	3.2	Gage
108	Thickness of booster retainer shoulder		0.40%	3.2	Gage
Minor					
201	Diameter of holes		0.65%	3.2	Gage
202	Chamfer missing		0.65%	3.2	Visual
203	Protective finish missing or damaged (bare spot)		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.9	Visual

NOTES: a. Five (5) retainers shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If one sample shows evidence of corrosion or salt deposits, the lot shall be rejected.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.5	Flange, Rocket				9244447
					NEXT HIGHER ASSEMBLY
					9329588
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test	(a)	--	3.2	4.5.1
102	Largest outside diameter		0.40%	3.2	Gage
103	Second largest outside diamter		0.40%	3.2	Gage
104	Runout of second largest outside diameter		0.40%	3.2	Gage
105	Third largest outside diameter		0.40%	3.2	Gage
106	Diameter of protector body flange counterbore		0.40%	3.2	Gage
107	Diameter of protector bodyhole		0.40%	3.2	Gage
108	Runout of protector body hole		0.40%	3.2	Gage
109	Total thickness		0.40%	3.2	Gage
110	Depth of body protector flange counterbore		0.40%	3.2	Gage
111	Angle of tapered surface		0.40%	3.2	Gage
Minor					
201	Diameter of screw holes, max (6)		0.65%	3.2	Gage
202	Diameter of screw hole counterbores, max (6)		0.65%	3.2	Gage

NOTES: a. Five (5) flanges shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If one sample shows evidence of corrosion or salt deposts, the lot shall be rejected.

DRDAR-QA Form 160 Jul 77

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.5 Cont'd.	Flange, Rocket		9244447
			NEXT HIGHER ASSEMBLY 9329588

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
203	True position of screw holes (6)		0.65%	3.2	Gage
204	Width of slot		0.65%	3.2	Gage
205	Protective finish missing or damaged (bare spot)		0.65%	3.2	Visual
206	Paint missing or damaged		0.65%	3.2	Visual
207	Poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.6	Support, Blasting Cap		9244449
			NEXT HIGHER ASSEMBLY 9329588

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test (corrosion resistance)	(a)	--	3.2	4.5.1
102	Pitch diameter of threads		0.40%	3.2	Gage
103	Minor diameter of threads, max		0.40%	3.2	Gage
104	True position of pitch diameter of threads with datum A		0.40%	3.2	Gage
105	Outside diameter (thread end)		0.40%	3.2	Gage
106	Inside diamter of blasting cap cavity		0.40%	3.2	Gage
107	Runout of blasting cap cavity with datum A		0.40%	3.2	Gage
108	Depth of thread cavity		0.40%	3.2	Gage
109	Diameter of O ring groove		0.40%	3.2	Gage
110	True position of O ring groove with datum A		0.40%	3.2	Gage
111	Total length		0.40%	3.2	Gage
112	Width of O ring groove		0.40%	3.2	Gage
113	Distance between O ring groove and thread face		0.40%	3.2	Gage
114	Depth to bottom of blasting cap cavity		0.40%	3.2	Gage

NOTES: a. Five (5) supports shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If one sample shows evidence of corrosion or salt deposits, the lot shall be rejected.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.6 Cont'd.	Support, Blasting Cap				9244449
					NEXT HIGHER ASSEMBLY 9329588
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Distance from large end to shoulder		0.65%	3.2	Gage
202	Diameter of undercut (when applicable)		0.65%	3.2	Gage
203	Width of undercut (when applicable)		0.65%	3.2	Gage
204	Protective finish missing or damaged (bare spot)		0.65%	3.2	Visual
205	Paint missing or damaged		0.65%	3.2	Visual
206	Poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244456
4.4.2.7	Blasting Cap, Electric Time Delay				NEXT HIGHER ASSEMBLY 9329588
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
101	Water resistance - functioning	(a)	0.40%	3.5	4.5.4
102	Low temperature functioning	(a/b)	0.40%	3.6.1	4.5.5
103	High temperature functioning	(b)	0.40%	3.6.2	4.5.6
104	Shunt damaged or missing		100%	3.2	Visual
105	Insulation or lead wires damaged		0.40%	3.2	Visual
Minor					
201	Length of leads, min		0.65%	3.2	Gage
202	Diameter		0.65%	3.2	Gage
203	Poor workmanship		1.0%	3.9	Visual

a. Sampling shall be as specified in MIL-STD-105, using Code Letter G.
b. Sampling shall be as specified in (A). One-half the samples shall be tested at the low temperature and the other half tested at the high temperature. If any failure occurs at either temperature, the lot shall be rejected.

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9329588
4.4.2.8	Detonator Assembly				NEXT HIGHER ASSEMBLY 9244401
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test of butt and parallel splices		100%	3.4	4.5.3
102	Cap screw turns when min torque is applied		0.40%	3.2	Gage
103	Distance from top of spring pin to counterbore face of flange		0.40%	3.2	Gage
104	Spring pin not flush or below flush to surface on protector body		0.40%	3.2	Gage
105	Insulation sleeving on blasting cap wires damaged or missing (2 places)		0.40%	3.2	Visual
106	Adhesive missing on blasting cap lateral surface		0.40%	3.2	Visual
107	Primer and sealant on threads missing (2 places)		0.40%	3.2	Visual
108	Part missing or incorrectly assembled (spring pin, cap screw, protector retainer, time delay blasting cap, booster assembly, retaining ring, packing O-ring, blasting cap support)		0.40%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9329588
4.4.2.8 Cont'd.	Detonator Assembly				NEXT HIGHER ASSEMBLY 9244401
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
109	Booster assembly damaged (dented, punctured or wrinkled)		0.40%	3.2	Visual
110	Ends of wires not twisted or taped		0.40%	3.2	Visual
Minor					
201	Lubricant around O-ring and adjacent surface missing		0.65%	3.2	Visual
202	marking misleading, illegible or missing		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.9	Rocket Motor-Detonator Assembly				9244401
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Shorting (Safety) or Continuity plugs missing, improperly installed or making improper contact		100%	3.3	Visual/Manual
2	Warning tags (2) missing, incorrect or illegiole		100%	3.3	Visual
Major					
101	Pull test of butt splice		100%	3.4	4.5.3
102	Resistance of installed circuit		100%	3.3	4.5.2
103	Butt splice wires incorrectly stripped or not taped or crimped as required		0.40%	3.3	Visual
104	Corrosion or foreign matter on any component or surface in rocket motor assembly		0.40%	3.9	Visual
105	Sealant or primer missing from cap screw threads (6)		0.40%	3.3	Visual
106	Butt splice incorrectly assembled		0.40%	3.3	Visual
107	Rocket flange groove not in line with conduit		0.40%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.9 Cont'd	Rocket Motor-Detonator Assembly				9244401
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
109	Tape over wires at open end of rocket motor assembly incorrect color or missing		0.40%	3.3	Visual
110	Felt pad on detonator assembly missing or peeling		0.40%	3.3	Visual
111	Wire leads from cable assembly incorrectly stripped or not spliced		0.40%	3.3	Visual
112	Wire leads from igniter assembly not spliced or insecurely crimped		0.40%	3.3	Visual
113	Firing lead assembly improperly coiled, wrapped or taped or insecurely fastened to rocket motor assembly		0.40%	3.3	Visual
114	Cable assembly not securely taped to rocket motor assembly		0.40%	3.3	Visual
115	Booster assembly in detonator assembly damaged (cut, punctured or wrinkled)		0.40%	3.3	Visual
116	Part missing or damaged (clamps, screws)		0.40%	3.3	Visual
Minor					
201	Poor workmanship (excl. 105 above)		1.0%	3.9	Visual
202	Marking on motor assembly misleading, illegible or missing		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Box, Fiberboard (prior to sealing)				9329725
					NEXT HIGHER ASSEMBLY 9329726
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Component improperly packed		0.40%	3.2	Visual
Minor 201	Packing components missing, inadequate or improperly positioned		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9329725
4.4.2.11	Box, Fiberboard (after sealing)				NEXT HIGHER ASSEMBLY 9329726
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box punctured, torn or cut		0.40%	3.2	Visual
Minor					
201	Contents loose (when box is tilted)		0.65%	3.2	Manual
202	Marking missing, incorrect or illegible		0.65%	3.2	Visual
203	Sealing strip incomplete or loose		0.65%	3.2	Visual
204	Corner not blunted		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Packing Box (prior to securing top)	1 OF 1	9329726
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Contents positioned improperly		0.65%	3.2	Visual/Manual
202	Foreign Material in box		0.65%	3.2	Visual
203	Insufficient area for subsequent seals		0.65%	3.2	Visual
204	End, side, and top fillers missing or inadequate		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-50974C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Packing Box (after securing top)				9329726
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contents exposed or loose		0.40%	3.2	Visual/Manual
102	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
103	Marking missing, incorrect, or illegible		0.40%	3.2	Visual
Minor					
201	Hardware improperly engaged, missing, or broken		0.65%	3.2	Visual
202	Seal missing, unsealed or improperly positioned		0.65%	3.2	Visual
203	Board broken or split		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection. (See 6.4)

4.5.1 Salt spray test. The salt spray test shall be performed utilizing the equipment, methods and procedures specified in ASTM B-117. Exposure time and sodium chloride solution shall be in accordance with the applicable finish specification.

4.5.2 Resistance of installed circuit. This test shall be performed 100% on the installed circuit of the loaded rocket motor assemblies. Measurement must be made from receptacle for firing lead assembly, with firing lead assembly 3P and shorting plug 7P removed. The equipment shall limit the current to 10 milliamperes (.010 amperes) maximum. Any unit exhibiting a resistance outside the permitted range specified shall be classed defective and removed from the lot.

WARNING: This test shall be considered dangerous and shall be performed behind a suitable barricade.

NOTE: The continuity plug assembly 3S, used in connecting other units shall not be removed while conducting this test.

4.5.3 Pull test of butt splice. The lead wires from the opposite ends of each butt splice shall be attached to the applicable test fixture. The required force shall be applied to each butt splice in a smooth, gradual manner. Observation shall be made for evidence of slippage of the lead wires in the splice. Any assembly which fails to comply with the requirement shall be classed defective and removed from the lot.

4.5.4 Water resistance (time delay electric blasting cap). The blasting cap shall be subjected to water immersion in not less than one (1) foot of water, water temperature of $70^{o}F + 5^{o}F$, for not less than 1 hour. Upon conclusion of the hour, the blasting caps shall be functioned using a firing current of 2 to 5 amperes. Any blasting cap which fails to function shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

4.5.5 Low temperature functioning (time delay electric blasting cap). The blasting caps shall be temperature-conditioned at $-40^{o}+2^{o}F$ not less than six (6) hours. They shall then be mounted in the required test fixture and functioned. The delay time shall be recorded. Delay time is defined as the time from application of required voltage to high order detonation of the blasting cap. Any unit which fails the requirement specified shall be classed defective.

4.5.6 High temperature functioning (time delay electric blasting cap). The blasting caps shall be tested as specified in 4.5.5, except that the conditioning temperature shall be $+130^{o} \pm 2^{o}F$.

4.5.7 Dimensional control of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Office to substantiate the request.

5. PACKAGING

5.1 Cleaning. The following items shall be cleaned in accordance with process C-1 of MIL-P-116:

Rocket-Motor Detonator Assembly	Dwg. 9244401
Clamp, Conduit	Dwg. 9244410
Conduit, Detonator Wires	Dwg. 9244422
Splice, Butt Firing Circuit	Dwg. 9244425
Body, Protector, Rocket	Dwg. 9244426
Retainer, Protector, Rocket	Dwg. 9244427
Flange, Rocket	Dwg. 9244447
Support, Blasting Cap	Dwg. 9244449
Blasting Cap, Electric, Time Delay	Dwg. 9244456
Detonator Assembly	Dwg. 9329588

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

5.2 Drying. The components and assemblies referenced in 5.1 shall be dried in accordance with MIL-P-116.

5.3 Unit packaging.

5.3.1 Level A. All items referenced in 5.1, except the Rocket-Motor Detonator Assembly, the Blasting Cap, Electric, Time Delay and the Detonator Assembly, shall be individually packaged in accordance with submethod IA-8 of MIL-P-116, utilizing a heatsealed barrier bag, Type 1, Class E, per MIL-B-117.

5.3.2 Level B. Unit packaging shall be as specified in 5.3.1.

5.3.3 Level C.

5.3.3.1. The Rocket-Motor Detonator Assembly shall be packaged in accordance with Dwg. 9329725.

5.3.3.2 The Blasting Cap, Electric, Time Delay and the Detonator Assembly shall be packaged in accordance with the Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Commercial. Commercial packaging shall be in accordance with MIL-STD-1188, except the Rocket-Motor Detonator Assembly, the Blasting Cap, electric Time Delay and the Detonator Assembly shall not be packaged commercial.

5.5 Intermediate packaging.

5.5.1 Level A. All items referenced in 5.1, except the Rocket-Motor Detonator Asembly, the Blasting Cap, Electric, Time Delay, and the Detonator Assembly, shall be packaged in a snug-fitting fiberboard box conforming to Class WWVR, Grade V3c, of PPP-B-636, utilizing enough cushioning material, PPP-C-843, to assure a tight pack and closed in accordance with PPP-B-636.

5.5.2 Level B. Intermediate packaging shall be as specified in 5.5.1.

5.5.3 Commercial. Packaging shall be in accordance with MIL-STD-1188, except those items referenced in 5.4 shall not be commercially packaged.

5.6 Packing.

5.6.1 Level A. Intermediate packages specified in 5.5.1 shall be overpacked in Grade B, Style A, B, I or J, PPP-B-601 boxes, Class 2, Style 4, PPP-B-621 boxes or Class 3, Style 2 or 3, PPP-B-585 boxes. Closure and strapping shall be in accordance with applicable container specifications except strapping shall conform to Type I or IV, Finish A, QQ-S-781.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

5.6.2 Level B. Packing shall be as specified in 5.6.1.

5.6.3 Level C.

5.6.3.1 The Rocket-Motor Detonator Assembly shall be packed in accordance with Dwg. 9329726 or 9340544, as applicable.

5.6.3.2 The Blasting Cap, Electric, Time Delay and the Detonator Assembly shall be packed in accordance with the Code of Federal Regulations, Title 49, Parts 100-199.

5.6.4 Commercial. Commercial packing shall be in accordance with MIL-STD-1188, except those items referenced in 5.4 shall not be commercially packed.

5.7 Marking.

5.7.1 Level A. Marking shall be in accordance with MIL-STD-129.

5.7.2 Level B. Marking shall be in accordance with MIL-STD-129.

5.7.3 Level C. Marking shall be in accordance with MIL-STD-129, Dwgs. 9329726, 9340554, or Code of Federal Regulations, Title 49, Parts 100 to 199, as applicable.

5.7.4 Commercial. Marking shall be in accordance with MIL-STD-1188.

5.8 Shipping. When assemblies from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of lots in transit.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.

6.3 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

6.4 Submission of test data. When required by incorporation of DD Form 1423 into the contract, all test data required in Section 4 of this specification shall be submitted in accordance with Data Item Description DI-R-1724. In addition to the normal distribution of records, one copy of all test data shall be forwarded to the address specified in 6.3.

(Copies of data items description required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A255)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT R & D COMMAND
ATTN: DRDAR-QAT-M
DOVER, NEW JERSEY 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-50974C (AR)	Motor-Detonator Assembly, Rocket, Loading, Assembl And Packing (For Demolition Kit, Cratering: M180

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION (Mark one)
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER (Specify): _____
b. ADDRESS (Street, City, State, ZIP Code)	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER (Last, First, MI) – Optional	b. WORK TELEPHONE NUMBER (Include Area Code) – Optional
c. MAILING ADDRESS (Street, City, State, ZIP Code) – Optional	8. DATE OF SUBMISSION (YYMMDD)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:04Z
Check the source to verify that this is the current version before use.