MIL-M-51282D(EA)
14 November 1986
SUPERSEDING
MIL-M-51282C(EA)
8 August 1983

MILITARY SPECIFICATION

MASKS, CHEMICAL-BIOLOGICAL, FIELD, M17A1

This specification is approved for use by U.S. Army Chemical Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a chemical-biological mask having the capability for water drinking and resuscitation.

1.2 Classification. The masks shall be of the following sizes, as specified (see 6.2):

Small	-	Drawing 5-1-551-10
Medium	-	Drawing 5-1-551-20
Large	-	Drawing 5-1-551-30
Extra Small	-	Drawing 5-1-551-40

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-SPD-TS, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

AMSC N/A

FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781 - Strapping, Steel, and Seals.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-F-320 - Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

MILITARY

MIL-F-51425 - Filter Element Set, Chemical-Biological Mask, M13A2.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.

2.1.2 Drawings, technical data package lists, and publications. The following drawings, technical data package lists, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS AND TECHNICAL DATA PACKAGE LISTS (TDPL)

U.S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

TDPL 5-1-551 - Masks, Chemical-Biological, Field, M17A1.
TDPL 136-5-540-1 - Airflow Resistance Tester, Q179.
TDPL 136-5-630 - Valve Assembly Leakage Tester, Q210.
TDPL 136-42-102-20 - Penetrometer, Filter Testing, DOP, Q127.
TDPL 136-42-750-2D - Gas Mask Leakage Tester, M14.
TDPL 136-44-20 - Inhalation and Exhalation Resistance Indicator, Q213.
TDPL 136-45-202-15 - Outlet Valve Leakage Indicator, M4A1.
TDPL 136-301-38 - Dry Bubble Air Leakage Tester, Q204.
5220-A51-4017 - Target Gage.

(Copies of specifications, standards, drawings, technical data package lists, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Preproduction. Prior to the start of regular production, a preproduction sample of masks shall be produced, in accordance with this specification, for examination and tests (see 4.3).

3.2 Materials and components.

3.2.1 Materials. All materials cited on TDPL 5-1-551 and its subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.2.2 Components. All components of the field chemical-biological masks shall conform to the specifications and drawings listed on TDPL 5-1-551 and its subsidiary drawings.

3.2.3 Filter elements. Only matched pairs of filter elements shall be used for testing or packaged with finished mask (see MIL-F-51425).

3.3 Manufacture and assembly. The masks shall be manufactured and assembled in accordance with Drawing 5-1-551.

3.4 Leakage.

3.4.1 Mask leakage. With the outlet valve sealed and the filter element inlet sealed, leakage of the mask shall not exceed 0.003 percent penetration when tested as specified in 4.4.4.1.

3.4.2 Outlet-valve leakage. Leakage of the outlet valve shall not exceed 15 milliliters (ml) of air per minute at a pressure differential of 25 millimeters (mm) of water when tested as specified in 4.4.4.2.

3.4.3 Drink system leakage. The drink system shall not leak more than 0.50 ml of air per minute at a pressure differential of 6.0 inches of water when tested as specified in 4.4.4.9.

3.4.4 Resuscitation valve seat housing assembly leakage (assembled into the mask). The resuscitation valve seat housing assembly when subjected to a pressure of 20.00 inches [50.80 centimeters (cm)] of water shall retain a minimum pressure of 14.00 inches (35.56 cm) of water when tested as specified in 4.4.4.10.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:05Z
Check the source to verify that this is the current version before use.

3.5 Resistance.

3.5.1 Inhalation resistance. Inhalation resistance of the mask shall not exceed 55 mm of water at a continuous airflow of 85 liters per minute when tested as specified in 4.4.4.3.

3.5.2 Exhalation resistance. The exhalation resistance of the mask shall not exceed 32 mm of water at a continuous airflow of 85 liters per minute when tested as specified in 4.4.4.4.

3.6 Drinking assembly airflow. The drinking assembly shall have an airflow of 2.0 liters of air per minute at a maximum pressure differential of 2.2 inches of water when the lever is actuated counterclockwise until fully against its stop when tested as specified in 4.4.4.5.

3.7 Filter elements.

3.7.1 Aerosol penetration. The filter elements shall be tested for penetration. The penetration of each filter element shall not exceed 0.015 percent when tested as specified in 4.4.4.6.

3.8 Actuation of resuscitation tube. When the lever is fully actuated toward the stop in a clockwise direction the resuscitation tube shall move smoothly without distortion of the support assembly and shall fall within the periphery of and pass through the target gage area so that the mouthpiece extends beyond the back surface of the gage when tested as specified in 4.4.4.7.

3.9 Actuation of drinking tube. When the lever is fully actuated toward the stop in a counterclockwise direction the drinking arm shall move smoothly and the mouthpiece shall fall within the periphery of and pass through the target gage area so that the mouthpiece extends beyond the back surface of the gage when tested as specified in 4.4.4.8. The kink tube shall be open and not twisted and shall not move from the metal housing or arm flange.

3.10 Workmanship. The mask assembly shall be free from contamination and imperfections such as dirt, grease, oil, foreign matter, malfunctioning of hardware, and damage such as cracks, burrs, sharp edges, tears, punctures, scratches, permanent set of rubber parts, or distortion of metal parts.

3.11 Lot marking. Lot number as specified by the procuring activity shall be embossed on the faceblank as required by Drawing 5-1-553.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.2 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A sample of 125 field chemical-biological masks of each size shall be produced, using the same methods, materials, and equipment as will be used during regular production.

4.3.2 Inspection procedure. The 125 sample masks of each size shall be examined for all requirements of the drawings and of this specification.

4.3.3 Tests. The 125 sample masks of each size shall be tested in accordance with 4.4.4.

4.3.4 Acceptance/rejection criteria. The preproduction sample shall meet the examination and tests specified in 4.3.2 and 4.3.3 to be acceptable. The contractor shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the masks of one size produced by one manufacturer, at one plant from the same materials and under essentially the same manufacturing conditions. However, no more than one lot of faceblanks and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

voicemitter outlet-valve assemblies and no more than two lots of nosecup assemblies and filter elements shall be represented in any one lot of finished masks. The two lots of nosecup assemblies and two lots of filter elements must be sequentially produced. Any change in equipment or procedure used in regular production from that used in the preproduction sample shall be approved by the Government prior to its institution.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For tests. Sampling for 4.4.4.6 shall be conducted in accordance with MIL-STD-105, using level S-3.

4.4.3 Inspection procedure. The sample masks shall be examined in accordance with the classification of defects and with MIL-STD-105. Each item in the lot shall be examined for critical defects. Filter elements shall be examined in accordance with 4.4.4.6 using an AQL of 0.65 percent defective.

4.4.3.1 Classification of defects.

(a) Masks, chemical-biological, field, M17A1 (Drawing 5-1-551).

Categories	Defects	Acceptance standards
Critical:		
1	Drink system leakage	4.4.4.9
2	Mask leakage	4.4.4.1
3	Outlet valve leakage	4.4.4.2
4	Lens split or cracked	
Major:	AQL 1.0 percent defective	
101	Component missing, incorrect, or incorrectly assembled	
102	Workmanship (3.10)	
103	Inlet valve cap does not attach or detach properly	
104	Marking incorrect	
105	Unmatched pair of filter elements	
106	Headharness buckle not free to rotate in loop of clip	
107	Lever inoperative in clockwise or counterclockwise directions	
108	Drinking tube actuation incorrect	4.4.4.8
109	Drinking tube does not retract into nosecup well when the lever is actuated clockwise	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

110	Resuscitation tube actuation incorrect	4.4.4.7
111	Resuscitation tube does not retract into nosecup well	
112	Resuscitation valve disk distorted or folded	
	AQL 0.25 percent defective	
113	Inhalation resistance	4.4.4.3
114	Exhalation resistance	4.4.4.4
115	Drinking assembly airflow	4.4.4.5
116	Resuscitation valve seat housing assembly leakage	4.4.4.10
117	Multiple marking on single tab	
118	Tackiness of rubber in lot marking area	
Minor:	AQL 2.5 percent defective	
201	Protective finish missing or or incorrect	
202	Marking missing or illegible	
203	Lot marking in wrong location on forehead tabs	

(b) Packaging (section 5).

Categories	Defects
Minor:	AQL 2.5 percent defective
201	Unit pack assembly incorrect (5.1)
202	Packing assembly incorrect (5.2)
203	Shipping container (5.2.1 and 5.2.2) construction, closure, or strapping not correct
204	Marking illegible or incorrect
205	Palletization assembly or strapping not as specified

4.4.4 Tests.

4.4.4.1 Mask assembly leakage. Leakage of the mask assembly, complete with filter elements less inlet valve assembly, shall be determined with the M14 Gas Mask Leakage Tester (TDPL 136-42-750-2D).

4.4.4.2 Outlet valve leakage. The leakage of the outlet valve shall be determined with the M4A1 Outlet Valve Leakage Indicator (TDPL 136-45-202-15).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.4.4.3 Inhalation resistance. Inhalation resistance of the mask (Drawing 5-1-551) shall be determined with the Q213 Inhalation and Exhalation Resistance Indicator (TDPL 136-44-20).

4.4.4.4 Exhalation resistance. Exhalation resistance of the mask (Drawing 5-1-551) shall be determined with the Q213 Inhalation and Exhalation Resistance Indicator (TDPL 136-44-20).

4.4.4.5 Drinking assembly airflow. Airflow through the drinking assembly of the mask shall be determined with the Q179 Airflow Resistance Tester (TDPL 136-5-540-1).

4.4.4.6 Aerosol penetration. Penetration of the filter elements shall be determined with the Q127 Penetrometer (TDPL 136-42-102-4), at a flow rate of 16 liters per minute.

4.4.4.7 Actuation of resuscitation tube. Position the mask in the modified extended position target gage and position the target. Actuate the lever three times as specified in 3.8. The mouthpiece must fall within the periphery of and pass through the gage (5220-A51-4017).

4.4.4.8 Actuation of the drinking tube. Position the mask in the modified extended position target gage and position the target. Actuate the lever three times as specified in 3.9. The mouthpiece must fall within the periphery of and pass through the gage (5220-A51-4017).

4.4.4.9 Drink system leakage. Leakage of the mask drink system shall be determined with the Q204 Dry Bubble Air Leakage Tester (TDPL 136-301-38). During testing the lever shall be turned counterclockwise to the stop to detect leakage of the quick disconnect coupling valve. After testing the quick disconnect coupling valve, a suitable plug shall be inserted into the drink mouthpiece to form a leak tight seal. The lever shall be turned counterclockwise to the stop and the quick disconnect valve plunger shall be depressed to detect leakage in the drink system tubing components.

4.4.4.10 Resuscitation valve seat housing assembly leakage (assembled into the mask). Leakage of the valve seat housing assembly shall be determined with the Q210 Valve Assembly Leakage Tester (TDPL 136-5-630).

4.4.5 Acceptance/rejection criteria. For the test in 4.4.4.6 if any filter element or pair of filter elements fails to meet the requirements of this specification, the lot represented shall be rejected.

5. PACKAGING

5.1 Preservation and unit packing, level A. Each mask (Drawing 5-1-551-10, -20, -30, or -40) shall be unit packed as specified on Drawing 5-1-333. No preservation compounds shall be used on any portion of the mask or its components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

5.2 Packing, level A or B (see 6.2).

5.2.1 Level A. Eight masks of one size (see Drawing 5-1-551), unit packed as specified in 5.1, shall be packed in an overseas type cleated plywood box conforming to style I, grade A, weight of contents 0-100 pounds, type 1 load of PPP-B-601, having approximate inside dimensions of 597 mm by 489 mm by 311 mm (23-1/2 by 19-1/4 by 12-1/4 inches) length, width, and depth respectively. Arrangement of the packages in the box shall be two rows of four each. Filler pads fabricated of weather-resistance fiberboard conforming to PPP-F-320 shall be included, as necessary, to make a tight pack. The box shall be closed and strapped in accordance with the appendix to PPP-B-601, using strapping and seals conforming to QQ-S-781 (Strapping - type 1 (Regular duty), finish B, grade 2 and Seals - type D, style I or IV, finish B, grade 2).

5.2.2 Level B. Eight masks of one size (see Drawing 5-1-551), unit packed as specified in 5.1, shall be packed as specified in 5.2.1, except that the box shall be a weather-resistance fiberboard type conforming to either type CF, variety SW, grade V3c, or type SF, grade V3s (normal requirements), of PPP-B-636. The box shall be closed in accordance with the Method V closure requirements and reinforced using nonmetallic or tape banding in accordance with reinforcing requirements in the appendix to PPP-B-636.

5.3 Palletization. Masks packed in accordance with 5.2.1 and 5.2.2 shall be palletized in accordance with the applicable requirements of MIL-STD-147. When the quantity of packed masks (5.2.1 and 5.2.2) is insufficient to constitute a full pallet load, the packed masks may not be palletized.

5.4 Marking. In addition to any special marking required in contract or order (see 6.2), the unit packs (5.1) shall be marked in accordance with instructions on Drawing 5-1-333. The level A and B shipping containers (5.2.1 and 5.2.2) and pallet loads of level A and B packs (5.3) shall be marked in accordance with the applicable requirements of MIL-STD-129. Each level A and B shipping container (5.2.1 and 5.2.2) shall be marked to show the corresponding lot number and cure date markings as shown on the unit pack containers (5.1) contained therein. When two or more unit packs bear different cure dates, the earliest date shall be shown on the shipping container. These markings shall be in conformance with the requirements of MIL-STD-129. Pallet loads containing more than one lot of masks shall be marked to maintain lot integrity. The lot number shall be identified on a label and placed as near to the address markings as possible. The maximum label size shall be 102 mm by 152 mm (4 by 6 inches) and the lettering not less than 6.5 mm (1/4 inches) in height. The label requirement shall be in accordance with MIL-STD-129. Omit nomenclature (Mask, Chemical-Biological Field, M17A1) marking on outside shipping containers for this item. Do not omit other identification marking on outside shipping containers.

5.5 Repair parts. When the mask's components are procured for storage and issue as repair parts, preservation, unit packing, and marking shall be as specified on their packaging data sheets or Special Packaging Instructions which are identified by part number/National Stock Number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The mask covered by this specification is intended for protection of the eyes and respiratory system against toxicological warfare agents. It is not intended for protection against carbon monoxide or ammonia.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Size of mask.
(c) Preproduction:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

(d) Elements for lot numbering (see Directive 511).
(e) Level of packing required (see 5.2).

6.3 Component specifications.

Number	Title
MIL-B-51097	Backing Material, C18.
MIL-B-51170	Bag, Waterproof, Chemical-Biological Mask, M1.
MIL-C-50081	Cap-Inlet Valve Assembly, C20.
MIL-C-51285	Carrier, Chemical-Biological Mask: Field, M15A1.
MIL-C-13724	Charcoal, Activated, Impregnated, ASC.
MIL-C-51232	Cloth, Marquisette, Polyester.
MIL-C-51096	Core Material, C18.
MIL-C-51280	Cover, Voicemitter-Outlet Valve, C13R1.
MIL-D-50082	Discs, Inlet and Nosecup Valve.
MIL-D-10132	Discs, Valve.
MIL-E-51420	Edgeseal Materials, Chemical-Biological Filter.
MIL-E-50069	Eyering, Field Protective Mask, C4.
MIL-F-51286	Faceblanks, Chemical-Biological Mask, C17R1.
MIL-F-51425	Filter Element Set, Chemical-Biological Mask, C13A2.
MIL-F-51095	Filter Material, Gas-Aerosol, C18R1.
MIL-H-10120	Headharness, C8R1.
MIL-L-50064	Lenses, Ophthalmic, Simple.
MIL-N-51287	Nosecup Assemblies, Chemical-Biological Mask, C10.
MIL-O-50077	Outsert, Eyelens, M1.
MIL-R-50068	Ring, Crimping (For ABC-M17 Mask).
MIL-R-51283	Rubber Fabricated Products for M17A1/M17A2 Masks.
MIL-S-51421	Screening, Chemical-Biological Filter.
MIL-V-50065	Valve, Nosecup.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Number	Title
MIL-V-51281	Voicemitter-Outlet Valve Assembly, Chemical-Biological Mask, C29R5.
SQAP 5-1-332	Faceform, Exterior Support, Protective Mask.
SQAP 5-2-955	Button, Flap, Long.
SQAP 5-2-956	Button, Flap, Short.
SQAP 5-2-962	Clip and Buckle Assembly.
QAP 5-2-965	Temple Pin.
SQAP 5-81-104	Valve Seat Housing.
SQAP 5-81-114	Coupling Assembly, Quick Disconnect.
SQAP 5-81-12[illegible]	Mouthpiece.
QAP 5-81-123	Housing.
QAP 5-81-140	Expander Ring.
QAP 22-4-48	Web Strap Buckle.
QAP 5-3-1001	Stiffarator.

6.4 Subject term (key word) listing.

Chemical-biological mask
Mask, field
Protective equipment
Protective mask

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A871

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

[illegible] for examination and nondestructive tests. Sampling shall be con-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
U.S. Army Chemical Research, Development
and Engineering Center
ATTN: SMCCR-SPT-S
Aberdeen Proving Ground, MD 21010-5423

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-51282D(EA)	MASKS, CHEMICAL-BIOLOGICAL, FIELD, M17A1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark c*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Are Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.