INCH-POUND

MIL-O-51142C(EA)
3 May 1993
SUPERSEDING
MIL-O-51142B(EA)
21 September 1987

# MILITARY SPECIFICATION

# OUTSERT, EYELENS ANTIGLARE, CHEMICAL-BIOLOGICAL MASK, ABC-M2

*This specification is approved for use by the U.S. Army Edgewood Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.*

## 1. SCOPE

**1.1 Scope.** This specification covers one type of chemical-biological mask eyelens outsert.

## 2. APPLICABLE DOCUMENTS

**2.1 Government documents.**

**2.1.1 Specifications, standards, and handbooks.** The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

FEDERAL

FED. TEST METHOD STD. NO. 101 - Test Procedures for Packaging Materials

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Technical Director, U.S. Army Edgewood Research, Development and Engineering Center, ATTN: SCBRD-ENE (Std/Specs/Pkg), Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

**2.1.2 Other Government documents, drawings, and publications.** The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. ARMY EDGEWOOD RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

DRAWINGS

5-2-1602 - Outsert, Eyelens Antiglare, Chemical-Biological Mask, M2

SPECIAL PACKAGING INSTRUCTIONS (SPI)

P5-2-1602 - Outsert, Eyelens Antiglare, Chemical-Biological Mask, M2

(Copies are available from Commander, U.S. Army Information Systems Command, ATTN: SMCRI-IMO-D, Rock Island, IL 61299-7210.)

**2.2 Non-Government publications.** The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issue of the documents cited in the solicitation (see 6.2).

ASTM STANDARDS

D 570 - Water Absorption of Plastics
D 882 - Tensile Properties of Thin Plastic Sheets and Films
D 3951 - Commercial Packaging

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

**2.3 Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

**3.1 Materials.** All materials cited on Drawing 5-2-1602 or in subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth in the drawings.

**3.1.1 Lens (plastic sheet stock).**

**3.1.1.1 Composition and physical performance.** The plastic sheet stock shall be cellulose acetate conforming to table I, 3.1.1.1.1 and 3.1.1.1.2.

TABLE I. Lens material properties

| Property | Unit | Minimum | Maximum | Test Paragraph |
|---|---|---|---|---|
| Water absorption | percent | --- | 7.0 | 4.4.6.2 |
| Tensile strength | psi | 4,750 | --- | 4.4.6.3 |
| Elongation at rupture | percent | 20 | --- | 4.4.6.3 |

**3.1.1.1.1 Visible light transmission.** The visible light transmission of the lens material shall conform to table II with a tolerance of ± 4 percent transmission at any given wavelength, when tested as specified in 4.4.6.4.

3.1.1.1.2 **Color perception.** There shall be no loss of color perception through the lens material when tested as specified in 4.4.6.5.

3.1.1.2 **Optical characteristics.** The lens material shall be free from imbedded particles, bubbles, crazed areas, blemishes, localized imperfections (such as a group of closely positioned defects) or other defects which are visible to the unaided eye.

3.2 **Components.** All components of the outsert shall conform to the specifications and drawings listed on Drawing 5-2-1602 and subsidiary drawings.

**3.3 Manufacture and assembly.** The outsert shall be manufactured and assembled as specified on Drawing 5-2-1602 and subsidiary drawings listed thereon.

**3.4 First article.** Unless otherwise specified in the contract, a first article sample shall be produced in accordance with this specification for examination and tests (see 4.3 and 6.2), prior to the start of regular production.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

TABLE II. Light transmission

| Wavelength (Millimicrons) | Percent Transmission |
|---|---|
| 400 | 10.0 |
| 420 | 12.0 |
| 440 | 13.5 |
| 460 | 14.5 |
| 480 | 14.9 |
| 500 | 15.0 |
| 520 | 15.1 |
| 540 | 14.8 |
| 560 | 14.6 |
| 580 | 13.5 |
| 600 | 13.5 |
| 620 | 14.8 |
| 640 | 15.7 |
| 660 | 16.8 |
| 680 | 15.4 |
| 700 | 16.6 |

3.5 **Workmanship.**

3.5.1 **Lens material (plastic sheet).** The lens material shall be free from ragged, crushed or uneven edges; contamination such as dirt or grease and damage such as cuts, punctures, wrinkles, tears or holes.

3.5.2 **Outsert lens.** The outsert lens shall be free from contamination such as dirt or grease and damage such as warpage, cracks or scratches.

## 4. QUALITY ASSURANCE PROVISIONS

**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

**4.1.1 Responsibility for compliance.** All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

**4.1.2 Contractor assurance of compliance.** The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing, special packaging instruction, and specification requirements using, as a minimum, the conformance criteria specified herein.

**4.1.3 Alternative inspection provisions.** Alternative inspection procedures, methods, or equipment, such as statistical process control, tool control, and other types of sampling procedures may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the inspection provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation and approval. (See 6.5.) When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the quality assurance provisions specified herein. In cases of dispute as to whether the contractor's proposed alternative provides equal quality assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

**4.3 First article inspection.**

**4.3.1 Inspections to be performed.** As determined by the Government, the first article sample items shall be examined and tested in accordance with this specification using either the first article procedures in this specification or other first article procedures which will be provided by the Government. As determined by the Government, the sample first article items may be subjected to any or all of the examinations and tests specified in this specification and be inspected for compliance with any or all of the requirements of the applicable drawings and special packaging instructions.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

**4.3.2 Sample.** The first article sample shall consist of 15 outserts and 4 sheets of plastic sheet stock manufactured and packaged (when military packaging of outserts is required) using the same methods, materials, equipment, and processes as will be used during regular production and 3 empty unit pack containers used for outserts. Empty unit pack containers shall only be required as part of the first article sample when military packaging is required. The first article sample shall be submitted for inspection and approval in accordance with the terms of the contract.

**4.3.3 Inspection procedure.** Five outserts, four sheets of plastic sheet stock, and when applicable, the outsert packaging in the first article sample shall be examined and tested in accordance with the classification of characteristics in 4.4.5.

**4.3.4 Acceptance criteria.** If any first article sample item fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure to comply with any of the requirements. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

**4.4 Quality conformance inspection.**

**4.4.1 Lotting.**

**4.4.1.1 For lens material.** The plastic sheet stock for the lenses shall consist of all sheet material manufactured under the same conditions, processes, time and material. The lot size, for the purpose of determining the sample size in accordance with table III, shall be expressed in units of plastic sheets.

**4.4.1.2 For outserts.** A lot shall consist of the outserts produced by one manufacturer, at one plant, from the same materials, under the same manufacturing conditions, at the same time and from no more than one lot of lens material.

**4.4.2 Sampling.** Sampling shall be conducted in accordance with the classification of characteristics in 4.4.5 and, when specified, table III. Samples shall be selected at random.

**4.4.3 Inspection procedure.** Every item in the lot shall be inspected for critical characteristics. The lot represented shall be rejected when nonconformance to a critical characteristic is found. Sample outserts, plastic sheet stock and, when applicable, the packaging thereof shall be examined and tested in accordance with the classification of characteristics in 4.4.5. Failure of any sample item to conform to any characteristic in the classification of characteristics based on the sampling and acceptance criteria specified therein shall be cause for rejection of the lot represented.

**4.4.4 Inspection characteristics.** Critical characteristics are characteristics whose nonconformance to specified requirements is likely to result in hazardous or unsafe conditions



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

for individuals using, maintaining, or depending upon the product or whose nonconformance to specified requirements is likely to prevent performance of the tactical function of a major end item. Major characteristics are characteristics whose nonconformance to specified requirements is likely to result in failure or to reduce materially the usability of the item for its intended purpose. Minor characteristics are characteristics whose nonconformance to specified requirements is not likely to reduce materially the operation or usability of the item for its intended purpose.

TABLE III. Sampling

| Lot size | Inspection levels and sample sizes | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | I | II | III | IV | V | VI | VII | VIII | IX | X | XI |
| 2 to 8 | * | * | * | * | * | * | * | * | 5 | 3 | 2 |
| 9 to 15 | * | * | * | * | * | * | 13 | 8 | 5 | 3 | 2 |
| 16 to 25 | * | * | * | * | * | 20 | 13 | 8 | 5 | 3 | 3 |
| 26 to 50 | * | * | * | * | 32 | 20 | 13 | 8 | 5 | 5 | 5 |
| 51 to 90 | * | * | * | 50 | 32 | 20 | 13 | 8 | 7 | 6 | 5 |
| 91 to 150 | * | * | 125 | 50 | 32 | 20 | 13 | 12 | 11 | 7 | 6 |
| 151 to 280 | * | * | 125 | 50 | 32 | 20 | 20 | 19 | 13 | 10 | 7 |
| 281 to 500 | * | 315 | 125 | 50 | 48 | 47 | 29 | 21 | 16 | 11 | 9 |
| 501 to 1200 | * | 315 | 125 | 75 | 73 | 47 | 34 | 27 | 19 | 15 | 11 |
| 1201 to 3200 | 1250 | 315 | 125 | 116 | 73 | 53 | 42 | 35 | 23 | 18 | 13 |
| 3201 to 10000 | 1250 | 315 | 192 | 116 | 86 | 68 | 50 | 38 | 29 | 22 | 15 |
| 10001 to 35000 | 1250 | 315 | 294 | 135 | 108 | 77 | 60 | 46 | 35 | 29 | 15 |
| 35001 to 150000 | 1250 | 490 | 294 | 170 | 123 | 96 | 74 | 56 | 40 | 29 | 15 |
| 150001 to 500000 | 1250 | 715 | 345 | 200 | 156 | 119 | 90 | 64 | 40 | 29 | 15 |
| 500001 and over | 1250 | 715 | 435 | 244 | 189 | 143 | 102 | 64 | 40 | 29 | 15 |

*Indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection.
Accept the lot represented on zero nonconforming characteristics and reject the lot represented on one or more nonconforming characteristics for all inspection levels.

**4.4.5 Classification of characteristics.** Quality conformance examinations and tests shall be as specified in the following classification of characteristics paragraphs. When specified herein, accept on 0 and reject on 1 attributes sampling inspection shall be performed on the designated characteristics using the stated levels in table III for selection of sample sizes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER 5-2-1602 |
|---|---|---|---|
| 4.4.5(a) | Outsert, eyelens antiglare, chemical-biological mask, M2 | | NEXT HIGHER ASSY |

| CATEGORY | CHARACTERISTIC | SAMPLING AND ACCEPTANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101 | Dimensions (2-13/32, 7-31/32) | Table III, level VII | 3.3 | CE |
| 102 | Tab fastener correctly applied and located | Table III, level VII | 3.3 | CE |
| 103 | Optical characteristics | Table III, level VII | 3.1.1.2 | VI |
| 104 | Workmanship | Table III, level VII | 3.5.2 | VI |

NOTES:
CE - Commercial inspection equipment
VI - Visual inspection



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.5(b) | Plastic sheet and film, cellulose acetate (used for lens fabrication) | | NEXT HIGHER ASSY |

| CATEGORY | CHARACTERISTIC | SAMPLING AND ACCEPTANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101 | Optical characteristics | Table III, level VII* | 3.1.1.2 | VI |
| 102 | Water absorption | 4; Acc 0, Rej 1 | 3.1.1.1 | 4.4.6.2 |
| 103 | Tensile strength and elongation | 4; Acc 0, Rej 1 | 3.1.1.1 | 4.4.6.3 |
| 104 | Visible light transmission | 4; Acc 0, Rej 1 | 3.1.1.1.1 | 4.4.6.4 |
| 105 | Color perception | 4; Acc 0, Rej 1 | 3.1.1.1.2 | 4.4.6.5 |
| 106 | Thickness (Drawing 5-2-1601) | Table III, level VII | 3.2 | CE |
| 107 | Workmanship | Table III, level VII | 3.5.1 | VI |

NOTES:

CE - Commercial inspection equipment VI - Visual inspection

*A limit of defects per sheet shall be established by dividing the total area of the sheet ($ft^2$) by 4. For example, if the sheet is 4 feet by 4 feet, then the maximum number of defects per sheet shall be 16 divided by 4 = 4 defects. A sheet shall be considered defective and the lot of plastic sheets shall be rejected when the number of defects of any sample sheet exceeds this limit.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.5(c) | Packaging | | SPI P5-2-1602 |
| | | | NEXT HIGHER ASSY |

| CATEGORY | CHARACTERISTIC | SAMPLING AND ACCEPTANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101 | Unit pack container leakage | Table III, level IX | 5.2 | 4.4.7.1 |
| 102 | Unit pack container seam | Table III, level IX* | 5.2 | 4.4.7.2** |
| 103 | Item not completely clean and dry prior to unit packing | Table III, level IX | 5.2 | VI |
| 104 | Intimate wrap correct | Table III, level IX | 5.2 | VI and CE |
| 105 | Stiffener correct | Table III, level IX | 5.2 | VI and CE |
| 106 | Unit pack container correct | Table III, level IX | 5.2 | VI and CE |
| 107 | Unit pack container markings correct | Table III, level IX | 5.2 | VI and CE |

NOTES:

This paragraph is not applicable to packaging for interplant shipment.

* Samples shall consist of closed empty unit pack containers

** Destructive test

CE – Commercial inspection equipment

VI – Visual inspection



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.4.6 **Tests.**

4.4.6.1 **Test methods.** The test specimens shall be conditioned and tested at 23° ± 1.0°C and 50 ± 4 percent relative humidity unless other conditions are specified in this specification or in the individual test method.

4.4.6.2 **Water absorption.** Three specimens from each sample shall be tested in accordance with ASTM D 570.

4.4.6.3 **Tensile strength and elongation.** Five specimens from each sample shall be conditioned for 48 hours as specified in 4.4.6.1 and then tested in accordance with ASTM D 882.

4.4.6.4 **Visible light transmission.** Three specimens from each sample shall be tested for visible light transmission using a General Electric Recording Spectrophotometer or equivalent, in accordance with the operating instructions thereto.

4.4.6.5 **Color perception.** A minimum of six people shall be tested for normal color vision using any standard method such as the Holmgren Test, Stilling Charts, Ishiharn Charts, or American Optical Company tests. The test shall be repeated with the subjects viewing the charts through each of four specimens from each sample of sheet material.

4.4.7 **Packaging tests.**

4.4.7.1 **Unit pack container leakage.** The leakage of the unit pack container and its contents, unit packed for shipment, shall be tested for leakage in accordance with method 5009.3 of FED. TEST METHOD STD. NO. 101 using the hot water technique.

4.4.7.2 **Heat seal seam separation.** The heat seal seam of the unit pack container shall be tested in accordance with method 2024 of FED. TEST METHOD STD. NO. 101, except that the static load shall be 38 (+2 or −0) ounces and a 5 percent reduction in the static load shall be permitted when the room temperature exceeds 90°F in the test area.

## 5. PACKAGING

5.1 **Interplant shipment.** When packaging is for interplant shipments (see 6.3) the outserts shall be packaged in accordance with ASTM D 3951.

5.2 **Repair parts.** For all shipments, other than interplant shipments (see 6.3), packaging (preservation, unit packing, packing and marking) shall be as specified in SPI P5-2-1602.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

**6.1 Intended use.** The outsert covered by this specification is intended for use with the ABC-M25A1 Tank Chemical-Biological Mask and ABC-M24 Aircraft Chemical-Biological Mask.

**6.2 Acquisition requirements.** Acquisition documents must specify the following:

(a) Title, number, and date of this specification
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see section 2)
(c) First article:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract when testing is performed by the Government.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

(d) Whether military packaging or interplant shipment packaging is required (see 5.1)
(e) Level of packing required (see SPI P5-2-1602)

**6.3 Interplant shipment.** Packaging and marking for interplant shipment is for supplies and materials that do not directly enter the military supply system. Typical interplant shipments are shipments from a vendor to a subcontractor or a prime contractor, or between contractors and subcontractors, or from a vendor or contractor to a military arsenal, plant or other activity for evaluation, immediate use, or further processing as specified in the applicable contract.

**6.4 International interest.** Certain provisions of this specification are the subject of international standardization agreement QSTAG 216. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

**6.5 Submission of alternative inspection provisions.** Proposed alternative inspection provisions should be submitted by the contractor to the procuring contracting officer for evaluation and approval by the technical activity responsible for preparation of this specification.

**6.6 Changes from previous issues.** Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

6.7 **Subject term (key word) listing.**

Cellulose acetate
Lens
Light transmission
Plastic

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A051



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-O-51142C(EA) | 930503 |

3. DOCUMENT TITLE
Outsert, Eyelens Antiglare, Chemical-Biological Mask, ABC-M2

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION |
|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON<br>(If applicable) |

7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

| a. NAME | b. TELEPHONE (Include Area Code) |
|---|---|
| U.S. Army Edgewood Research, Development and Engineering Center | (1) Commercial: (410)671-3259<br>(2) AUTOVON: DSN 584-3259 |
| c. ADDRESS (Include Zip Code)<br>Tech Dir, U.S. Army ERDEC<br>ATTN: SCBRD-ENE-S (Stds/Specs/Pkg)<br>Aberdeen Proving Ground, MD 21010-5423 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 |

DD Form 1426, OCT 89 — Previous editions are obsolete. — 198/290

Source: https://assist.dla.mil. Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-O-51142C(EA)
NOTICE 1
28 September 1995

# MILITARY SPECIFICATION

## OUTSERT, EYELENS ANTIGLARE, CHEMICAL-BIOLOGICAL MASK, ABC-M2

This notice should be filed in front of MIL-O-51142C(EA) dated 3 May 1993.

MIL-O-51142C(EA) is inactive for new design and is no longer used except for replacement purposes.

Preparing activity:

Army - EA

Project No. 4240-A150

AMSC N/A

FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.