MIL-T-50595C (AR)
1 March 1979
SUPERSEDING
MIL-T-50595B (PA)
23 September 1976

MILITARY SPECIFICATION

TRIPOD ASSEMBLY, DEMOLITION KIT, M180, METAL PARTS FOR AND ASSEMBLY

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings, and provides quality assurance provisions for the fabrication of parts, assembling and packing for one type of Tripod designated as Tripod Assembly for Demolition Kit, M180.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents.- The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components

FSC 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

DRAWINGS (Sec 6.6)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9244403 - Tripod Assembly, Demolition Kit

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

*AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B 117 - Salt Spray (Fog) Testing

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

3. REQUIREMENTS

3.1 Materials.- Materials shall be in accordance with applicable drawings, specifications and standards.

* 3.2 Parts.- All parts shall be in accordance with the applicable drawings, specifications and standards.

3.3 Tripod Assembly.- The tripod assemblies shall comply with all requirements specified on Drawing (Dwg.) F9244403, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 First article inspection.- This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

3.5 Workmanship.- All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner; and all manufacturing, processing, and assembly operations shall be correctly performed. Parts shall be free of burrs, weld spatter, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part or assembly, nor shall any part be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. (Required packing shall be dry.)

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.- Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.- The following types of inspection shall be conducted on this item.

a. First Article Inspection.
b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the items specified in Table I.

4.3.2 Inspections to be performed.- See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.- See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

	Guide (Dwg. 9329700) Examination for defects	10	100%	3.1	4.4.4.16
	Strap, Left (Dwg. 9329701) Examination for defects	10	100%	3.1	4.4.4.17
	Strap, Right (Dwg. 9329702) Examination for defects	10	100%	3.1	4.4.4.18
	Strap, Top (Dwg. 9329703) Examination for defects	10	100%	3.1	4.4.4.19

NOTES:
(a) This test shall be performed on the ten (10) samples subjected to the examination for defects.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
	*Tripod Assembly, Demolition Kit, M180				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	*Launch Leg, Lower, Tripod (Dwg 9244460)				
	Examination for defects	10	100%	3.1	4.4.2.8
	Salt Spray Test	(a)	100%	3.1	4.5.3
	*Launch Leg, Upper, Tripod (Dwg. 9244461)				
	Examination for defects	10	100%	3.1	4.4.2.9
	Salt Spray Test	(a)	100%	3.1	4.5.3
	*Support Leg, Lower, Tripod (Dwg. 9244462)				
	Examination for defects	10	100%	3.1	4.4.2.10
	Salt Spray Test	(a)	100%	3.1	4.5.3
	*Support Leg, Upper Tripod (Dwg. 9244463)				
	Examination for defects	10	100%	3.1	4.4.2.11
	Salt Spray Test	(a)	100%	3.1	4.5.3
	Apex Fitting, Tripod (Dwg. 9244428)				
	Examination for defects	10	100%	3.1	4.4.2.12
	Salt Spray Test	(a)	100%	3.1	4.5.3
	*M57 Firing Device, Modified (Dwg. 9244458)				
	Examination for defects	10	100%	3.1	4.4.2.13
	Functioning	(a)	100%	3.1	4.5.4
	Tripod Assembly, Demolition Kit (Dwg. 9244403)				
	Examination for defects	10	100%	3.1	4.4.2.22

NOTES:

* (a) This test shall be performed on the ten (10) samples subjected to the examination for defects.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
	*Tripod, Demolition Kit, M180				See Below
					NEXT HIGHER ASSEMBLY —
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	*Cable Assembly (Dwg. 9244466)				
	Examination for defects	10	100%	3.1	4.4.2.21
	Pull Test	(a)	100%	3.1	4.5.1

Source: https://assist.dla.mil - Downloaded: 2026-02-27T04:02Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

* 4.4.1 Inspection lot formation.- Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Tripod Assemblies shall contain Firing Devices, M57, of one lot interfix number from one manfacturer.

* 4.4.2 Examination.- (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244433
4.4.2.1	Bracket, Launch Leg, Tripod				NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Diameter of bolt holes		0.65%	3.1	Gage
202	True position of bolt holes		0.65%	3.1	Gage
203	Angle		0.65%	3.1	Gage
204	Thickness		0.65%	3.1	Gage
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244435
4.4.2.2	Bracket, Tripod for M57 Firing Device				NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFFRENCE /INSPECTION METHOD
Critical	None defined				
Major					
*101	True position of drilled hole(s) with longitudinal axis		0.40%(a)	3.1	Gage
*102	Width of firing device opening		0.40%(a)	3.1	Gage
*103	Diameter of drilled hole		0.40%(a)	3.1	Gage
Minor					
201	Diameter of launch leg sleeve hole		0.65%(a)	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: *(a) See 4.5.5 for alternate inspection procedure for cast parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Support, Upper, Tripod For Shaped Charge	1	1	9244443
				NEXT HIGHER ASSEMBLY 9244403

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
*101	Pitch diameter of thread, maximum (max)		0.40%(a)	3.1	Gage
*102	Minor diameter of thread, max		0.40%(a)	3.1	Gage
*103	Location of shaped charge hole with respect to launch leg hcle		0.40%(a)	3.1	Gage
Minor					
*201	Diameter of small hole		0.65%(a)	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: * (a) See 4.5.5 for alternate inspection procedure for cast parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244444
4.4.2.4	Support, Lower, Tripod				NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
*101	True position of charge hole		0.40%(a)	3.1	Gage
Minor					
*201	Diameter of launch leg hole		0.65%(a)	3.1	Gage
*202	Diameter of charge hole		0.65%(a)	3.1	Gage
*203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: * (a) See 4.5.5. for alternate inspection procedure for cast parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
*4.4.2.5	Pin, Launch, Tripod	1	1	9244431
				NEXT HIGHER ASSEMBLY 9244429

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
*101	Circular runout of outside diameter with flange		0.40%	3.1	Gage
102	Diameter of hole		0.40%	3.1	Gage
Minor					
201	Length from edge of flange to end		0.65%	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244430
4.4.2.6	Fitting, Launch, Tripod				NEXT HIGHER ASSEMBLY 9244429
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of launch leg hole with outside diameter		0.40%	3.1	Gage
102	True position of launch pin holes with inside diameter of launch leg holes		0.40%	3.1	Gage
103	Diameter of launch leg hole		0.40%	3.1	Gage
104	Diameter of launch pin hole		0.40%	3.1	Gage
105	Diameter of bolt hole		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244434
4.4.2.7	Suspension Band, Tripod				NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component missing or loose		0.40%	3.1	Visual-Manual
102	Tripod strap bracket improperly assembled to tripod strap assembly		0.40%	3.1	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244460
*4.4.2.8	Launch Leg, Lower, Tripod				NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of lower support mounting hole with outside diameter		0.40%	3.1	Gage
102	True position of detent pin mounting hole with outside diameter		0.40%	3.1	Gage
103	Total length		0.40%	3.1	Gage
104	Outside diamter		0.40%	3.1	Gage
Minor					
201	Diameter of detent pin mounting hole		0.65%	3.1	Gage
202	Diameter of lower support mounting hole		0.65%	3.1	Gage
203	Angle of end		0.65%	3.1	Gage
204	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Launch Leg, Upper, Tripod				9244461
					NEXT HIGHER ASSEMBLY
					9200403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
*101	Location of pin slot		0.40%	3.1	Gage
102	Inside diameter of expanded section		0.40%	3.1	Gage
103	Width of slot in expanded section		0.40%	3.1	Gage
*104	True position of middle launch assembly mounting hole with outside diameter		0.40%	3.1	Gage
105	True position of apex fitting mounting hole with outside diameter		0.40%	3.1	Gage
106	True position of upper launch assembly hole		0.40%	3.1	Gage
107	Location of lower launch assembly hole		0.40%	3.1	Gage
108	Location of apex fitting mounting hole		0.40%	3.1	Gage
109	Total length		0.40%	3.1	Gage
110	Outside diameter of small end		0.40%	3.1	Gage
Minor					
201	Length of expanded section		0.65%	3.1	Gage
202	Depth of slot in expanded section		0.65%	3.1	Gage
*203	Width of pin slot		0.65%	3.1	Gage
*204	Depth of pin slot		0.65%	3.1	Gage
205	Diameter of apex fitting mounting hole		0.65%	3.1	Gage
206	Evidence of poor workmanship		1.00%	3.5	Visual
*207	Protective finish missing from inside surface		0.65%	3.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Support Leg, Lower, Tripod	1	1	9244462
				NEXT HIGHER ASSEMBLY 9244403

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of hole with outside diameter		0.40%	3.1	Gage
102	Outside diameter		0.40%	3.1	Gage
103	Total length		0.40%	3.1	Gage
Minor					
201	Diameter of drilled hole		0.65%	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.11	Support Leg, Upper, Tripod	1	1	9244463
				NEXT HIGHER ASSEMBLY 9244403

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large inside diameter		0.40%	3.1	Gage
102	Outside diameter of smaller expanded section		0.40%	3.1	Gage
103	True position of apex fitting mounting hole with small outside diameter		0.40%	3.1	Gage
104	True position of hole at flared end with small outside diameter		0.40%	3.1	Gage
105	Total length		0.40%	3.1	Gage
Minor					
201	Depth of large inside diameter		0.65%	3.1	Gage
202	True position of cable mounting hole with apex fitting mounting hole		0.65%	3.1	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9244428
*4.4.2.12	Apex Fitting, Tripod				NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
*101	Angle between legs		0.40%(a)	3.1	Gage
*102	Width between support leg opening		0.40%(a)	3.1	Gage
*103	Width between launch leg opening		0.40%(a)	3.1	Gage
*104	True position of leg mounting hole		0.40%(a)	3.1	Gage
*105	Length of flange		0.40%(a)	3.1	Gage
Minor					
*201	Diameter of bolt hole through leg		0.65%(a)	3.1	Gage
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: * (a) See 4.5.5 for alternate inspection procedure for cast parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
*4.4.2.13	M57 Firing Device, Modified		1	1	9244458
					NEXT HIGHER ASSEMBLY 9244403
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Safety pin missing or loose		100%	3.1	Visual
Major					
101	Case cracked or split		0.40%	3.1	Visual
102	Functioning		100%	3.1	4.5.4
Minor					
201	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9329698
*4.4.2.14	Guide, T-Bolt				NEXT HIGHER ASSEMBLY 9329696
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Major					
201	Length		0.65%(a)	3.1	Gage
202	Width of gap, max		0.65%(a)	3.1	Gage
203	Inside diameter, max		0.65%(a)	3.1	Gage
204	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: (a) See 4.5.6 for alternate inspection procedure for stamped parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.15	Cap		9329699
			NEXT HIGHER ASSEMBLY 9329698

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Inside diameter from beginning of radius		0.65%(a)	3.1	Gage
202	Diameter of hole, max		0.65%(a)	3.1	Gage
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:
(a) See 4.5.6 for alternate inspection procedure for stamped parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9329700
*4.4.2.16	Guide				NEXT HIGHER ASSEMBLY 9329696
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Inside diameter max. (2 places)		0.65%(a)	3.1	Gage
202	Width of slot		0.65%(a)	3.1	Gage
203	Depth of slot		0.65%(a)	3.1	Gage
204	Total width (bolt portion)		0.65%(a)	3.1	Gage
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: (a) See 4.5.6 for alternate inspection procedure for stamped parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
*4.4.2.17	Strap, Left	1	1	9329701
				NEXT HIGHER ASSEMBLY 9329696

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Radius of arc		0.65%(a)	3.1	Gage
202	Inside length		0.65%(a)	3.1	Gage
203	Inside diameter of loop		0.65%(a)	3.1	Gage
204	Width of part		0.65%(a)	3.1	Gage
205	Spot weld missing or defective (Material separating, etc.)		0.65%(a)	3.1	Visual
206	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: (a) See 4.5.6 for alternate inspection procedures for stamped parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9329702
*4.4.2.18	Strap, Right				NEXT HIGHER ASSEMBLY 9329696
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Radius of arc		0.65%(a)	3.1	Gage
202	Inside length		0.65%(a)	3.1	Gage
203	Inside diameter of larger loop		0.65%(a)	3.1	Gage
204	Inside diameter of smaller loop		0.65%(a)	3.1	Gage
205	Width of part		0.65%(a)	3.1	Gage
206	Spot weld missing or defective (material separating, etc.)		0.65%	3.1	Visual
207	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: (a) See 4.5.6 for alternate inspection procedure for stamped parts.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.19	Strap, Top	1 OF 1	9329703
			NEXT HIGHER ASSEMBLY 9329696

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%(a)	3.1	Gage
202	True position of cutout		0.65%(a)	3.1	Gage
203	Width of part		0.65%(a)	3.1	Gage
204	Radius of part		0.65%(a)	3.1	Gage
205	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: (a) See 4.5.6. for alternate inspection procedure for stamped parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9329696
*4.4.2.20	Strap Assembly				NEXT HIGHER ASSEMBLY 9244434
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Part missing		0.40%	3.1	Visual
102	Part improperly assembled		0.40%	3.1	Visual
103	Part damaged (cracked or deformed)		0.40%	3.1	Visual
104	Spot weld missing or defective (material separating, etc.)		0.40%	3.1	Visual
105	Yield strength	4.5.2	-	3.1	4.5.2
Minor					
201	Inside length of straps between loops		0.65%	3.1	Gage
202	Bolt threads damaged		0.65%	3.1	Visual
203	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
*4.4.2. 2	Cable Assembly, Tripod	1	1	9244466
				NEXT HIGHER ASSEMBLY 9244403

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test	4.5.1	-	3.1	4.5.1
Minor					
201	Distance between loop and sleeve (both ends)		0.65%	3.1	Gage
202	Distance between loops		0.65%	3.1	Straight Edge
203	Swage missing or improper		0.65%	3.1	Visual
204	Cable defective (frayed end, broken, etc.)		0.65%	3.1	Visual
205	Protective varnish missing from end		0.65%	3.1	Visual
206	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-50595C(AR)

PARAGRAPH	TITLE		SHEET OF	DRAWING NUMBER
*4.4.2.22	Tripod Assembly, Demolition Kit		1 1	9244403
				NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component missing or loose		0.40%	3.1	Visual-Manual
102	Cable assembled improperly		0.40%	3.1	Visual
103	Upper and lower launch legs assembled improperly		0.40%	3.1	Visual
104	Upper and lower support legs assembled improperly		0.40%	3.1	Visual
105	Cable not taut		0.40%	3.1	Visual
*106	Component damaged (cracked, dented or deformed)		0.40%	3.1	Visual
*107	Sealing compound missing from upper support set screw threads		0.40%	3.1	Visual
108	Tripod suspension band improperly assembled to launch fitting assembly		0.40%	3.1	Visual
Minor					
201	Protective finish missing or incomplete		0.65%	3.1	Visual
202	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection Tables.

* 4.4.4 Inspection equipment.- The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures. (See 6.4)

* 4.5.1 Pull test of cable assembly (Dwg. 9244466) major defect.- Ten (10) cable assemblies shall be selected from each lot for this test. Test equipment shall be in accordance with 4.4.4. If any cable assembly fails to comply with the pull requirement specified on the applicable drawing, it shall be classed defective and the lot shall be rejected. The cable assembly shall be assembled to an approved fixture and subjected to the pull specified on the applicable drawing.

* 4.5.2 Yield strength of strap assembly (Dwg. 9329696) major defect.- Ten (10) assemblies shall be selected from each lot for this test. Test equipment shall be in accordance with 4.4.4. If any strap assembly fails to comply with the yield requirement specified on the applicable drawing, it shall be classed defective and the lot shall be rejected. The test procedure shall be as specified on the applicable drawing.

* 4.5.3 Salt spray test.- The specified parts shall be subjected to the salt spray test in accordance with ASTM B 117 using a 5% atomized sodium chloride solution. Exposure time shall be not less than two (2) hours. Examination shall be made for any evidence of corrosion or salt deposits indicative of improper coating. Any evidence of improper coating shall cause the part to be classed defective.

* 4.5.4 Functioning of M57 Firing Device (Dwg. 9244458).- This check test shall be performed 100% as specified in the applicable drawing. The test shall be performed as follows: Place the bail in the angular slot (functioning position) and depress the handle fully once and observe for a flash of the red light on the M40 test set. Place the bail in the vertical slot (safe position). The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

bail must remain in the safe position following completion of this test. If the red light on the M40 Test Set fails to flash, the M57 Firing Device shall be classed defective and not used in production. A record shall be kept of any defective devices for Governmental informational use. (See 6.4)

* 4.5.5 Dimensional control of cast parts.- In place of the normal sampling associated with the Classification of Defects and with the approval of the Contracting Officer, a sample of at least three (3) parts (as cast) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of 5000 parts. Individual cavity identification must be provided.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

* 4.5.6 Dimensional control of stamped parts.- In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

If any defective parts are found when inspection is performed for the control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

5. PACKAGING

5.1 Level C.- The Tripod Assembly, Demolition Kit, M180, shall be packaged, packed, preserved and marked in accordance with MIL-STD-1169.

* 5.2 Shipping.- When Tripod Assemblies from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. - This tripod assembly is part of the M180 cratering demolition kit.

6.2 Ordering data.- See MIL-A-48078.

* 6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs, as required, to Commander, ATTN: DRDAR-QAA-I, ARRADCOM, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects or test paragraph number.

* 6.4 Data submission.- Results of all tests performed by the contractor shall be submitted in accordance with Data Item D1-R-1721 on the DD Form 1423 for the contract. Distribution shall include the following:

Commander
ARRADCOM
ATTN: DRDAR-QAA-Q
Dover, N.J. 07801

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

* 6.5 Data cards.- (See MIL-A-48078). Distribution of data cards shall include the address specified in 6.4.

* 6.6 Drawings.- Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research and Development Command" (ARRADCOM) may also include drawings prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.7 Asterisks.- The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1375-A239

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-50595C(AR)
TRIPOD ASSEMBLY, DEMOLITION KIT, M180, METAL PARTS FOR AND ASSEMBLY

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.