MIL-W-50849D(AR)
9 June 1986
SUPERSEDING
MIL-W-50849C(AR)
6 May 1977

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M250
INERT PARTS FOR

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the Quality Assurance Provisions and Special requirements for the fabrication of the inert parts for one type of warhead designated as Warhead, Guided Missile, HE, M250.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-I-6866	-	Inspection, Penetrant, Method of
MIL-W-22248	-	Weldments, Aluminum and Aluminum Alloy
MIL-L-25567	-	Leak Test Compound, Oxygen Systems
MIL-W-46132	-	Welding, Fusion, Electron Beam, Process

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-L-52909	-	Lacquer, Acrylic, Camouflage, Lusterless

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

9268064	-	Warhead, GM, M250, Metal Parts Assembly
9285514	-	Body Assembly "Simulated" (Electron Beam Weld-Inspection Sample)

2.1.3 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B247	-	Aluminum Alloy Die and Hand Forgings
ASTM D1400-67	-	Measurement of Dry Film Thickness of Nonmetallic Coatings of Paint, Varnish, Lacquer and Related Products Applied on a Nonmagnetic Metal Base

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:03Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials, parts and explosive components shall be in accordance with applicable drawings and specifications.

3.1.1 Forgings. Forgings shall be in accordance with the applicable drawing and ASTM B247, Aluminum Alloy Die and Hand Forgings. They shall meet the chemical and mechanical properties requirements, and shall be subjected to the quality conformance inspections and tests, specified therein. A certificate of conformance shall be furnished for each lot of forgings.

3.1.2 Camouflage paint. The camouflage paint shall comply with all requirements specified in MIL-L-52909.

3.2 Assemblies. The components and assemblies shall comply with all requirements specified on drawing 9268064 and associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Adhesive bonding procedures. The contractor shall establish a Standard Operating Procedure (SOP) for the adhesive bonding of the fragment assembly, dwg. 9256695, and shall submit this SOP for approval following the same instructions set forth herein for the submission of inspection equipment designs. Changes to the approved SOP will require the approval of the Contracting Officer.

3.4 Electron beam weld of body assembly. The Electron Beam (E.B.) Weld of the Body Assembly shall meet the requirements of drawing 9296901 and further, shall not exhibit evidence of cracking or porosity within .090 inches of the outer surface of the warhead; except at the interface, where cracking cannot be totally eliminated the weld shall exhibit a minimum width of .050 inches of weld material containing no cracking. Surface porosity shall not exceed one sixteenth (1/16) of an inch in diameter for a single cavity, nor one eighth (1/8) of an inch in diameter for the composite total of all cavities over the length of the weld. Welding equipment shall be qualified per military specification MIL-W-46132, Welding, Fusion, Electron Beam, Process.

3.5 Air test certification of weld. The Electron Beam Weld of the S&A well tube shall withstand an internal air pressure of 5 to 7 pounds per square inch (psi) for a minimum of twenty (20) seconds with no evidence of leakage.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:03Z
Check the source to verify that this is the current version before use.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, unblended radii, cold solder joints, surface defects, cracks, grease, dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.7.1 Workmanship of forgings. Forgings shall be of uniform quality and free from blisters, fins, seams, laps, bursts, cracks, segregations or other injurious defects.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article samples shall consist of the following items in sample quantities as indicated:

	Part Description	Drawings	Quantity
a.	Plate, Body Forward	9256692	6
b.	Plate, Body Aft	9256693	6 Plus one unmachined forging, if contractor elects to forge.
c.	Body Forward	9256687	6
d.	Body, Aft	9256688	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

	Part Description	Drawings	Quantity
e.	Ring, Aft	9268116	6
f.	Plug, Loading	9285287	6
g.	Packing, O-Ring	9270714	6
h.	Loading Plug Assembly	9285288	3
i.	Ring, Inner	9280486	6
j.	Cushion	9272848	3
k.	Cup, Booster	9266752	6
l.	Tube, S&A Well	9271663	6
m.	Body and Plate Weldment (prior to anodizing)	9255589	6
n.	Body and Plate Weldment (subsequent to anodizing)	9256689	3
o.	Fragment Assembly	9256695	6 Plus an approved SOP.
p.	Plate, Body, Aft "Simulated"	9285512	3
q.	Plate, Body, Forward "Simulated"	9285513	3
r.	Body Assembly "Simulated" (E.B. Weld-Inspection Sample)	9285514	3
s.	Weldment, Body Assembly	9296901	8 Plus eight (8) E.B. Weld-inspection samples. Seven welded prior to the eight Body Assembly Weldments and one welded after the Body Assembly weldments.
t	Body Assembly (subsequent to anodizing)	9256708	6
u.	Body Assembly (subsequent to painting)	9256708	6
v.	Sleeve, Protective	9276743	6
w.	Container, Guided Missile, MK34, Mod 0, Modified for Warhead	9276750	3
x.	Packing and Marking for Box, Packing Ammunition, Wire-bound, for Warhead GM, HE, M250	9276741	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. The first article parts submitted in accordance with paragraph 4.3.1 will be subjected by the Government to any or all the requirements of the applicable drawings and to the inspections of Table I. All inspections listed in Table I shall be classified Major unless otherwise specified.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH 4.3.3.1	TITLE		SHEET 1 OF 4		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate, Body Forward (Dwg. 9256692) Examination for Defects	6	-	3.2	4.4.2.1
	Plate, Body Aft (Dwg. 9256693) Examination for Defects	6	-	3.1.1, 3.2, 3.7.1	4.4.2.2/See Note (a)
	Body, Forward (Dwg. 9256687) Examination for Defects	6	-	3.2	4.4.2.3
	Body, Aft (Dwg. 9256688) Examination for Defects	6	-	3.2	4.4.2.4
	Ring, Aft (Dwg. 9268116) Examination for Defects	6	-	3.2	4.4.2.5
	Plug, Loading (Dwg. 9285287) Examination for Defects	6	-	3.2	4.4.2.6
	Packing, O-Ring (Dwg. 9270714) Examination for Defects	6	-	3.2	4.4.2.7

NOTES:
(a) Where contractor elects to forge, the first article sample forging shall be examined for surface defects, mechanical properties and heat-treat response as specified in ASTM B247.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH 4.3.3.1	TITLE		SHEET 2 OF 4		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Loading Plug Assembly (Dwg. 9285288) Examination for Defects	3	-	3.2	4.4.2.8
	Ring, Inner (Dwg. 9280486) Examination for Defects	6	-	3.2	4.4.2.9
	Cushion (Dwg. 9272848) Examination for Defects	3	-	3.2	See Note (a)
	Cup, Booster (Dwg. 9266752) Examination for Defects	6	-	3.2	4.4.2.10
	Tube, S&A Well (Dwg. 9271663) Examination for Defects	6	-	3.2	4.4.2.11
	Body and Plate Weldment (prior to anodizing) (Dwg. 9256689) Examination for Defects	6	-	3.2	4.4.2.12
	Body and Plate Weldment (subsequent to anodizing) (Dwg. 9256689) Examination for Defects	3	-	3.2	4.4.2.13

NOTES:

(a) All drawing dimensions of the cushion shall be checked on the First Article Sample.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER See Below
4.3.3.1					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fragment Assembly (Dwg. 9256695)				
	Examination for Defects	6	-	3.2	4.4.2.14
	Verification of an approved bonding SOP	-	-	3.3	
	Plate, Body, Aft "Simulated" (Dwg. 9285512)				
	Examination for Defects	3	-	3.2	4.4.2.15
	Plate, Body, Forward "Simulated" (Dwg. 9285513)				
	Examination for Defects	3	-	3.2	4.4.2.16
	Body Assembly "Simulated" (E.B. Weld - Inspection Sample) (Dwg. 9285514)				
	Examination for Defects	3	-	3.2	4.4.2.17
	Weldment, Body Assembly (Dwg. 9296901)				
	Examination for Defects	8 + 8	-	3.4, 3.5	4.4.2.18/See Note (a)

NOTES: (a) Eight Body Assembly Weldments plus eight E.B. weld inspection samples shall be welded, seven E.B. weld samples prior to the eight Body Assembly Weldments and one E.B. weld sample after the Body Assembly Weldments. The E.B. weld samples only shall be sectioned, polished and examined for compliance with the requirements of para 3.4. Body Assembly Weldments shall comply with para 3.5, the surface porosity requirement of para 3.4 and the examinations of para 4.4.2.17.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-W-50849D(AR)

PARAGRAPH 4.3.3.1	TITLE		SHEET 4 OF 4		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Verification of Equipment Qualification	-	-	3.2,3.4	See Note (a)
	Body Assembly (subsequent to anodizing) (Dwg. 9256708) Examination for Defects	6	-	3.2	4.4.2.19
	Body Assembly (subsequent to painting) (Dwg. 9256708) Examination for Defects	6	-	3.2	4.4.2.20
	Sleeve Protective (Dwg. 9276743) Examination for Defects	6	-	3.2	4.4.2.21
	Container, Guided Missile, MK34, Mod 0 Modified for Warhead, GM, HE, M250 (Dwg. 9276750) Examination for Defects	3	-	3.2	4.4.2.22
	Packing and Marking for Box, Packing Ammunition, Wirebound, for Warhead GM, HE, M250 (Dwg. 9276741) Examination for Defects	3	-	3.2	4.4.2.23

NOTES:
(a) Welding equipment shall be qualified per paragraphs 4.1, 4.1.1, 4.1.2 and 4.1.4 of MIL-W-46132. This shall be verified.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for Major and Minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256692
4.4.2.1	Plate, Body Forward				NEXT HIGHER ASSEMBLY 9256689
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Outside diameter of hub, min.		0.40%	3.2	Gage
102.	Thickness of slant section, min.		0.40%	3.2	Gage
103.	Flange thickness, min.		0.40%	3.2	Gage
104.	Overall length		0.40%	3.2	Gage
105.	Length of outside diameter		0.40%	3.2	Gage
106.	Runout of hub diameter to datum A and datum B		0.40%	3.2	Gage
Minor					
201.	Corner radius of flange		0.65%	3.2	Gage
202.	Inside length of flange		0.65%	3.2	Gage
203.	Threaded hole missing		2.5%	3.2	Visual
204.	Chamfer missing from aft end of neck diameter		1.0%	3.2	Visual
205.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256693
4.4.2.2	Plate, Body Aft				NEXT HIGHER ASSEMBLY 9296901
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Certificate of conformance missing		-	3.1.1	Visual/See Note (a)
102.	Pitch diameter of thread		0.40%	3.2	Gage
103.	Minor diameter of thread, max.		0.40%	3.2	Gage
104.	Length of thread		0.40%	3.2	Gage
105.	Inside taper		0.40%	3.2	Gage
106.	Outside diameter		0.40%	3.2	Gage
107.	True position of threads to outside diameter		0.40%	3.2	Gage
108.	Inside diameter		0.40%	3.2	Gage
109.	True position of inside diameter to outside diameter		0.40%	3.2	Gage
110.	Length from forward end to inside shoulder		0.40%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		1.0%	3.7, 3.7.1	Visual

NOTES: (a) A certificate of conformance to the chemical and mechanical properties requirements of ASTM B247 shall be furnished by the contractor with each lot of forgings. This requirement does not apply if the contractor does not elect to use forgings.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256687
4.4.2.3	Body, Forward				NEXT HIGHER ASSEMBLY 9256689
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Inside diameter of neck		0.40%	3.2	Gage
102.	Outside diameter of body		0.40%	3.2	Gage
Minor					
201.	Length of neck, min.		0.65%	3.2	Gage
202.	Length		0.65%	3.2	Gage
203.	Corner radius, cracked or improper		0.65%	3.2	Visual
204.	Chamfer improper		1.0%	3.2	Visual
205.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256688
4.4.2.4	Body, Aft				NEXT HIGHER ASSEMBLY 9256689
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Outside diameter		0.40%	3.2	Gage
102.	Perpendicularity of aft end to outside diameter		0.40%	3.2	Gage
Minor					
201.	Small inside diameter		0.65%	3.2	Gage
202.	Length		0.65%	3.2	Gage
203.	Chamfer missing or improper		1.0%	3.7	Visual
204.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Ring, Aft	1 OF 1	9268116
			NEXT HIGHER ASSEMBLY: 9256689

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Inside datum diameter		0.40%	3.2	Gage
102.	Length of male thread		0.40%	3.2	Gage
103.	Pitch diameter of male thread		0.40%	3.2	Gage
104.	Major diameter of male thread, min.		0.40%	3.2	Gage
105.	Pitch diameter of female thread		0.40%	3.2	Gage
106.	Minor diameter of female thread, max.		0.40%	3.2	Gage
107.	Surface finish of inside datum diameter		0.40%	3.2	Visual
108.	True position of female thread to inside datum diameter		0.40%	3.2	Gage
109.	Perpendicularity of flange to male thread		0.40%	3.2	Gage
110.	Chamfer for inside datum diameter		0.40%	3.2	Visual
Minor					
201.	Flange thickness		0.65%	3.2	Gage
202.	Hole diameter		0.65%	3.2	Gage
203.	Flange diameter		0.65%	3.2	Gage
204.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9285287
4.4.2.6	Plug, Loading				NEXT HIGHER ASSEMBLY 9285288
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Outside diameter		0.40%	3.2	Gage
102.	O-Ring groove diameter		0.40%	3.2	Gage
103.	True position of O-Ring groove to outside diameter		0.40%	3.2	Gage
104.	Width of O-Ring groove		0.40%	3.2	Gage
105.	O-Ring groove edges not broken		0.40%	3.2	Visual
Minor					
201.	Length		0.65%	3.2	Gage
202.	Protective finish missing or improper		1.0%	3.2	Visual
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9270714
4.4.2.7	Packing, O-Ring				NEXT HIGHER ASSEMBLY 9285288
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Inside diameter		0.40%	3.2	Gage
102.	Thickness		0.40%	3.2	Gage
103.	O-Ring split or damaged		0.40%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9285288
4.4.2.8	Loading Plug Assembly				NEXT HIGHER ASSEMBLY 9268064
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major 101.	O-Ring damaged or missing		0.40%	3.2	Visual
Minor 201.	Loading plug damaged		0.65%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Ring, Inner	1 OF 1	9280486
			NEXT HIGHER ASSEMBLY: 9280811

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Pitch diameter of thread		0.40%	3.2	Gage
102.	Major diameter of thread, min.		0.40%	3.2	Gage
103.	Length		0.40%	3.2	Gage
Minor					
201.	Pitch diameter of threaded hole		0.65%	3.2	Gage
202.	Distance from threaded hole to inside diameter of ring		0.65%	3.2	Gage
203.	Slots in end missing		0.65%	3.2	Visual
204.	Protective finish missing or improper		1.0%	3.2	Visual
205.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9266752
4.4.2.10	Cup, Booster				NEXT HIGHER ASSEMBLY 9268064
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Inside diameter		1.0%	3.2	Gage
Minor					
201.	Length of cup, min.		0.65%	3.2	Gage
202.	Protective finish, missing or improper		1.0%	3.2	Visual
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9271663
4.4.2.11	Tube, S&A Well				NEXT HIGHER ASSEMBLY 9296901
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Flatness of bottom		0.40%	3.2	Gage
102.	Inside diameter of tube		1.0%	3.2	Gage
103.	Perpendicularity of flange to outside diameter		0.40%	3.2	Gage
104.	Length of tube		0.40%	3.2	Gage
105.	Thickness of bottom at counterbore		0.40%	3.2	Gage
106.	Thickness of bottom		0.40%	3.2	Gage
Minor					
201.	Diameter of flange, min.		0.65%	3.2	Gage
202.	Diameter of counterbore		0.65%	3.2	Gage
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Body and Plate Weldment (prior to anodizing)		9256689
			NEXT HIGHER ASSEMBLY: 9256695

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Penetrant Test		100%	3.2	See Note (a)
102.	Artificial aging not, or improperly accomplished		1.0%	3.2	Visual
Minor					
201.	Length		0.65%	3.2	Gage
202.	Serialization missing or improper		1.0%	3.2	Visual
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) Each body and plate weldment shall be penetrant examined with MIL-I-6866 (Type I, Method A or B) and shall comply with the requirements set forth in MIL-W-22248 for Class III weldments. Any assembly which fails to comply with the requirements shall be classed defective and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256689
4.4.2.13	Body and Plate Weldment (subsequent to anodizing)				NEXT HIGHER ASSEMBLY 9256695
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor					
201.	Protective finish missing or improper		1.0%	3.2	Visual
202.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256695
4.4.2.14	Fragment Assembly				NEXT HIGHER ASSEMBLY 9296901
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Small inside diameter of forward plate		0.40%	3.2	Gage
102.	Runout of forward plate diameter to flange and thread of aft ring		0.40%	3.2	Gage
103.	Non-compliance with establishing bonding procedures		Note	3.3	Visual
104.	Neck diameter of forward plate		0.40%	3.2	Gage
105.	Runout of neck diameter to flange and thread of aft ring		0.40%	3.2	Gage
106.	Chamfer for neck diameter, min.		0.40%	3.2	Gage
107.	Weight test		100%	3.2	4.5.2/Gage
Minor					
201.	Epoxy coat missing or of unusual color or texture		1.0%	3.2	Visual
202.	Fiberglass wrap missing or improper		1.0%	3.2	Visual
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) Verification of compliance with the established SOP for bonding shall be on a lot basis, based upon the inspector's judgement and knowledge of the SOP.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9285512
4.4.2.15	Plate, Body, Aft "Simulated"				NEXT HIGHER ASSEMBLY 9285514
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Inside diameter of forward end		100%	3.2	Gage
102.	Length of inside diameter of forward end		100%	3.2	Gage
103.	Outside diameter outside the range of the typical plate, body, aft outside diameter		100%	3.2	Gage
104.	True position of large inside diameter to outside diameter		100%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9285513
4.4.2.16	Plate, Body, Forward "Simulated"				NEXT HIGHER ASSEMBLY 9285514
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Small outside diameter		100%	3.2	Gage
102.	Inside diameter		100%	3.2	Gage
103.	True position of small outside diameter to large outside diameter		100%	3.2	Gage
Minor					
201.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9285514
4.4.2.17	Body Assembly "Simulated" (E.B. Weld - Inspection Sample)				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Parts cleaned before assembly		100%	3.2	Visual
102.	Aft plate improperly assembled		100%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9296901
4.4.2.18	Weldment, Body Assembly				NEXT HIGHER ASSEMBLY 9256708
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Metallographic examination	2 per shift per machine	-	3.4	4.5.1/Gage
102.	Air test certification		100%	3.5	4.5.3/Gage
103.	Runout of S&A well tube to outside diameter		100%	3.2	Gage
104.	Distance from end to top of S&A well tube, min.		100%	3.2	Gage
105.	Surface porosity		100%	3.4	Visual
106.	Bottom of S&A well tube damaged or stretched to the extent that it is no longer flat		100%	3.7	Visual
Minor					
201.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER 9256708
4.4.2.19	Body Assembly (subsequent to anodizing)		NEXT HIGHER ASSEMBLY 9268064

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Depth to S&A well bottom		100%	3.2	Gage
102.	Outside diameter of forward plate flange		0.40%	3.2	Gage
103.	Outside diameter of forward plate hub		0.40%	3.2	Gage
104.	Runout of forward plate hub to forward and aft plate flanges		0.40%	3.2	Gage
105.	Distance from forward plate flange to end of groove		0.40%	3.2	Gage
106.	Perpendicularity of forward plate flange to outside diameter of forward and aft plate flanges		0.40%	3.2	Gage
107.	Outside diameter of aft plate flange		0.40%	3.2	Gage
108.	Outside diameter of aft plate hub		0.40%	3.2	Gage
109.	Runout of aft plate hub to forward and aft plate flanges		0.40%	3.2	Gage
110.	Perpendicularity of aft plate flange to outside diameter of forward and aft plate flanges		0.40%	3.2	Gage
111.	Diameter of forward plate groove		0.40%	3.2	Gage
112.	Profile of forward flange		0.40%	3.2	Gage
113.	Diameter of aft plate groove		0.40%	3.2	Gage
114.	Profile of aft flange		0.40%	3.2	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9256708
4.4.2.19	Body Assembly (subsequent to anodizing)				NEXT HIGHER ASSEMBLY 9268064
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
115.	Symmetry of aft slot to forward slot		0.40%	3.2	Gage
116.	Distance from aft plate flange to end of groove		0.40%	3.2	Gage
117.	Runout of forward plate flange to outside diameter of body		0.40%	3.2	Gage
118.	Runout of aft plate flange to outside diameter of body		0.40%	3.2	Gage
119.	True position of S&A well to forward hub and flange		100%	3.2	Gage
120.	Outside diameter		100%	3.2	Gage
Minor					
201.	Length of forward plate slot		0.65%	3.2	Gage
202.	Width of forward plate slot		0.65%	3.2	Gage
203.	Depth of forward plate slot		0.65%	3.2	Gage
204.	Length of aft plate slot		0.65%	3.2	Gage
205.	Width of aft plate slot		0.65%	3.2	Gage
206.	Slot entrance		1.0%	3.2	Visual
207.	Distance between forward and aft plate flanges		0.65%	3.2	Gage
208.	Protective finish improper		1.0%	3.2	Visual
209.	Protective plug missing from S&A well		1.0%	3.2	Visual
210.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D (AR)

PARAGRAPH	TITLE				DRAWING NUMBER
4.4.2.20	Body Assembly (subsequent to painting)		1 SHEET	1 OF	9256708
					NEXT HIGHER ASSEMBLY 9268064
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Thickness of camouflage paint		0.65%	3.2	4.5.4/Gage
102	Certificate of conformance missing		-	3.1.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9276743
4.4.2.21	Sleeve, Protective				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Inside diameter		0.40%	3.2	Gage/See Note (a)
102.	Length of sleeve, max.		0.40%	3.2	Gage
103.	Outside diameter		0.40%	3.2	Gage/See Note (a)
Minor					
201.	Overlapping of inner liner		0.65%	3.2	Visual
202.	Slots missing		1.0%	3.2	Visual
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) This inspection shall be accomplished not less than 30 hours after manufacture.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9276750
4.4.2.22	Container, Guided Missile, MK 34, Mod 0 Modified for Warhead, GM, HE M250				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Handles broken, loose, or hazardous to handle because of displaced spring wires		100%	3.2	Visual/Manual
102.	Hinges damaged or loose		100%	3.2	Visual/Manual
103.	Cover gasket loose, missing or broken		0.65%	3.2	Visual
104.	Interior of container improperly cleaned		0.65%	3.2	Visual
Minor					
201.	Protective finish improper		1.0%	3.2	Visual
202.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-0-26T04:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-50849D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.23	Packing and Marking for Box, Packing, Ammunition, Wirebound, for Warhead, GM, HE, M250				9276741
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	End protectors missing		0.40%	3.2	Visual
102.	Protective sleeves missing		0.40%	3.2	Visual
103.	Insufficient filler to assure a tight pack		0.40%	3.2	Visual
Minor					
201.	Improper placement of filler material		0.65%	3.2	Visual
202.	Warheads not staggered within container		1.0%	3.2	Visual
203.	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Body assembly weldment metallographic examination. A test specimen manufactured in accordance with drawing 9285514 shall be used for a weld sample. A sample shall be welded at the beginning and end of each shift of each welding machine. The samples shall be sectioned, and one surface polished and microscopically examined at 20X magnification minimum, (25X is permissible). An acceptable weld shall meet the depth, width and surface porosity requirements of drawing 9296901, and shall not exhibit evidence of cracking or porosity within .090 inches of the outer surface. At the interface, where cracking cannot be totally eliminated, an acceptable weld shall exhibit a minimum width of .050 inches of weld material containing no cracking. That is, cracking extending from the interface is acceptable provided at least .050 inches of weld material remains uncracked. Any sample which fails to meet these requirements shall be classed defective, and the production of that shift shall be removed from the lot.

4.5.2 Fragment assembly weight. This test shall be conducted using a scale calibrated in, and accurate to one hundredth of a pound. Each fragment assembly shall be weighed and shall meet the weight requirement specified on drawing 9256695. Any assembly failing to meet the requirement shall be classed defective and removed from the lot.

4.5.3 Air test certification of weld. The weld of the S&A well tube shall be certified with a test fixture which shall seal the aft end of the warhead while subjecting it to an internal air pressure of 5 to 7 pounds per square inch (psi). The specified air pressure shall be applied for a minimum of twenty (20) seconds. Observation shall be made for the escape of air; leakage shall class the unit defective. Leakage shall be determined through the use of a leak test compound which meets the requirements of MIL-L-25567, Type 1.

4.5.4 Camouflage paint thickness. The camouflage paint thickness of the warhead shall be tested in accordance with Method A or C of ASTM D 1400-67. The primer thickness shall be measured

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

prior to applying the camouflage paint. These measurement locations shall be noted dimensionally and recorded so subsequent camouflage paint thickness measurements are in the same area. Camouflage paint thickness shall be measured at a minimum of two (2) randomly selected points on the exterior.

5. PACKAGING

5.1 Packing and marking.

5.1.1 Level A. The assemblies shall be packed and marked in accordance with MIL-STD-1169 and dwg. 9276741.

6. NOTES

6.1 Intended use. The warhead covered by this specification is intended for use on the Chaparral missile.

6.2 Ordering data. See MIL-A-48078.

6.2.1 Contract data requirements. The requirements for submission of data from the requirements paragraphs will be listed directly on a DD Form 1423 incorporated into the contract. Data Item Description DI-T-1906 will be required in connection with this specification.

6.2.2 Submission of data. Submit data, as required, to Commander, U.S. Army Armament Research and Development Center, ATTN: AMSMC-QAR-R(D), Dover, New Jersey 07801-5001.

6.3 Submission of designs for approval. See 6.2.3 of MIL-A-48078. Submit equipment and designs, as required, to Commander, U.S. Army Armament Research and Development Center, ATTN: AMSMC-QAR-I(D), Dover, New Jersey 07801-5001.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or ARRADCOM drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A512)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-50849D	WARHEAD, GUIDED MISSILE, HE. M250 INERT PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 1426 82 MAR PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:03Z
Check the source to verify that this is the current version before use.