
INCH-POUND
MS14002K
12 September 2022
SUPERSEDING
MS14002J
w/Amendment 1
21 March 2017

DETAIL SPECIFICATION SHEET

SWITCH, TOGGLE, POSITIVE BREAK, ENVIRONMENTALLY SEALED, SOLDER LUG, DOUBLE POLE, .469 MOUNTING BUSHING, 25 AMPERES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification sheet and MIL-DTL-8834.



NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerances are ±.010 on decimals and ±5° on angles.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

For hardware detail specifications, see appendix of MIL-DTL-8834.

In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

For design feature purposes, this specification takes precedence over acquisition documents referenced herein.

. Configuration of switch case housing, terminals, and barrier; design optional providing maximum dimensions specified are not exceeded.

Weight: .113 pound maximum (51.2 grams).

Altitude requirements: 80,000 feet.

115 V ac 60 hertz electrical endurance tests are to be performed at room temperature and pressure.

. Contact bounce: Shall not exceed 3.5 milliseconds.

TABLE I. Detail requirements.

MS dash no	Circuits made between terminals as indicated with the toggle lever in these positions:			Current capacity amperes per pole 28 volts dc 1/			Current capacity amperes per pole 1/ 115 volts 400 hertz ac			Current capacity amperes per pole 1/ 115 volts 60 hertz ac		
	Opposite keyway side	Center position	Keyway side	Lamp load circuit	Resis-tive circuit	Induct-ive circuit	Lamp load circuit	Resis-tive circuit	Induct-ive circuit	Lamp load circuit	Resis-tive circuit	Induct-ive circuit
-212	on 2-3, 5-6	off	on 1-2, 4-5	7	25	15	7	25	15	7	50	15
-222		none	off									
-232			on 1-2, 4-5									
-242	mom-on 2-3, 5-6	off	none									
-262		none	mom-on 1-2, 4-5									
-272		off										
-282	none											
-292	on 2-3, 5-6	none	mom-off									
-302	off		mom-on 1-2, 4-5									
-312	on 2-3, 5-6	off										

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:31Z
Check the source to verify that this is the current version before use.

TABLE I. Detail requirements - Continued.

MS dash no	Current capacity amperes per pole 1/ 250 volts 60 hertz ac			Current capacity amperes per pole 1/ 125 volts dc			Current capacity amperes per pole 1/ 250 volts dc			Life low current level switching 30 mV
	Lamp load circuit	Resis-tive circuit	Induct-ive circuit	Lamp load circuit	Resis-tive circuit	Induct-ive circuit	Lamp load circuit	Resis-tive circuit	Induct-ive circuit	
-212										
-222										
-232										
-242										
-262		10	7		750 mA			500 mA		10 mA
-272										
-282										
-292										
-302										
-312										

1/ Application information ratings at room temperature.

Referenced documents”
MIL-DTL-8834

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army – CR
Navy – AS
Air Force – 85
DLA - CC

Preparing activity:
DLA – CC

(Project 5930-2022-067)

Review activities:
Army - AR, MI
Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:31Z
Check the source to verify that this is the current version before use.